

# Material Safety Data Sheet

24 Hour Assistance:  
1-847-367-7700  
Rust-Oleum Corp.  
www.rustoleum.com

## Section 1 - Chemical Product / Company Information

Product Name: STRUST SSPR 6PK LOWES MEX GLS SNRISE RED  
Revision Date: 11/25/2009  
Identification Number: 253961  
Product Use/Class: Marking Paint/Aerosol  
Supplier: Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, IL 60061  
USA  
Manufacturer: Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, IL 60061  
USA  
Regulatory Department

## Section 2 - Composition / Information On Ingredients

Chemical Name	CAS Number	Weight % Less Than	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL CEILING
Isobutylene	67-64-1	30.0	500 ppm	750 ppm	1000 ppm	N.E.
Refined Petroleum Gas	68476-86-8	30.0	N.E.	N.E.	N.E.	N.E.
Alkyd Resin	PROPRIETARY	20.0	N.E.	N.E.	N.E.	N.E.
Isobutylene	1330-20-7	10.0	100 ppm	150 ppm	100 ppm	N.E.
Ethyl Acetate	123-86-4	10.0	150 ppm	200 ppm	150 ppm	N.E.
Benzene	100-41-4	5.0	100 ppm	125 ppm	100 ppm	N.E.
Diethylene Glycol Monobutyl Ether	111-76-2	5.0	20 ppm	N.E.	50 ppm	N.E.

## Section 3 - Hazards Identification

Emergency Overview \*\*\*: Contents Under Pressure. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Vapors may cause flash fire or explosion. Harmful if swallowed. Extremely flammable liquid and vapor.

Effects Of Overexposure - Eye Contact: Causes eye irritation.

Effects Of Overexposure - Skin Contact: May be harmful if absorbed through skin. Prolonged or repeated contact may cause skin irritation. Substance may cause slight skin irritation.

Effects Of Overexposure - Inhalation: High vapor concentrations are irritating to the eyes, nose, throat and lungs. Avoid breathing vapors. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Harmful if inhaled.

Effects Of Overexposure - Ingestion: Aspiration hazard if swallowed; can enter lungs and cause damage. Substance may be harmful if swallowed.

Effects Of Overexposure - Chronic Hazards: IARC lists Ethylbenzene as a possible human carcinogen (group 2B). May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and reproductive damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

## Section 4 - First Aid Measures

DO NOT allow rubbing of eyes or keeping eyes closed.

: Aid - Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

: Aid - Inhalation: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

: Aid - Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

---

---

## Action 5 - Fire Fighting Measures

---

---

Flash Point: -156 F  
(below flash)

LOWER EXPLOSIVE LIMIT: 0.7 %  
UPPER EXPLOSIVE LIMIT : 12.8 %

Extinguishing Media: Film Forming Foam, Carbon Dioxide, Dry Chemical, Water Fog

Usual Fire And Explosion Hazards: Water spray may be ineffective. Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. FLASH POINT IS LESS THAN 212 ° F. EXTREMELY FLAMMABLE LIQUID AND VAPOR! Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Perforation of the pressurized container may cause bursting of the can.

Special Firefighting Procedures: Evacuate area and fight fire from a safe distance.

---

---

## Action 6 - Accidental Release Measures

---

---

Steps To Be Taken If Material Is Released Or Spilled: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools.

---

---

## Action 7 - Handling And Storage

---

---

Handling: Wash thoroughly after handling. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing vapor or mist. Use only in a well-ventilated area. Wash hands before eating.

Storage: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 ° F. Store in quantities in buildings designed and protected for storage of NFPA Class I flammable liquids. Contents under pressure. Do not expose to heat or store above 120 ° F.

---

---

## Action 8 - Exposure Controls / Personal Protection

---

---

Engineering Controls: Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosure with exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Never workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

Hand Protection: Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves afford adequate skin protection.

er protective equipment: Refer to safety supervisor or industrial hygienist for further information regarding personal protective pment and its application.

ienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking.

---

---

## ction 9 - Physical And Chemical Properties

---

---

ing Range:	-34 - 999 F	Vapor Density:	Heavier than Air
r:	Solvent Like	Odor Threshold:	N.E.
earance:	Liquid	Evaporation Rate:	Faster than Ether
ibility in H2O:	Slight		
ize Point:	N.D.	Specific Gravity:	0.754
or Pressure:	N.D.	PH:	N.A.
sical State:	Liquid		

section 16 for abbreviation legend)

---

---

## ction 10 - Stability And Reactivity

---

---

ditions To Avoid: Avoid temperatures above 120 ° F. Avoid all possible sources of ignition.

mpatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

ardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes. By open flame, carbon monoxide carbon dioxide.

ardous Polymerization: Will not occur under normal conditions.

ability: This product is stable under normal storage conditions.

---

---

## ction 11 - Toxicological Information

---

---

duct LD50: N.D.

Product LC50: N.D.

<b>imical Name</b>	<b>LD50</b>	<b>LC50</b>
tone	5800 mg/kg (Rat)	50100 mg/m3 (Rat, 8Hr)
efined Petroleum Gas	N.E.	N.E.
lified Alkyd Resin	N.E.	N.E.
rine	4300 mg/kq (Rat, Oral)	5000 ppm (Rat, Inhalation, 4Hr)
ntyl Acetate	13100 mg/kg (Rat, Oral)	2000 ppm (Rat, Inhalation, 4 H
lbenzene	3500 mg/kg (Rat, Oral)	N.E.
lene Glycol Monobutyl Ether	1519 mg/kg (Mouse, Oral)	700 ppm (Rat, Inhalation, 7Hr)

---

---

## ction 12 - Ecological Information

---

---

logical Information: Product is a mixture of listed components.

---

---

## ction 13 - Disposal Information

---

---

posal Information: Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter str ns or sewer systems.

Proper Shipping Name:	ORM-D, Consumer Commodity	Packing Group:	N.A.
Technical Name:	N.A.	Hazard Subclass:	N.A.
Hazard Class:	2.1	Resp. Guide Page:	126
UN/NA Number:	UN1950		

Section 15 - Regulatory Information

15.1 SARA Hazard Category

This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD, PRESSURIZED GAS HAZARD

15.2 Section 313:

Below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title I Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS Number
Gasoline	1330-20-7
Gasoline/benzene	100-41-4
Gasoline/diethylene Glycol Monobutyl Ether	111-76-2

15.3 Toxic Substances Control Act:

Below are the substances (if any) contained in this product that are subject to the reporting requirements of TSCA 12(B) if exported from the United States:

It is the policy of Rust-Oleum Corporation to use only TSCA compliant materials in its products.

15.4 State Regulations: As follows -

15.4.1 New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

None

15.4.2 Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%.

None

15.4.3 California Proposition 65:

WARNING! This product contains a chemical(s) known by the State of California to cause cancer.

WARNING! This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm.

15.5 International Regulations: As follows -

MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**JADIAN WHMIS CLASS:** AB5 D2A D2B

---

---

## Section 16 - Other Information

---

---

**S Ratings:**

Health: 2*	Flammability: 4	Reactivity: 0	Personal Protection: X
------------	-----------------	---------------	------------------------

**REASON FOR REVISION:** Regulatory Update

**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.