Date Printed: 7/8/2024 Page 1 / 5

# Safety Data Sheet



\* Trusted Quality Since 1921 \* www.rustoleum.com

### 1. Identification

Product Name: W NO 0 CLNR TR ALKA DEGREASER Revision Date:

Product Identifier: 395406 Supercedes Date: New SDS

Recommended Use: No Information

Supplier: Rust-Oleum Corporation

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Phone: +1 (847) 367-7700

Preparer: Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 847-367-7700

Manufacturer:

Rust-Oleum Corporation 11 Hawthorn Parkway

Vernon Hills, IL 60061

USA

7/8/2024

Phone: +1 (847) 367-7700

### 2. Hazards Identification

#### Classification

#### Symbol(s) of Product

No symbol is required per 2012 OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### Signal Word

No Signal Word has been assigned.

# 3. Composition / Information on Ingredients

#### **HAZARDOUS SUBSTANCES**

Wt.%Chemical NameCAS-No.RangeGHS SymbolsGHS Statements

Potassium Hydroxide 1310-58-3 0.1-1.0 GHS05-GHS06 H301-314

### 4. First-Aid Measures

**First Aid - Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

First Aid - Skin Contact: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**First Aid - Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

Date Printed: 7/8/2024 Page 2 / 5

**First Aid - Ingestion:** If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

### 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Agueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

Unusual Fire and Explosion Hazards: Keep containers tightly closed. No unusual fire or explosion hazards noted.

**Special Fire Fighting Procedures:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): Not a combustible dust.

### 6. Accidental Release Measures

Steps to Be Taken If Material Is Released or Spilled: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

### 7. Handling and Storage

**Handling:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

Storage: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

### 8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Potassium Hydroxide	1310-58-3	1.0	N.E.	N.E.	N.E.	N.E.

#### PERSONAL PROTECTION

**Engineering Controls:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin Protection: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other Protective Equipment: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**Hygienic Practices:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

Date Printed: 7/8/2024 Page 3 / 5

# 9. Physical and Chemical Properties

Appearance: **Physical State:** Liquid Liquid Odor: Solvent Like **Odor Threshold:** N.E. Specific Gravity: 1.006 pH: N.A. Freeze Point, °C: Viscosity: N.D. N.D. Solubility in Water: Partition Coefficient, n-octanol/ Slight N.D.

Decomposition Temp., °C: N.D. water:

Boiling Range, °C: 100 - 100 Explosive Limits, vol%: N.A. - N.A.

Flammability:Does not Support CombustionFlash Point, °C:537Evaporation Rate:Slower than EtherAuto-Ignition Temp., °C:N.D.Vapor Density:Heavier than AirVapor Pressure:N.D.

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

Conditions to Avoid: Avoid excess heat.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

**Hazardous Polymerization:** Will not occur under normal conditions. **Stability:** This product is stable under normal storage conditions.

# 11. Toxicological Information

Effects of Overexposure - Eye Contact: Irritating, and may injure eye tissue if not removed promptly.

Effects of Overexposure - Skin Contact: Low hazard for usual industrial handling or commercial handling by trained personnel.

Effects of Overexposure - Inhalation: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

Effects of Overexposure - Ingestion: Substance may be harmful if swallowed.

Effects of Overexposure - Chronic Hazards: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.Chemical NameOral LD50Dermal LD50Vapor LC501310-58-3Potassium Hydroxide284 mg/kg RatN.E.N.E.

N.E. - Not Established

# 12. Ecological Information

Ecological Information: No ecotoxicity data was found for this product.

### 13. Disposal Information

Disposal: Dispose of material in accordance to local, state, and federal regulations and ordinances.

Date Printed: 7/8/2024 Page 4 / 5

# 14. Transport Information

**Domestic (USDOT)** International (IMDG) Air (IATA) TDG (Canada) **UN Number:** N.A. N.A. N.A. N.A. **Proper Shipping Name:** Not Regulated Not Regulated Not Regulated Not Regulated **Hazard Class:** N.A. N.A. N.A. N.A.

N.A.

Nο

N.A.

Nο

N.A.

Nο

# 15. Regulatory Information

## U.S. Federal Regulations:

### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

**Packing Group:** 

**Limited Quantity:** 

#### **SARA Section 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### **Toxic Substances Control Act**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

### U.S. State Regulations:

### California Proposition 65

WARNING: Cancer - www.P65Warnings.ca.gov.

N.A.

Nο

### 16. Other Information

**HMIS RATINGS** 

Health: 2\* Flammability: 1 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 1 Instability: 0

Volatile Organic Compounds: 0.01% SDS REVISION DATE: 7/8/2024

**REASON FOR REVISION:** 

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

Date Printed: 7/8/2024 Page 5 / 5

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.