

**24 Hour Assistance:**  
**1-847-367-7700**  
**Rust-Oleum Corp.**  
**[www.rustoleum.com](http://www.rustoleum.com)**

Product Name:	CLEAN METAL WHITE PRIMER	Revision Date:	12/07/2010
Identification Number:	1280504		
Product Use/Class:	Primer/Alkyd		
Supplier:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
Preparer:	Regulatory Department		

<u><b>Chemical Name</b></u>	<u><b>CAS Number</b></u>	<u><b>Weight % Less</b></u>				<u><b>OSHA PEL</b></u>
		<u><b>Than</b></u>	<u><b>ACGIH TLV-TWA</b></u>	<u><b>ACGIH TLV-STEL</b></u>	<u><b>OSHA PEL-TWA</b></u>	<u><b>CEILING</b></u>
Mineral Spirits	64742-88-7	35.0	100 ppm	N.E.	100 ppm	N.E.
Titanium Dioxide	13463-67-7	15.0	10 mg/m3	N.E.	15 mg/m3 (Total Dust)	N.E.
Magnesium Silicate	14807-96-6	15.0	2 mg/m3	N.E.	0.1 mg/m3 (Respirable)	N.E.
Tremolite (nonasbestiform)	14567-73-8	10.0	0.1 fibers/cm3	N.E.	0.1 fibers/cm3	N.E.
Strontium Zinc Phosphosilicate	MIXTURE	5.0	N.E.	N.E.	N.E.	N.E.
Anthophyllite (Nonasbestiform)	17068-78-9	1.0	0.1 fibers/cm3	N.E.	0.1 fibers/cm3	N.E.

**\*\*\* Emergency Overview \*\*\*:** Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Harmful if swallowed. Causes eye irritation. Vapors irritating to eyes and respiratory tract. Combustible liquid and vapor.

Effects Of Overexposure - Eye Contact: Causes eye irritation.

Effects Of Overexposure - Skin Contact: May cause skin irritation.

Effects Of Overexposure - Inhalation: High vapor concentrations are irritating to the eyes, nose, throat and lungs. May cause headaches and dizziness. Harmful if inhaled.

Effects Of Overexposure - Ingestion: Aspiration hazard if swallowed; can enter lungs and cause damage. Substance may be harmful if swallowed.

Effects Of Overexposure - Chronic Hazards: Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

## **Section 4 - First Aid Measures**

First Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

First Aid - Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

First Aid - Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation.

First Aid - Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

## **Section 5 - Fire Fighting Measures**

Flash Point: 104 F (Setaflash)

Extinguishing Media: Film Forming Foam, Carbon Dioxide, Dry Chemical, Water Fog

Unusual Fire And Explosion Hazards: Keep containers tightly closed.

Special Firefighting Procedures: Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance.

## **Section 6 - Accidental Release Measures**

Steps To Be Taken If Material Is Released Or Spilled: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

## **Section 7 - Handling And Storage**

Handling: Wash thoroughly after handling. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing vapor or mist. Avoid contact with eyes. Wash hands before eating.

Storage: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Keep away from heat, sparks, flame and sources of ignition. Keep container closed when not in use.

## **Section 8 - Exposure Controls / Personal Protection**

Engineering Controls: Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

Skin Protection: Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other protective equipment: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking.

## Section 9 - Physical And Chemical Properties

Vapor Density:	Heavier than Air	Odor:	Solvent Like
Appearance:	Liquid	Evaporation Rate:	Slower than Ether
Solubility in H <sub>2</sub> O:	Slight	Freeze Point:	N.D.
Specific Gravity:	1.283	PH:	N.A.
Physical State:	Liquid		

(See section 16 for abbreviation legend)

## Section 10 - Stability And Reactivity

Conditions To Avoid: Avoid all possible sources of ignition.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes. By open flame, carbon monoxide and carbon dioxide.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

## Section 11 - Toxicological Information

<b>Chemical Name</b>	<b>LD50</b>	<b>LC50</b>
Mineral Spirits	>5000 mg/kg (Rat, Oral)	>1400 ppm (Rat, Inhalation, 4Hr)
Titanium Dioxide	>7500 mg/kg (Rat, Oral)	N.E.
Magnesium Silicate	N.E.	TCLo: 11 mg/m <sup>3</sup> (Inhalation)
Tremolite (nonasbestiform)	N.E.	N.E.
Strontium Zinc Phosphosilicate	N.E.	N.E.
Anthophyllite (Nonasbestiform)	N.E.	N.E.

## Section 12 - Ecological Information

Ecological Information: Product is a mixture of listed components.

**Section 13 - Disposal Information**

Disposal Information: Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter storm drains or sewer systems.

**Section 14 - Transportation Information**

	<b>Domestic (USDOT)</b>	<b>International (IMDG)</b>	<b>Air (IATA)</b>
Proper Shipping Name:	Paint, Not Regulated	Paint	Paint
Hazard Class:	N.A.	3	3
UN Number:	N.A.	UN1263	UN1263
Packing Group:	N.A.	III	III
Limited Quantity:	No	IMDG 34-08, 3.4.7	Yes

**Section 15 - Regulatory Information****CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

**SARA Section 313:**

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<b><u>Chemical Name</u></b>	<b><u>CAS Number</u></b>
Strontium Zinc Phosphosilicate	MIXTURE
Anthophyllite (Nonasbestiform)	17068-78-9

**Toxic Substances Control Act:**

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of TSCA 12(B) if exported from the United States:

**U.S. State Regulations: As follows -****New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

<b><u>Chemical Name</u></b>	<b><u>CAS Number</u></b>
Alkyd Resin	PROPRIETARY

**Pennsylvania Right-to-Know:**

The following non-hazardous ingredients are present in the product at greater than 3%.

**Chemical Name**

Alkyd Resin  
Magnesium Silicate  
Serpentine

**CAS Number**

PROPRIETARY  
MIXTURE  
12135-86-3

**International Regulations: As follows -****CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**CANADIAN WHMIS CLASS:** B3 D2A D2B

<b>Section 16 - Other Information</b>
---------------------------------------

**NFPA Ratings:**

Health: 2                      Flammability: 2                      Instability: 0

**VOLATILE ORGANIC COMPOUNDS, g/l:** 445

**REASON FOR REVISION:** Regulatory Update

**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.