Date Printed: 12/16/2022 Page 1 / 6

# Safety Data Sheet



www.rustoleum.com

### 1. Identification

MODMAS QT EXT MET CHOCOLATE **Product Name:** 

SHIMMER

**Product Identifier:** 337163

Recommended Use: Acrylic/Exterior Metallic

**Rust-Oleum Corporation** Supplier:

11 Hawthorn Parkway Vernon Hills, IL 60061

**USA** 

Preparer: Regulatory Department

24 Hour Hotline: 847-367-7700 **Emergency Telephone:** 

# \* Trusted Quality Since 1921

Supercedes Date: 4/23/2018

**Revision Date:** 

**Rust-Oleum Corporation** Manufacturer:

11 Hawthorn Parkway Vernon Hills, IL 60061

**USA** 

12/16/2022

#### 2. Hazards Identification

#### Classification

Symbol(s) of Product



#### Signal Word

Danger

#### Possible Hazards

8% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### **GHS HAZARD STATEMENTS**

H317 Skin Sensitizer, category 1 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. Respiratory Sensitizer, category 1

Reproductive Toxicity, category 1B H360 May damage fertility or the unborn child.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. P280

P285 In case of inadequate ventilation wear respiratory protection.

P321 For specific treatment see label.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local, regional and national regulations.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

Date Printed: 12/16/2022 Page 2 / 6

P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

#### GHS SDS PRECAUTIONARY STATEMENTS

P363 Wash contaminated clothing before reuse.

#### 3. Composition / Information on Ingredients

#### **HAZARDOUS SUBSTANCES**

| Chemical Name                                      | CAS-No. V       | Vt.% Range | GHS Symbols                 | GHS Statements                       |
|--|-----------------|------------|-----------------------------|--------------------------------------|
| Mica   | 12001-26-2      | 2.5-10     | Not Available               | Not Available                        |
| Polypropylene Glycol                               | 25322-69-4      | 1.0-2.5    | Not Available               | Not Available                        |
| Titanium Dioxide                                   | 13463-67-7      | 1.0-2.5    | Not Available               | Not Available                        |
| Dipropylene Glycol Monobutyl Ether                 | 29911-28-2      | 0.1-1.0    | Not Available               | Not Available                        |
| 2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate    | 25265-77-4      | 0.1-1.0    | GHS06                       | H331                                 |
| Manganese Dioxide                                  | 1313-13-9       | 0.1-1.0    | GHS07                       | H332                                 |
| N-Methyl 2-Pyrrolidone                             | 872-50-4        | 0.1-1.0    | GHS07-GHS08                 | H315-319-332-335-360                 |
| Aqueous Ammonia                                    | 1336-21-6       | 0.1-1.0    | GHS05-GHS07                 | H302-314-335                         |
| Carbon Black                                       | 1333-86-4       | 0.1-1.0    | Not Available               | Not Available                        |
| bis(1,2,2,6,6-Pentamethyl-4-Piperidinyl) Sebacate  | 41556-26-7      | 0.1-1.0    | GHS07-GHS08                 | H317-361                             |
| Polymeric Benzotriazole                            | 104810-48-<br>2 | 0.1-1.0    | GHS07                       | H317                                 |
| Ammonium Persulfate                                | 7727-54-0       | 0.1-1.0    | GHS03-GHS07-<br>GHS08       | H272-302-315-317-319-332-334<br>-335 |
| Dipropylene Glycol Monomethyl Ether                | 34590-94-8      | 0.1-1.0    | Not Available               | Not Available                        |
| Carbamic Acid, 1H-Benzimidazol-2-yl-, Methyl Ester | 10605-21-7      | <0.1       | GHS08                       | H340-360                             |
| 3-lodo-2-Propynyl Butyl Carbamate                  | 55406-53-6      | <0.1       | GHS05-GHS06-<br>GHS07-GHS08 | H302-317-318-331-372                 |

# 4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

Date Printed: 12/16/2022 Page 3 / 6

# 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): No Information

#### Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

#### 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

#### 8. Exposure Controls / Personal Protection

| Chemical Name   | CAS-No.     | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA | OSHA PEL-<br>CEILING |
|---|-------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Mica  | 12001-26-2  | 10.0                  | 0.1 mg/m3         | N.E.               | N.E.         | N.E.                 |
| Polypropylene Glycol                                      | 25322-69-4  | 5.0                   | N.É.              | N.E.               | N.E.         | N.E.                 |
| Titanium Dioxide  | 13463-67-7  | 5.0                   | 0.2 mg/m3         | N.E.               | 15 mg/m3     | N.E.                 |
| Dipropylene Glycol Monobutyl<br>Ether                     | 29911-28-2  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| 2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate           | 25265-77-4  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Manganese Dioxide   | 1313-13-9   | 1.0                   | 0.02 mg/m3        | N.E.               | N.E.         | 5 mg/m3              |
| N-Methyl 2-Pyrrolidone                                    | 872-50-4    | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Aqueous Ammonia   | 1336-21-6   | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Carbon Black  | 1333-86-4   | 1.0                   | 3 mg/m3           | N.E.               | 3.5 mg/m3    | N.E.                 |
| bis(1,2,2,6,6-Pentamethyl-4-<br>Piperidinyl) Sebacate     | 41556-26-7  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Polymeric Benzotriazole                                   | 104810-48-2 | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Ammonium Persulfate                                       | 7727-54-0   | 1.0                   | 0.1 mg/m3         | N.E.               | N.E.         | N.E.                 |
| Dipropylene Glycol Monomethyl Ether                       | 34590-94-8  | 1.0                   | 50 ppm            | N.E.               | 100 ppm      | N.E.                 |
| Carbamic Acid, 1H-<br>Benzimidazol-2-yl-, Methyl<br>Ester | 10605-21-7  | 0.1                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| 3-lodo-2-Propynyl Butyl<br>Carbamate                      | 55406-53-6  | 0.1                   | N.E.              | N.E.               | N.E.         | N.E.                 |

#### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Date Printed: 12/16/2022 Page 4 / 6

Engineering Measures for Combustible Dust: No Information

#### 9. Physical and Chemical Properties

Appearance: Physical State: Liquid Liquid Odor: Odor Threshold: Mild N.E. Specific Gravity: 1.108 pH: N.D. Freeze Point, °C: Viscosity: N.D. N.D. Solubility in Water: Partition Coefficient, n-octanol/ Miscible N.D. water: Decomposition Temp., °C: N.D. Boiling Range, °C: **Explosive Limits, vol%:** 100 - 537 2.6 - 12.6Flash Point, °C: Flammability: Does not Support Combustion 94 **Evaporation Rate:** Auto-Ignition Temp., °C: Slower than Ether N.D. Vapor Density: Vapor Pressure: Heavier than Air N.D.

(See "Other information" Section for abbreviation legend)

#### 10. Stability and Reactivity

Conditions to Avoid: Avoid excess heat. Keep from freezing.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

**Hazardous Polymerization:** Will not occur under normal conditions. **Stability:** This product is stable under normal storage conditions.

#### 11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black.

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula. Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No.    | Chemical Name                                   | Oral LD50        | Dermal LD50        | Vapor LC50     |
|------------|---|------------------|--------------------|----------------|
| 12001-26-2 | Mica  | N.E.             | N.E.               | 25000          |
| 25322-69-4 | Polypropylene Glycol                            | 3750 mg/kg Rat   | >3000 mg/kg Rabbit | N.E.           |
| 13463-67-7 | Titanium Dioxide                                | >10000 mg/kg Rat | 6000               | N.E.           |
| 29911-28-2 | Dipropylene Glycol Monobutyl Ether              | N.E.             | N.E.               | 25             |
| 25265-77-4 | 2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate | 3200 mg/kg Rat   | >15200 mg/kg Rat   | >3.55 mg/L Rat |
| 1313-13-9  | Manganese Dioxide                               | 9000 mg/kg Rat   | N.E.               | N.E.           |
| 872-50-4   | N-Methyl 2-Pyrrolidone                          | 3914 mg/kg Rat   | 8000 mg/kg Rabbit  | 20 mg/L Rat    |
| 1336-21-6  | Aqueous Ammonia                                 | 350 mg/kg Rat    | N.E.               | N.E.           |
| 1333-86-4  | Carbon Black                                    | >15400 mg/kg Rat | N.E.               | N.E.           |

Date Printed: 12/16/2022 Page 5 / 6

| 41556-26-7               | bis(1,2,2,6,6-Pentamethyl-4-Piperidinyl) Sebacate                                   | 2615 mg/kg Rat  | N.E.                | N.E.     |
|--------------------------|---|-----------------|---------------------|----------|
| 7727-54-0                | Ammonium Persulfate   | 495 mg/kg Rat   | >10000 mg/kg Rabbit | N.E.     |
| 34590-94-8<br>10605-21-7 | Dipropylene Glycol Monomethyl Ether<br>Carbamic Acid, 1H-Benzimidazol-2-yl-, Methyl | 5350 mg/kg Rat  | 9500 mg/kg Rabbit   | >20 mg/L |
|                          | Ester   | >5050 mg/kg Rat | >10000 mg/kg Rabbit | N.E.     |
| 55406-53-6               | 3-lodo-2-Propynyl Butyl Carbamate   | 1470 mg/kg Rat  | >2000 mg/kg Rat     | N.E.     |

N.E. - Not Established

# 12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components. No ecotoxicity data was found for this product.

### 13. Disposal Information

DISPOSAL: Dispose of material in accordance to local, state, and federal regulations and ordinances.

# 14. Transport Information

| UN Number:                                     | Domestic (USDOT) | International (IMDG) | <u>Air (IATA)</u> | TDG (Canada)  |
|--|------------------|----------------------|-------------------|---------------|
|  | N.A.             | N.A.                 | N.A.              | N.A.          |
| Proper Shipping Name:                          | Not Regulated    | Not Regulated        | Not Regulated     | Not Regulated |
| Hazard Class: Packing Group: Limited Quantity: | N.A.             | N.A.                 | N.A.              | N.A.          |
|  | N.A.             | N.A.                 | N.A.              | N.A.          |
|  | No               | No                   | No                | No            |

# 15. Regulatory Information

# U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Reproductive toxicity, Respiratory or Skin Sensitization

#### **SARA Section 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u>                | <u>CAS-No.</u> |
|-------------------------------------|----------------|
| Manganese Dioxide                   | 1313-13-9      |
| N-Methyl 2-Pyrrolidone              | 872-50-4       |
| Aqueous Ammonia                     | 1336-21-6      |
| Ammonium Persulfate                 | 7727-54-0      |
| Dipropylene Glycol Monomethyl Ether | 34590-94-8     |
| 3-lodo-2-Propynyl Butyl Carbamate   | 55406-53-6     |

#### **Toxic Substances Control Act**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

# U.S. State Regulations:

Date Printed: 12/16/2022 Page 6 / 6

#### California Proposition 65

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

#### 16. Other Information

**HMIS RATINGS** 

Health: 2\* Flammability: 1 Physical Hazard: 0 Personal Protection: X

**NFPA RATINGS** 

Health: 2 Flammability: 1 Instability: 0

Volatile Organic Compounds: 116 g/L SDS REVISION DATE: 12/16/2022

REASON FOR REVISION: Product Composition Changed

Substance and/or Product Properties Changed in

Section(s):

02 - Hazard Identification

09 - Physical & Chemical Properties

15 - Regulatory Information16 - Other Information

Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.