Page 1 / 5 Date Printed: 4/24/2018

# Safety Data Sheet



# 1. Identification

OKON 1-GL 4 PK SEALD SURF GRAFFITI **Product Name:** 

BARRI

**Product Identifier:** OK221

**Product Use/Class:** Graffiti Barrier

**Rust-Oleum Corporation** Supplier:

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Preparer: Regulatory Department

24 Hour Hotline: 847-367-7700 **Emergency Telephone:** 

# www.rustoleum.com

**Revision Date:** 4/24/2018

> Supercedes Date: 3/30/2015

**Rust-Oleum Corporation** Manufacturer:

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

# 2. Hazard Identification

#### Classification

#### Symbol(s) of Product

Not a hazardous substance or mixture per 2012 OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### Signal Word

No Signal Word has been assigned.

# 3. Composition / Information On Ingredients

#### HAZARDOUS SUBSTANCES

Chemical Name	CAS-No.	<u>Wt.%</u> Range	GHS Symbols	GHS Statements
2,2,4-Trimethyl-1,3-Pentanediol Isobutyrate	25265-77-4	1.0-2.5	GHS06	H331
Diethylaminoethanol	100-37-8	0.1-1.0	GHS02-GHS05- GHS06	H226-302-311-314-332-335

# 4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

Date Printed: 4/24/2018 Page 2 / 5

**FIRST AID - INGESTION:** If swallowed, rinse mouth with water. If feeling unwell, get medical attention. Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

# 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): No Information

### Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

# 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing. Avoid contact with eyes. **STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep from freezing. Keep container closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

# 8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
2,2,4-Trimethyl-1,3-Pentanediol Isobutyrate	25265-77-4	5.0	N.E.	N.E.	N.E.	N.E.
Diethylaminoethanol	100-37-8	1.0	2 ppm	N.E.	10 ppm	N.E.

#### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications. Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

Date Printed: 4/24/2018 Page 3 / 5

# 9. Physical and Chemical Properties

Appearance: **Physical State:** Liquid Liquid Odor: **Odor Threshold:** Solvent Like N.E. **Relative Density:** 1.017 pH: N.A. Freeze Point, °C: Viscosity: N.D. N.D. Solubility in Water: Miscible Partition Coefficient, n-octanol/ N.D. water: Decompostion Temp., °C: N.D. Explosive Limits, vol%: Boiling Range, °C: 100 - 381 0.6 - 7.0Flash Point, °C: Flammability: **Does not Support Combustion** 94 Auto-ignition Temp., °C: **Evaporation Rate:** Slower than Ether N.D. Vapor Density: Heavier than Air Vapor Pressure: N.D.

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid contact with strong acid and strong bases.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**HAZARDOUS DECOMPOSITION:** By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

# 11. Toxicological Information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Causes eye irritation. Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Substance may cause slight skin irritation. Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
25265-77-4	2,2,4-Trimethyl-1,3-Pentanediol Isobutyrate	3200 mg/kg Rat	>15200 mg/kg Rat	>3.55 mg/L Rat
100-37-8	Diethylaminoethanol	1320 mg/kg Rat	932 mg/kg Rabbit	N.Ĕ.

N.E. - Not Established

# 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

# 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

Date Printed: 4/24/2018 Page 4 / 5

# 14. Transport Information

Domestic (USDOT) International (IMDG) Air (IATA) TDG (Canada)
UN Number: N.A. N.A. N.A. N.A. N.A.

Proper Shipping Name: Not Regulated Not Regulated Not Regulated Not Regulated

Hazard Class:N.A.N.A.N.A.N.A.Packing Group:N.A.N.A.N.A.N.A.Limited Quantity:NoNoNoNo

# 15. Regulatory Information

# **U.S. Federal Regulations:**

# **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

No Information

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.Diethylaminoethanol100-37-8

#### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

Date Printed: 4/24/2018 Page 5 / 5

# 16. Other Information

**HMIS RATINGS** 

Health: 2 Flammability: 1 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 1 Instability 0

VOLATILE ORGANIC COMPOUNDS, g/L: 49

SDS REVISION DATE: 4/24/2018

**REASON FOR REVISION:** Product Composition Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

02 - Hazard Identification05 - Fire-fighting Measures

09 - Physical & Chemical Properties

15 - Regulatory Information16 - Other InformationStatement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.