Date Printed: 2/19/2015 Page 1 / 7

Safety Data Sheet



1. Identification

SEMI TSTRS 576PK BULK .25 OZ NEON **Product Name:**

YLW

Product Identifier: 11773131A

Product Use/Class: Brushing Paint/ Oil-Based Enamel

The Testors Corporation Supplier:

440 Blackhawk Park Drive Rockford, IL 61104

USA

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 847-367-7700 www.testors.com

2/19/2015

New SDS

USA

The Testors Corporation

Rockford, IL 61104

440 Blackhawk Park Drive

Revision Date:

Manufacturer:

Supercedes Date:

2. Hazard Identification

EMERGENCY OVERVIEW: May cause eye, skin, or respiratory tract irritation. KEEP OUT OF REACH OF CHILDREN. Harmful if inhaled. Harmful if swallowed. Causes eye irritation. Flammable liquid and vapor. Use ventilation necessary to keep exposures below recommended exposure limits, if any. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Vapor Harmful. Causes Eye, Skin, Nose, and Throat Irritation.

Classification

Symbol(s) of Product







Signal Word Danger

GHS HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Acute Toxicity, Oral, category 5	H303	May be harmful if swallowed.
Acute Toxicity, Dermal, category 5	H313	May be harmful in contact with skin.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Organic Peroxide, categories C, D	H242	Heating may cause a fire.
Aspiration Hazard, category 2	H305	May be harmful if swallowed and enters airways.
Eye Irritation, category 2B	H320	Causes eye irritation.
Flammable Liquid, category 1	H224	Extremely flammable liquid and vapour.

Date Printed: 2/19/2015 Page 2 / 7

H340 May cause genetic defects. Classified as mutagenic Category 1 if one Germ Cell Mutagenicity, category 1B ingredient is present at or above 0.1%. Applies to liquids, solids (w/w units) and gases (v/v). The substance may also have its own exposure limit. Routes of exposure are dependent on ingredient form. H350 May cause cancer. Classified as carcinogenic Category 1 on the basis of Carcinogenicity, category 1B epidemiological and/or animal data. Mixtures are classified as carcinogenic when at least 1 ingredient has been classified as carcinogenic and is present at 0.1% or above Routes of exposure are dependant on ingredient form. Reproductive Toxicity, category 2 H361 Suspected of damaging fertility or the unborn child. Classifed Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies. STOT, repeated exposure, category 1 H372 Causes damage to organs <or state all organs affected, if known> through

prolonged or repeated exposure <state route of exposure if it is conclusively

proven that no other routes of exposure cause the hazard>.

GHS PRECAUTIONARY STATEMENTS

P102 Keep out of reach of children. P103 Read label before use.

P202 Do not handle until all safety precautions have been read and understood.

P234 Keep only in original container.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash ... thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P285 In case of inadequate ventilation wear respiratory protection.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P351 Rinse cautiously with water for several minutes.

P374 Fight fire with normal precautions from a reasonable distance.

P402 Store in a dry place.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P370+P378 In case of fire: Use ... for extinction.
P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to ...
P321 Specific treatment (see ... on this label).
P352 Wash with plenty of soap and water.

P362 Take off contaminated clothing and wash before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P220 Keep/Store away from clothing/.../combustible materials.

P410 Protect from sunlight.

P420 Store away from other materials.

P411+P235 Store at temperatures not exceeding ... °C/... °F. Keep cool.

P201 Obtain special instructions before use.

Date Printed: 2/19/2015 Page 3 / 7

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P302+P350 IF ON SKIN: Gently wash with plenty of soap and water.

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

Chemical Name	CAS-No.	Wt.% Range	GHS Symbols	GHS Statements
Stoddard Solvent	8052-41-3	25-50	GHS02-GHS08	H224-340-350-372
Aliphatic Hydrocarbon	64742-89-8	10-25	GHS08	H340-350
Toluene	108-88-3	2.5-10	GHS02-GHS07- GHS08	H225-302-332-361-336-373-315
Aromatic Petroleum Distillates	64742-94-5	2.5-10	GHS06	H227-310
Naphthalene	91-20-3	0.1-1.0	GHS02-GHS07- GHS08	H228-312-351-302

The text for GHS Hazard Statements shown above (if any) is given in the "16. Other Information" section.

4. First-aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: No unusual fire or explosion hazards noted. Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials. Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Keep away from heat, sparks, flame and sources of ignition. Avoid excess heat. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids.

Date Printed: 2/19/2015 Page 4 / 7

8. Exposure Controls/Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Stoddard Solvent	8052-41-3	35.0	100 ppm	N.E.	500 ppm	N.E.
Aliphatic Hydrocarbon	64742-89-8	15.0	350 ppm	N.E.	500 ppm	N.E.
Toluene	108-88-3	5.0	20 ppm	N.E.	200 ppm	300 ppm
Aromatic Petroleum Distillates	64742-94-5	5.0	N.E.	N.E.	N.E.	N.E.
Naphthalene	91-20-3	1.0	10 ppm	15 ppm (NIOSH)	10 ppm	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

9. Physical and Chemical Properties

Appearance:LiquidPhysical State:LiquidOdor:Solvent LikeOdor Threshold:N.E.Relative Density:0.927pH:N.A.

Freeze Point, °C: N.D. Viscosity: No Information

Solubility in Water: Negligible Partition Coefficient, n-

Decompostion Temp., °C: No Information Octanol/water: No Information

Boiling Range, °C: 0 - 370 Explosive Limits, vol%: 0.9 - 7.0 Flammability: Supports Combustion Flash Point, °C: 20

Evaporation Rate: Slower than Ether Auto-ignition Temp., °C: No Information Vapor Density: Heavier than Air Vapor Pressure: No Information

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid temperatures above 120 ° F. Avoid contact with strong acid and strong bases. Avoid all possible sources of ignition.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes Serious Eye Irritation

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May be absorbed through the skin in harmful amounts. Causes skin

Date Printed: 2/19/2015 Page 5 / 7

irritation. Allergic reactions are possible.

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
64742-89-8	Aliphatic Hydrocarbon	N.I.	3000 mg/kg Rabbit	N.I.
108-88-3	Toluene	636 mg/kg Rat	8390 mg/kg Rabbit	12.5 mg/L Rat
64742-94-5	Aromatic Petroleum Distillates	>5000 mg/kg Rat	>2 mL/kg Rabbit	N.I.
91-20-3	Naphthalene	N.Ī.	1120 mg/kg Rabbit	N.I.

N.I. - No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

14. Transport Information

	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	TDG (Canada)
UN Number:	N.A.	1263	1263	N.A.
Proper Shipping Name:	Paint Products in Limited Quantities	Paint	Paint	Paint Products in Limited Quantities
Hazard Class:	N.A.	3	3	N.A.
Packing Group:	N.A.	II	II	N.A.
Limited Quantity:	Yes	Yes	No	Yes

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.Toluene108-88-3Naphthalene91-20-3

Date Printed: 2/19/2015 Page 6 / 7

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

CALIFORNIA PROPOSITION 65:

WARNING: This product contains a substance known to the State of California to cause cancer.

Chemical NameCAS-No.Naphthalene91-20-3

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

WARNING: This product contains a substance known to the State of California to cause birth defects or other reproductive

harm.

Chemical NameCAS-No.Toluene108-88-3

International Regulations:

CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

16. Other Information

HMIS RATINGS

Health: 2* Flammability: 3 Physical Hazard: 0 Personal Protection: X

CANADIAN WHMIS CLASS: B2 D2A

NFPA RATINGS

Health: 2 Flammability: 3 Instability 0

VOLATILE ORGANIC COMPOUNDS, g/L: 515

MSDS REVISION DATE: 2/19/2015

REASON FOR REVISION: No Information

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined


Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H227	Combustible liquid
H228	Flammable solid.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.

Date Printed: 2/19/2015 Page 7 / 7

	· · · · · · · · · · · · · · · · · · ·
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects <state cause="" conclusively="" exposure="" hazard="" if="" is="" it="" no="" of="" other="" proven="" route="" routes="" that="" the="">.</state>
H350	May cause cancer <state cause="" conclusively="" exposure="" hazard="" if="" is="" it="" no="" of="" other="" proven="" route="" routes="" that="" the="">.</state>
H351	Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Mixtures with concentrations of suspected carcinogens ingredients at concentration present between 0.1% and 1.0% labelling the SDS will be optional depending on authorities. If Category 2 carcinogenic present at a concentration of 1% or above labelling the SDS will be expected. Routes of exposure are dependant on ingredient form.
H361	Suspected of damaging fertility or the unborn child. Classifed Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.
H372	Causes damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through prolonged or repeated exposure <state cause="" conclusively="" exposure="" hazard="" if="" is="" it="" no="" of="" other="" proven="" route="" routes="" that="" the="">.</state></or>
H373	May cause damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through prolonged or repeated exposure <state cause="" conclusively="" exposure="" hazard="" if="" is="" it="" no="" of="" other="" proven="" route="" routes="" that="" the="">.</state></or>

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.