Material Safety Data Sheet

24 Hour Assistance:
1-847-367-7700
Rust-Oleum Corp.
www.rustoleum.com

ection 1 - Chemical Product / Company Information

duct Name:	STRUST SSPR 6PK LOWES MEX GLOSS ALMOND	Revision Date:	11/25/2009
ntification Number:	253963		
duct Use/Class:	Marking Paint/Aerosol		
plier:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
parer:	Regulatory Department		

ection 2 - Composition / Information On Ingredients

nical Name	CAS Number	Weight % Less Than	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL CEILI
fied Petroleum Gas	68476-86-8	30.0	N.E.	N.E.	N.E.	N.E.
ne	67-64-1	25.0	500 ppm	750 ppm	1000 ppm	N.E.
fied Alkyd Resin	PROPRIETARY	15.0	N.E.	N.E.	N.E.	N.E.
um Dioxide	13463-67-7	15.0	10 mg/m3	N.E.	15 mg/m3 (Total Dust)	N.E.
e	1330-20-7	10.0	100 ppm	150 ppm	100 ppm	N.E.
yl Acetate	123-86-4	10.0	150 ppm	200 ppm	150 ppm	N.E.
benzene	100-41-4	5.0	100 ppm	125 ppm	100 ppm	N.E.
ene Glycol Monobutyl Ether	111-76-2	5.0	20 ppm	N.E.	50 ppm	N.E.

ection 3 - Hazards Identification

Emergency Overview ***: Contents Under Pressure. Harmful if inhaled. May affect the brain or nervous system causing dizziness, dache or nausea. Vapors may cause flash fire or explosion. Harmful if swallowed. Extremely flammable liquid and vapor.

cts Of Overexposure - Eye Contact: Causes eye irritation.

cts Of Overexposure - Skin Contact: May be harmful if absorbed through skin. Prolonged or repeated contact may cause skin ation. Substance may cause slight skin irritation.

cts Of Overexposure - Inhalation: High vapor concentrations are irritating to the eyes, nose, throat and lungs. Avoid breathing vap ists. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Harmful if inhaled.

cts Of Overexposure - Ingestion: Aspiration hazard if swallowed; can enter lungs and cause damage. Substance may be harmful llowed.

cts Of Overexposure - Chronic Hazards: Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinoge umans" by IARC. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on durat level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the ula.
C lists Ethylbenzene as a possible human carcinogen (group 2B). May cause central nervous system disorder (e.g., narcosis involv ss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. Reports have associated repeated anc onged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in ratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive rders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage.

nary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

ection 4 - First Aid Measures

NOT allow rubbing of eyes or keeping eyes closed.

: Aid - Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

: Aid - Inhalation: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, ge
lical assistance immediately.

: Aid - Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs ar
se severe lung damage. Get immediate medical attention.

ction 5 - Fire Fighting Measures

h Point: -156 F
aflash)

LOWER EXPLOSIVE LIMIT: 0.7 %
UPPER EXPLOSIVE LIMIT : 12.8 %

nguishing Media: Film Forming Foam, Carbon Dioxide, Dry Chemical, Water Fog

sual Fire And Explosion Hazards: Water spray may be ineffective. Closed containers may explode when exposed to extreme heat.
ors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. FLASH POINT IS LESS THAN 2
EXTREMELY FLAMMABLE LIQUID AND VAPOR! Keep containers tightly closed. Isolate from heat, electrical equipment, sparks a
n flame. Perforation of the pressurized container may cause bursting of the can.

cial Firefighting Procedures: Evacuate area and fight fire from a safe distance.

ction 6 - Accidental Release Measures

os To Be Taken If Material Is Released Or Spilled: Contain spilled liquid with sand or earth. DO NOT use combustible materials suc
awdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Remove all
ces of ignition, ventilate area and remove with inert absorbent and non-sparking tools.

ction 7 - Handling And Storage

dling: Wash thoroughly after handling. Follow all MSDS/label precautions even after container is emptied because it may retain
luct residues. Avoid breathing vapor or mist. Use only in a well-ventilated area. Wash hands before eating.

age: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 ° F. St
e quantities in buildings designed and protected for storage of NFPA Class I flammable liquids. Contents under pressure. Do not
ose to heat or store above 120 ° F.

ction 8 - Exposure Controls / Personal Protection

ineering Controls: Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosur
l exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-p
ilation equipment.

piratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed
never workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor
ridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure
s.

ection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an
ontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide
quate protection.

Protection: Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene glov
afford adequate skin protection.

Protection: Use safety eyewear designed to protect against splash of liquids.

ipment and its application.

ienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking.

ction 9 - Physical And Chemical Properties

ing Range:	-34 - 999 F	Vapor Density:	Heavier than Air
r:	Solvent Like	Odor Threshold:	N.E.
earance:	Liquid	Evaporation Rate:	Faster than Ether
ubility in H2O:	Slight		
eze Point:	N.D.	Specific Gravity:	0.830
or Pressure:	N.D.	PH:	N.A.
sical State:	Liquid		

section 16 for abbreviation legend)

ction 10 - Stability And Reactivity

ditions To Avoid: Avoid temperatures above 120 ° F. Avoid all possible sources of ignition.

mpatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

ardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes. By open flame, carbon monoxide carbon dioxide.

ardous Polymerization: Will not occur under normal conditions.

bility: This product is stable under normal storage conditions.

ction 11 - Toxicological Information

duct LD50: N.D.

Product LC50: N.D.

mical Name	LD50	LC50
efied Petroleum Gas	N.E.	N.E.
tone	5800 mg/kg (Rat)	50100 mg/m3 (Rat, 8Hr)
lified Alkyd Resin	N.E.	N.E.
nium Dioxide	>7500 mg/kg (Rat, Oral)	N.E.
ene	4300 mg/kg (Rat, Oral)	5000 ppm (Rat, Inhalation, 4Hr
utyl Acetate	13100 mg/kg (Rat, Oral)	2000 ppm (Rat, Inhalation, 4 H
lbenzene	3500 mg/kg (Rat, Oral)	N.E.
lene Glycol Monobutyl Ether	1519 mg/kg (Mouse, Oral)	700 ppm (Rat, Inhalation, 7Hr)

ction 12 - Ecological Information

logical Information: Product is a mixture of listed components.

ction 13 - Disposal Information

posal Information: Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter st ns or sewer systems.

ction 14 - Transportation Information

T Technical Name:	N.A.	Hazard Subclass:	N.A.
T Hazard Class:	2.1	Resp. Guide Page:	126
T UN/NA Number:	UN1950		

ction 15 - Regulatory Information

RCLA - SARA Hazard Category

product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311and 312 of the Superfund endment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following gories:

IEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD, PRESSURIZED GAS HAZARD

RA Section 313:

ed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title I Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

mical Name	CAS Number
ene	1330-20-7
lbenzene	100-41-4
lene Glycol Monobutyl Ether	111-76-2

ic Substances Control Act:

ed below are the substances (if any) contained in this product that are subject to the reporting requirements of TSCA 12(B) if export the United States:

the policy of Rust-Oleum Corporation to use only TSCA compliant materials in its products.

. State Regulations: As follows -

Jersey Right-to-Know:

following materials are non-hazardous, but are among the top five components in this product.

e

nsylvania Right-to-Know:

following non-hazardous ingredients are present in the product at greater than 3%.

mical Name	CAS Number
um Sulfate	7727-43-7

fornia Proposition 65:

RNING! This product contains a chemical(s) known by the State of California to cause cancer.

RNING! This product contains a chemical(s) known to the State of California to cause birth defects or other reproductive harm.

ernational Regulations: As follows -

NADIAN WHMIS:

MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

ADIAN WHMIS CLASS: AB5 D2A D2B

S Ratings:

lth: 2* Flammability: 4 Reactivity: 0 Personal Protection: X

ASON FOR REVISION: Regulatory Update

end: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

t-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate
ble as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materi
beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these
erials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results
ained from their use. All materials may present unknown hazards and should be used with caution. The information and
mmendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of th
to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and
ulations.