

# Revision Date: 9/13/2018 Seal Krete High Performance Floor Coating Systems Multi Component Product Information Sheet

# 502101KIT SKHP Epoxy-Shell WB 50 Armor Gray 2-Prt Kit 5 GL is a multi component product composed of the following individual chemical components:

502101A SKHP Epoxy-Shell WB 50 Armor Gray Part A

311545 Epoxy-Shell WB50 Part B EP6010

SDSs for each component follow this cover sheet.

# **Transportation Information**

UN Number:	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	TDG (Canada)
	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class: Packing Group:	N.A.	N.A.	N.A.	N.A.
	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	N.A.	N.A.	N.A.	N.A.

Finished Good Schedule B Harmonized Tariff Code 3907.30.0000

Date Printed: 9/13/2018 Page 1 / 6

# Safety Data Sheet



www.rustoleum.com

### 1. Identification

Product Name: SKHP Epoxy-Shell WB 50 Armor Gray Part A Revision Date: 9/13/2018

Product Identifier: 502101A Supercedes Date: 3/1/2018

Recommended Use: Floor Coating/Epoxy Waterbased

**USA** 

Supplier: Rust-Oleum Corporation Manufacturer: Rust-Oleum Corporation 11 Hawthorn Parkway 11 Hawthorn Parkway

Vernon Hills, IL 60061 Vernon Hills, IL 60061

USA

Preparer: Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 847-367-7700

### 2. Hazard Identification

#### Classification

Symbol(s) of Product



#### **Signal Word** Danger

#### Possible Hazards

20% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### **GHS HAZARD STATEMENTS**

Reproductive Toxicity, category 2 H361 Suspected of damaging fertility or the unborn child.

Acute Toxicity, Inhalation, category 4 H332 Harmful if inhaled.

Skin Irritation, category 2 H315 Causes skin irritation.

Serious Eye Damage, category 1 H318 Causes serious eye damage.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P201 Obtain special instructions before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Date Printed: 9/13/2018 Page 2 / 6

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local, regional and national regulations.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P264 Wash hands thoroughly after handling.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 For specific treatment see label

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 If exposed immediately call a POISON CENTER or doctor/physician.

# 3. Composition / Information On Ingredients

#### **HAZARDOUS SUBSTANCES**

Chemical Name	CAS-No.	Wt.% Range	GHS Symbols	GHS Statements
Modified Polyamine	PROPRIET ARY	10-25	GHS05-GHS08	H315-318-361
Titanium Dioxide	13463-67-7	10-25	Not Available	Not Available
2-Ethylhexanoic Acid	149-57-5	2.5-10	GHS07-GHS08	H302-312-361
N,N-Dimethyl Benzenemethanamine	103-83-3	2.5-10	GHS02-GHS05- GHS06	H226-301-312-314-330
Dipropylene Glycol Monobutyl Ether	29911-28-2	0.1-1.0	Not Available	Not Available

# 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

Date Printed: 9/13/2018 Page 3 / 6

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

# 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** No unusual fire or explosion hazards noted. Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): No Information

#### 6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

# 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

# 8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Modified Polyamine	PROPRIETARY	20.0	N.E.	N.E.	N.E.	N.E.
Titanium Dioxide	13463-67-7	20.0	10 mg/m3	N.E.	15 mg/m3	N.E.
2-Ethylhexanoic Acid	149-57-5	5.0	5 mg/m3 (Vapor)	N.E.	N.E.	N.E.
N,N-Dimethyl Benzenemethanamine	103-83-3	5.0	N.E.	N.E.	N.E.	N.E.
Dipropylene Glycol Monobutyl Ether	29911-28-2	1.0	N.E.	N.E.	N.E.	N.E.

#### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

Date Printed: 9/13/2018 Page 4 / 6

Viscosity:

water:

Partition Coefficient, n-octanol/

N.D.

N.D.

# 9. Physical and Chemical Properties

Appearance:LiquidPhysical State:LiquidOdor:Solvent LikeOdor Threshold:N.E.

Relative Density: 1.284 pH: Not Determined

Freeze Point, °C: N.D.

Solubility in Water: Slight

Decompostion Temp., °C: N.D.

Boiling Range, °C: 100 - 177 Explosive Limits, vol%: 6.7 - N.A.

Flammability:Does not Support CombustionFlash Point, °C:99Evaporation Rate:Slower than EtherAuto-ignition Temp., °C:N.D.Vapor Density:Heavier than AirVapor Pressure:N.D.

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

**CONDITIONS TO AVOID: No Information** 

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

#### 11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	2500 mg/kg	N.E.
149-57-5	2-Ethylhexanoic Acid	1600 mg/kg Rat	1140 mg/kg Rabbit	N.E.
103-83-3	N,N-Dimethyl Benzenemethanamine	265 mg/kg Rat	1494 mg/kg Rabbit	N.E.

N.E. - Not Established

# 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

# 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

Date Printed: 9/13/2018 Page 5 / 6

# 14. Transport Information

	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	TDG (Canada)
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated

N.A.

N.A.

Nο

N.A.

N.A.

Nο

N.A.

N.A.

Nο

N.A.

N.A.

Nο

# 15. Regulatory Information

# U.S. Federal Regulations:

### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Serious eye damage or eye irritation

#### Sara Section 313:

**Hazard Class:** 

**Packing Group:** 

**Limited Quantity:** 

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

# U.S. State Regulations:

### California Proposition 65:

No Prop. 65 warning is required.

Date Printed: 9/13/2018 Page 6 / 6

#### 16. Other Information

**HMIS RATINGS** 

Health: 2\* Flammability: 1 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 1 Instability 0

SDS REVISION DATE: 9/13/2018

**REASON FOR REVISION:** Substance Chemical Name Changed

Substance Regulatory CAS Number Changed

Substance Hazardous Flag Changed Substance Hazard Threshold % Changed

Substance and/or Product Properties Changed in Section(s):

08 - Exposure Controls/Personal Protection

15 - Regulatory Information16 - Other Information

Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Date Printed: 9/13/2018 Page 1 / 6

# Safety Data Sheet



www.rustoleum.com

### 1. Identification

Product Name: Epoxy-Shell WB50 Part B EP6010 Revision Date: 9/13/2018

Product Identifier: 311545 Supercedes Date: 3/1/2018

Recommended Use: High Performance/Epoxy Coating

Supplier: Rust-Oleum Corporation Manufacturer: Rust-Oleum Corporation 11 Hawthorn Parkway 11 Hawthorn Parkway

Vernon Hills, IL 60061 Vernon Hills, IL 60061

USA

USA

Preparer: Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 847-367-7700

### 2. Hazard Identification

#### Classification

Symbol(s) of Product





Signal Word Warning

#### Possible Hazards

17% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### **GHS HAZARD STATEMENTS**

Germ Cell Mutagenicity, category 2 H341 Suspected of causing genetic defects

STOT, single exposure, category 3, RTI H335 May cause respiratory irritation.

Skin Irritation, category 2 H315 Causes skin irritation.

Eye Irritation, category 2 H319 Causes serious eye irritation.

Skin Sensitizer, category 1 H317 May cause an allergic skin reaction.

#### GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

Date Printed: 9/13/2018 Page 2 / 6

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local, regional and national regulations.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P264 Wash hands thoroughly after handling.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 For specific treatment see label

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P272 Contaminated work clothing should not be allowed out of the workplace.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

#### **GHS SDS PRECAUTIONARY STATEMENTS**

P363 Wash contaminated clothing before reuse.

# 3. Composition / Information On Ingredients

#### HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt.%</u> Range	GHS Symbols	GHS Statements
Epichlorohydrin-bisphenol A resin	25068-38-6	75-100	GHS07	H315-317-319-335

Date Printed: 9/13/2018 Page 3 / 6

O-Cresyl, Glycidylether 2210-79-9 2.5-10 GHS06-GHS08 H315-317-331-341

Dipropylene Glycol Monobutyl Ether 29911-28-2 2.5-10 Not Available Not Available

### 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

# 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** No unusual fire or explosion hazards noted. Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): No Information

#### 6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

#### 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

# 8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Epichlorohydrin-bisphenol A resin	25068-38-6	85.0	N.E.	N.E.	N.E.	N.E.
O-Cresyl, Glycidylether	2210-79-9	10.0	N.E.	N.E.	N.E.	N.E.
Dipropylene Glycol Monobutyl Ether	29911-28-2	10.0	N.E.	N.E.	N.E.	N.E.

#### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Date Printed: 9/13/2018 Page 4 / 6

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

# 9. Physical and Chemical Properties

**Physical State:** Appearance: Liquid Liquid Odor Threshold: Odor: Solvent Like N.E. Relative Density: pH: 1.133 N.A. Freeze Point, °C: Viscosity: N.D. N.D. Solubility in Water: Slight Partition Coefficient, n-octanol/ N.D. water: Decompostion Temp., °C: N.D. Boiling Range, °C: 230 - 260 Explosive Limits, vol%: N.A. - N.A. Flammability: Does not Support Combustion Flash Point, °C: 94 **Evaporation Rate:** Auto-ignition Temp., °C: Slower than Ether N.D. Vapor Density: Vapor Pressure: N.D. Heavier than Air

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

**CONDITIONS TO AVOID:** No Information

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

# 11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
25068-38-6	Epichlorohydrin-bisphenol A resin	11400 mg/kg Rat	>5000	25 g/L
2210-79-9	O-Cresyl, Glycidylether	4000 mg/kg Rat	N.E.	6.1 mg/L Rat

N.E. - Not Established

# 12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

# 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

Date Printed: 9/13/2018 Page 5 / 6

# 14. Transport Information

Domestic (USDOT) International (IMDG) Air (IATA) TDG (Canada)
UN Number: N.A. N.A. N.A. N.A. N.A.

Proper Shipping Name: Not Regulated Not Regulated Not Regulated Not Regulated

Hazard Class:N.A.N.A.N.A.N.A.Packing Group:N.A.N.A.N.A.N.A.Limited Quantity:NoNoNoNo

# 15. Regulatory Information

# **U.S. Federal Regulations:**

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

# **U.S. State Regulations:**

#### California Proposition 65:

No Prop. 65 warning is required.

#### 16. Other Information

**HMIS RATINGS** 

Health: 2\* Flammability: 1 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 1 Instability 0

SDS REVISION DATE: 9/13/2018

REASON FOR REVISION: Substance and/or Product Properties Changed in Section(s):

15 - Regulatory Information16 - Other Information

Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Date Printed: 9/13/2018 Page 6 / 6

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.