

Safety Data Sheet



1. Identification

| | | | |
|-----------------------------|--|-------------------------|--|
| Name on Label: | Part A | | |
| Product Name: | ULTRA-HYDRO STOP DUNES TAN 3 GAL PART A | Revision Date: | 4/17/2025 |
| Product Identifier: | 359074 | Supersedes Date: | 12/6/2019 |
| Recommended Use: | Part A/ Base | | |
| Supplier: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA | Manufacturer: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA |
| Preparer: | Regulatory Department | | |
| Emergency Telephone: | 24 Hour Hotline: 847-367-7700 | | |

2. Hazard Identification

Classification

Symbol(s) of Product



Signal Word

Warning

Possible Hazards

8% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS Hazard Statements

| | | |
|-----------------------------|------|--------------------------------------|
| Skin Irritation, category 2 | H315 | Causes skin irritation. |
| Skin Sensitizer, category 1 | H317 | May cause an allergic skin reaction. |
| Eye Irritation, category 2A | H319 | Causes serious eye irritation. |

GHS Label Precautionary Statements

| | |
|----------------|--|
| P261 | Avoid breathing dust, fumes, gas, mists, vapours, or spray. |
| P264 | Wash thoroughly after handling. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |
| P280 | Wear protective gloves, protective clothing, eye protection, and face protection. |
| P302+P352 | IF ON SKIN: Wash with plenty of soap and water. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P321 | Specific treatment (see notice on this label). |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice. |

P337+P317

If eye irritation persists: Get medical help.

P362+P364

Take off contaminated clothing and wash it before reuse.

P501

Dispose of contents and container in accordance with local, regional and national regulations.

GHS SDS Precautionary Statements

P363

Wash contaminated clothing before reuse.

3. Composition / Information on Ingredients**HAZARDOUS SUBSTANCES**

| <u>Chemical Name</u> | <u>CAS-No.</u> | <u>Wt.% Range</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|-----------------------------------|----------------|-----------------------|--------------------|------------------------|
| Epichlorohydrin-Bisphenol A Resin | 25068-38-6 | 80-100 | GHS07 | H315-317-319 |
| Benzyl Alcohol | 100-51-6 | 5.0-10 | GHS07 | H302+H312+H332-317-319 |
| Titanium Dioxide | 13463-67-7 | 5.0-10 | Not Available | Not Available |
| Amorphous Silica | 7631-86-9 | 0.1-1.0 | Not Available | Not Available |
| C.I. Pigment Yellow 14 | 5468-75-7 | 0.1-1.0 | Not Available | Not Available |

Actual concentrations of ingredients are withheld as trade secret.

4. First Aid Measures

First Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

First Aid - Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing clothing. Get medical attention immediately. Wash clothing separately before reuse. Wash contaminated clothing and decontaminate footwear before reuse.

First Aid - Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

First Aid - Ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: Aqueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

Unusual Fire and Explosion Hazards: Keep containers tightly closed.

Special Fire Fighting Procedures: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred. Containers can rupture and release highly toxic material if exposed to heat. Substance is non-combustible but reacts with many metals to form explosive hydrogen gas.

Special Fire and Explosion Hazard (Combustible Dust): Not a combustible dust.

6. Accidental Release Measures

Steps to Be Taken If Material Is Released or Spilled: Avoid runoff into sewers and waterways. Provide ventilation and approach spill from upwind using proper personal protective equipment as indicated in Section 8. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

7. Handling and Storage

Handling: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid prolonged or repeated contact with skin. Do not get in eyes, on skin or clothing.

Storage: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|-----------------------------------|------------|-----------------------|---------------|----------------|--------------|------------------|
| Epichlorohydrin-Bisphenol A Resin | 25068-38-6 | 85.0 | N.E. | N.E. | N.E. | N.E. |
| Benzyl Alcohol | 100-51-6 | 10.0 | N.E. | N.E. | N.E. | N.E. |
| Titanium Dioxide | 13463-67-7 | 10.0 | 0.2 mg/m3 | N.E. | 15 mg/m3 | N.E. |
| Amorphous Silica | 7631-86-9 | 1.0 | N.E. | N.E. | 20 mppcf | N.E. |
| C.I. Pigment Yellow 14 | 5468-75-7 | 1.0 | N.E. | N.E. | N.E. | N.E. |

PERSONAL PROTECTION

Engineering Controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 (U.S.) and/or SOR/86-304 Part XII 12.13 and CSA Standard Z180.1 (Canada) requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin Protection: Use impervious gloves to prevent skin contact and absorption of this material through the skin.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other Protective Equipment: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

| | | | |
|------------------------------------|-----------------------------|--|-------------------|
| Physical State | Liquid | Decomposition Temperature, °C | N.D. |
| Color | Tan | pH | N.A. |
| Odor | Solvent Like | Kinematic Viscosity | N.D. |
| Odor Threshold | N.E. | Solubility in Water | Slight |
| Freezing Point / Melting Point, °C | N.D. | Partition Coefficient, n-octanol/water | N.D. |
| Boiling Range, °C | 205 - 2,500 | Vapor Pressure | N.D. |
| Flammability | Does not Support Combustion | Evaporation Rate | Slower than Ether |
| Lower Explosion Limit, vol% | 1.3 | Specific Gravity | 1.220 |
| Upper Explosion Limit, vol% | 13.0 | Vapor Density | Heavier than Air |
| Flash Point, °C | 101 | Particle Characteristics | N.A. |
| Auto-Ignition Temperature, °C | N.D. | | |

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid contact with metals. Avoid excess heat.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalis. Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

Effects of Overexposure - Eye Contact: Can cause severe eye irritation. Causes eye burns. Causes eye and skin irritation which may lead to dermatitis with repeated exposures. Irritating, and may injure eye tissue if not removed promptly. High vapor concentrations can irritate eyes, nose and respiratory passages.

Effects of Overexposure - Skin Contact: Prolonged or repeated skin contact may cause irritation. Substance is corrosive. Causes severe skin burns. Causes skin irritation. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis). Severely irritating; may cause permanent skin damage.

Effects of Overexposure - Inhalation: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs.

Effects of Overexposure - Ingestion: Corrosive and may cause severe and permanent damage to mouth, throat and stomach. Harmful if swallowed.

Effects of Overexposure - Chronic Hazards: Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010) Prolonged or repeated skin contact may cause dermatitis.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
|------------|-----------------------------------|------------------|--------------------|-------------|
| 25068-38-6 | Epichlorohydrin-Bisphenol A Resin | 11400 mg/kg Rat | >5000 | 25 g/L |
| 100-51-6 | Benzyl Alcohol | 1230 mg/kg Rat | 2000 mg/kg Rabbit | 11 mg/L Rat |
| 13463-67-7 | Titanium Dioxide | >2000 mg/kg Rat | 6000 | N.E. |
| 7631-86-9 | Amorphous Silica | 7900 mg/kg Rat | >5000 mg/kg Rabbit | 25 mg/L |
| 5468-75-7 | C.I. Pigment Yellow 14 | >10000 mg/kg Rat | >3000 mg/kg Rat | N.E. |

N.E. - Not Established

12. Ecological Information

Ecological Information: No ecotoxicity data was found for this product.

13. Disposal Considerations

Disposal: Dispose of material in accordance to local, state, and federal regulations and ordinances. RCRA Hazardous Waste: This material, when discarded or disposed of, could be a hazardous waste according to federal regulations (40 CFR 261) due to the characteristic of corrosivity (D002). Check state and local regulations for disposal requirements. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate, or otherwise inappropriate.

14. Transport Information

| | Domestic (USDOT) | International (IMDG) | Air (IATA) | TDG (Canada) |
|-----------------------|------------------|---|---|---------------|
| UN Number: | N.A. | 3082 | 3082 | N.A. |
| Proper Shipping Name: | Not Regulated | Environmentally hazardous substance, Liquid, N.O.S.(Epoxy resin) MARINE POLLUTANT | Environmentally hazardous substance, Liquid, N.O.S.(Epoxy resin) MARINE POLLUTANT | Not Regulated |
| Hazard Class: | N.A. | 9 | 9 | N.A. |
| Packing Group: | N.A. | III | III | N.A. |
| Limited Quantity: | No | No | No | No |

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation

SARA Section 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No SARA 313 components exist in this product.

Toxic Substances Control Act

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations:

California Proposition 65

WARNING:

Reproductive Harm - www.P65Warnings.ca.gov.

16. Other Information

HMIS RATINGS

| | | | | | | | |
|---------|----|---------------|---|------------------|---|----------------------|---|
| Health: | 2* | Flammability: | 1 | Physical Hazard: | 0 | Personal Protection: | X |
|---------|----|---------------|---|------------------|---|----------------------|---|

NFPA RATINGS

| | | | | | |
|---------|---|---------------|---|--------------|---|
| Health: | 2 | Flammability: | 1 | Instability: | 0 |
|---------|---|---------------|---|--------------|---|

Volatile Organic Compounds: 25 g/L

SDS REVISION DATE: 4/17/2025

REASON FOR REVISION:

Product Composition Changed
 Substance and/or Product Properties Changed in Section(s):
 01 - Identification
 02 - Hazard Identification
 03 - Composition / Information on Ingredients
 05 - Fire-Fighting Measures
 08 - Exposure Controls / Personal Protection
 09 - Physical & Chemical Properties
 11 - Toxicological Information
 14 - Transport Information
 15 - Regulatory Information
 Substance Hazard Threshold % Changed
 Substance Hazardous Flag Changed
 Substance Chemical Name Changed
 Revision Statement(s) Changed

Legend:

N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.