

# Safety Data Sheet



## 1. Identification

<b>Product Name:</b>	AUTORF 6PK MARKER POLISHED METAL	<b>Revision Date:</b>	5/14/2015
<b>Product Identifier:</b>	HON1019A	<b>Supersedes Date:</b>	5/4/2015
<b>Product Use/Class:</b>	Touch-Up Paint/Marker		
<b>Supplier:</b>	The Testors Corporation 440 Blackhawk Park Drive Rockford, IL 61104 USA	<b>Manufacturer:</b>	The Testors Corporation 440 Blackhawk Park Drive Rockford, IL 61104 USA
<b>Preparer:</b>	Regulatory Department		
<b>Emergency Telephone:</b>	24 Hour Hotline: 847-367-7700		

## 2. Hazard Identification

**EMERGENCY OVERVIEW:** May cause eye, skin, or respiratory tract irritation. KEEP OUT OF REACH OF CHILDREN. Harmful if inhaled. Harmful if swallowed. Causes eye irritation. Flammable liquid and vapor. Use ventilation necessary to keep exposures below recommended exposure limits, if any. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Vapor Harmful. Causes Eye, Skin, Nose, and Throat Irritation.

### Classification

### Symbol(s) of Product



### Signal Word

Danger

### GHS HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Acute Toxicity, Oral, category 5	H303	May be harmful if swallowed.
Acute Toxicity, Dermal, category 5	H313	May be harmful in contact with skin.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Organic Peroxide, categories C, D	H242	Heating may cause a fire.
Aspiration Hazard, category 2	H305	May be harmful if swallowed and enters airways
Eye Irritation, category 2B	H320	Causes eye irritation
Germ Cell Mutagenicity, category 1B	H340	May cause genetic defects . Classified as mutagenic Category 1 if one ingredient is present at or above 0.1% Applies to liquids, Solids (w/w units) and gases (v/v). The substance may also have its own exposure limit. Routes of exposure are dependant on ingredient form.

Carcinogenicity, category 1B	H350	May cause cancer. Classified as carcinogenic Category 1 on the basis of epidemiological and/or animal data. Mixtures are classified as carcinogenic when at least 1 ingredient has been classified as carcinogenic and is present at 0.1% or above. Routes of exposure are dependant on ingredient form.
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.
STOT, repeated exposure, category 2	H373	May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

#### GHS LABEL PRECAUTIONARY STATEMENTS

P102	Keep out of reach of children.
P103	Read label before use.
P234	Keep only in original container.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P285	In case of inadequate ventilation wear respiratory protection.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P350	Gently wash with plenty of soap and water.
P374	Fight fire with normal precautions from a reasonable distance.
P402	Store in a dry place.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P362	Take off contaminated clothing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P201	Obtain special instructions before use.
P308+P313	IF exposed or concerned: Get medical advice/attention.

### 3. Composition/Information On Ingredients

#### HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt.% Range</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
1-Methoxy-2-propyl acetate	108-65-6	25-50	GHS02-GHS06	H226-310
Toluene	108-88-3	25-50	GHS02-GHS07-GHS08	H225-302-332-361-336-373-315
Stoddard Solvent	8052-41-3	2.5-10	GHS02-GHS08	H224-340-350-372
Xylene (mixed isomers)	1330-20-7	1.0-2.5	GHS02-GHS07	H226-312-332-315
Ethylbenzene	100-41-4	0.1-1.0	GHS02-GHS07	H225-332
Carbon Black	1333-86-4	0.1-1.0	GHS02	H251
Titanium Dioxide	13463-67-7	0.1-1.0		

The text for GHS Hazard Statements shown above (if any) is given in the "16. Other Information" section.

### 4. First-aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

## 5. Fire-fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** No unusual fire or explosion hazards noted. Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials. Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Keep away from heat, sparks, flame and sources of ignition. Avoid excess heat. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids.

## 8. Exposure Controls/Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
1-Methoxy-2-propyl acetate	108-65-6	40.0	50 ppm (AIHA WEEL)	N.E.	N.E.	N.E.
Toluene	108-88-3	30.0	20 ppm	N.E.	200 ppm	300 ppm
Stoddard Solvent	8052-41-3	5.0	100 ppm	N.E.	500 ppm	N.E.
Xylene (mixed isomers)	1330-20-7	5.0	100 ppm	150 ppm	100 ppm	N.E.
Ethylbenzene	100-41-4	1.0	20 ppm	125 ppm	100 ppm	N.E.
Carbon Black	1333-86-4	1.0	3 mg/m3 (Inhalable Dust)	N.E.	3.5 mg/m3	N.E.
Titanium Dioxide	13463-67-7	1.0	10 mg/m3 (Total Dust)	N.E.	15 mg/m3 [Total Dust]	N.E.

### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

## 9. Physical and Chemical Properties

<b>Appearance:</b>	Liquid	<b>Physical State:</b>	Liquid
<b>Odor:</b>	Solvent Like	<b>Odor Threshold:</b>	N.E.
<b>Relative Density:</b>	0.981	<b>pH:</b>	N.A.
<b>Freeze Point, °C:</b>	N.D.	<b>Viscosity:</b>	No Information
<b>Solubility in Water:</b>	Slight	<b>Partition Coefficient, n-octanol/water:</b>	No Information
<b>Decomposition Temp., °C:</b>	No Information	<b>Explosive Limits, vol%:</b>	1.0 - 9.5
<b>Boiling Range, °C:</b>	223 - 410	<b>Flash Point, °C:</b>	13
<b>Flammability:</b>	Does not Support Combustion	<b>Auto-ignition Temp., °C:</b>	No Information
<b>Evaporation Rate:</b>	Slower than Ether	<b>Vapor Pressure:</b>	No Information
<b>Vapor Density:</b>	Heavier than Air		

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid temperatures above 120 ° F. Avoid contact with strong acid and strong bases. Avoid all possible sources of ignition.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**HAZARDOUS DECOMPOSITION:** By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Causes Serious Eye Irritation

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May be absorbed through the skin in harmful amounts. Causes skin irritation. Allergic reactions are possible.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** IARC lists Ethylbenzene as a possible human carcinogen (group 2B). Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)Contains carbon black. Chronic

inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black.

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
108-65-6	1-Methoxy-2-propyl acetate	8532 mg/kg Rat	>5 g/kg Rabbit	N.I.
108-88-3	Toluene	636 mg/kg Rat	8390 mg/kg Rabbit	12.5 mg/L Rat
1330-20-7	Xylene (mixed isomers)	4300 mg/kg Rat	N.I.	47635 mg/L Rat
100-41-4	Ethylbenzene	3500 mg/kg Rat	15354 mg/kg Rabbit	17.2 mg/L Rat
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	N.I.	N.I.

N.I. - No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

## 14. Transport Information

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>TDG (Canada)</u>
<b>UN Number:</b>	N.A.	1263	1263	N.A.
<b>Proper Shipping Name:</b>	Paint Products in Limited Quantities	Paint	Paint	Paint Products in Limited Quantities
<b>Hazard Class:</b>	N.A.	3	3	N.A.
<b>Packing Group:</b>	N.A.	II	II	N.A.
<b>Limited Quantity:</b>	Yes	Yes	No	Yes

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
----------------------	----------------

Toluene	108-88-3
Xylene (mixed isomers)	1330-20-7
Ethylbenzene	100-41-4

**Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

**CALIFORNIA PROPOSITION 65:**

WARNING: This product contains a substance known to the State of California to cause cancer.

<u>Chemical Name</u>	<u>CAS-No.</u>
Ethylbenzene	100-41-4
Carbon Black	1333-86-4
Titanium Dioxide	13463-67-7
Benzene	71-43-2
Naphthalene	91-20-3

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

WARNING: This product contains a substance known to the State of California to cause birth defects or other reproductive harm.

<u>Chemical Name</u>	<u>CAS-No.</u>
Toluene	108-88-3
N-Methyl 2-Pyrrolidone	872-50-4
Benzene	71-43-2

**International Regulations:****CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**16. Other Information****HMIS RATINGS**

Health: 2\*      Flammability: 3      Physical Hazard: 0      Personal Protection: X

CANADIAN WHMIS CLASS: B2 D2A

**NFPA RATINGS**

Health: 2      Flammability: 3      Instability: 0

VOLATILE ORGANIC COMPOUNDS, g/L: 712

MSDS REVISION DATE: 5/14/2015





REASON FOR REVISION: No Information

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H251	Self-heating: may catch fire.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H350	May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H361	Suspected of damaging fertility or the unborn child. Classified Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.
H372	Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H373	May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02	
GHS06	
GHS07	
GHS08	

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.