

Material Safety Data Sheet

24 Hour Assistance:
1-847-367-7700
Rust-Oleum Corp.
www.rustoleum.com

Section 1 - Chemical Product / Company Information

Product Name: STRUST SSPR 6PK LOWES MEX GLS ORANGE
Revision Date: 11/24/2009
Identification Number: 253925
Product Use/Class: Marking Paint/Aerosol
Supplier: Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, IL 60061
USA
Manufacturer: Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, IL 60061
USA
Preparer: Regulatory Department

Section 2 - Composition / Information On Ingredients

| Chemical Name | CAS Number | Weight % Less Than | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA | OSHA PEL CEILING |
|-----------------------------------|-------------|--------------------|---------------|----------------|-----------------------|------------------|
| Gasoline | 67-64-1 | 30.0 | 500 ppm | 750 ppm | 1000 ppm | N.E. |
| Refined Petroleum Gas | 68476-86-8 | 25.0 | N.E. | N.E. | N.E. | N.E. |
| Alkyd Resin | PROPRIETARY | 20.0 | N.E. | N.E. | N.E. | N.E. |
| Ethyl Acetate | 1330-20-7 | 10.0 | 100 ppm | 150 ppm | 100 ppm | N.E. |
| Xylene | 123-86-4 | 10.0 | 150 ppm | 200 ppm | 150 ppm | N.E. |
| Benzene | 100-41-4 | 5.0 | 100 ppm | 125 ppm | 100 ppm | N.E. |
| Titanium Dioxide | 13463-67-7 | 5.0 | 10 mg/m3 | N.E. | 15 mg/m3 (Total Dust) | N.E. |
| Diethylene Glycol Monobutyl Ether | 111-76-2 | 5.0 | 20 ppm | N.E. | 50 ppm | N.E. |

Section 3 - Hazards Identification

Emergency Overview ***: Contents Under Pressure. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Vapors may cause flash fire or explosion. Harmful if swallowed. Extremely flammable liquid and vapor.

Effects Of Overexposure - Eye Contact: Causes eye irritation.

Effects Of Overexposure - Skin Contact: May be harmful if absorbed through skin. Prolonged or repeated contact may cause skin irritation. Substance may cause slight skin irritation.

Effects Of Overexposure - Inhalation: High vapor concentrations are irritating to the eyes, nose, throat and lungs. Avoid breathing vapors. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Harmful if inhaled.

Effects Of Overexposure - Ingestion: Aspiration hazard if swallowed; can enter lungs and cause damage. Substance may be harmful if swallowed.

Effects Of Overexposure - Chronic Hazards: Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the material.

OSHA lists Ethylbenzene as a possible human carcinogen (group 2B). May cause central nervous system disorder (e.g., narcosis involving loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

: Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention
NOT allow rubbing of eyes or keeping eyes closed.

: Aid - Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

: Aid - Inhalation: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get
medical assistance immediately.

: Aid - Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and
cause severe lung damage. Get immediate medical attention.

Action 5 - Fire Fighting Measures

Flash Point: -156 F
(no flash)

LOWER EXPLOSIVE LIMIT: 0.7 %
UPPER EXPLOSIVE LIMIT : 12.8 %

Extinguishing Media: Film Forming Foam, Carbon Dioxide, Dry Chemical, Water Fog

Special Fire And Explosion Hazards: Water spray may be ineffective. Closed containers may explode when exposed to extreme heat.
Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. FLASH POINT IS LESS THAN 20 ° F.
EXTREMELY FLAMMABLE LIQUID AND VAPOR! Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and
open flame. Perforation of the pressurized container may cause bursting of the can.

Special Firefighting Procedures: Evacuate area and fight fire from a safe distance.

Action 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Contain spilled liquid with sand or earth. DO NOT use combustible materials such
as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Remove all
sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools.

Action 7 - Handling And Storage

Handling: Wash thoroughly after handling. Follow all MSDS/label precautions even after container is emptied because it may retain
product residues. Avoid breathing vapor or mist. Use only in a well-ventilated area. Wash hands before eating.

Storage: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 ° F. Store
in small quantities in buildings designed and protected for storage of NFPA Class I flammable liquids. Contents under pressure. Do not
expose to heat or store above 120 ° F.

Action 8 - Exposure Controls / Personal Protection

Engineering Controls: Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosure
with exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof
ventilation equipment.

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed.
If workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor
cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure
limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an
uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide
adequate protection.

avoid adequate skin protection.

Protection: Use safety eyewear designed to protect against splash of liquids.

er protective equipment: Refer to safety supervisor or industrial hygienist for further information regarding personal protective
pment and its application.

ienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking.

ction 9 - Physical And Chemical Properties

| | | | |
|-----------------|--------------|-------------------|-------------------|
| ing Range: | -34 - 999 F | Vapor Density: | Heavier than Air |
| r: | Solvent Like | Odor Threshold: | N.E. |
| earance: | Liquid | Evaporation Rate: | Faster than Ether |
| ibility in H2O: | Slight | | |
| ize Point: | N.D. | Specific Gravity: | 0.789 |
| or Pressure: | N.D. | PH: | N.A. |
| sical State: | Liquid | | |

section 16 for abbreviation legend)

ction 10 - Stability And Reactivity

ditions To Avoid: Avoid temperatures above 120 ° F. Avoid all possible sources of ignition.

mpatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

ardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes. By open flame, carbon monoxide
carbon dioxide.

ardous Polymerization: Will not occur under normal conditions.

ability: This product is stable under normal storage conditions.

ction 11 - Toxicological Information

duct LD50: N.D.

Product LC50: N.D.

| imical Name | LD50 | LC50 |
|-----------------------------|--------------------------|---------------------------------|
| tone | 5800 mg/kg (Rat) | 50100 mg/m3 (Rat, 8Hr) |
| efined Petroleum Gas | N.E. | N.E. |
| lified Alkyd Resin | N.E. | N.E. |
| ine | 4300 mg/kg (Rat, Oral) | 5000 ppm (Rat, Inhalation, 4Hr) |
| tyl Acetate | 13100 mg/kg (Rat, Oral) | 2000 ppm (Rat, Inhalation, 4 H |
| lbenzene | 3500 mg/kg (Rat, Oral) | N.E. |
| nium Dioxide | >7500 mg/kg (Rat, Oral) | N.E. |
| lene Glycol Monobutyl Ether | 1519 mg/kg (Mouse, Oral) | 700 ppm (Rat, Inhalation, 7Hr) |

ction 12 - Ecological Information

logical Information: Product is a mixture of listed components.

ction 13 - Disposal Information

ction 14 - Transportation Information

| | | | |
|-----------------------|---------------------------|-------------------|------|
| Proper Shipping Name: | ORM-D, Consumer Commodity | Packing Group: | N.A. |
| Technical Name: | N.A. | Hazard Subclass: | N.A. |
| Hazard Class: | 2.1 | Resp. Guide Page: | 126 |
| UN/NA Number: | UN1950 | | |

ction 15 - Regulatory Information

CLA - SARA Hazard Category

product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311and 312 of the Superfund
ndment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following
gories:

EDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD, PRESSURIZED GAS HAZARD

IA Section 313:

ed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title I
Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>mical Name</u> | <u>CAS Number</u> |
|------------------------------|-------------------|
| ne | 1330-20-7 |
| /lbenzene | 100-41-4 |
| /lene Glycol Monobutyl Ether | 111-76-2 |

ic Substances Control Act:

ed below are the substances (if any) contained in this product that are subject to the reporting requirements of TSCA 12(B) if export
n the United States:

the policy of Rust-Oleum Corporation to use only TSCA compliant materials in its products.

i. State Regulations: As follows -

/ Jersey Right-to-Know:

following materials are non-hazardous, but are among the top five components in this product.

e

nsylvania Right-to-Know:

following non-hazardous ingredients are present in the product at greater than 3%.

| <u>mical Name</u> | <u>CAS Number</u> |
|-------------------|-------------------|
| um Sulfate | 7727-43-7 |

ifornia Proposition 65:

RNING! This product contains a chemical(s) known by the State of California to cause cancer.

International Regulations: As follows -

ADIAN WHMIS:

MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

ADIAN WHMIS CLASS: AB5 D2A D2B

Section 16 - Other Information

S Ratings:

Health: 2* Flammability: 4 Reactivity: 0 Personal Protection: X

REASON FOR REVISION: Regulatory Update

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.