Date Printed: 9/3/2015 Page 1 / 5

Safety Data Sheet



www.multicolorpaint.com

1. Identification

Product Name: MULTSPC QT STONE ACCNT LIMESTONE Revision Date: 8/24/2015

05SLS

Product Identifier: 997216QT Supercedes Date: New SDS

Product Use/Class: Paint/Waterborne

Supplier: Multicolor Specialties, Inc. Manufacturer: Multicolor Specialties, Inc.

1200 Storbeck Drive Waupun, WI 53963

USA

USA

1200 Storbeck Drive

Waupun, WI 53963

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 847-367-7700

2. Hazard Identification

Classification

Symbol(s) of Product





Signal Word

Danger

Possible Hazards

6% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

Skin Sensitizer, category 1 H317 May cause an allergic skin reaction.

Acute Toxicity, Inhalation, category 4 H332 Harmful if inhaled.

Carcinogenicity, category 1B H350 May cause cancer. Classified as carcinogenic Category 1 on the basis of

epidemiological and/or animal data. Mixtures are classified as carcinogenic when at least 1 ingredient has been classified as carcinogenic and is present at 0.1% or above Routes of exposure are dependent on ingredient form.

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P261 Avoid breathing dust, fumes, gases, mists, vapors, or spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

GHS SDS PRECAUTIONARY STATEMENTS

Wash contaminated clothing before reuse.

Date Printed: 9/3/2015 Page 2 / 5

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

P363

Chemical Name	CAS-No.	<u>Wt.%</u> <u>Range</u>	GHS Symbols	GHS Statements
Titanium Dioxide	13463-67-7	2.5-10	No Information	No Information
Ethylene Glycol Monobutyl Ether	111-76-2	1.0-2.5	GHS06	H302-311-315-319-330
Propanoic acid,2-methyl-,monoester with 2,2,4-trimethyl-1,3-pentanediol	25265-77-4	1.0-2.5	No Information	No Information
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	64742-52-5	0.1-1.0	GHS08	H350
1,2-Benzisothiozole-3(2H)-one	2634-33-5	<0.1	GHS05-GHS07	H302-315-317-318

4. First-aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, rinse mouth with water. If feeling unwell, get medical attention. Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

8. Exposure Controls/Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Titanium Dioxide	13463-67-7	5.0	10 mg/m3	N.E.	15 mg/m3	N.E.
Ethylene Glycol Monobutyl Ether	111-76-2	5.0	20 ppm	N.E.	50 ppm	N.E.

Date Printed: 9/3/2015 Page 3 / 5

Propanoic acid,2- methyl-,monoester with 2,2,4- trimethyl-1,3-pentanediol	25265-77-4	5.0	N.E.	N.E.	N.E.	N.E.
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	64742-52-5	1.0	N.E.	N.E.	N.E.	N.E.
1,2-Benzisothiozole-3(2H)-one	2634-33-5	0.1	N.E.	N.E.	N.E.	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

9. Physical and Chemical Properties

Appearance: **Physical State:** Liquid Liquid Odor: Odor Threshold: Solvent Like N.E. Relative Density: N.D. pH: 1.076 Freeze Point, °C: 32 Viscosity: No Information Solubility in Water: Partition Coefficient, n-Miscible N.D. octanol/water: Decompostion Temp., °C: N.D. Boiling Range, °C: Explosive Limits, vol%: -18 - 244 0.6 - 10.6Flammability: Does not Support Combustion Flash Point, °C: 94 **Evaporation Rate:** Slower than Ether Auto-ignition Temp., °C: N.D. Vapor Pressure: Vapor Density: Heavier than Air N.D.

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid contact with strong acid and strong bases.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

Date Printed: 9/3/2015 Page 4 / 5

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	N.I.	N.I.
111-76-2	Ethylene Glycol Monobutyl Ether	470 mg/kg Rat	220 mg/kg Rabbit	N.I.
25265-77-4	Propanoic acid,2-methyl-,monoester with 2,2,4-trimethyl-1,3-pentanediol	3200 mg/kg Rat	>15200 mg/kg Rat	N.I.
2634-33-5	1,2-Benzisothiozole-3(2H)-one	1020 mg/kg Rat	N.I.	N.I.

N.I. - No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

14. Transport Information

	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	TDG (Canada)
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.Ethylene Glycol Monobutyl Ether111-76-2

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

Date Printed: 9/3/2015 Page 5 / 5

16. Other Information

HMIS RATINGS

Health: 1 Flammability: 1 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 1 Flammability: 1 Instability 0

VOLATILE ORGANIC COMPOUNDS, g/L: 205

SDS REVISION DATE: 8/24/2015

REASON FOR REVISION:

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.