Material Safety Data Sheet

24 Hour Assistance: 1-847-367-7700 Rust-Oleum Corp. www.rustoleum.com

Section 1 - Chemical Product / Company Information

Product Name: Varathane Canadian Pro Gloss Revision Date: 10/21/2008

Identification Number: C230000

Crystal Clear Waterbased

11 Hawthorn Parkway

Product Use/Class: Finish/Varathane

Supplier: Rust-Oleum Corporation Manufacturer: Rust-Oleum Corporation

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Vernon Hills, IL 60061 USA

Preparer: Regulatory Department

Section 2 - Composition / Information On Ingredients

		Weight % Less				<u>OSHA PEL</u>
Chemical Name	CAS Number	<u>Than</u>	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	CEILING
Dipropylene Glycol Monomethyl Ether	34590-94-8	5.0	100 ppm	N.E.	N.E.	N.E.
Methyl-n 2-Pyrrolidone	872-50-4	5.0	N.E.	N.E.	N.E.	N.E.
Dipropylene Glycol Monobutyl Ether	29911-28-2	5.0	N.E.	N.E.	N.E.	N.E.

Section 3 - Hazards Identification

*** Emergency Overview ***: No Information.

Effects Of Overexposure - Eye Contact: No Information.

Effects Of Overexposure - Skin Contact: No Information.

Effects Of Overexposure - Inhalation: No Information.

Effects Of Overexposure - Ingestion: No Information.

Effects Of Overexposure - Chronic Hazards: No Information.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

Section 4 - First Aid Measures

First Aid - Eye Contact: No Information.

First Aid - Skin Contact: No Information.

First Aid - Inhalation: No Information.

First Aid - Ingestion: No Information.

Section 5 - Fire Fighting Measures

Flash Point: 175 F LOWER EXPLOSIVE LIMIT: 0.6 % (Setaflash) UPPER EXPLOSIVE LIMIT: 17.0 %

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam, Water Fog

Unusual Fire And Explosion Hazards: No unusual Hazards

Special Firefighting Procedures: No Information.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Isolate and dispose of in accordance with state and federal regualtions.

Section 7 - Handling And Storage

Handling: No Information.

Storage: No Information.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: No Information.

Respiratory Protection: No Information.

Skin Protection: No Information.

Eye Protection: No Information.

Other protective equipment: No Information.

Hygienic Practices: No Information.

Section 9 - Physical And Chemical Properties

Boiling Range: 192 - 999 F Vapor Density: Heavier than air

Odor: Ammonia-like Odor Threshold: N.E.

Appearance: Slightly cloudy, particle free Evaporation Rate: Slower than ether

Solubility in H2O: Miscible

Freeze Point: N.D. Specific Gravity: 1.021 Vapor Pressure: N.D. PH: 8.0 - 8.5 Physical State: Liquid

(See section 16 for abbreviation legend)

Section 10 - Stability And Reactivity

Conditions To Avoid: No Information.

Incompatibility: No Information.

Hazardous Decomposition: Will not occur under normal conditions

Hazardous Polymerization: Will not occur under normal conditions

Stability: Stable under normal conditions

Section 11 - Toxicological Information

Product LD50: N.D. Product LC50: N.D.

Chemical NameLD50LC50Dipropylene Glycol Monomethyl Ether5350 mg/kg RATN.E.Methyl-n 2-Pyrrolidone4200 mg/kg RatN.E.Dipropylene Glycol Monobutyl Ether4400 mg/kg oral RATN.E.

Section 12 - Ecological Information

Ecological Information: No Information.

Section 13 - Disposal Information

Disposal Information: Dispose of in accordance with state and federal regulations

Section 14 - Transportation Information

DOT Proper Shipping Name: Paint Packing Group: --DOT Technical Name: --- Hazard Subclass: --DOT Hazard Class: Not Regulated Resp. Guide Page: ---

DOT UN/NA Number: ---

Section 15 - Regulatory Information

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

SARA Section 313:

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u> Methyl-n 2-Pyrrolidone **CAS Number** 872-50-4

Toxic Substances Control Act:

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of TSCA 12(B) if exported from the United States:

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name
Deionized Water
Oil Modified Polyurethane Polymer
Acrylic Resin

CAS Number 7732-18-5 NOT AVAILABLE PROPRIETARY

Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>
Deionized Water
Oil Modified Polyurethane Polymer
Acrylic Resin

CAS Number 7732-18-5 NOT AVAILABLE PROPRIETARY

California Proposition 65:

This product contains no known chemcials known by the State of California to cause cancer

WARNING! This product contains a chemical(s) known to the state of California to cause birth defects or other reproductive harm.

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

CANADIAN WHMIS CLASS: D2B

Section 16 - Other Information

HMIS Ratings:

Health: 1 Flammability: 1 Reactivity: 0 Personal Protection: X

REASON FOR REVISION: Regulatory Update

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.