

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 06/21/2018

Supersedes:03/02/2016

Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : PRONTO CARB SPRAY 16.25 OZ.
Product code : 817100

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Carburetor Spray

1.3. Details of the supplier of the safety data sheet

National Pronto Association
2601 Heritage Ave
Grapevine, TX 76051
T 817-430-9449

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 2 H223
Compressed gas H280
Acute Tox. 3 (Oral) H301
Acute Tox. 3 (Dermal) H311
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Repr. 2 H361
STOT SE 1 H370
STOT SE 3 H336
STOT RE 2 H373

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H223 - Flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H301+H311 - Toxic if swallowed or in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H370 - Causes damage to organs
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US)

: P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P260 - Do not breathe dust, fumes, gas, mist, vapor spray
P261 - Avoid breathing dust, fume, gas, mist, vapor spray
P264 - Wash affected areas thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,
P302+P352 - If on skin: Wash with plenty of soap and water
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P307+P311 - If exposed: Call a poison center/doctor
P308+P313 - If exposed or concerned: Get medical advice/attention
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.
P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment: See section 4.1 on SDS
P322 - Specific treatment (see ... on this label)
P330 - Rinse mouth
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse
P362+P364 - Take off contaminated clothing and wash it before reuse
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P410+P403 - Protect from sunlight. Store in a well-ventilated place
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS-US classification |
|---|--------------------|---------|--|
| Acetone | (CAS No) 67-64-1 | 30 - 50 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| Toluene | (CAS No) 108-88-3 | 10 - 30 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 |
| Methanol | (CAS No) 67-56-1 | 10 - 30 | Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370 |
| Carbon Dioxide, Liquefied, Under Pressure | (CAS No) 124-38-9 | 5 - 10 | Compressed gas, H280 |

The exact percentage is a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation : Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Immediately call a poison center or doctor/physician. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Immediately call a poison center or doctor/physician. Obtain medical attention if pain, blinking or redness persist. Direct contact with the eyes is likely to be irritating.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation : Shortness of breath. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.

Symptoms/injuries after eye contact : Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.

Symptoms/injuries after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.
Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
Other information : Aerosol Level 2.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released product, pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe dust,fumes,gas,mist,vapor spray.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Take off immediately all contaminated clothing and wash it before reuse. Observe normal hygiene standards. Keep container tightly closed. Observe strict hygiene. Reduce/avoid exposure and/or contact. Observe very strict hygiene - avoid contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.
Incompatible products : Strong bases. Strong acids.

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Toluene (108-88-3) | | |
|--|-------------------------------------|---|
| USA ACGIH | ACGIH TWA (mg/m ³) | 75 mg/m ³ |
| USA ACGIH | ACGIH TWA (ppm) | 20 ppm |
| USA OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| USA OSHA | OSHA PEL (Ceiling) (ppm) | 300 ppm |
| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 9000 mg/m ³ |
| USA ACGIH | ACGIH TWA (ppm) | 5000 ppm (Carbon dioxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |
| USA ACGIH | ACGIH STEL (mg/m ³) | 54000 |
| USA ACGIH | ACGIH STEL (ppm) | 30000 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 9000 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 5000 ppm |
| Methanol (67-56-1) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 262 mg/m ³ |
| USA ACGIH | ACGIH TWA (ppm) | 200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |
| USA ACGIH | ACGIH STEL (mg/m ³) | 328 mg/m ³ |
| USA ACGIH | ACGIH STEL (ppm) | 250 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 260 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| Benzene (71-43-2) | | |
| USA ACGIH | ACGIH TWA (ppm) | 1 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 5 ppm |
| USA ACGIH | ACGIH Ceiling (ppm) | 25 ppm |
| USA OSHA | OSHA PEL (TWA) (ppm) | 1 ppm |
| USA OSHA | OSHA PEL (Ceiling) (ppm) | 5 ppm |
| Acetone (67-64-1) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 1188 mg/m ³ |
| USA ACGIH | ACGIH TWA (ppm) | 500 ppm |
| USA ACGIH | ACGIH STEL (mg/m ³) | 1782 mg/m ³ |
| USA ACGIH | ACGIH STEL (ppm) | 750 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 2400 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |

8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Materials for protective clothing : GIVE EXCELLENT RESISTANCE:
Hand protection : Wear protective gloves.
Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------------|--|
| Respiratory protection | : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. |
| Environmental exposure controls | : Avoid release to the environment. |
| Consumer exposure controls | : Avoid contact during pregnancy/while nursing. |
| Other information | : Do not eat, drink or smoke during use. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | : Gas |
| Appearance | : Liquid. |
| Color | : Colourless to light yellow. |
| Odor | : Solvent-like odour. |
| Odor threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : -78 °C (Lowest Component-Acetone) |
| Boiling point | : 56.11 °C (Lowest Component-Acetone) |
| Flash point | : -18 °C (Lowest Component-Acetone) |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : 0.82 |
| Specific gravity / density | : 0.82 g/cm ³ |
| Solubility | : Poorly soluble in water. |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : Heating may cause a fire. Heating may cause an explosion. |
| Oxidizing properties | : No data available |
| Explosion limits | : No data available |

9.2. Other information

| | |
|-------------|------------------|
| VOC content | : 45 % |
| Gas group | : Compressed gas |

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|----------------|---|
| Acute toxicity | : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. |
|----------------|---|

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|----------------------------|---|
| Toluene (108-88-3) | |
| LD50 oral rat | 5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value) |
| LD50 dermal rabbit | > 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87) |
| LC50 inhalation rat (mg/l) | > 28.1 mg/l/4h (Rat; Air, Literature study) |
| Methanol (67-56-1) | |
| LD50 oral rat | >= 2528 mg/kg body weight application as 50% aqueous solution |
| LD50 dermal rabbit | 17100 mg/kg corresponding to 20 ml/kg bw according to the authors |
| LC50 inhalation rat (mg/l) | 128.2 mg/l/4h Air |
| Benzene (71-43-2) | |
| LD50 oral rat | > 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg bodyweight; Rat; Experimental value) |
| LD50 dermal rabbit | > 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit) |
| LC50 inhalation rat (mg/l) | 43.767 mg/l/4h (Rat; Experimental value) |
| LC50 inhalation rat (ppm) | 13700 ppm/4h (Rat; Experimental value) |
| Acetone (67-64-1) | |
| LD50 oral rat | 5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value) |
| LD50 dermal rabbit | 20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402) |
| LC50 inhalation rat (mg/l) | 71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value) |
| LC50 inhalation rat (ppm) | 30000 ppm/4h (Rat; Experimental value) |

| | |
|-----------------------------------|---|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Not classified Based on available data, the classification criteria are not met |
| Carcinogenicity | : Not classified |

| | |
|---------------------------|---|
| Toluene (108-88-3) | |
| IARC group | 3 |
| Benzene (71-43-2) | |
| IARC group | 1 |

| | |
|---|---|
| Reproductive toxicity | : Suspected of damaging fertility or the unborn child. |
| Specific target organ toxicity – single exposure | : Causes damage to organs. May cause drowsiness or dizziness. |
| Specific target organ toxicity – repeated exposure | : May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | : Not classified |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin. |
| Symptoms/injuries after inhalation | : Shortness of breath. May cause drowsiness or dizziness. |
| Symptoms/injuries after skin contact | : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation. |
| Symptoms/injuries after eye contact | : Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue. Causes serious eye irritation. |
| Symptoms/injuries after ingestion | : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|---|
| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
| LC50 fish 1 | 35 mg/l (LC50; 96 h; Salmo gairdneri) |
| Methanol (67-56-1) | |
| LC50 fish 1 | 15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value) |
| EC50 Daphnia 1 | > 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value) |
| LC50 fish 2 | 10800 mg/l (LC50; 96 h; Salmo gairdneri) |
| Benzene (71-43-2) | |
| LC50 fish 1 | 5.3 mg/l (LC50; 96 h; Salmo gairdneri) |
| EC50 Daphnia 2 | 10 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna) |
| Threshold limit algae 1 | 100 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value) |

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Acetone (67-64-1) | |
|---|--|
| LC50 fish 1 | 6210 mg/l (96 h; Pimephales promelas; Nominal concentration) |
| EC50 Daphnia 1 | 8800 mg/l (48 h; Daphnia pulex) |
| LC50 fish 2 | 5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss) |
| TLM fish 1 | 13000 ppm (96 h; Gambusia affinis; Turbulent water) |
| TLM fish 2 | > 1000 ppm (96 h; Pisces) |
| Threshold limit other aquatic organisms 1 | 3000 mg/l (Plankton) |
| Threshold limit other aquatic organisms 2 | 28 mg/l (Protozoa) |
| Threshold limit algae 1 | 7500 mg/l (Scenedesmus quadricauda; pH = 7) |
| Threshold limit algae 2 | 3400 mg/l (48 h; Chlorella sp.) |

12.2. Persistence and degradability

| PRONTO CARB SPRAY 16.25 OZ. | |
|------------------------------------|------------------|
| Persistence and degradability | Not established. |

| Toluene (108-88-3) | |
|---------------------------------|--|
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil. |
| Biochemical oxygen demand (BOD) | 2.15 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 2.52 g O ₂ /g substance |
| ThOD | 3.13 g O ₂ /g substance |
| BOD (% of ThOD) | 0.69 |

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|---|---|
| Persistence and degradability | Biodegradability: not applicable. Not applicable (gas). |
| Biochemical oxygen demand (BOD) | Not applicable |
| Chemical oxygen demand (COD) | Not applicable |
| ThOD | Not applicable |

| Methanol (67-56-1) | |
|---------------------------------|---|
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil. |
| Biochemical oxygen demand (BOD) | 0.6 - 1.12 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.42 g O ₂ /g substance |
| ThOD | 1.5 g O ₂ /g substance |
| BOD (% of ThOD) | 0.8 (Literature study) |

| Benzene (71-43-2) | |
|---------------------------------|--|
| Persistence and degradability | Readily biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air. Not established. |
| Biochemical oxygen demand (BOD) | 2.18 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 2.15 g O ₂ /g substance |
| ThOD | 3.1 g O ₂ /g substance |
| BOD (% of ThOD) | 0.7 |

| Acetone (67-64-1) | |
|---------------------------------|---|
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established. |
| Biochemical oxygen demand (BOD) | 1.43 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.92 g O ₂ /g substance |
| ThOD | 2.2 g O ₂ /g substance |
| BOD (% of ThOD) | (20 day(s)) 0.872 |

12.3. Bioaccumulative potential

| PRONTO CARB SPRAY 16.25 OZ. | |
|------------------------------------|------------------|
| Bioaccumulative potential | Not established. |

| Toluene (108-88-3) | |
|---------------------------|--|
| BCF fish 2 | 90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water) |
| Log Pow | 2.73 (Experimental value; Other; 20 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|---|----------------------------------|
| Log Pow | 0.83 (Experimental value) |
| Bioaccumulative potential | Bioaccumulation: not applicable. |

| Methanol (67-56-1) | |
|---------------------------|-----------------------------------|
| BCF fish 1 | < 10 (BCF; 72 h; Leuciscus idus) |
| Log Pow | -0.77 (Experimental value; Other) |

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Methanol (67-56-1) | |
|-------------------------------|--|
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |
| Benzene (71-43-2) | |
| BCF fish 1 | 19 (BCF) |
| BCF fish 2 | < 10 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 3 days; Leuciscus idus; Flow-through system; Fresh water; Experimental value) |
| BCF other aquatic organisms 1 | 30 (BCF; 24 h; Chlorella sp.) |
| Log Pow | 2.13 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). Not established. |
| Acetone (67-64-1) | |
| BCF fish 1 | 0.69 (Pisces) |
| BCF other aquatic organisms 1 | 3 |
| Log Pow | -0.24 (Test data) |
| Bioaccumulative potential | Not bioaccumulative. Not established. |

12.4. Mobility in soil

| Toluene (108-88-3) | |
|---------------------------|---|
| Surface tension | 0.03 N/m (20 °C) |
| Methanol (67-56-1) | |
| Surface tension | 0.023 N/m (20 °C) |
| Log Koc | Koc,PCKOCWIN v1.66; 1; Calculated value |
| Benzene (71-43-2) | |
| Surface tension | 0.029 N/m (20 °C) |
| Log Koc | Koc,134.1; QSAR |
| Acetone (67-64-1) | |
| Surface tension | 0.0237 N/m (20 °C) |

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity

ICAO/IATA (air): UN1950, Aerosols, 2.1 , Limited Quantity

IMO/IMDG (water): UN1950, Aerosols, 2.1 , Limited Quantity

Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols
Flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. Additional information

Emergency Response Guide (ERG) Number : 24-HOUR EMERGENCY INFORMATION: CHEMTREC (800) 424-9300

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

PRONTO CARB SPRAY 16.25 OZ.

| | |
|-------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard |
|-------------------------------------|--|

Toluene (108-88-3)

Subject to reporting requirements of United States SARA Section 313
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on the United States SARA Section 302

| | |
|-------------------------------------|---|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard |
|-------------------------------------|---|

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

| | |
|-------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Sudden release of pressure hazard Immediate (acute) health hazard |
|-------------------------------------|--|

Methanol (67-56-1)

Subject to reporting requirements of United States SARA Section 313
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on the United States SARA Section 302
Listed on the United States SARA Section 355

| | |
|-------------------------------------|---|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard |
|-------------------------------------|---|

Benzene (71-43-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

| | |
|-------------------------------------|---|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard |
|-------------------------------------|---|

15.2. International regulations

CANADA

PRONTO CARB SPRAY 16.25 OZ.

| | |
|----------------------|--|
| WHMIS Classification | Class B Division 5 - Flammable Aerosol |
|----------------------|--|

Toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

| | |
|----------------------|--|
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
|----------------------|--|

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Methanol (67-56-1) | |
|---|---|
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
| Benzene (71-43-2) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| Acetone (67-64-1) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects |

EU-Regulations

| Toluene (108-88-3) | |
|--|--|
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) | |
| Methanol (67-56-1) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) | |
| Benzene (71-43-2) | |
| Acetone (67-64-1) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) | |
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) | |

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.3; R63

F; R11

T; R39/23/24/25

Xn; R20/21/22

Xn; R48/20

Xi; R36/38

Full text of R-phrases: see section 16

15.2.2. National regulations

| Methanol (67-56-1) | |
|---|--|
| Listed on the Canadian IDL (Ingredient Disclosure List) | |
| Benzene (71-43-2) | |
| Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory | |
| Acetone (67-64-1) | |
| Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECI (Korean Existing Chemicals Inventory) Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List) | |

15.3. US State regulations

| PRONTO CARB SPRAY 16.25 OZ. | |
|---|------------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | Yes |
| U.S. - California - Proposition 65 - Developmental Toxicity | Yes |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Yes |
| State or local regulations | U.S. - California - Proposition 65 |

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | | | | |
|---|---|---|---|-----------------------------------|
| Toluene (108-88-3) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| Yes | Yes | No | Yes | |
| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No | No | No | No | |
| Methanol (67-56-1) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No | Yes | No | No | |
| Benzene (71-43-2) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| Yes | Yes | No | Yes | |
| Acetone (67-64-1) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| Yes | Yes | No | Yes | |
| Toluene (108-88-3) | | | | |
| State or local regulations | | | | |
| U.S. - California - Proposition 65 U.S. - New Jersey - Special Health Hazards Substances List New Jersey Right-to-Know U.S. - Massachusetts - Right To Know List Rhode Island Right to Know U.S. - Michigan - Critical Materials List U.S. - New Jersey - Environmental Hazardous Substances List U.S. - Illinois - Toxic Air Contaminants U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List | | | | |
| Methanol (67-56-1) | | | | |
| State or local regulations | | | | |
| U.S. - California - Proposition 65 New Jersey Right-to-Know Florida Right to Know U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List | | | | |
| Benzene (71-43-2) | | | | |
| State or local regulations | | | | |
| U.S. - California - Proposition 65 U.S. - Pennsylvania - RTK (Right to Know) List New Jersey Right-to-Know | | | | |
| Acetone (67-64-1) | | | | |
| State or local regulations | | | | |
| U.S. - California - Proposition 65 Benzene 71-43-2 U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List | | | | |

PRONTO CARB SPRAY 16.25 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Indication of changes : Revision - See : *.

Other information : None.


Full text of H-phrases:

| | |
|------|---|
| H223 | Flammable aerosol |
| H225 | Highly flammable liquid and vapor |
| H280 | Contains gas under pressure; may explode if heated |
| H301 | Toxic if swallowed |
| H304 | May be fatal if swallowed and enters airways |
| H311 | Toxic in contact with skin |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H331 | Toxic if inhaled |
| H336 | May cause drowsiness or dizziness |
| H361 | Suspected of damaging fertility or the unborn child |
| H370 | Causes damage to organs |
| H373 | May cause damage to organs through prolonged or repeated exposure |

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 1 Slight Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.