

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 10/05/2024

Version: 1.4

SECTION 1: IDENTIFICATION

Product Identifier
Product Form: Mixture
Product Name: Perasafe 23
Product Code: AFCO 4363
Intended Use of the Product

Use of the Substance/Mixture: FDA approved antimicrobial agent for application on poultry carcasses, poultry carcass parts, poultry organs, whole, half, or quartered meat carcasses, red meat carcass parts, trim, and organs, ready-to-eat meats and poultry, seafood,

fish, fruits & vegetables. For professional use only. **Product dilution information**: 0.035% -0.87%

Name, Address, and Telephone of the Responsible Party

Company AFCO

800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329 www.afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

PRODUCT as SOLD

 Org. Perox. F
 H242

 Ox. Liq. 1
 H271

 Met. Corr. 1
 H290

 Acute Tox. 4 (Oral)
 H302

 Acute Tox. 4 (Inhalation: dust, mist)
 H332

 Skin Corr. 1A
 H314

 Eye Dam. 1
 H318

 Aquatic Acute 2
 H401

PRODUCT at USE DILUTION

Skin Irrit. 3 H316 Eye Irrit. 2 H319

Label Elements
GHS-US Labeling
PRODUCT as SOLD

Hazard Pictograms (GHS-US)



GHS05



Signal Word (GHS-US) : Danger.

Hazard Statements (GHS-US) : H242 - Heating may cause a fire

H271 - May cause fire or explosion; strong oxidizer

H290 - May be corrosive to metals

H302+H332 - Harmful if swallowed or if inhaled H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H401 - Toxic to aquatic life

10/05/2024 EN (English US) 1/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary Statements (GHS-US) : P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.

P220 - Keep/Store away from clothing, combustible materials, incompatible materials.

P221 - Take any precaution to avoid mixing with combustible materials, incompatible materials.

P234 - Keep only in original container.

P260 - Do not breathe vapors, mist, spray.

P261 - Avoid breathing dust/fumes/gas/mist/vapors/spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P283 - Wear fire/flame resistant/retardant clothing.

P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P306+P360 - If on clothing: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.

P310 - Immediately call a POISON CENTER or doctor/physician.

P312 - Call a POISON CENTER/doctor/physician if you feel unwell.

P321 - Specific treatment (see section 4).

P330 - If swallowed, rinse mouth.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use appropriate media for extinction.

P371+P380+P375 - In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

P390 - Absorb spillage to prevent material damage.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P410 - Protect from sunlight.

P411+P235 - Store at temperatures not exceeding storage and handling temperatures. Keep

P420 - Store away from other materials.

P501 - Dispose of contents/container to local, regional, national, territorial, provincial, and international regulations.

PRODUCT at USE DILUTION

Hazard Pictograms (GHS-US)



Signal Word (GHS-US) Warning.

Hazard Statements (GHS-US) H316 - Causes mild skin irritation

H319 - Causes serious eye irritation

Precautionary Statements (GHS-US) : P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P280 - Wear protective gloves, eye protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

10/05/2024 EN (English US) 2/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

contact lenses, if present and easy to do. Continue rinsing.
P332+P313 - If skin irritation occurs: Get medical attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes. Contains an oxidizing material which may accelerate fire. Flammable vapors can accumulate in head space of closed systems.

Unknown Acute Toxicity (GHS-US) Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Mixture

PRODUCT as SOLD

Name	Product identifier	% (w/w)	Classification (GHS-US)
Acetic acid	(CAS No) 64-19-7	30-40	Flam. Liq. 3, H226
			Skin Corr. 1A, H314
			Eye Dam. 1, H318
			Aquatic Acute 3, H402
Water	(CAS No) 7732-18-5	20-30	Not classified
Peroxyacetic acid	(CAS No) 79-21-0	22-24	Flam. Liq. 3, H226
			Org. Perox. D, H242
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Acute Tox. 4 (Inhalation), H332
			Skin Corr. 1A, H314
			Aquatic Acute 1, H400
Hydrogen peroxide	(CAS No) 7722-84-1	9-11	Ox. Liq. 1, H271
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Acute Tox. 4 (Inhalation: vapour), H332
			Skin Corr. 1A, H314
			STOT SE 3, H335
			Aquatic Acute 3, H402
			Aquatic Chronic 3, H412
1-Hydroxyethane-1,1-diphosphonic acid	(CAS No) 2809-21-4	0.1-1	Met. Corr. 1, H290
			Acute Tox. 4 (Oral), H302
			Eye Dam. 1, H318

PRODUCT at USE DILUTION

Name	Product identifier	% (w/w)	Classification (GHS-US)
Acetic acid	(CAS No) 64-19-7	0.30	Flam. Liq. 3, H226
			Skin Corr. 1A, H314
			Eye Dam. 1, H318
			Aquatic Acute 3, H402
Peroxyacetic acid	(CAS No) 79-21-0	0.20	Flam. Liq. 3, H226
			Org. Perox. D, H242
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Acute Tox. 4 (Inhalation), H332
			Skin Corr. 1A, H314
			Aquatic Acute 1, H400
Hydrogen peroxide	(CAS No) 7722-84-1	0.09	Ox. Liq. 1, H271

10/05/2024 EN (English US) 3/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312
Acute Tox. 4 (Inhalation: vapour), H332
Skin Corr. 1A, H314 STOT SE 3, H335
Aquatic Acute 3, H402
Aquatic Chronic 3, H412

Full text of H-phrases: see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

PRODUCT as SOLD

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Drench affected area with water for several minutes. Immediately call a POISON CENTER or doctor/physician.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

PRODUCT at USE DILUTION:

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.

Inhalation: Remove to fresh air. Get medical attention if symptoms occur.

Skin Contact: Rinse with plenty of water. **Eye Contact:** Rinse with plenty of water.

Ingestion: Rinse mouth. Get medical attention if symptoms occur.

Most Important Symptoms and Effects Both Acute and Delayed

PRODUCT as SOLD

General: Harmful if swallowed. Harmful if inhaled. Corrosive. Causes burns. Causes serious eye damage.

Inhalation: Harmful if inhaled. May cause respiratory irritation. Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Skin Contact: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Eye Contact: Causes serious eye damage.

Ingestion: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Chronic Symptoms: None.
PRODUCT as Use DILUTION

General: Harmful if swallowed. May cause mild skin irritation. Causes serious eye irritation.

Inhalation: May cause respiratory irritation. **Skin Contact:** May cause mild skin irritation. **Eye Contact:** Causes serious eye irritation.

Ingestion: Harmful if swallowed. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Chronic Symptoms: None.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam.

10/05/2024 EN (English US) 4/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Product is not flammable but, during fire product can decompose and generate oxygen which can initiate or promote combustion. Strong oxidizer.

Explosion Hazard: Heated containers may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Thermal decomposition generates: Corrosive vapors, acetic acid, and oxygen which supports combustion.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. For major fire and large quantities, evacuate area. Fight fire from protected location or maximum distance because of risk that heated containers could rupture.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Corrosive vapours, acetic acid.

Other information: Do not allow run-off from fire fighting to enter drains or water courses. Chemical type extinguishers are not effective with peracetic acid or hydrogen peroxide.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Remove ignition sources. Do NOT breathe (vapors, mist, spray). Do not allow product to spread into the environment. Avoid all contact with skin, eyes, or clothing. Approach from upwind.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Small spills may be flushed to an approved sewer line with generous amounts of water. For larger spills, dike well ahead of spill with non-reactive material such as sand. Cautiously neutralize spilled liquid. Spill may be neutralized with soda ash (sodium carbonate) broadcast on surface. Use 0.7 to 1 lb. (20 - 28.35 g) of soda ash for each gallon of spilled material. The resultant neutralized product will become carbon dioxide and water. Flush material with water and collect for disposal into plastic containers. **Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Absorb spillage to prevent material damage.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb spillage to prevent material damage Do not take up in combustible material such as: saw dust or cellulosic material. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: May be corrosive to metals. Handle empty containers with care because residual vapors are flammable. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. May cause or intensify fire; oxidizer. When heated to decomposition, emits toxic fumes.

Handling Temperature: Not available.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do no eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling. Always wash your hands immediately after handling this product, and once again before leaving the workplace.

10/05/2024 EN (English US) 5/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: None known.

Storage Conditions: Store in a cool, dry, well-ventilated area. Avoid temperatures above 30°C (86°F). Do not store near reducing agents, fuels, organic materials, or other non-compatible materials. Do not store in direct sunlight, or near sources of ignition or heat. Product can be shipped on wooden pallets but should be stored on plastic pallets or plastic-covered pallets. Store drums in upright position only. Empty drums as thoroughly as possible. Triple rinse before disposal.

Incompatible Materials: Dirt, metals, strong bases, reducing agents, organic material, paper, wood, leather and heavy metals and their salts. May react violently with combustible materials. May react violently with finely divided metals. Never return product to original container.

Storage Temperature: Not available.

Storage Area: Store in a well-ventilated place. Keep cool. Protect from sunlight.

Specific End Use(s)

FDA approved antimicrobial agent for application on poultry carcasses, poultry carcass parts, poultry organs, whole, half, or quartered meat carcasses, red meat carcass parts, trim, and organs. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters		
Acetic acid (64-19-7)		
Mexico	OEL TWA (mg/m³)	25 mg/m³
Mexico	OEL TWA (ppm)	10 ppm
Mexico	OEL STEL (mg/m³)	37 mg/m³
Mexico	OEL STEL (ppm)	15 ppm
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	25 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	25 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	10 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	37 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	15 ppm
USA IDLH	US IDLH (ppm)	50 ppm
Ontario	OEL STEL (ppm)	15 ppm
Ontario	OEL TWA (ppm)	10 ppm
Québec	VECD (mg/m³)	37 mg/m ³
Québec	VECD (ppm)	15 ppm
Québec	VEMP (mg/m³)	25 mg/m³
Québec	VEMP (ppm)	10 ppm
Hydrogen peroxide (7722-84	4-1)	
Mexico	OEL TWA (mg/m³)	1.5 mg/m³
Mexico	OEL TWA (ppm)	1 ppm
Mexico	OEL STEL (mg/m³)	3 mg/m³
Mexico	OEL STEL (ppm)	2 ppm
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	1.4 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1.4 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	1 ppm
USA IDLH	US IDLH (ppm)	75 ppm
Ontario	OEL TWA (ppm)	1 ppm
Québec	VEMP (mg/m³)	1.4 mg/m³
Québec	VEMP (ppm)	1 ppm

10/05/2024 EN (English US) 6/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Peroxyacetic acid (79-21-0)			
USA ACGIH	ACGIH STEL (ppm)	0.4 ppm	

Exposure Controls PRODUCT as SOLD

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. If user operations generate fumes, vapors, gas, or spray use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or regulatory limits.

Personal Protective Equipment: Protective clothing. Protective goggles. Gloves. Face shield.









Materials for Protective Clothing: Chemically resistant materials and fabrics. Anti-static clothing in natural material or heat resistant synthetic material.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Face shield and/or Chemical goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist

are expected to exceed exposure limits.

Thermal Hazard Protection: Wear suitable protective clothing. **Other Information:** When using, do not eat, drink or smoke.

PRODUCT at USE DILUTION:

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. If user operations generate fumes, vapors, gas, or spray use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or regulatory limits.

Personal Protective Equipment: Protective goggles. Gloves.





Hand Protection: Wear protective gloves.

Eye Protection: Safety goggles.

Skin and Body Protection: None usually needed.
Respiratory Protection: None usually needed.
Thermal Hazard Protection: None usually needed.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Liquid
Appearance : Colorless

Odor : Sharp, pungent, vinegar-like

Odor Threshold : Not available

pH (1%) : 2.80

Relative Evaporation Rate (butylacetate=1): Not availableMelting Point: -27°C (-17°F)Freezing Point: Not availableBoiling Point: 87°C (188°F)

Flash Point : >100°C (>212°F) – Closed cup

10/05/2024 EN (English US) 7/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition Temperature : 251-254°C (484-489°F)

Decomposition Temperature: Not availableFlammability (solid, gas): Not availableLower Flammable Limit: Not availableUpper Flammable Limit: Not availableVapor Pressure: 45 mm Hg (25°C)Relative Vapor Density at 20°C: Not available

Specific Gravity: 1.13Solubility: Complete.Partition coefficient: n-octanol/water: Not availableViscosity: Not available

Explosion Data – Sensitivity to Mechanical Impact: Not expected to present an explosion hazard due to mechanical impact.

Explosion Data – Sensitivity to Static Discharge : Static discharge could act as an ignition source.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates: Corrosive vapors. When heated to decomposition, generates acetic acid and oxygen which supports combustion.

Chemical Stability: Shelf life is one year from date of manufacture. Oxidizer - May intensify fire.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Open flames, elevated temperatures, any source of heat, direct sunlight. Combustibles such as paper, wood, and leather. Higher temperatures will accelerate decomposition resulting in a loss of assay.

Incompatible Materials: Dirt, metals, strong bases, reducing agents, organic material, paper, wood, leather and heavy metals and their salts. May react violently with combustible materials. May react violently with finely divided metals.

Hazardous Decomposition Products: Thermal decomposition generates: Corrosive vapors, acetic acid and oxygen which supports combustion.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

PRODUCT as SOLD

Acute Toxicity: Harmful if swallowed. Harmful if inhaled.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available. **Carcinogenicity:** Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

Potential Adverse Human Health Effects and Symptoms: Harmful if inhaled. Harmful if swallowed.

Symptoms/Injuries After Inhalation: Harmful if inhaled. May cause respiratory irritation. Inhalation may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/Injuries After Skin Contact: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed. Contact may cause immediate severe irritation progressing quickly to chemical burns.

PRODUCT at USE DILUTION:

Acute Toxicity: Harmful if swallowed. LD50 and LC50 Data: Not available.

10/05/2024 EN (English US) 8/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin Corrosion/Irritation: Causes mild skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available. **Carcinogenicity:** Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

Potential Adverse Human Health Effects and Symptoms: Harmful if swallowed.

Symptoms/Injuries After Inhalation: None expected under normal use.

Symptoms/Injuries After Skin Contact: Redness, irritation. Symptoms/Injuries After Eye Contact: Redness, irritation.

Symptoms/Injuries After Ingestion: Swallowing a small quantity of this material will result in irritation.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Peroxyacetic acid (79-21-0)	
LD50 Oral Rat	263 mg/kg
LD50 Dermal Rabbit	1410 μl/kg
LC50 Inhalation Rat (mg/l)	0.3 mg/l (Exposure time: 1 h)
Water (7732-18-5)	
LD50 Oral Rat	>90000 mg/kg
Acetic acid (64-19-7)	
LD50 Oral Rat	3310 mg/kg
LD50 Dermal Rabbit	1060 μl/kg
LC50 Inhalation Rat (mg/l)	11.4 mg/l/4h
Hydrogen peroxide (7722-84-1)	
LD50 Oral Rat	376 mg/kg
LD50 Dermal Rabbit	2000 mg/kg
LC50 Inhalation Rat (mg/l)	2 g/m³ (Exposure time: 4 h)
IARC Group	3
1-Hydroxyethane-1,1-diphosphonic acid (2809-21-4)	
LD50 Oral Rat	2400 mg/kg
LD50 Dermal Rabbit	>7940 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Toxic to aquatic life.

Acetic acid (64-19-7)	
LC50 Fish 1	79 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	65 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	75 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Hydrogen peroxide (7722-84-	1)
LC50 Fish 1	16.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	18 - 32 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	18 - 56 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
1-Hydroxyethane-1,1-diphosphonic acid (2809-21-4)	
LC50 Fish 1	868 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

10/05/2024 EN (English US) 9/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EC50 Daphnia 1	527 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	360 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
NOEC (acute)	1000 mg/kg (Exposure time: 14 Days - Species: Eisenia foetida [soil dry weight])

Persistence and Degradability Not available.

Bioaccumulative Potential

<u> </u>		
Perasafe 23 (AFCO 4363)		
Bioaccumulative Potential	Not established.	
Peroxyacetic acid (79-21-0)		
BCF fish 1	(not bioaccumulative, rapid degradation)	
Acetic acid (64-19-7)		
Log Pow	-0.31 (at 20°C)	
Hydrogen peroxide (7722-84-1)		
BCF fish 1	(no bioaccumulation)	
1-Hydroxyethane-1,1-diphosphonic acid (2809-21-4)		
BCF fish 1	<50	
Log Pow	3.49	

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic Acid Type F, Stabilized, <43%)

Hazard Class : 5.2 Identification Number : UN3109 Label Codes : 5.2, 8* Packing Group : II ERG Number : 145





Proper Shipping Name : ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic Acid Type F, Stabilized, <43%)

Hazard Class : 5.2
Identification Number : UN3109
Label Codes : 5.2, 8*
EmS-No. (Fire) : F-J
EmS-No. (Spillage) : S-R



14.3 In Accordance with IATA

Proper Shipping Name : ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic Acid Type F, Stabilized, <43%))

Identification Number: UN3109Hazard Class: 5Label Codes: 5.2, 8*

ERG Code (IATA) : 5L 14.4 In Accordance with TDG

Proper Shipping Name : ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic Acid Type F, Stabilized, <43%)

Hazard Class : 5.2, 8*
Identification Number : UN3109

10/05/2024 EN (English US) 10/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Label Codes

: 5.2

* - Corrosive symbol and subsidiary hazard required per 49CFR173.225(c), Table 1, Note 13, requiring the addition of the Corrosive Symbol and Subsidiary Class, applies to the specific entry listed above.

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Perasafe 23 (AFCO 4363)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard.
	Reactive hazard.
	Fire hazard.
	Delayed (chronic) health hazard.
Peroxyacetic acid (79-21-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.
Listed on SARA Section 302 (Specific toxic chemical listings).	
Listed on SARA Section 313 (Specific toxic chemical listings).	
SARA Section 302 Threshold Planning Quantity (TPQ) 500	
SARA Section 313 - Emission Reporting 1.0%	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Acetic acid (64-19-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Hydrogen peroxide (7722-84-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Listed on SARA Section 302 (Specific toxic chemical listings).	

1000 (concentration >52%)

1-Hydroxyethane-1,1-diphosphonic acid (2809-21-4)

SARA Section 302 Threshold Planning Quantity (TPQ)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

US State Regulations

Peroxyacetic acid (79-21-0)

- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728).
- U.S. New Jersey Discharge Prevention List of Hazardous Substances.
- U.S. New Jersey Environmental Hazardous Substances List.
- U.S. New Jersey Right to Know Hazardous Substance List.
- U.S. New Jersey Special Health Hazards Substances List.
- U.S. New Jersey TCPA Extraordinarily Hazardous Substances (EHS).
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances.
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List.
- U.S. Pennsylvania RTK (Right to Know) List.

Acetic acid (64-19-7)

- U.S. New Jersey Discharge Prevention List of Hazardous Substances.
- U.S. New Jersey Right to Know Hazardous Substance List.
- U.S. New Jersey Special Health Hazards Substances List.
- U.S. New York Occupational Exposure Limits TWAs.
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances.
- U.S. North Carolina Control of Toxic Air Pollutants.
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List.
- U.S. Pennsylvania RTK (Right to Know) List.
- U.S. Texas Effects Screening Levels Long Term.
- U.S. Texas Effects Screening Levels Short Term.

Hydrogen peroxide (7722-84-1)

U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1.

10/05/2024 EN (English US) 11/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2.
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity.
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1.
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2.
- U.S. Massachusetts Right To Know List.
- U.S. New Jersey Discharge Prevention List of Hazardous Substances.
- U.S. New Jersey Environmental Hazardous Substances List.
- U.S. New Jersey Right to Know Hazardous Substance List.
- U.S. New Jersey Special Health Hazards Substances List.
- U.S. New York Occupational Exposure Limits TWAs.
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances.
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List.
- U.S. Pennsylvania RTK (Right to Know) List.
- U.S. Texas Effects Screening Levels Long Term.
- U.S. Texas Effects Screening Levels Short Term.

1-Hydroxyethane-1,1-diphosphonic acid (2809-21-4)

- U.S. Texas Effects Screening Levels Long Term.
- U.S. Texas Effects Screening Levels Short Term.

Canadian Regulations

Peroxyacetic acid (79-21-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Acetic acid (64-19-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Hydrogen peroxide (7722-84-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

1-Hydroxyethane-1,1-diphosphonic acid (2809-21-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 10/05/2024

Other Information : This document has been prepared in accordance with the SDS requirements of the

OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4.
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4.
Acute Tox. 4 (Inhalation: dust, mist)	Acute toxicity (inhalation: dust, mist) Category 4.
Acute Tox. 4 (Inhalation: vapour)	Acute toxicity (inhalation: vapour) Category 4.
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4.
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1.
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2.
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3.
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3.
Eye Dam. 1	Serious eye damage/eye irritation Category 1.
Flam. Liq. 3	Flammable liquids Category 3.
Met. Corr. 1	Corrosive to metals Category 1.

10/05/2024 EN (English US) 12/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Org. Perox. D	Organic Peroxide Category D.
Org. Perox. F	Organic Peroxide Category F.
Ox. Liq. 1	Oxidizing liquids Category 1.
Skin Corr. 1A	Skin corrosion/irritation Category 1A.
STOT SE 3	Specific target organ toxicity (single exposure) Category 3.
H226	Flammable liquid and vapor.
H242	Heating may cause a fire.
H271	May cause fire or explosion; strong oxidizer.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was

given.

NFPA Fire Hazard : 1 - Must be preheated before ignition can occur.

NFPA Reactivity : 2 - Normally unstable and readily undergo violent

decomposition but do not detonate. Also: may react violently with water or may form potentially explosive

OX

mixtures with water.

NFPA Specific Hazard : OX - This denotes an oxidizer, a chemical which can greatly

increase the rate of combustion/fire.

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken, and medical treatment is

given.

Flammability : 1 - Slight Hazard.

Physical : 2 - Moderate Hazard.

Party Responsible for the Preparation of This Document

AFCO

800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS SDS 2015 (U.S., Can., Mex.)

10/05/2024 EN (English US) 13/13