

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 10/05/2023

SECTION 1: IDENTIFICATION

Product Identifier
Product Form: Mixture
Product Name: CCT-400
Product Code: AFCO 6051

Intended Use of the Product

Chlorinated alkaline thin film (gel) cleaner for removing protein and fatty soils from food processing equipment in the meat, poultry, dairy, and beverage industries. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

AFCO

800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329 www. afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290 Acute Tox. 5 (Oral) H303 Skin Corr. 1C H314 Eye Dam. 1 H318 Aquatic Acute 2 H401 Aquatic Chronic 2 H411

Label Elements GHS-US Labeling

Hazard Pictograms (GHS-US)





Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H290 - May be corrosive to metals

H303 - May be harmful if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H401 - Toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements (GHS-US): P234 - Keep only in original container.

P260 - Do not breathe mist, spray, vapors.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear eye protection, face protection, protective clothing, protective gloves.

P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

10/05/2023 EN (English US) 1/10

Version: 1.2

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/physician.

P321 - Specific treatment (see Section 4).

P363 - Wash contaminated clothing before reuse.

P390 - Absorb spillage to prevent material damage

P391- Collect spillage.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

% (w/w)

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Classification (GHS-US)

Other Hazards

Other Hazards Not Contributing to the Classification: N/A.

Other Hazards: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Contact with metals may evolve flammable hydrogen gas.

Unknown Acute Toxicity (GHS-US) Not available. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product identifier

Substances

Name

Name	Product identifier	% (W/W)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	70 - 90	Not classified
Potassium hydroxide	(CAS No) 1310-58-3	5 - 10	Met. Corr. 1, H290
			Acute Tox. 4 (Oral), H302
			Skin Corr. 1A, H314
			Eye Dam. 1, H318
N,N-Dimethyltetradecylamine oxide	(CAS No) 3332-27-2	1 - 5	Acute Tox. 4 (Oral), H302
			Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Aquatic Acute 1, H400
			Aquatic Chronic 2, H411
Sodium xylene sulfonate	(CAS No) 1300-72-7	1 - 5	Acute Tox. 4 (Oral), H302
			Skin Irrit. 2, H315
			Eye Irrit. 2A, H319
			STOT SE 3, H335
Sodium hypochlorite	(CAS No) 7681-52-9	1-5	Met. Corr. 1, H290
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
			STOT SE 3, H335
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410
Sulfuric acid, mono-C10-16-alkyl esters,	(CAS No) 68585-47-7	0.1 - 1	Acute Tox. 4 (Oral), H302
sodium salts			Skin Irrit. 2, H315
			Eye Dam. 1, H318
Sulfuric acid, monodecyl ester, sodium salt	(CAS No) 142-87-0	0.1 - 1	Acute Tox. 4 (Oral), H302
			Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Aquatic Chronic 3, H412
Sodium lauryl sulfate	(CAS No) 151-21-3	0.1 - 1	Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Inhalation: dust, mist), H332
			Skin Irrit. 2, H315
			Eye Dam. 1, H318
			STOT SE 3, H335
			Aquatic Acute 2, H401
			Aquatic Chronic 3, H412

Full text of H-phrases: see section 16.

10-05.2023 EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Rinse cautiously with water for at least 30 minutes. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed. May cause irritation of respiratory tract.

Inhalation: May cause respiratory irritation. **Skin Contact:** Causes severe skin burns. **Eye Contact:** Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects. **Chronic Symptoms:** None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive. Contact with soft metals may release flammable hydrogen gas.

Reactivity: Thermal decomposition generates: Corrosive vapors and toxic fumes.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not breath fumes from fires or vapors from decompostion. Do not allow run-off from fire fighting to enter drains or water sources.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen oxides. Sulfur oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Handle in accordance with good industrial hygiene and safety practice.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Eliminate ignition sources. Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

10-05.2023 EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Cautiously neutralize spilled liquid. Absorb spillage to prevent material damage. Absorb and/or contain spill with inert material, then place in suitable container. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: May be corrosive to soft metals.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling. Avoid breathing gas, mist, or spray.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Store in original container. Keep container closed when not in use. Avoid extremely high or low temperatures, incompatible materials.

Incompatible Materials: Acids. Strong oxidizers. Aluminum. Tin. Zinc. Soft metals.

Specific End Use(s) Chlorinated alkaline thin film (gel) cleaner for removing protein and fatty soils from food processing equipment in the meat, poultry, dairy, and beverage industries. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Potassium hydroxide (131	otassium hydroxide (1310-58-3)	
USA ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³
USA NIOSH	NIOSH REL (ceiling) (mg/m³)	2 mg/m³
Ontario	OEL Ceiling (mg/m³)	2 mg/m³
Québec	PLAFOND (mg/m³)	2 mg/m³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Alarm detectors should be used when toxic gases may be released. Gas detectors should be used when flammable gases/vapors may be released. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. If user operations generate fumes, gas, vapors, spray, or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or regulatory limits.

Personal Protective Equipment: Safety glasses. Face shield. Corrosionproof clothing. Gloves. Protective goggles.









Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses. Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: A respirator is not needed under normal and intended conditions of use. If airborne concentrations of vapor or mist are expected to exceed exposure limits, use NIOSH-approved respirator.

Consumer Exposure Controls: Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<u>Information on Basic Physical and Chemical Properties</u>

Physical State : Liquid

Appearance : Clear yellow green

10-05.2023 EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor : Low

Odor Threshold : Not available

pH : >13

Relative Evaporation Rate (butylacetate=1) Not available Not available **Melting Point Freezing Point** Not available 98.9°C (210.02°F) **Boiling Point Flash Point** Not flammable Not available **Auto-ignition Temperature Decomposition Temperature** Not available Flammability (solid, gas) Not flammable **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available **Vapor Pressure** Not available Relative Vapor Density at 20°C Not available

Specific Gravity : 1.14

Solubility : Complete in water.

Partition coefficient: n-octanol/water : Not available

Viscosity : Not available

Explosion Data – Sensitivity to Mechanical Impact : Not expected to present an explosion hazard due to mechanical impact.

Explosion Data – Sensitivity to Static Discharge : Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates: Corrosive vapors and toxic fumes.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous reactions will not occur under normal conditions.

Conditions to Avoid: Extremely high or low temperatures. Incompatible materials.

Incompatible Materials: Strong acids. Strong oxidizers. Soft Metals.

Hazardous Decomposition Products: Thermal decomposition generates: Corrosive vapors. Carbon oxides (CO, CO₂). Nitrogen oxides. Sodium oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burn. (pH: >13)

Serious Eye Damage/Irritation: Causes serious eye damage. (pH: >13)

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available. **Carcinogenicity:** Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: May cause respiratory irritation. Symptoms/Injuries After Skin Contact: Causes severe skin burns. Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

10-05.2023 EN (English US) 5/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50 and LC50 Data:

LOSO DATA.		
lfuric acid, monodecyl ester, sodium salt (142-87-0)		
LD50 Oral Rat	1950 mg/kg	
Sodium lauryl sulfate (151-21-3)	dium lauryl sulfate (151-21-3)	
LD50 Oral Rat	977 mg/kg	
LD50 Dermal Rabbit	580 mg/kg	
LC50 Inhalation Rat	>3900 mg/m³ (Exposure time: 1 h)	
ATE US (dust, mist)	1.50 mg/l/4h	
Potassium hydroxide (1310-58-3)		
LD50 Oral Rat	214 mg/kg	
ATE (oral)	333.000 mg/kg body weight	
Sodium xylene sulfonate (1300-72-7)		
LD50 Oral Rat	1000 mg/kg	
LD50 Dermal Rabbit	> 2000 mg/kg	
Sulfuric acid, mono-C10-16-alkyl esters, sodium salts (68585-47-7)		
LD50 Oral Rat	>2000 mg/kg	
ATE US (oral)	500.00 mg/kg body weight	
N,N-Dimethyltetradecylamine oxide (3332-27-2)		
LD50 Oral Rat	> 1495 mg/kg	
ATE US (oral)	500.00 mg/kg body weight	
Sodium hypochlorite (7681-52-9)		
LD50 Oral Rat	8200 mg/kg	
LD50 Dermal Rabbit	>10000 mg/kg	
IARC Group	3	

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not classified.

Sodium lauryl sulfate (151-	21-3)	
LC50 Fish 1	1 8 - 12.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Daphnia 1	1.8 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 Fish 2	15 - 18.9 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
Sodium hypochlorite (7681-52-9)		
LC50 Fish 1	0.06 (0.06 - 0.11) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	0.033 - 0.044 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
LC50 Fish 2	4.5 (4.5 - 7.6) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Daphnia 2 0.033 (0.033 - 0.044) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])		

Persistence and Degradability

CCT-400 (AFCO 6051)	'-400 (AFCO 6051)	
Persistence and Degradability	Not established.	
Bioaccumulative Potential		
CCT-400 (AFCO 6051)		
Bioaccumulative Potential	Not established.	
Sodium lauryl sulfate (151-21-3)		
BCF fish 1	(will not bioconcentrate)	
Log Pow	1.6	
Potassium hydroxide (1310-58-3)		
Log Pow	0.65	

10-05.2023 EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: This material is hazardous to the aquatic environment. Keep out of sewers and waterways. **Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Hazardous waste due to toxicity.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hypochlorite)

Hazard Class : 8

Identification Number : UN3266

Label Codes : 8
Packing Group : III
Marine Pollutant : Yes
ERG Number : 154
14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hypochlorite)

Hazard Class : 8

Identification Number : UN3266

Packing Group : III
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
Marine pollutant : Yes



14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hypochlorite)

Packing Group : III

Identification Number : UN3266

Hazard Class : 8 Label Codes : 8 ERG Code (IATA) : 8L

14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hypochlorite)

Packing Group : III
Hazard Class : 8
Identification Number : UN3266

Label Codes : 8



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

	CCT-400 (AFCO 6051)	Γ-400 (AFCO 6051)		
	SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard.		
Water (7732-18-5)				
	Listed on the United States TSCA (Toxic Substances Control Act) inventory.			

Sulfuric acid, monodecyl ester, sodium salt (142-87-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

10-05.2023 EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium hypochlorite (7681-52-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

Sodium lauryl sulfate (151-21-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

Potassium hydroxide (1310-58-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

Sodium xylene sulfonate (1300-72-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

Sulfuric acid, mono-C10-16-alkyl esters, sodium salts (68585-47-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

N,N-Dimethyltetradecylamine oxide (3332-27-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

US State Regulations

Potassium hydroxide (1310-58-3)

- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Sulfuric acid, monodecyl ester, sodium salt (142-87-0)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Sodium hypochlorite (7681-52-9)

- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Sodium lauryl sulfate (151-21-3)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Sodium xylene sulfonate (1300-72-7)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Sulfuric acid, mono-C10-16-alkyl esters, sodium salts (68585-47-7)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Canadian Regulations

Sulfuric acid, monodecyl ester, sodium salt (142-87-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Potassium hydroxide (1310-58-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

10-05.2023 EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium lauryl sulfate (151-21-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sodium xylene sulfonate (1300-72-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sulfuric acid, mono-C10-16-alkyl esters, sodium salts (68585-47-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

N,N-Dimethyltetradecylamine oxide (3332-27-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sodium hypochlorite (7681-52-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 10/05/2023

Other Information : This document has been prepared in accordance with the SDS requirements of the

OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Inhalation: dust, mist)	Acute toxicity (inhalation: dust, mist) Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1	
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2	
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3	
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3	
Eye Dam. 1	Serious eye damage/eye irritation Category 1	
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A	
Met. Corr. 1	Corrosive to metals Category 1	
Skin Corr. 1A	Skin corrosion/irritation Category 1A	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H290	May be corrosive to metals	
H302	Harmful if swallowed	
H303	May be harmful if swallowed.	
H314	Causes severe skin burns and eye damage	
H315	Causes skin irritation	
H318	Causes serious eye damage	
H319	Causes serious eye irritation	
H332	Harmful if inhaled	
H335	May cause respiratory irritation	
H400	Very toxic to aquatic life	
H401	Toxic to aquatic life	
H402	Harmful to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	
H411	Toxic to aquatic life with long lasting effects	
H412	Harmful to aquatic life with long lasting effects	

10-05.2023 EN (English US) 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was

given.

NFPA Fire Hazard : 0 - Materials that will not burn.

NFPA Reactivity : 1 - Normally stable, but can become unstable at elevated

temperatures and pressures or may react with water with

some release of energy, but not violently.

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 0 - Minimal Hazard. **Physical** : 1 - Slight Hazard.

Party Responsible for the Preparation of This Document

AFCO

800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS SDS 2015 (U.S., Can., Mex.)

10-05.2023 EN (English US) 10/10