ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP LIQUID HEAT MAX 64OZ 4CT

Material number : ZULHM64

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	light yellow
Odour	chlorine-like

GHS Classification

Skin corrosion : Category 1 Serious eye damage : Category 1

GHS label elements

Hazard pictograms

Corrosion

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off

ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration [%]
sodium hypochlorite	7681-52-9	>= 6 - < 10
potassium hydroxide	1310-58-3	>= 2 - < 4
sodium hydroxide	1310-73-2	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with

difficulty.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: No hazardous combustion products are known

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment.

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Keep away from metals.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
sodium hypochlorite	7681-52-9	STEL	2 mg/m3	US WEEL
potassium hydroxide	1310-58-3	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		С	2 mg/m3	OSHA P0
		С	2 mg/m3	CAL PEL
sodium hydroxide	1310-73-2	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		С	2 mg/m3	OSHA P0
		С	2 mg/m3	CAL PEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

Material Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

When using do not eat or drink. Hygiene measures

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light yellow Odour chlorine-like

Odour Threshold No data available

: 13.8 рΗ

Melting point/freezing point : No data available **Boiling point** : No data available

Flash point

does not flash

Upper explosion limit : No data available Lower explosion limit : No data available : No data available Vapour pressure

Density : 1.15 g/cm3

Solubility(ies)

Water solubility : completely soluble Partition coefficient: n-: No data available

octanol/water

Viscosity

: No data available Viscosity, kinematic

ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Incompatible materials : Acids

Metals

Organic materials

Ammonia

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 3,704 mg/kg

Method: Calculation method

Components:

ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

sodium hydroxide:

Acute dermal toxicity : Acute toxicity estimate Rabbit: 1,350 mg/kg

Skin corrosion/irritation

Product:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

sodium hydroxide:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l

Exposure time: 96 h

ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

Test Method: static test

LC50 (Oncorhynchus tshawytscha (chinook salmon)):

152 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 40 mg/l

Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 34 - 47 mg/l

Exposure time: 48 h

EC50 (Crangon crangon (shrimp)): 33 - 100 mg/l

Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

Components:

sodium hydroxide:

Additional ecological

information

: Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II, RQ (SODIUM

HYPOCHLORITE)

Transportation Regulation: IMDG (Vessel):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IATA (Cargo Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IATA (Passenger Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: TDG (Canada):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
sodium hypochlorite	7681-52-9	100	1451

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

ZEP LIQUID HEAT MAX 640Z 4CT

Print Date 05/23/2025 Version 1.1 Revision Date 05/23/2025

Further information

NFPA:

HEALTH	3
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Signal word Hazard statements

Precautionary statements

Danger:

Causes severe skin burns and eye damage.

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective

clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before

Disposal: Dispose of contents/container in accordance with local regulation.

SAFETY DATA SHEET ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.1 Revision Date 05/23/2025 Print Date 05/23/2025

Version:	1.1
Revision Date:	05/23/2025
Print Date:	05/23/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.