

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT
Material number : ZHCR128NG

Manufacturer or supplier's details

Company : Zep Inc.
Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137
Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937
For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Drain & Sewer Care

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	light yellow
Odour	Chlorine

GHS Classification

Skin corrosion : Category 1
Serious eye damage : Category 1

GHS label elements

Hazard pictograms :



Corrosion

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention:**

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
sodium hypochlorite	7681-52-9	>= 3 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing and shoes.
Wash off immediately with plenty of water for at least 15 minutes.
Wash contaminated clothing before reuse.
If symptoms persist, call a physician.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

Most important symptoms and effects, both acute and delayed	: Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Notes to physician	: Symptoms may include blistering, irritation, burns, and pain. Causes severe skin burns and eye damage. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national regulations.
-------------------------	--

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Do not store near acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
sodium hypochlorite	7681-52-9	STEL	2 mg/m3	US WEEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light yellow

Odour : Chlorine

Odour Threshold : No data available

pH : > 13

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

Melting point/freezing point	: No data available
Boiling point	: > 100 °C
Flash point	: Not applicable
Evaporation rate	: 1
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 1.059 g/cm ³
Solubility(ies)	
Water solubility	: soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Incompatible materials	: Acids Ammonia soft metals
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
------------------------------	---------------

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

Symptoms of Overexposure : Symptoms may include blistering, irritation, burns, and pain.
Causes severe skin burns and eye damage.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: No data available

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: The product should not be allowed to enter drains, water

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

Contaminated packaging : courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.
: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, III - Limited quantity

Transportation Regulation: IMDG (Vessel):
UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, III - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, III

Transportation Regulation: IATA (Passenger Air):
UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, III

Transportation Regulation: TDG (Canada):
UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, III - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium hypochlorite	7681-52-9	100	3203

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

- SARA 311/312 Hazards** : Skin corrosion or irritation
Serious eye damage or eye irritation
- SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
- SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

Further information

NFPA:

HEALTH	3
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Causes severe skin burns and eye damage.

Precautionary statements

:

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse.

Disposal: Dispose of contents/container in accordance with local regulation.

SAFETY DATA SHEET

ZEP 10 MINUTE DRAIN OPENER GEL 1GL 4CT

Version 5.2

Revision Date 06/10/2025

Print Date 07/10/2025

Version:	5.2
Revision Date:	06/10/2025
Print Date:	07/10/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP LIQUID HEAT MAX 1GL 4CT
Material number : ZULHM128

Manufacturer or supplier's details

Company : Zep Inc.
Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137
Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937
For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Drain & Sewer Care

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	light yellow
Odour	chlorine-like

GHS Classification

Skin corrosion : Category 1
Serious eye damage : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention:**

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration [%]
sodium hypochlorite	7681-52-9	≥ 6 - < 10
potassium hydroxide	1310-58-3	≥ 2 - < 5
sodium hydroxide	1310-73-2	≥ 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

	Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Effects are immediate and delayed. Effects are dependent on exposure (dose, concentration, contact time). Causes severe skin burns and eye damage.
Notes to physician	: Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	:
Further information	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Do not store near acids.
Keep away from metals.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
sodium hypochlorite	7681-52-9	STEL	2 mg/m3	US WEEL
potassium hydroxide	1310-58-3	C	2 mg/m3	ACGIH
		C	2 mg/m3	NIOSH REL
		C	2 mg/m3	OSHA P0
		C	2 mg/m3	CAL PEL
sodium hydroxide	1310-73-2	C	2 mg/m3	ACGIH
		C	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		C	2 mg/m3	OSHA P0
		C	2 mg/m3	CAL PEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: light yellow
Odour	: chlorine-like
Odour Threshold	: No data available
pH	: 13.8
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: does not flash
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 1.15 g/cm ³
Solubility(ies)	
Water solubility	: completely soluble
Partition coefficient: n-octanol/water	: No data available
Viscosity	
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Incompatible materials	: Acids Metals Organic materials

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

Hazardous decomposition products : Ammonia
: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.
Symptoms of Overexposure : Effects are immediate and delayed.
Effects are dependent on exposure (dose, concentration, contact time).
Causes severe skin burns and eye damage.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 3,704 mg/kg
Method: Calculation method

Components:

sodium hydroxide:
Acute dermal toxicity : Acute toxicity estimate Rabbit: 1,350 mg/kg

Skin corrosion/irritation

Product:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

sodium hydroxide :

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l
Exposure time: 96 h
Test Method: static test

LC50 (Oncorhynchus tshawytscha (chinook salmon)): 152 mg/l
Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 40 mg/l
Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 34 - 47 mg/l
Exposure time: 48 h

EC50 (Crangon crangon (shrimp)): 33 - 100 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

Components:

sodium hydroxide :

Additional ecological information : Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II, RQ (SODIUM HYPOCHLORITE)

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

Transportation Regulation: IMDG (Vessel):
UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IATA (Cargo Air):
UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IATA (Passenger Air):
UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: TDG (Canada):
UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium hypochlorite	7681-52-9	100	1451

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025



WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

Further information

NFPA:

HEALTH	3
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Corrosion

Signal word

: **Danger:**

Hazard statements

: Causes severe skin burns and eye damage.

Precautionary statements

:

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse.

Disposal: Dispose of contents/container in accordance with local regulation.

SAFETY DATA SHEET

ZEP LIQUID HEAT MAX 1GL 4CT

Version 1.2

Revision Date 05/29/2025

Print Date 07/10/2025

Version:	1.2
Revision Date:	05/29/2025
Print Date:	07/10/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT
Material number : ZULHG128

Manufacturer or supplier's details

Company : Zep Inc.
Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137
Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937
For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Drain & Sewer Care

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	viscous liquid
Colour	light yellow
Odour	chlorine-like

GHS Classification

Skin corrosion : Category 1
Serious eye damage : Category 1

GHS label elements

Hazard pictograms :



Corrosion

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P363 Wash contaminated clothing before reuse.
Disposal:
P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
sodium hypochlorite	7681-52-9	$\geq 5 - < 10$
potassium hydroxide	1310-58-3	$\geq 1 - < 5$
sodium hydroxide	1310-73-2	$\geq 1 - < 5$

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
Wash off immediately with plenty of water for at least 15 minutes.
Remove contaminated clothing and shoes.

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

In case of eye contact	: Wash contaminated clothing before reuse. If skin irritation persists, call a physician. : Small amounts splashed into eyes can cause irreversible tissue damage and blindness. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include blistering, irritation, burns, and pain. Causes severe skin burns and eye damage. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Dry chemical Water spray jet Alcohol-resistant foam Carbon dioxide (CO2)
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment.
Environmental precautions	: Prevent product from entering drains.

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

- Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities.
: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Do not store near acids.
Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
sodium hypochlorite	7681-52-9	STEL	2 mg/m3	US WEEL
potassium hydroxide	1310-58-3	C	2 mg/m3	ACGIH
		C	2 mg/m3	NIOSH REL
		C	2 mg/m3	OSHA P0
		C	2 mg/m3	CAL PEL
sodium hydroxide	1310-73-2	C	2 mg/m3	ACGIH
		C	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		C	2 mg/m3	OSHA P0
		C	2 mg/m3	CAL PEL

- Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

Hand protection	
Remarks	: Protective gloves The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems. Ensure that eyewash stations and safety showers are close to the workstation location.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: viscous liquid
Colour	: light yellow
Odour	: chlorine-like
Odour Threshold	: No data available
pH	: 13.8
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 1.15 g/cm ³
Bulk density	: No data available
Solubility(ies)	
Water solubility	: completely soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Incompatible materials : Acids
Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration, contact time).
Effects are immediate and delayed.
Symptoms may include blistering, irritation, burns, and pain.
Causes severe skin burns and eye damage.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 3,703 mg/kg
Method: Calculation method

Components:

sodium hydroxide:

Acute dermal toxicity : Acute toxicity estimate Rabbit: 1,350 mg/kg

Skin corrosion/irritation

Product:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

sodium hydroxide :

Toxicity to fish	: LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l Exposure time: 96 h Test Method: static test
	LC50 (Oncorhynchus tshawytscha (chinook salmon)): 152 mg/l Exposure time: 96 h
	LC50 (Oncorhynchus mykiss (rainbow trout)): 40 mg/l Exposure time: 48 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 34 - 47 mg/l Exposure time: 48 h
	EC50 (Crangon crangon (shrimp)): 33 - 100 mg/l Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water	: Remarks: No data available
--	------------------------------

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

Components:

sodium hydroxide :

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

Additional ecological information : Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
UN1760, CORROSIVE LIQUIDS, N.O.S., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IMDG (Vessel):
UN1760, CORROSIVE LIQUIDS, N.O.S., (SODIUM HYPOCHLORITE), 8, II, MP: (SODIUM HYPOCHLORITE)

Transportation Regulation: IATA (Cargo Air):
UN1760, Corrosive liquid, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IATA (Passenger Air):
UN1760, Corrosive liquids, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: TDG (Canada):
UN1760, CORROSIVE LIQUIDS, N.O.S., (SODIUM HYPOCHLORITE), 8, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium hypochlorite	7681-52-9	100	1602

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

Further information

NFPA:

HEALTH	3
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme

HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms

:



Corrosion

Signal word

: **Danger:**

Hazard statements

: Causes severe skin burns and eye damage.

Precautionary statements

:

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse.

Disposal: Dispose of contents/container in accordance with local regulation.

SAFETY DATA SHEET

ZEP LIQUID HEAT HAIR - BUILDUP - GREASE REMOVER GEL 1GL 4CT

Version 3.1

Revision Date 10/01/2023

Print Date 07/10/2025

Version:	3.1
Revision Date:	10/01/2023
Print Date:	07/10/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.