



Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 5/24/2016

Version: 1.1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Identifier

Product Form: Mixture

Product Name: Super Power Foam CI (AFCO 5339SA)

Product Code: AFCO 5339SA

Intended Use of the Product

Use of the Substance/Mixture: Foam cleaning in meat, poultry, and food processing plants. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

Alex C. Fergusson, LLC.
800 Development Avenue
Chambersburg, PA 17201
T 800-345-1329
www.afcocare.com

Emergency Telephone Number

Emergency number : 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290
Skin Corr. 1A H314
Eye Dam. 1 H318
STOT SE 3 H335
Aquatic Acute 1 H400
Aquatic Chronic 2 H411

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

:



GHS05



GHS07



GHS09

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H290 - May be corrosive to metals
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H400 - Very toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

: P234 - Keep only in original container.
P260 - Do not breathe vapors, mist, spray.
P261 - Avoid breathing fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P310 - Immediately call a POISON CENTER or doctor.
P312 - Call a POISON CENTER/doctor/physician if you feel unwell.
P321 - Specific treatment (see section 4).
P363 - Wash contaminated clothing before reuse.
P390 - Absorb spillage to prevent material damage.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P406 - Store in corrosive resistant container with a resistant inner liner.
P501 - Dispose of contents/container to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	70-90	Not classified
Sodium hydroxide	(CAS No) 1310-73-2	1-5	Met. Corr. 1, H290 Skin Corr. 1A, H314 Aquatic Acute 3, H402
Sodium hypochlorite	(CAS No) 7681-52-9	1-5	Met. Corr. 1, H290 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Potassium hydroxide	(CAS No) 1310-58-3	1-5	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318
Lauryldimethylamine oxide	(CAS No) 1643-20-5	1 - 5	Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400
Pentasodium triphosphate	(CAS No) 7758-29-4	0.1 - 1	Not classified
Sodium polyacrylate	(CAS No) 9003-04-7	0.1 - 1	Eye Irrit. 2A, H319

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed. May cause irritation of respiratory tract.

Inhalation: May cause respiratory irritation.

Skin Contact: Causes severe irritation which will progress to chemical burns.

Eye Contact: Causes serious eye damage. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Ingestion: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Chronic Symptoms: Not available

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable Extinguishing Media: Ammonia or Nitrogen containing fire extinguishing agents. Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable. Contains sodium hypochlorite which may act as an oxidizer in some cases intensifying a fire.

Explosion Hazard: Product is not explosive.

Reactivity: Thermal decomposition generates : Corrosive vapors. If the product is involved in a fire, it can release toxic chlorine gases, and explosive hydrogen gas. When heated to decomposition, emits toxic fumes. Ammonium or nitrogen containing compounds can react with the sodium hypochlorite in this product releasing toxic chlorine gas. May be corrosive to metals.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Potassium oxides. May liberate toxic gases. Sodium oxides. Phosphorus oxides. Chlorine gas. Nitrogen oxides. Carbon oxides (CO, CO₂). Explosive hydrogen gas.

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not allow product to spread into the environment. Do NOT breathe (vapors, mist, spray). Avoid all contact with skin, eyes, or clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Absorb spillage to prevent material damage. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: May be corrosive to metals. When heated to decomposition, emits toxic fumes. May produce explosive hydrogen gas on contact with incompatibilities or upon thermal decomposition. Ammonium or nitrogen containing compounds can react with the sodium hypochlorite in this product releasing toxic chlorine gas. Contains sodium hypochlorite which may act as an oxidizer in some cases intensifying a fire.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. May be corrosive to metals.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from extremely high or low temperatures, direct sunlight, heat, incompatible materials.

Incompatible Materials: Strong acids, Strong oxidizers.

Special Rules on Packaging: Keep only in original container.

Specific End Use(s)

Foam cleaning in meat, poultry, and food processing plants. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Potassium hydroxide (1310-58-3)		
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m ³)	2 mg/m ³
Sodium hydroxide (1310-73-2)		
Mexico	OEL Ceiling (mg/m ³)	2 mg/m ³
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	10 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m ³)	2 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Alarm detectors should be used when toxic gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. If user operations generate fumes, gas, vapors, spray, or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or regulatory limits.

Personal Protective Equipment: Protective goggles. Face shield. Protective clothing. Gloves.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosionproof clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: A respirator is not needed under normal and intended conditions of use. If airborne concentrations of vapor or mist are expected to exceed exposure limits, use NIOSH-approved respirator.

Other Information: When using, do not eat, drink or smoke.

Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Pale-yellow green,clear
Odor	: Chlorine
Odor Threshold	: Not available
pH	: 13.3
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 101.7 (215.06°F)
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.15
Solubility	: Complete.
Log Pow	: Not available
Log Kow	: Not available
Viscosity, Kinematic	: Not available
Viscosity, Dynamic	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not available
Explosion Data – Sensitivity to Static Discharge	: Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates : Corrosive vapors. If the product is involved in a fire, it can release toxic chlorine gases. Explosive hydrogen gas. When heated to decomposition, emits toxic fumes. Ammonium or nitrogen containing compounds can react with the sodium hypochlorite in this product releasing toxic chlorine gas. May be corrosive to metals.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Heat. Combustible materials. Incompatible materials.

Incompatible Materials: Strong acids. Strong oxidizers. Metals. May be corrosive to metals. Phosphorus. Nitrogen containing compounds, ammonium compounds.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Thermal decomposition generates : Corrosive vapors. Toxic gases. Chlorine gas. Hydrogen gas. Nitrogen oxides. Phosphorus oxides. Sodium oxides. Potassium oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity : Not classified

LD50 and LC50 Data Not available

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

pH: 13.3

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 13.3

Respiratory or Skin Sensitization: Not classified

Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Causes severe irritation which will progress to chemical burns.

Symptoms/Injuries After Eye Contact: Causes serious eye damage. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms/Injuries After Ingestion: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data

Water (7732-18-5)	
LD50 Oral Rat	> 90000 mg/kg
ATE (dust, mist)	100000.000 mg/l/4h
Potassium hydroxide (1310-58-3)	
LD50 Oral Rat	333 mg/kg
Pentasodium triphosphate (7758-29-4)	
LD50 Oral Rat	3100 mg/kg
LD50 Dermal Rabbit	> 7940 mg/kg
Sodium hypochlorite (7681-52-9)	
LD50 Oral Rat	8200 mg/kg
LD50 Dermal Rabbit	> 10000 mg/kg
Sodium hypochlorite (7681-52-9)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Sodium hydroxide (1310-73-2)	
LC50 Fish 1	40 mg/l
Lauryldimethylamine oxide (1643-20-5)	
ErC50 (algae)	0.11 mg/l (72 hour)
Sodium hypochlorite (7681-52-9)	
LC50 Fish 1	0.06 (0.06 - 0.11) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.033 - 0.044 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	4.5 (4.5 - 7.6) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	0.033 (0.033 - 0.044) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

Persistence and Degradability

Super Power Foam CI (AFCO 5339SA)	
Persistence and Degradability	May cause long-term adverse effects in the environment.

Bioaccumulative Potential

Super Power Foam CI (AFCO 5339SA)	
Bioaccumulative Potential	Not established.

Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potassium hydroxide (1310-58-3)	
Log Pow	0.65

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hydroxide, sodium hypochlorite)

Hazard Class : 8

Identification Number : UN3266

Label Codes : 8

Packing Group : III

Marine Pollutant : Marine pollutant

ERG Number : 154

14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hydroxide, sodium hypochlorite)

Hazard Class : 8

Identification Number : UN3266

Packing Group : III

Label Codes : 8

EmS-No. (Fire) : F-A

EmS-No. (Spillage) : S-B

Marine pollutant : Marine pollutant

14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hydroxide, sodium hypochlorite)

Packing Group : III

Identification Number : UN3266

Hazard Class : 8

Label Codes : 8

ERG Code (IATA) : 8L

14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide, sodium hydroxide, sodium hypochlorite)

Packing Group : III

Hazard Class : 8

Identification Number : UN3266

Label Codes : 8

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Super Power Foam CI (AFCO 5339SA)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Potassium hydroxide (1310-58-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Sodium hydroxide (1310-73-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Pentasodium triphosphate (7758-29-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Sodium polyacrylate (9003-04-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Lauryldimethylamine oxide (1643-20-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Sodium hypochlorite (7681-52-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	


US State Regulations

Potassium hydroxide (1310-58-3)
U.S. - Louisiana - Reportable Quantity List for Pollutants U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Tennessee - Occupational Exposure Limits - Ceilings U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Sodium hydroxide (1310-73-2)
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728) U.S. - Louisiana - Reportable Quantity List for Pollutants U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - New York - Occupational Exposure Limits - TWAs U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Pentasodium triphosphate (7758-29-4)
U.S. - Louisiana - Reportable Quantity List for Pollutants U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium polyacrylate (9003-04-7)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Lauryldimethylamine oxide (1643-20-5)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Sodium hypochlorite (7681-52-9)	
U.S. - Louisiana - Reportable Quantity List for Pollutants	
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - New Jersey - Special Health Hazards Substances List	
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Canadian Regulations	
Super Power Foam CI (AFCO 5339SA)	
WHMIS Classification	Class E - Corrosive Material
	
Water (7732-18-5)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Potassium hydroxide (1310-58-3)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class E - Corrosive Material
Sodium hydroxide (1310-73-2)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class E - Corrosive Material
Pentasodium triphosphate (7758-29-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Sodium polyacrylate (9003-04-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Lauryldimethylamine oxide (1643-20-5)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class E - Corrosive Material
Sodium hypochlorite (7681-52-9)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Listed on the Canadian Ingredient Disclosure List	

Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

WHMIS Classification	Class C - Oxidizing Material Class E - Corrosive Material Class F - Dangerously Reactive Material
----------------------	---

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION

Revision date : 5/24/2016

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.


GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA Fire Hazard : 0 - Materials that will not burn.

NFPA Reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 0 Minimal Hazard

Physical : 1 Slight Hazard

Party Responsible for the Preparation of This Document

Super Power Foam CI (AFCO 5339SA)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Alex C. Fergusson, LLC.
800 Development Avenue
Chambersburg, PA 17201
T 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS