



CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 11/14/2024

Version: 1.2

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: CCT-HS

Product Code: AFCO 6057

Intended Use of the Product

Caustic thin film (gel) cleaner for removing fatty and greasy soils from food processing equipment in the meat, poultry, dairy, and beverage industries. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

AFCO
550 Development Avenue
Chambersburg, PA 17201
T: 800-345-1329
www.afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290
Acute Tox. 4 (Oral) H302
Skin Corr. 1C H314
Eye Dam. 1 H318
Aquatic Acute 2 H401
Aquatic Chronic 3 H412

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

:



GHS05

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H290 - May be corrosive to metals
H302 - Harmful if swallowed.
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H401 - Toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

: P234 - Keep only in original container.
P260 - Do not breathe mist, spray, vapors.
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/physician.

P321 - Specific treatment (see Section 4).

P363 - Wash contaminated clothing before reuse.

P390 - Absorb spillage to prevent material damage.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: N/A.

Other Hazards: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Contact with metals may evolve flammable hydrogen gas.

Unknown Acute Toxicity (GHS-US) Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Name	Product identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	70 - 90	Not classified
Potassium hydroxide	(CAS No) 1310-58-3	10 - 20	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318
Sodium hydroxide	(CAS No) 1310-73-2	1 - 5	Met. Corr. 1, H290 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
Ethyl alcohol	(CAS No) 64-17-5	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
N,N-Dimethyltetradecylamine oxide	(CAS No) 3332-27-2	1 - 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Sodium xylene sulfonate	(CAS No) 1300-72-7	1 - 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Fatty acids, coco, potassium salts	(CAS No) 61789-30-8	1 - 5	Not classified
Benzenesulfonic acid, C10-16-alkyl derivatives, sodium salts	(CAS No) 68081-81-2	1 - 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Sodium gluconate	(CAS No) 527-07-1	0.1 - 1	Not classified
1,2,4 butanetricarboxylic, 2-phosphono-	(CAS No) 37971-36-1	0.1 - 1	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318
Sodium lauryl sulfate	(CAS No) 151-21-3	0.1 - 1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation: dust, mist), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318

CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

			STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
--	--	--	---

Full text of H-phrases: see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Rinse cautiously with water for at least 30 minutes. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

Inhalation: None under normal and intended conditions of product use.

Skin Contact: Causes severe skin burns.

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive. Contact with soft metals may release flammable hydrogen gas.

Reactivity: Thermal decomposition generates: Corrosive vapors and toxic fumes.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not breath fumes from fires or vapors from decomposition. Do not allow run-off from fire fighting to enter drains or water sources.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen oxides. Sulfur oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Handle in accordance with good industrial hygiene and safety practice.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Eliminate ignition sources. Stop leak if safe to do so. Ventilate area.

CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Cautiously neutralize spilled liquid. Absorb spillage to prevent material damage. Absorb and/or contain spill with inert material, then place in suitable container. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: May be corrosive to soft metals.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling. Avoid breathing gas, mist, or spray.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Store in original container. Keep container closed when not in use.

Incompatible Materials: Strong acids. Strong oxidizers. Aluminum. Tin. Zinc. Soft metals.

Specific End Use(s) Caustic thin film (gel) cleaner for removing fatty and greasy soils from food processing equipment in the meat, poultry, dairy, and beverage industries. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Sodium hydroxide (1310-73-2)		
Mexico	OEL Ceiling (mg/m ³)	2 mg/m ³
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	10 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m ³)	2 mg/m ³
Potassium hydroxide (1310-58-3)		
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m ³)	2 mg/m ³
Ethyl alcohol (64-17-5)		
Mexico	OEL TWA (mg/m ³)	1900 mg/m ³
Mexico	OEL TWA (ppm)	1000 ppm
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
Ontario	OEL STEL (ppm)	1000 ppm
Québec	VEMP (mg/m ³)	1880 mg/m ³
Québec	VEMP (ppm)	1000 ppm

CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Alarm detectors should be used when toxic gases may be released. Gas detectors should be used when flammable gases/vapors may be released. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. If user operations generate fumes, vapor, spray, or mist use process enclosures, local exhaust ventilation, or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal Protective Equipment: Safety glasses. Face shield. Corrosionproof clothing. Gloves. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses. Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: None needed under normal and intended conditions of product use.

Consumer Exposure Controls: Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear pale yellow
Odor	: Low
Odor Threshold	: Not available
pH	: >13
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 98.9°C (210.02°F)
Flash Point	: Not flammable
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not flammable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Specific Gravity	: 1.22
Solubility	: Complete in water.
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates: Corrosive vapors and toxic fumes.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous reactions will not occur under normal conditions.

Conditions to Avoid: Extremely high or low temperatures. Incompatible materials.

Incompatible Materials: Acids. Strong oxidizers. Soft Metals.

Hazardous Decomposition Products: Thermal decomposition generates: Corrosive vapors. Carbon oxides (CO, CO₂). Nitrogen oxides. Sodium oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns and eye damage. **pH:** > 13

Serious Eye Damage/Irritation: Causes serious eye damage. **pH:** > 13

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available.

Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: None under normal and intended conditions of product use.

Symptoms/Injuries After Skin Contact: Causes severe skin burns and eye damage.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Water (7732-18-5)	
LD50 Oral Rat	> 90000 mg/kg
Potassium hydroxide (1310-58-3)	
LD50 Oral Rat	333 mg/kg
ATE (oral)	333.000 mg/kg body weight
Sodium hydroxide (1310-73-2)	
LD50 Dermal Rabbit	1350 mg/kg
Ethyl alcohol (64-17-5)	
LD50 Oral Rat	10470 mg/kg
LD50 Dermal Rat	20 ml/kg
LC50 Inhalation Rat (mg/l)	124.7 mg/l/4h
Sodium lauryl sulfate (151-21-3)	
LD50 Oral Rat	977 mg/kg
LD50 Dermal Rabbit	580 mg/kg
LC50 Inhalation Rat	> 3900 mg/m ³ (Exposure time: 1 h)
ATE US (dust, mist)	1.50 mg/l/4h
Sodium xylene sulfonate (1300-72-7)	
LD50 Oral Rat	1000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg

CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N,N-Dimethyltetradecylamine oxide (3332-27-2)	
LD50 Oral Rat	> 1495 mg/kg
ATE US (oral)	500.00 mg/kg body weight
1,2,4-Butanetricarboxylic acid, 2-phosphono- (37971-36-1)	
LD50 Oral Rat	> 4000 mg/kg
LD50 Dermal Rat	> 4000 mg/kg
LC50 Inhalation Rat (mg/l)	> 1979 mg/m ³ (Exposure time: 4 h)

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not classified.

Sodium hydroxide (1310-73-2)	
LC50 Fish 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
Sodium lauryl sulfate (151-21-3)	
LC50 Fish 1	8 - 12.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	1.8 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	15 - 18.9 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Ethyl alcohol (64-17-5)	
LC50 Fish 1	9.468 (9.468 - 12.624) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) converted from ml/l
EC50 Daphnia 1	9268 (9268 - 14221) mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
1,2,4-Butanetricarboxylic acid, 2-phosphono- (37971-36-1)	
EC50 Other Aquatic Organisms 1	140 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

Persistence and Degradability

CCT-HS (AFCO 6057)	
Persistence and Degradability	Not established.

Bioaccumulative Potential

CCT-HS (AFCO 6057)	
Bioaccumulative Potential	Not established.
Sodium lauryl sulfate (151-21-3)	
BCF fish 1	(will not bioconcentrate)
Log Pow	1.6
Potassium hydroxide (1310-58-3)	
Log Pow	0.65
Ethyl alcohol (64-17-5)	
Log Pow	-0.32
Bioaccumulative Potential	Not established.

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Hazardous waste due to toxicity.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide, potassium hydroxide)

CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Class : 8
Identification Number : UN3266
Label Codes : 8
Packing Group : III
Marine Pollutant : Yes
ERG Number : 154



14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide, potassium hydroxide)
Hazard Class : 8
Identification Number : UN3266
Packing Group : III
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
Marine pollutant : Yes



14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide, potassium hydroxide)
Packing Group : III
Identification Number : UN3266
Hazard Class : 8
Label Codes : 8
ERG Code (IATA) : 8L



14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide, potassium hydroxide)
Packing Group : III
Hazard Class : 8
Identification Number : UN3266
Label Codes : 8



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

CCT-HS (AFCO 6057)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard.
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Potassium hydroxide (1310-58-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Sodium hydroxide (1310-73-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Sodium lauryl sulfate (151-21-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Sodium xylene sulfonate (1300-72-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Ethyl alcohol (64-17-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
1,2,4-Butanetricarboxylic acid, 2-phosphono- (37971-36-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	

CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzenesulfonic acid, C10-16-alkyl derivatives, sodium salts (68081-81-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Fatty acids, coco, potassium salts (61789-30-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
N,N-Dimethyltetradecylamine oxide (3332-27-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Sodium gluconate (527-07-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
US State Regulations	
Ethyl alcohol (64-17-5)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.
Ethyl alcohol (64-17-5)	
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - New York - Occupational Exposure Limits - TWAs RTK - U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
Sodium hydroxide (1310-73-2)	
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728) U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances RTK - U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - New York - Occupational Exposure Limits - TWAs U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List RTK - U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
Sodium lauryl sulfate (151-21-3)	
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
Sodium xylene sulfonate (1300-72-7)	
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
Potassium hydroxide (1310-58-3)	
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	

CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzenesulfonic acid, C10-16-alkyl derivatives, sodium salts (68081-81-2)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
Sodium gluconate (527-07-1)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
1,2,4-Butanetricarboxylic acid, 2-phosphono- (37971-36-1)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

Sodium hydroxide (1310-73-2)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Sodium lauryl sulfate (151-21-3)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Ethyl alcohol (64-17-5)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Benzenesulfonic acid, C10-16-alkyl derivatives, sodium salts (68081-81-2)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Water (7732-18-5)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Potassium hydroxide (1310-58-3)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Sodium xylene sulfonate (1300-72-7)
Listed on the Canadian DSL (Domestic Substances List) inventory.
N,N-Dimethyltetradecylamine oxide (3332-27-2)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Sodium gluconate (527-07-1)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Fatty acids, coco, potassium salts (61789-30-8)
Listed on the Canadian DSL (Domestic Substances List) inventory.
1,2,4-Butanetricarboxylic acid, 2-phosphono- (37971-36-1)
Listed on the Canadian DSL (Domestic Substances List) inventory.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date	:	11/11/2024
Other Information	:	This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation: dust, mist)	Acute toxicity (inhalation: dust, mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A

CCT-HS (AFCO 6057)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flam. Liq. 2	Flammable liquids Category 2
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H290	May be corrosive to metals
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA Fire Hazard

: 0 - Materials that will not burn.

NFPA Reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken, and medical treatment is given.

Flammability

: 0 - Minimal Hazard.

Physical

: 1 - Slight Hazard.

Party Responsible for the Preparation of This Document

AFCO
550 Development Avenue
Chambersburg, PA 17201
T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS SDS 2015 (U.S., Can., Mex.)