## ZEP LIQUID HEAT HAIRBUILDUP GREASE REMOVER QT 12CT

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP LIQUID HEAT HAIRBUILDUP GREASE REMOVER QT

12CT

Material number : ZULH34

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

## **Emergency telephone numbers**

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

## Recommended use of the chemical and restrictions on use

Recommended use : Drain & Sewer Care

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

#### **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	liquid
Colour	colourless, light yellow
Odour	slight, Chlorine

## **GHS Classification**

Skin corrosion : Category 1 Serious eye damage : Category 1

**GHS label elements** 

Hazard pictograms

Compaign

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

Precautionary statements : **Prevention**:

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
sodium hypochlorite	7681-52-9	>= 5 - < 10
sodium hydroxide	1310-73-2	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

## **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

> Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Keep respiratory tract clear. If swallowed

DO NOT induce vomiting unless directed to do so by a

physician or poison control center. Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital. Effects are immediate and delayed.

Most important symptoms and effects, both acute and

Notes to physician

delayed

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. : Treat symptomatically. Symptoms may be delayed.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Water spray jet

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Specific extinguishing

methods

Further information

: No hazardous combustion products are known

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment.

: Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Keep away from metals.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
sodium hypochlorite	7681-52-9	STEL	2 mg/m3	US WEEL
sodium hydroxide	1310-73-2	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		С	2 mg/m3	OSHA P0
		С	2 mg/m3	CAL PEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location. Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

## ZEP LIQUID HEAT HAIRBUILDUP GREASE REMOVER QT 12CT

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : colourless, light yellow

Odour : slight, Chlorine

Odour Threshold : No data available

Melting point/freezing point : No data available

Boiling point : > 100 °C

Flash point

does not flash

: > 12.5

Evaporation rate : 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 1 106 g/gm²

Density : 1.106 g/cm3

Bulk density : No data available

Solubility(ies)

pΗ

Water solubility : soluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available Viscosity, kinematic : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

## ZEP LIQUID HEAT HAIRBUILDUP GREASE REMOVER QT 12CT

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Incompatible materials : Acids Metals

Organic materials

Ammonia

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain. Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**Acute toxicity** 

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

**Components:** 

sodium hydroxide:

Acute dermal toxicity : Acute toxicity estimate Rabbit: 1,350 mg/kg

Skin corrosion/irritation

Product:

## ZEP LIQUID HEAT HAIRBUILDUP GREASE REMOVER QT 12CT

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

Remarks: Extremely corrosive and destructive to tissue.

## Serious eye damage/eye irritation

## **Product:**

Remarks: May cause irreversible eye damage.

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

## Carcinogenicity

No data available

## Reproductive toxicity

No data available

## STOT - single exposure

No data available

## STOT - repeated exposure

No data available

## **Aspiration toxicity**

No data available

#### **Further information**

## Product:

Remarks: No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

## **Components:**

## sodium hydroxide:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l

Exposure time: 96 h Test Method: static test

LC50 (Oncorhynchus tshawytscha (chinook salmon)):

152 mg/l

Exposure time: 96 h

## ZEP LIQUID HEAT HAIRBUILDUP GREASE REMOVER QT 12CT

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

LC50 (Oncorhynchus mykiss (rainbow trout)): 40 mg/l

Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 34 - 47 mg/l

Exposure time: 48 h

EC50 (Crangon crangon (shrimp)): 33 - 100 mg/l

Exposure time: 48 h

## Persistence and degradability

No data available

**Bioaccumulative potential** 

**Product:** 

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

Components:

sodium hydroxide:

Additional ecological

information

: Harmful to aquatic life.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II - Limited quantity

Transportation Regulation: IMDG (Vessel):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, II -

Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IATA (Passenger Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: TDG (Canada):

UN3266, CORROŠIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, II -

Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
sodium hypochlorite	7681-52-9	100	1602

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

# SAFETY DATA SHEET ZEP LIQUID HEAT HAIRBUILDUP GREASE REMOVER QT 12CT

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

## The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**

Revision Date 10/01/2023 Print Date 07/10/2025 Version 2.1

#### **Further information**

## NFPA:

HEALTH	3
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

## HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms



Signal word Hazard statements Precautionary statements Danger:

Causes severe skin burns and eye damage.

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before

**Disposal:** Dispose of contents/container in accordance with local regulation.

# SAFETY DATA SHEET ZEP LIQUID HEAT HAIRBUILDUP GREASE REMOVER QT 12CT

Version 2.1 Revision Date 10/01/2023 Print Date 07/10/2025

Version:	2.1
Revision Date:	10/01/2023
Print Date:	07/10/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

## **ZEP LIQUID HEAT GEL 640Z 6CT**

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP LIQUID HEAT GEL 64OZ 6CT

Material number : ZULHG64

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

## **Emergency telephone numbers**

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

Recommended use : Drain & Sewer Care

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

## **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	viscous liquid	
Colour	light yellow	
Odour	chlorine-like	

#### **GHS Classification**

Skin corrosion : Category 1 Serious eye damage : Category 1

**GHS** label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention**:

## **ZEP LIQUID HEAT GEL 640Z 6CT**

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
sodium hypochlorite	7681-52-9	>= 5 - < 10
potassium hydroxide	1310-58-3	>= 1 - < 5
sodium hydroxide	1310-73-2	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

## **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with

difficulty.

Wash off immediately with plenty of water for at least 15

minutes.

Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

tissue damage and blindness.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

Notes to physician

delayed

Effects are dependent on exposure (dose, concentration, contact time).

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain.

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. : Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Dry chemical

Water spray jet

Alcohol-resistant foam Carbon dioxide (CO2) : High volume water jet

Unsuitable extinguishing

media

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Specific extinguishing

methods

: No hazardous combustion products are known

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Collect contaminated fire extinguishing water separately. This Further information

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures **Environmental precautions**  : Use personal protective equipment.

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

## **ZEP LIQUID HEAT GEL 640Z 6CT**

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Oxidizing agents

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
sodium hypochlorite	7681-52-9	STEL	2 mg/m3	US WEEL
potassium hydroxide	1310-58-3	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		С	2 mg/m3	OSHA P0
		С	2 mg/m3	CAL PEL
sodium hydroxide	1310-73-2	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		С	2 mg/m3	OSHA P0
		С	2 mg/m3	CAL PEL

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : Protective gloves The suitability for a specific workplace

should be discussed with the producers of the protective

gloves.

Eye protection : Tightly fitting safety goggles

# SAFETY DATA SHEET ZEP LIQUID HEAT GEL 64OZ 6CT

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

Wear face-shield and protective suit for abnormal processing

problems.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : viscous liquid

Colour : light yellow
Odour : chlorine-like

Odour Threshold : No data available

pH : 13.8

Melting point/freezing point : No data available Boiling point : No data available

Flash point

Not applicable

Evaporation rate : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 1.15 g/cm<sup>3</sup>

Bulk density : No data available

Solubility(ies)

Water solubility : completely soluble Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available
Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available Viscosity, kinematic : No data available

## **ZEP LIQUID HEAT GEL 640Z 6CT**

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : No data available Incompatible materials

: Acids

Hazardous decomposition

products

: No hazardous decomposition products are known.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

Condition

: None known.

Oxidizing agents

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration,

contact time).

Effects are immediate and delayed.

Symptoms may include blistering, irritation, burns, and pain.

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

**IARC** No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**ACGIH** No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

No component of this product present at levels greater than or **OSHA** 

equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**Acute toxicity** 

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 3,703 mg/kg

Method: Calculation method

Components:

sodium hydroxide:

## **ZEP LIQUID HEAT GEL 640Z 6CT**

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

Acute dermal toxicity : Acute toxicity estimate Rabbit: 1,350 mg/kg

#### Skin corrosion/irritation

## **Product:**

Remarks: Extremely corrosive and destructive to tissue.

## Serious eye damage/eye irritation

## **Product:**

Remarks: May cause irreversible eye damage.

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

## Carcinogenicity

No data available

## Reproductive toxicity

No data available

## STOT - single exposure

No data available

## STOT - repeated exposure

No data available

## **Aspiration toxicity**

No data available

## **Further information**

## **Product:**

Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

## **Components:**

## sodium hydroxide:

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l

Exposure time: 96 h
Test Method: static test

## **ZEP LIQUID HEAT GEL 640Z 6CT**

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

LC50 (Oncorhynchus tshawytscha (chinook salmon)):

152 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 40 mg/l

Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 34 - 47 mg/l

Exposure time: 48 h

EC50 (Crangon crangon (shrimp)): 33 - 100 mg/l

Exposure time: 48 h

## Persistence and degradability

No data available

## Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water

: Remarks: No data available

## Mobility in soil

No data available

## Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

**Components:** 

sodium hydroxide:

Additional ecological

information

: Harmful to aquatic life.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

## **ZEP LIQUID HEAT GEL 640Z 6CT**

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN1760, CORROSIVE LIQUIDS, N.O.S., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IMDG (Vessel):

UN1760, CORROSIVE LIQUIDS, N.O.S., (SODIUM HYPOCHLORITE), 8, II, MP: (SODIUM

HYPOCHLORITE)

Transportation Regulation: IATA (Cargo Air):

UN1760, Corrosive liquid, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IATA (Passenger Air):

UN1760, Corrosive liquids, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: TDG (Canada):

UN1760, CORROSIVE LIQUIDS, N.O.S., (SODIUM HYPOCHLORITE), 8, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

## **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium hypochlorite	7681-52-9	100	1602

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

## **ZEP LIQUID HEAT GEL 640Z 6CT**

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

## The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**

Print Date 07/10/2025 Version 3.1 Revision Date 10/01/2023

#### **Further information**

## NFPA:

HEALTH	3
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

## HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms



Signal word Hazard statements Precautionary statements Danger:

Causes severe skin burns and eye damage.

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before

**Disposal:** Dispose of contents/container in accordance with local regulation.

# SAFETY DATA SHEET ZEP LIQUID HEAT GEL 640Z 6CT

Version 3.1 Revision Date 10/01/2023 Print Date 07/10/2025

Version:	3.1
Revision Date:	10/01/2023
Print Date:	07/10/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

## **ZEP LIQUID HEAT MAX 640Z 4CT**

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

ZEP LIQUID HEAT MAX 64OZ 4CT Material name

Material number ZULHM64

Manufacturer or supplier's details

Company Zep Inc.

Address 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Compliance Services - 877-428-9937 Telephone

## **Emergency telephone numbers**

For SDS Information Compliance Services - 877-428-9937 For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded. **Emergency** In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

Recommended use : Drain & Sewer Care

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

## **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	liquid	
Colour	light yellow	
Odour	chlorine-like	

#### **GHS Classification**

Skin corrosion : Category 1 Serious eye damage : Category 1

**GHS** label elements

Hazard pictograms

Signal word Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : Prevention:

## **ZEP LIQUID HEAT MAX 640Z 4CT**

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
sodium hypochlorite	7681-52-9	>= 6 - < 10
potassium hydroxide	1310-58-3	>= 2 - < 5
sodium hydroxide	1310-73-2	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with

difficulty.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital. Effects are immediate and delayed.

Most important symptoms and effects, both acute and

Notes to physician

delayed

Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards.

Treat symptomatically. Symptoms may be delayed.

**SECTION 5. FIREFIGHTING MEASURES** 

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: No hazardous combustion products are known

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES** 

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## **ZEP LIQUID HEAT MAX 640Z 4CT**

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

Keep away from metals.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
sodium hypochlorite	7681-52-9	STEL	2 mg/m3	US WEEL
potassium hydroxide	1310-58-3	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		С	2 mg/m3	OSHA P0
		С	2 mg/m3	CAL PEL
sodium hydroxide	1310-73-2	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		С	2 mg/m3	OSHA P0
		С	2 mg/m3	CAL PEL

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

## **ZEP LIQUID HEAT MAX 640Z 4CT**

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025

Skin and body protection Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

: liquid Appearance

: light yellow Colour Odour chlorine-like

Odour Threshold No data available

13.8 pΗ

: No data available Melting point/freezing point Boiling point No data available

Flash point

does not flash

Upper explosion limit No data available Lower explosion limit No data available Vapour pressure No data available

Density : 1.15 g/cm3

Solubility(ies)

Water solubility : completely soluble Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No decomposition if stored and applied as directed.

Conditions to avoid No data available

Incompatible materials Acids Metals

Organic materials

## **ZEP LIQUID HEAT MAX 640Z 4CT**

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025

Ammonia

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure

: Effects are immediate and delayed.

Effects are dependent on exposure (dose, concentration,

contact time).

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**Acute toxicity** 

**Product:** 

Acute oral toxicity : Acute toxicity estimate : 3,704 mg/kg

Method: Calculation method

Components:

sodium hydroxide:

Acute dermal toxicity : Acute toxicity estimate Rabbit: 1,350 mg/kg

#### Skin corrosion/irritation

**Product:** 

Remarks: Extremely corrosive and destructive to tissue.

## Serious eye damage/eye irritation

**Product:** 

Remarks: May cause irreversible eye damage.

## **ZEP LIQUID HEAT MAX 640Z 4CT**

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025

## Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

**Aspiration toxicity** 

No data available

#### **Further information**

**Product:** 

Remarks: No data available

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

## **Components:**

sodium hydroxide :

Toxicity to fish : LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l

Exposure time: 96 h Test Method: static test

LC50 (Oncorhynchus tshawytscha (chinook salmon)):

152 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 40 mg/l

Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 34 - 47 mg/l

Exposure time: 48 h

EC50 (Crangon crangon (shrimp)): 33 - 100 mg/l

Exposure time: 48 h

## **ZEP LIQUID HEAT MAX 640Z 4CT**

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025

## Persistence and degradability

No data available

## **Bioaccumulative potential**

**Product:** 

Partition coefficient: n-

octanol/water

: Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

**Components:** 

sodium hydroxide:

Additional ecological

information

: Harmful to aquatic life.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

## **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II, RQ (SODIUM

HYPOCHLORITE)

## **ZEP LIQUID HEAT MAX 640Z 4CT**

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025

Transportation Regulation: IMDG (Vessel):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IATA (Cargo Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: IATA (Passenger Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, II

Transportation Regulation: TDG (Canada):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, II

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ	
		(lbs)	(lbs)	
sodium hypochlorite	7681-52-9	100	1451	

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## California Prop. 65

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025



WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

## The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

## **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**

Revision Date 05/29/2025 Print Date 07/10/2025 Version 1.2

#### **Further information**

## NFPA:

HEALTH	3
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

## HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms



Signal word Hazard statements Precautionary statements Danger:

Causes severe skin burns and eye damage.

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before

**Disposal:** Dispose of contents/container in accordance with local regulation.

# SAFETY DATA SHEET ZEP LIQUID HEAT MAX 640Z 4CT

Version 1.2 Revision Date 05/29/2025 Print Date 07/10/2025

Version:	1.2
Revision Date:	05/29/2025
Print Date:	07/10/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

## **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Version 5.2 Revision Date 06/10/2025 Print Date 07/10/2025

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : ZEP 10 MINUTE DRAIN OPENER GEL 64OZ 6CT

Material number : ZHCR64NG6

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE

Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

## **Emergency telephone numbers**

For SDS Information : Compliance Services - 877-428-9937
For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

Recommended use : Drain & Sewer Care

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

## **SECTION 2. HAZARDS IDENTIFICATION**

## **Emergency Overview**

Appearance	liquid	
Colour	light yellow	
Odour	Chlorine	

#### **GHS Classification**

Skin corrosion : Category 1 Serious eye damage : Category 1

**GHS** label elements

Hazard pictograms

Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention**:

## **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Version 5.2 Revision Date 06/10/2025 Print Date 07/10/2025

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local

regulation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

Chemical name	CAS-No.	Concentration [%]
sodium hypochlorite	7681-52-9	>= 3 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

## **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing and shoes.

Wash off immediately with plenty of water for at least 15

minutes.

Wash contaminated clothing before reuse. If symptoms persist, call a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

## **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Version 5.2 Revision Date 06/10/2025 Print Date 07/10/2025

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

: Symptoms may include blistering, irritation, burns, and pain.

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards.

: Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

Most important symptoms

Notes to physician

and effects, both acute and

media

delaved

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: No hazardous combustion products are known

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Collect contaminated fire extinguishing water separately. This Further information

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Environmental precautions Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas.

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains, inform

respective authorities.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.

> Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

## **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Version 5.2 Revision Date 06/10/2025 Print Date 07/10/2025

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Do not store near acids.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
sodium hypochlorite	7681-52-9	STEL	2 mg/m3	US WEEL

**Engineering measures** : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options

include: eye wash stations or showers, or eye wash bottles

with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : light yellow
Odour : Chlorine

Odour Threshold : No data available

pH : > 13

## **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Version 5.2 Revision Date 06/10/2025 Print Date 07/10/2025

Melting point/freezing point : No data available

Boiling point : > 100 °C

Flash point

Not applicable

Evaporation rate : 1

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 1.059 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Conditions to avoid : No data available Incompatible materials : Acids

Ammonia soft metals

Hazardous decomposition

products

Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).

## **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects**

Aggravated Medical

Condition

: None known.

## **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Version 5.2 Revision Date 06/10/2025 Print Date 07/10/2025

Symptoms of Overexposure : Symptoms may include blistering, irritation, burns, and pain.

Causes severe skin burns and eye damage.

Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

## **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

#### Skin corrosion/irritation

#### **Product:**

Remarks: Extremely corrosive and destructive to tissue.

## Serious eye damage/eye irritation

#### **Product:**

Remarks: May cause irreversible eye damage.

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

## Reproductive toxicity

No data available

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

## **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Version 5.2 Revision Date 06/10/2025 Print Date 07/10/2025

## **Aspiration toxicity**

No data available

#### **Further information**

#### **Product:**

Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

## Persistence and degradability

No data available

## **Bioaccumulative potential**

#### **Product:**

Partition coefficient: n-

octanol/water

: Remarks: No data available

#### Mobility in soil

No data available

#### Other adverse effects

No data available

# Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

## **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Version 5.2 Revision Date 06/10/2025 Print Date 07/10/2025

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, III - Limited quantity

Transportation Regulation: IMDG (Vessel):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, III -

Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, III

Transportation Regulation: IATA (Passenger Air):

UN3266, Corrosive liquid, basic, inorganic, n.o.s., (SODIUM HYPOCHLORITE), 8, III

Transportation Regulation: TDG (Canada):

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S., (SODIUM HYPOCHLORITE), 8, III -

Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

## **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

## **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium hypochlorite	7681-52-9	100	3203

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

## **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Version 5.2 Revision Date 06/10/2025 Print Date 07/10/2025

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

**DSL** All components of this product are on the Canadian DSL

TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

**Inventory Acronym and Validity Area Legend:** 

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**

# **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Print Date 07/10/2025 Version 5.2 Revision Date 06/10/2025

#### **Further information**

## NFPA:

HEALTH	3
FLAMMABILITY	0
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme

## HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### **OSHA - GHS Label Information:**

Hazard pictograms



Signal word Hazard statements Precautionary statements Danger:

Causes severe skin burns and eye damage.

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before

**Disposal:** Dispose of contents/container in accordance with local regulation.

# **ZEP 10 MINUTE DRAIN OPENER GEL 640Z 6CT**

Version 5.2 Revision Date 06/10/2025 Print Date 07/10/2025

Version:	5.2
Revision Date:	06/10/2025
Print Date:	07/10/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.