

# SAFETY DATA SHEET

## ZEP DRY GRAPHITE 20N14\_12CT

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP DRY GRAPHITE 20N14\_12CT

Material number : 000000000000164016

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street  
Edmonton, Alberta T5S 1N6  
Canada

Telephone : Compliance Services - 877-428-9937

#### Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation  
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	dark grey
Odour	alcohol-like

#### GHS Classification

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Eye irritation : Category 2A  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

#### GHS label elements

Hazard pictograms :



Flame



Gas cylinder



Exclamation  
mark

Signal word : Danger

# SAFETY DATA SHEET

## ZEP DRY GRAPHITE 20N14\_12CT

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

- Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.
- Precautionary statements : **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear eye protection/ face protection.  
**Response:**  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:**  
P501 Dispose of contents/container in accordance with local regulation.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous components

Chemical name	CAS-No.	Concentration [%]
propan-2-ol	67-63-0	>= 60 - < 80
propane	74-98-6	>= 10 - < 30
butane	106-97-8	>= 10 - < 30
graphite	7782-42-5	>= 1 - < 5

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical

# SAFETY DATA SHEET

## ZEP DRY GRAPHITE 20N14\_12CT

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

advice.

- |   |   |
|---|---|
| In case of skin contact                                     | : Wash off with soap and water.<br>Remove contaminated clothing and shoes.<br>Wash contaminated clothing before re-use.<br>If skin irritation persists, call a physician.   |
| In case of eye contact                                      | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.<br>Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.                                     |
| If swallowed  | : Keep respiratory tract clear.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>DO NOT induce vomiting unless directed to do so by a physician or poison control center.<br>If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : Effects are immediate and delayed.<br>Effects are dependent on exposure (dose, concentration, contact time).<br>Causes serious eye irritation.<br>Review section 2 of SDS to see all potential hazards.   |
| Notes to physician  | : Treat symptomatically. Symptoms may be delayed.   |

---

### SECTION 5. FIREFIGHTING MEASURES

- |   |   |
|---|---|
| Suitable extinguishing media                  | : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  |
| Unsuitable extinguishing media                | : High volume water jet   |
| Hazardous combustion products                 | : Carbon dioxide (CO <sub>2</sub> )<br>Carbon monoxide<br>Smoke   |
| Specific extinguishing methods                | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.   |
| Further information                           | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>Use water spray to cool unopened containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary.  |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

# SAFETY DATA SHEET

## ZEP DRY GRAPHITE 20N14\_12CT

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains, inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL

# SAFETY DATA SHEET

## ZEP DRY GRAPHITE 20N14\_12CT

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m3	CA QC OEL
		STEV	500 ppm 1,230 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m3	CA QC OEL
		STEL	1,000 ppm	ACGIH
graphite	7782-42-5	TWA (Respirable)	2 mg/m3	CA BC OEL
		TWAEV (Respirable fibres)	5 mg/m3	CA QC OEL
		TWAEV (Total fibres)	10 mg/m3	CA QC OEL
		TWAEV (respirable dust)	2 mg/m3	CA QC OEL

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

**Engineering measures** : effective ventilation in all processing areas

### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection  
Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.  
Safety glasses  
Wear face-shield and protective suit for abnormal processing

# SAFETY DATA SHEET

## ZEP DRY GRAPHITE 20N14\_12CT

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

problems.

- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Colour : dark grey
- Odour : alcohol-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point : No data available
- Flash point :  
No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : No data available
- Density : 0.79 g/cm<sup>3</sup>
- Solubility(ies)
- Water solubility : partly miscible
- Partition coefficient: n-octanol/water : No data available
- Viscosity
- Viscosity, kinematic : No data available
- Heat of combustion : 37.58 kJ/g

---

### SECTION 10. STABILITY AND REACTIVITY

- Reactivity : Stable
- Chemical stability : Stable under normal conditions.

# SAFETY DATA SHEET

## ZEP DRY GRAPHITE 20N14\_12CT

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Effects are dependent on exposure (dose, concentration, contact time). Causes serious eye irritation. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

#### Carcinogenicity:

##### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

##### ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

#### Acute toxicity

##### Product:

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
---------------------	---

##### Components:

##### propan-2-ol:

Acute oral toxicity	: LD50 Oral Rat: 4,396 mg/kg Method: Calculation method
---------------------	--

#### Skin corrosion/irritation

##### Product:

Remarks: May cause skin irritation in susceptible persons.

# SAFETY DATA SHEET

## ZEP DRY GRAPHITE 20N14\_12CT

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

### Serious eye damage/eye irritation

#### Product:

Remarks: May irritate eyes.

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

#### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

#### Components:

##### propan-2-ol :

Partition coefficient: n-octanol/water : log Pow: 0.05



# SAFETY DATA SHEET

## ZEP DRY GRAPHITE 20N14\_12CT

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

### butane :

Partition coefficient: n-octanol/water : Pow: 2.89

### Mobility in soil

No data available

### Other adverse effects

No data available

### Product:

Additional ecological information : No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity
--

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity
---

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity
--

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity
--

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity
--

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

# SAFETY DATA SHEET

## ZEP DRY GRAPHITE 20N14\_12CT

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

### SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

**The components of this product are reported in the following inventories:**

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


#### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

### SECTION 16. OTHER INFORMATION

#### WHMIS - GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements

:  
**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection.  
**Response:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.  
**Storage:** Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	1.0
Revision Date:	04/11/2025
Print Date:	09/03/2025

# **SAFETY DATA SHEET**

## **ZEP DRY GRAPHITE 20N14\_12CT**

Version 1.0

Revision Date 04/11/2025

Print Date 09/03/2025

---

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.