



# TM Desana MAX IC (AFCO 5567)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 02/10/2025

Version: 1.2

### SECTION 1: IDENTIFICATION

#### Product Identifier

**Product Form:** Solid

**Product Name:** TM Desana MAX IC

**Product Code:** AFCO 5567

#### Intended Use of the Product

**Use of the Substance/Mixture:** Indicator and cleaner. For professional use only.

#### Name, Address, and Telephone of the Responsible Party

##### **Company**

AFCO

550 Development Avenue

Chambersburg, PA 17201

T: 800-345-1329

[www.afcocare.com](http://www.afcocare.com)

#### Emergency Telephone Number

**Emergency Number** : 1-800-424-9300 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

##### **Classification (GHS-US)**

Met. Corr. 1 H290

Acute Tox. 4 (Dermal) H312

Skin Corr. 1A H314

Eye Dam. 1 H318

Aquatic Acute 3 H402

#### Label Elements

##### **GHS-US Labeling**

##### **Hazard Pictograms (GHS-US)**



##### **Signal Word (GHS-US)**

: Danger

##### **Hazard Statements (GHS-US)**

: H290 - May be corrosive to metals  
H312 - Harmful in contact with skin  
H314 - Causes severe skin burns and eye damage  
H318 - Causes serious eye damage  
H402 - Harmful to aquatic life

##### **Precautionary Statements (GHS-US)**

: P234 - Keep only in original container.  
P260 - Do not breathe dust if inhalable particles of dust occur during use.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection.  
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# TM Desana MAX IC (AFCO 5567)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P310 - Immediately call a POISON CENTER or doctor/physician.  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.  
P321 - Specific treatment (see section 4).  
P363 - Wash contaminated clothing before reuse.  
P390 - Absorb spillage to prevent material damage.  
P405 - Store locked up.  
P406 - Store in corrosive resistant container with a resistant inner liner.  
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

### Other Hazards

**Other Hazards Not Contributing to the Classification:** N/A.

**Other Hazards:** Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes. Contact with metals may evolve flammable hydrogen gas.

**Unknown Acute Toxicity (GHS-US):** Not available.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Substances

Name	Product identifier	% (w/w)	Classification (GHS-US)
Sodium hydroxide	(CAS No) 1310-73-2	50 - 100	Met. Corr. 1, H290 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
Potassium permanganate	(CAS No) 7722-64-7	<1	Ox. Sol. 2, H272 Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16.

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention.

**Skin Contact:** Immediately flush skin with plenty of water for several minutes. Get immediate medical advice/attention. Wash contaminated clothing before reuse.

**Eye Contact:** Seek medical attention immediately. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes serious eye damage. Corrosive to eyes and skin.

**Inhalation:** None under normal and intended conditions of use.

**Skin Contact:** Causes severe skin burns.

**Eye Contact:** Causes serious eye damage.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe irritation progressing quickly to chemical burns.

**Chronic Symptoms:** Not available.

### Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide, foam, dry chemical.

# TM Desana MAX IC (AFCO 5567)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Not flammable.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Thermal decomposition generates: Corrosive vapors. When heated to decomposition, emits toxic fumes. Corrosive to metals. Contact with soft metals may evolve flammable hydrogen gas.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Toxic fumes are released. Sodium oxides.

**Other information:** Do not allow run-off from fire fighting to enter drains or water courses.

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Do not allow product to spread into the environment. Do NOT breathe dust. Do not get in eyes, on skin, or on clothing.

#### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** None.

### **Environmental Precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

### **Methods and Material for Containment and Cleaning Up**

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Cautiously neutralize spilled liquid.

**Methods for Cleaning Up:** Recover the product by vacuuming, shovelling or sweeping. Avoid dust generation. Contact competent authorities after a spill.

### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection.

## **SECTION 7: HANDLING AND STORAGE**

### **Precautions for Safe Handling**

**Additional Hazards When Processed:** When heated to decomposition, emits toxic fumes. Corrosive vapors are released. Contact with soft metals may evolve flammable hydrogen gas.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

### **Conditions for Safe Storage, Including Any Incompatibilities**

**Technical Measures:** Comply with applicable regulations. May be corrosive to metals.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from incompatible materials.

**Incompatible Materials:** Acids. Soft metals. Moisture.

**Special Rules on Packaging:** Keep only in original container.

**Specific End Use(s):** Indicator and cleaner. For professional use only.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Control Parameters**

Sodium hydroxide (1310-73-2)		
Mexico	OEL Ceiling (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>

# TM Desana MAX IC (AFCO 5567)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Ontario	OEL Ceiling (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
Québec	PLAFOND (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>

### Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. If user operations generates dust, fumes, vapor, spray, or mist, use process enclosures, local exhaust ventilation, or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Personal Protective Equipment:** Protective goggles. Protective clothing. Gloves. Face shield.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. Corrosionproof clothing.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or face shield.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** A respirator is not needed under normal and intended conditions of product use.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Off white beads with purple crystals
Odor	: Odorless
Odor Threshold	: Not available
pH	: 13.5 (1%)
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not flammable
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not flammable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Specific Gravity	: Not available
Solubility	: Complete.
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

# TM Desana MAX IC (AFCO 5567)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Thermal decomposition generates: Corrosive vapors. When heated to decomposition, emits toxic fumes. Corrosive to metals. Contact with soft metals may evolve flammable hydrogen gas.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Incompatible materials.

**Incompatible Materials:** Acids. Soft metals. Moisture.

**Hazardous Decomposition Products:** Thermal decomposition generates: Corrosive vapors. Sodium oxides.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified.

**LD50 and LC50 Data:** Not available.

**Skin Corrosion/Irritation:** Causes severe skin burns. (pH(1%): 13.5)

**Serious Eye Damage/Irritation:** Causes serious eye damage. (pH(1%): 13.5)

**Respiratory or Skin Sensitization:** Not classified.

**Germ Cell Mutagenicity:** Not classified.

**Teratogenicity:** Not available.

**Carcinogenicity:** Not classified.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified.

**Reproductive Toxicity:** Not classified.

**Specific Target Organ Toxicity (Single Exposure):** Not classified.

**Aspiration Hazard:** Not classified.

**Symptoms/Injuries After Inhalation:** None under normal and intended conditions of use.

**Symptoms/Injuries After Skin Contact:** Causes severe skin burns.

**Symptoms/Injuries After Eye Contact:** Causes serious eye damage.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe irritation progressing quickly to chemical burns.

#### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

Sodium hydroxide (1310-73-2)	
LD50 Dermal Rabbit	1350 mg/kg
Potassium permanganate (7722-64-7)	
LD50 Oral Rat	1090 mg/kg

### SECTION 12: ECOLOGICAL INFORMATION

#### Toxicity

**Ecology - General:** Harmful to aquatic life with long lasting effects.

Sodium hydroxide (1310-73-2)	
LC50 Fish 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
Potassium permanganate (7722-64-7)	
LC50 Fish 1	0.3-0.6 mg/l (Exposure time: 96 hrs. - Species: Rainbow trout)
EC50 Daphnia 1	0.084 mg/l (Exposure time: 48 hrs. - Species: Daphnia magna)

#### Persistence and Degradability

TM Desana MAX IC (AFCO 5567)	
Persistence and Degradability	May cause long-term adverse effects in the environment.

#### Bioaccumulative Potential

TM Desana MAX IC (AFCO 5567)	
Bioaccumulative Potential	Not established.

**Mobility in Soil** Not available.

# TM Desana MAX IC (AFCO 5567)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Other Adverse Effects

Other Information: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

## SECTION 14: TRANSPORT INFORMATION

### 14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)  
Hazard Class : 8  
Identification Number : UN3262  
Label Codes : 8  
Packing Group : II  
ERG Number : 154



### 14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)  
Hazard Class : 8  
Identification Number : UN3262  
Packing Group : II  
Label Codes : 8  
EmS-No. (Fire) : F-A  
EmS-No. (Spillage) : S-B



### 14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)  
Packing Group : II  
Identification Number : UN3262  
Hazard Class : 8  
Label Codes : 8  
ERG Code (IATA) : 8L



### 14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)  
Packing Group : II  
Hazard Class : 8  
Identification Number : UN3262  
Label Codes : 8



**\*Note:** AF5567T (225 x 1.9oz./53g.) is allowed to ship as Limited Quantity.

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

TM Desana MAX IC (AFCO 5567)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard.
Sodium hydroxide (1310-73-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Potassium permanganate (7722-64-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	

### US State Regulations

Sodium hydroxide (1310-73-2)
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances

# TM Desana MAX IC (AFCO 5567)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term

### Canadian Regulations

#### Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### Potassium permanganate (7722-64-7)

Listed on the Canadian DSL(Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision date** : 02/10/2025

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.


### GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (Dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (Oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Met. Corr. 1	Corrosive to metals Category 1
Ox. Sol. 2	Oxidizing solids Category 2
Skin Corr. 1A	Skin corrosion/irritation Category 1A
H272	May intensify fire; oxidizer
H290	May be corrosive to metals
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H402	Harmful to aquatic life
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

**NFPA Health Hazard** : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

**NFPA Fire Hazard** : 0 - Materials that will not burn.

**NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

**Health** : 3 Serious Hazard - Major injury likely unless prompt action is taken, and medical treatment is given.

**Flammability** : 0 - Minimal Hazard.

**Physical** : 0 - Minimal Hazard.

# TM Desana MAX IC (AFCO 5567)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

### Party Responsible for the Preparation of This Document

AFCO

550 Development Avenue

Chambersburg, PA 17201

T: 800-345-1329

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS SDS 2015 (U.S., Can., Mex.)