

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP ECOM BUNDLE 1039615 ECRAG01

Material number : ECBD034

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview


Appearance	Aerosol containing a liquefied gas
Colour	opaque, white
Odour	characteristic

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
Storage:

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 5 - < 10
Solvent naphtha (petroleum), medium aliph.	64742-88-7	>= 5 - < 10
propane	74-98-6	>= 1 - < 5
butane	106-97-8	>= 1 - < 5
Amides, tall-oil fatty, N,N-bis(hydroxyethyl)	68155-20-4	>= 1 - < 5
sodium nitrite	7632-00-0	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.
If skin irritation persists, call a physician.
If on clothes, remove clothes.
Wash off immediately with plenty of water for at least 15 minutes.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
If in eyes, rinse with water for 15 minutes.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
- Most important symptoms and effects, both acute and : Effects may be delayed, symptoms may include minor eye or skin irritation.

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

delayed

Overexposure may cause mild eye or skin irritation.

Notes to physician

: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|---|
| Suitable extinguishing media | : Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical
Water spray jet |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon dioxide (CO ₂)
Carbon monoxide
Smoke
Silicon oxides
Nitrogen oxides (NO _x) |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions | : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities. |
| Methods and materials for containment and cleaning up | : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Soak up with inert absorbent material (e.g. sand, silica gel, |

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Avoid exposure - obtain special instructions before use.
Do not breathe vapours or spray mist.
Always replace cap after use.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
Keep in a dry, cool and well-ventilated place.
- Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm	CAL PEL

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

			1,800 mg/m3	
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : opaque, white

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : Not applicable

Flash point :
Not applicable

Evaporation rate : No data available

Flammability (solid, gas, liquid) : Extremely flammable aerosol.

Upper explosion limit : No data available

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 0.95 g/cm ³
Solubility(ies)	
Water solubility	: dispersible
Solubility in other solvents	: not determined
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: > 1000 mm ² /s (40 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides Sodium oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects may be delayed, symptoms may include minor eye or skin irritation. Overexposure may cause mild eye or skin irritation. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

IARC	Group 2A: Probably carcinogenic to humans	
	sodium nitrite	7632-00-0
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.	
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.	

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

Amides, tall-oil fatty, N,N-bis(hydroxyethyl):

Acute oral toxicity : LD50 Oral Rabbit: 2,200 mg/kg

LD50 Oral Mouse: 3,300 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 12,200 mg/kg

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

butane :

Partition coefficient: n- : Pow: 2.89
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to TSCA 12(b) export notification requirements.

No substances are subject to a Significant New Use Rule.

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

sodium nitrite 7632-00-0

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, which is/are known to the State of California to cause cancer, and methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

Further information

NFPA:

HEALTH	1
FLAMMABILITY	4
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme


HMIS III:

HEALTH	1
FLAMMABILITY	4
PHYSICAL HAZARD	3

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Flame

Gas cylinder

Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Precautionary statements

: **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	6.1
Revision Date:	10/01/2023
Print Date:	02/20/2026

SAFETY DATA SHEET

ZEP ECOM BUNDLE 1039615 ECRAG01

Version 6.1

Revision Date 10/01/2023

Print Date 02/20/2026

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.