



Rust Off (AFCO 3295)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 08/13/2024

Version: 1.2

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Rust Off

Product Code: AFCO 3295

Intended Use of the Product

Use of the Substance/Mixture: Alkaline rust remover. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

AFCO

550 Development Avenue

Chambersburg, PA 17201

T: 800-345-1329

www.afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290

Skin Corr. 1A H314

Eye Dam. 1 H318

Aquatic Acute 3 H402

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

:



GHS05

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H290 - May be corrosive to metals
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H402 - Harmful to aquatic life

Precautionary Statements (GHS-US)

: P234 - Keep only in original container.
P260 - Do not breathe dust if inhalable particles of dust occur during use.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P321 - Specific treatment (see section 4).
P363 - Wash contaminated clothing before reuse.
P390 - Absorb spillage to prevent material damage.

Rust Off (AFCO 3295)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: N/A.

Other Hazards: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes. Contact with metals may evolve flammable hydrogen gas.

Unknown Acute Toxicity (GHS-US) Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Name	Product identifier	% (w/w)	Classification (GHS-US)
Sodium hydroxide	(CAS No) 1310-73-2	50-60	Met. Corr. 1, H290 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
Sodium carbonate	(CAS No) 497-19-8	20-30	Eye Irrit. 2A, H319
Sodium gluconate	(CAS No) 527-07-1	10-20	Not classified
2-Butoxyethanol	(CAS No) 111-76-2	1-5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation: vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Triethanolamine	(CAS No) 102-71-6	1-5	Not Classified
Sodium chloride	(CAS No) 7647-14-5	1-5	Not classified

Full text of H-phrases: see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention.

Skin Contact: Immediately flush skin with plenty of water for several minutes. Get immediate medical advice/attention. Wash contaminated clothing before reuse.

Eye Contact: Seek medical attention immediately. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage. Corrosive to eyes and skin.

Inhalation: None under normal and intended conditions of use.

Skin Contact: Causes severe skin burns and eye damage.

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Chronic Symptoms: Not available.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

Rust Off (AFCO 3295)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Thermal decomposition generates: Corrosive vapors. When heated to decomposition, emits toxic fumes. Contact with soft metals may evolve flammable hydrogen gas.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Toxic fumes are released. Nitrogen oxides. Sodium oxides.

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not allow product to spread into the environment. Do NOT breathe dust. Do not get in eyes, on skin, or on clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Cautiously neutralize spilled liquid.

Methods for Cleaning Up: Recover the product by vacuuming, shovelling or sweeping. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: When heated to decomposition, emits toxic fumes. Corrosive vapors are released. Contact with soft metals may evolve flammable hydrogen gas.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. May be corrosive to soft metals.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from incompatible materials.

Incompatible Materials: Strong acids. Soft metals. Moisture.

Special Rules on Packaging: Keep only in original container.

Specific End Use(s)

Alkaline rust remover. For professional use only.

Rust Off (AFCO 3295)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Sodium hydroxide (1310-73-2)		
Mexico	OEL Ceiling (mg/m ³)	2 mg/m ³
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	10 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m ³)	2 mg/m ³
2-Butoxyethanol (111-76-2)		
Mexico	OEL TWA (mg/m ³)	120 mg/m ³
Mexico	OEL TWA (ppm)	26 ppm
Mexico	OEL STEL (mg/m ³)	360 mg/m ³
Mexico	OEL STEL (ppm)	75 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	24 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
Ontario	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m ³)	97 mg/m ³
Québec	VEMP (ppm)	20 ppm
Triethanolamine (102-71-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
Ontario	OEL TWA (mg/m ³)	3.1 mg/m ³
Ontario	OEL TWA (ppm)	0.5 ppm
Québec	VEMP (mg/m ³)	5 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. If user operations generates dust, fumes, vapor, spray, or mist, use process enclosures, local exhaust ventilation, or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Personal Protective Equipment: Protective goggles. Protective clothing. Gloves. Face shield.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosionproof clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: A respirator is not needed under normal and intended conditions of product use.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Solid

Appearance : Light Tan powder

Rust Off (AFCO 3295)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor	: Characteristic
Odor Threshold	: Not available
pH(1%)	: >13.0
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not flammable
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not flammable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Specific Gravity	: Not available
Solubility	: Complete
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates: Corrosive vapors. When heated to decomposition, emits toxic fumes. Contact with soft metals may evolve flammable hydrogen gas.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Incompatible materials.

Incompatible Materials: Strong acids. Soft metals. Moisture.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Thermal decomposition generates: Corrosive vapors. Sodium oxides. Nitrogen oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns and eye damage. **pH(1%):** 13.0

Serious Eye Damage/Irritation: Causes serious eye damage. **pH(1%):** >13.0

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available.

Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: None under normal and intended conditions of use.

Symptoms/Injuries After Skin Contact: Causes severe skin burns.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Rust Off (AFCO 3295)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Sodium carbonate (497-19-8)	
LD50 Oral Rat	4090 mg/kg
LC50 Inhalation Rat	2300 mg/m ³ (Exposure time: 2 h)
Sodium hydroxide (1310-73-2)	
LD50 Dermal Rabbit	1350 mg/kg
Sodium chloride (7647-14-5)	
LD50 Oral Rat	3550 mg/kg
LD50 Dermal Rabbit	>10000 mg/kg
Triethanolamine (102-71-6)	
LD50 Oral Rat	5530 mg/kg
LD50 Oral Rabbit	2200 mg/kg
2-Butoxyethanol (111-76-2)	
LD50 Oral Rat	470 mg/kg
LD50 Dermal Rat	1680 mg/kg
LC50 Inhalation Rat (ppm)	450 ppm/4h
ATE (dermal)	0.680 mg/kg body weight
ATE (gases)	450.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h
IARC Group	3
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life.

Sodium carbonate (497-19-8)	
LC50 Fish 1	300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	265 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	310 - 1220 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Sodium hydroxide (1310-73-2)	
LC50 Fish 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
2-Butoxyethanol (111-76-2)	
LC50 Fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
Triethanolamine (102-71-6)	
LC50 Fish 1	450-1000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [bluegill])
EC50 Other Aquatic Organisms 1	609.98 mg/l (Exposure time: 48 h - Species: (Daphnia))
Sodium chloride (7647-15-5)	
LC50 Daphnia 1	1661 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 1	5840 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus (bluegill))

Persistence and Degradability

Rust Off (AFCO 3295)	
Persistence and Degradability	Not established.

Bioaccumulative Potential

Rust Off (AFCO 3295)	
Bioaccumulative Potential	Not established.

Rust Off (AFCO 3295)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium carbonate (497-19-8)	
BCF fish 1	(no bioaccumulation)
2-Butoxyethanol (111-76-2)	
Log Pow	0.81 (at 25°C)

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)
Hazard Class : 8
Identification Number : UN3262
Label Codes : 8
Packing Group : II
ERG Number : 154



14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)
Hazard Class : 8
Identification Number : UN3262
Packing Group : II
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B



14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)
Packing Group : II
Identification Number : UN3262
Hazard Class : 8
Label Codes : 8
ERG Code (IATA) : 8L



14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)
Packing Group : II
Hazard Class : 8
Identification Number : UN3262
Label Codes : 8



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Rust Off (AFCO 3295)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard.
Sodium carbonate (497-19-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Sodium hydroxide (1310-73-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
2-Butoxyethanol (111-76-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	

Rust Off (AFCO 3295)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium gluconate (527-07-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

Triethanolamine (102-71-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

US State Regulations

Sodium carbonate (497-19-8)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Sodium hydroxide (1310-73-2)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)

U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New Jersey - Special Health Hazards Substances List

U.S. - New York - Occupational Exposure Limits - TWAs

U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

2-Butoxyethanol (111-76-2)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New Jersey - Special Health Hazards Substances List

U.S. - New York - Occupational Exposure Limits - Skin Designations

U.S. - New York - Occupational Exposure Limits - TWAs

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Sodium gluconate (527-07-1)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Triethanolamine (102-71-6)

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

RTK - U.S. - New Jersey - RTK (Right to Know) List

Sodium chloride (7647-14-5)

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

RTK - U.S. - New Jersey - RTK (Right to Know) List

Canadian Regulations

Sodium carbonate (497-19-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Sodium gluconate (527-07-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Triethanolamine (102-71-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Rust Off (AFCO 3295)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.


SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 08/13/2024
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation: dust, mist)	Acute toxicity (inhalation: dust, mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H402	Harmful to aquatic life

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA Fire Hazard : 0 - Materials that will not burn.
NFPA Reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken, and medical treatment is given.
Flammability : 0 - Minimal Hazard.
Physical : 1 - Slight Hazard.

Party Responsible for the Preparation of This Document

AFCO
550 Development Avenue
Chambersburg, PA 17201
T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.