

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Material number : 000000000000107235

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	white, opaque
Odour	mild

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

Chemical name	CAS-No.	Concentration [%] *
2-phenoxyethanol	122-99-6	>= 3 - < 5

* The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	: Do not leave the victim unattended.
If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: In case of contact, immediately flush skin with plenty of water. Take off contaminated clothing and shoes immediately. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Effects may be delayed, symptoms may include minor eye or skin irritation. Effects are immediate and delayed. Effects are dependent on exposure (dose, concentration, contact time). Overexposure may cause mild eye or skin irritation. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Dry chemical
Unsuitable extinguishing media	: Water spray jet

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO ₂) Carbon monoxide Nitrogen oxides (NO _x) Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Standard procedure for chemical fires.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Evacuate personnel to safe areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	: Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: Electrical installations / working materials must comply with the technological safety standards. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions.
Materials to avoid	: Oxidizing agents

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses

Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat, drink or smoke.
Wash hands before breaks and immediately after handling the product.

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: white, opaque
Odour	: mild
Odour Threshold	: No data available
pH	: 8.02
Melting point/freezing point	: No data available
Boiling point	: 100 °C
Flash point	: > 93.3 °C Method: closed cup
Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: not determined
Relative vapour density	: No data available
Density	: 1.028 g/cm ³
Solubility(ies)	
Water solubility	: soluble
Solubility in other solvents	: Not applicable
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: 9.4 mm ² /s (20 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No hazards to be specially mentioned.
Conditions to avoid	: No data available

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

Incompatible materials : Oxidizing agents

Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects may be delayed, symptoms may include minor eye or skin irritation.
Effects are immediate and delayed.
Effects are dependent on exposure (dose, concentration, contact time).
Overexposure may cause mild eye or skin irritation.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

Serious eye damage/eye irritation

Product:

Remarks: May irritate eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

Transportation Regulation: IMDG (Vessel):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ammonia, aqueous solution	1336-21-6	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

2-phenoxyethanol	122-99-6	3.4776 %
------------------	----------	----------

California Prop. 65



WARNING: This product can expose you to chemicals including styrene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

SECTION 16. OTHER INFORMATION

Further information

NFPA:

HEALTH	0
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Not a hazardous substance or mixture.

Version:	5.0
----------	-----

SAFETY DATA SHEET

ZEP SEAL 25 INTERIOR NON-RESILIENT FLOOR SEALER 5GL

Version 5.0

Revision Date 02/12/2026

Print Date 02/12/2026

Revision Date:	02/12/2026
Print Date:	02/12/2026

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.