

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Material number : 000000000001049944

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street
Edmonton, Alberta T5S 1N6
Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas
Colour	clear, colourless
Odour	characteristic

GHS Classification

Gases under pressure : Compressed gas
Skin irritation : Category 2
Eye irritation : Category 2A
Carcinogenicity : Category 1B

GHS label elements

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Hazard pictograms

:



Gas cylinder

Health hazard

Exclamation
mark

Signal word

: Danger

Hazard statements

: H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H350 May cause cancer.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
P403 Store in a well-ventilated place.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%] *
---------------	---------	---------------------

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

tetrachloroethylene	127-18-4	$\geq 80 - \leq 100$
carbon dioxide	124-38-9	$\geq 1 - < 5$

* The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

Get medical attention immediately.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
Remove contaminated clothing and shoes.
Wash contaminated clothing before reuse.
- In case of eye contact : Remove contact lenses.
In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If eye irritation persists, consult a specialist.
Protect unharmed eye.
Keep eye wide open while rinsing.
- If swallowed : DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Effects are dependent on exposure (dose, concentration, contact time).
Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Chronic effects are delayed and symptoms may not be observed during an exposure.
Causes skin irritation.
Causes serious eye irritation.
Review section 2 of SDS to see all potential hazards.

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|---|
| Suitable extinguishing media | : Dry chemical
Alcohol-resistant foam
Carbon dioxide (CO2) |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon dioxide (CO2)
Carbon monoxide
Smoke
Chlorine compounds
phosgene |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Immediately evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions | : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable |

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

container for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Container may be opened only under exhaust ventilation hood.
Always replace cap after use.
Dispose of rinse water in accordance with local and national regulations.
Do not breathe vapours or spray mist.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
Keep in a dry, cool and well-ventilated place.
No smoking.
- Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
tetrachloroethylene	127-18-4	STEL	100 ppm 678 mg/m3	CA AB OEL
		TWA	25 ppm 170 mg/m3	CA AB OEL
		TWA	25 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	25 ppm 170 mg/m3	CA QC OEL
		STEV	100 ppm 685 mg/m3	CA QC OEL
		TWA	25 ppm	ACGIH
		STEL	100 ppm	ACGIH
carbon dioxide	124-38-9	TWA	5,000 ppm	CA AB OEL

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

			9,000 mg/m3	
		STEL	30,000 ppm 54,000 mg/m3	CA AB OEL
		TWA	5,000 ppm	CA BC OEL
		STEL	15,000 ppm	CA BC OEL
		STEV	30,000 ppm 54,000 mg/m3	CA QC OEL
		TWAEV	5,000 ppm 9,000 mg/m3	CA QC OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameter s	Biological specimen	Sampling time	Permissible concentration	Basis
TETRACHLOROETHENE	127-18-4	Tetrachloro ethylene	In blood	Prior to shift (16 hours after exposure ceases)	0.5 mg/l	ACGIH BEI
		Tetrachloro ethylene	In end-exhaled air	Prior to shift (16 hours after exposure ceases)	3 ppm	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

Skin and body protection : No special protection is required.

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Hygiene measures : When using do not eat or drink.
When using do not smoke.

Wash hands before breaks and at the end of
workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Aerosol containing a compressed gas

Colour : clear, colourless

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : No data available

Flash point :
does not flash

Evaporation rate : not determined

Flammability (solid, gas, liquid) : The product is not flammable.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 5,860 - 6,894 hPa

Relative vapour density : No data available

Density : 1.619 g/cm³

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : not determined

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 4.88 kJ/g

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Aluminium Strong oxidizing agents
Hazardous decomposition products	: Carbon monoxide Carbon dioxide (CO ₂) Gaseous hydrogen chloride (HCl). Phosgene Chlorine

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Chronic effects are delayed and symptoms may not be observed during an exposure. Causes skin irritation. Causes serious eye irritation. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC	Group 2A: Probably carcinogenic to humans	
	tetrachloroethylene	127-18-4
ACGIH	Confirmed animal carcinogen with unknown relevance to	

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

humans

tetrachloroethylene

127-18-4

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 2,696 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

tetrachloroethylene:

Acute oral toxicity : LD50 Oral Rat: 2,629 mg/kg

Acute inhalation toxicity : LC50 Rat: 34,200 mg/l
Exposure time: 8 h

Acute dermal toxicity : LD50 Dermal Rabbit: 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Irritating to eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

tetrachloroethylene :

Partition coefficient: n-octanol/water : log Pow: 3.40

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- | | |
|------------------------|--|
| Waste from residues | : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations. |
| Contaminated packaging | : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum. |

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):

UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air):

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA):

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

SAFETY DATA SHEET

ZEP X-OUT III CARPET & FABRIC SPOTTER 20N20 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause cancer.

Precautionary statements

:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.
Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place.
Disposal: Dispose of contents/ container to an approved waste disposal plant.

Version:	1.2
Revision Date:	12/21/2025
Print Date:	12/21/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.