

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Material number : 000000000001049969

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street
Edmonton, Alberta T5S 1N6
Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	aromatic

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Eye irritation : Category 2A
Reproductive toxicity : Category 2
Specific target organ toxicity - : Category 3 (Central nervous system)

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

single exposure

Specific target organ toxicity - : Category 2

repeated exposure

(Inhalation)

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P410 + P412 Protect from sunlight. Do not expose to

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%] *
acetone	67-64-1	>= 45 - < 70
toluene	108-88-3	>= 10 - < 30
propane	74-98-6	>= 5 - < 10
2-butoxyethanol	111-76-2	>= 5 - < 10
butanone	78-93-3	>= 5 - < 10
butane	106-97-8	>= 5 - < 10

* The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.

In case of skin contact : Wash off with soap and plenty of water.
Wash off immediately with plenty of water for at least 15 minutes.
Wash contaminated clothing before re-use.

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Call a physician if irritation develops or persists.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.

Chronic effects are delayed and symptoms may not be observed during an exposure.
Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling, respiratory issues, and general pain.
Effects are dependent on exposure (dose, concentration, contact time).
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure if inhaled.
Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)
Foam
Dry chemical
Water

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion : Carbon dioxide (CO2)

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

products	Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Use a water spray to cool fully closed containers. Standard procedure for chemical fires.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Do not breathe vapours or spray mist. Always replace cap after use.
Conditions for safe storage	: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking.

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Observe label precautions.
Keep in a cool, well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Strong oxidizing agents
Do not store near acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm 1,200 mg/m3	CA AB OEL
		STEL	750 ppm 1,800 mg/m3	CA AB OEL
		TWA	250 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		STEV	1,000 ppm 2,380 mg/m3	CA QC OEL
		TWAEV	500 ppm 1,190 mg/m3	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
toluene	108-88-3	TWA	50 ppm 188 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m3	CA QC OEL
		TWA	20 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
2-butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm 97 mg/m3	CA QC OEL
		TWA	20 ppm	ACGIH
butanone	78-93-3	TWA	200 ppm 590 mg/m3	CA AB OEL
		STEL	300 ppm 885 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	50 ppm	CA QC OEL

SAFETY DATA SHEET**ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT**

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

			150 mg/m3	
		STEV	100 ppm 300 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m3	CA QC OEL
		STEL	1,000 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameter s	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
METHYLBENZENE	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g Creatinine	ACGIH BEI
2-BUTANONE	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure	2 mg/l	ACGIH BEI

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

				ceases)		
--	--	--	--	---------	--	--

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses

Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.

Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Aerosol containing a liquefied gas
Colour	: colourless
Odour	: aromatic
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas, liquid)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 0.810 g/cm ³
Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Decomposition temperature	: No data available
Heat of combustion	: 35.04 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Incompatible materials : Acids
Oxidizing agents

Hazardous decomposition products : Carbon monoxide
Carbon dioxide (CO₂)

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.

Chronic effects are delayed and symptoms may not be observed during an exposure.
Symptoms may differ depending on organs and systems affected. These effects generally are reflected in reduced function or change, which may include cramping, swelling, respiratory issues, and general pain.
Effects are dependent on exposure (dose, concentration, contact time).
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure if inhaled.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

2-butoxyethanol

111-76-2

Acute toxicity

Product:

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

2-butoxyethanol:

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

butanone:

Acute oral toxicity : LD50 Oral Rat: 2,737 mg/kg

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Acute inhalation toxicity : LC50 Mouse: 32,000 mg/l

Exposure time: 4 h

LC50 : 38,000 mg/l

Acute dermal toxicity : LD50 Dermal Rabbit: 6,480 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Irritating to eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Components:

toluene:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

toluene :

Partition coefficient: n-octanol/water : Pow: 2.73

butanone :

Partition coefficient: n-octanol/water : log Pow: 0.29

butane :

Partition coefficient: n-octanol/water : Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

toluene :

Additional ecological information : No data available

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- | | |
|------------------------|--|
| Waste from residues | : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations. |
| Contaminated packaging | : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum. |

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms :



Signal word : **Danger:**

SAFETY DATA SHEET

ZEP ERASE II VANDAL MARK REMOVER 20N14.5 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Hazard statements : Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.
Storage: Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.2
Revision Date:	12/21/2025
Print Date:	12/21/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.