

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP STAINLESS STEEL POLISH 20N16 12CT

Material number : 000000000000014301

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street
Edmonton, Alberta T5S 1N6
Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas
Colour	clear
Odour	characteristic

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Compressed gas
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitisation : Category 1

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT


Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements

: **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Hazardous components

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Chemical name	CAS-No.	Concentration [%] *
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 60 - < 80
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 30
Solvent naphtha (petroleum), light aliph.	64742-89-8	>= 5 - < 10
d-limonene	5989-27-5	>= 1 - < 5
carbon dioxide	124-38-9	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5
citral	5392-40-5	>= 0.1 - < 1

* The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
Remove contaminated clothing and shoes.
Wash contaminated clothing before reuse.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
Rinse immediately with plenty of water for at least 15 minutes.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
- Most important symptoms : Effects are immediate and delayed.

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

and effects, both acute and delayed

Symptoms may include irritation, redness, pain, and rash.
Effects are dependent on exposure (dose, concentration, contact time).
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Review section 2 of SDS to see all potential hazards.

Notes to physician

: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray jet

Unsuitable extinguishing media

: High volume water jet

Specific hazards during firefighting

: Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products

: Carbon dioxide (CO₂)
Carbon monoxide
Smoke

Specific extinguishing methods

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information

: Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters

: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Always replace cap after use.
Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Keep in a dry, cool and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis
------------	---------	----------------------------------	----------------------------------	-------

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

			concentration	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m3 (As total hydrocarbon vapour)	CA BC OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m3	CA AB OEL
		STEL	30,000 ppm 54,000 mg/m3	CA AB OEL
		TWA	5,000 ppm	CA BC OEL
		STEL	15,000 ppm	CA BC OEL
		STEV	30,000 ppm 54,000 mg/m3	CA QC OEL
		TWAEV	5,000 ppm 9,000 mg/m3	CA QC OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m3	CA QC OEL
		STEV	500 ppm 1,230 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
citral	5392-40-5	TWA (Inhalable fraction and vapor)	5 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Aerosol containing a compressed gas

Colour : clear

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Odour	: characteristic
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point	: 82.22 °C
Flash point	: No data available
Evaporation rate	: No data available
Flammability (solid, gas, liquid)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 0.846 g/cm ³
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 44.04 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Effects are dependent on exposure (dose, concentration, contact time).
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

d-limonene:

Acute oral toxicity : LD50 Oral Rat: 4,400 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: > 5,000 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

Product:

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Remarks: Causes sensitisation.

Components:

d-limonene:

Classification: May cause sensitisation by skin contact.

citral:

Classification: May cause sensitisation by skin contact.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

d-limonene :

Partition coefficient: n-octanol/water : log Pow: 4.232

propan-2-ol :

Partition coefficient: n-octanol/water : log Pow: 0.05

citral :

Partition coefficient: n-octanol/water : log Pow: 2.9 (25 °C)
Method: OECD Test Guideline 117

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):

UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms :



Signal word : **Danger:**

Hazard statements : Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statements : **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ eye protection/ face protection.
Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.
Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.2
Revision Date:	12/21/2025
Print Date:	12/21/2025

SAFETY DATA SHEET

ZEP STAINLESS STEEL POLISH 20N16 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.