

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP PERIMETER 20N18 12CT

Material number : 000000000000000501

#### Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street  
Edmonton, Alberta T5S 1N6  
Canada

Telephone : Compliance Services - 877-428-9937

#### Emergency telephone numbers

**For SDS Information** : Compliance Services - 877-428-9937

**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation  
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.

#### Recommended use of the chemical and restrictions on use

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

|            |                                    |
|------------|------------------------------------|
| Appearance | Aerosol containing a liquefied gas |
| Colour     | white                              |
| Odour      | alcohol-like, amine-like           |

#### GHS Classification

Flammable aerosols : Category 2  
Gases under pressure : Liquefied gas  
Skin corrosion : Category 1B  
Serious eye damage : Category 1

#### GHS label elements

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

H223 Flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.

Precautionary statements

:

**Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
**Storage:**  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:**  
P501 Dispose of contents/container in accordance with local regulation.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

#### Hazardous components

| Chemical name | CAS-No.  | Concentration [%] * |
|---------------|----------|---------------------|
| propan-2-ol   | 67-63-0  | >= 5 - < 10         |
| butane        | 106-97-8 | >= 5 - < 10         |

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

|                 |          |                |
|-----------------|----------|----------------|
| 2-aminoethanol  | 141-43-5 | $\geq 1 - < 5$ |
| 2-butoxyethanol | 111-76-2 | $\geq 1 - < 5$ |
| ethanol         | 64-17-5  | $\geq 1 - < 5$ |
| propane         | 74-98-6  | $\geq 1 - < 5$ |

\* The exact percentages of disclosed substances are withheld as trade secrets.

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.
- Do not leave the victim unattended.
- Show this safety data sheet to the doctor in attendance.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off with soap and water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.  
If on clothes, remove clothes.  
Wash off immediately with plenty of water for at least 15 minutes.  
Wash contaminated clothing before re-use.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If in eyes, rinse with water for 15 minutes.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include blistering, irritation, burns, and pain.  
Effects are dependent on exposure (dose, concentration,

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

contact time).  
Causes skin irritation.  
Causes serious eye damage.  
Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

---

### SECTION 5. FIREFIGHTING MEASURES

- |                                               |                                                                                                                                                                                                                                                                           |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media                  | : Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical                                                                                                                                                                                             |
| Unsuitable extinguishing media                | : High volume water jet                                                                                                                                                                                                                                                   |
| Specific hazards during firefighting          | : Do not allow run-off from fire fighting to enter drains or water courses.                                                                                                                                                                                               |
| Hazardous combustion products                 | : Carbon dioxide (CO <sub>2</sub> )<br>Carbon monoxide<br>Smoke<br>Nitrogen oxides (NO <sub>x</sub> )                                                                                                                                                                     |
| Specific extinguishing methods                | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                                                                                                                                                                 |
| Further information                           | : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>For safety reasons in case of fire, cans should be stored separately in closed containments.<br>Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary.                                                                                                                                                                                                  |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |                                                                     |                                                                                                                                                                                                                                                       |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Ensure adequate ventilation.<br>Remove all sources of ignition.<br>Evacuate personnel to safe areas.<br>Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions                                           | : Prevent product from entering drains.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains, inform                                                                                    |

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.  
Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Keep in a cool, well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Do not store near acids.

Storage temperature : 4.4 - 49 °C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

| Components  | CAS-No. | Value type<br>(Form of exposure) | Control parameters /<br>Permissible concentration | Basis     |
|-------------|---------|----------------------------------|---------------------------------------------------|-----------|
| propan-2-ol | 67-63-0 | TWA                              | 200 ppm<br>492 mg/m <sup>3</sup>                  | CA AB OEL |
|             |         | STEL                             | 400 ppm<br>984 mg/m <sup>3</sup>                  | CA AB OEL |
|             |         | TWA                              | 200 ppm                                           | CA BC OEL |
|             |         | STEL                             | 400 ppm                                           | CA BC OEL |
|             |         | TWAEV                            | 400 ppm                                           | CA QC OEL |

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

|                 |          |       |                          |           |
|-----------------|----------|-------|--------------------------|-----------|
|                 |          |       | 983 mg/m3                |           |
|                 |          | STEV  | 500 ppm<br>1,230 mg/m3   | CA QC OEL |
|                 |          | TWA   | 200 ppm                  | ACGIH     |
|                 |          | STEL  | 400 ppm                  | ACGIH     |
| butane          | 106-97-8 | TWA   | 1,000 ppm                | CA AB OEL |
|                 |          | TWA   | 600 ppm                  | CA BC OEL |
|                 |          | STEL  | 750 ppm                  | CA BC OEL |
|                 |          | TWAEV | 800 ppm<br>1,900 mg/m3   | CA QC OEL |
|                 |          | STEL  | 1,000 ppm                | ACGIH     |
| 2-aminoethanol  | 141-43-5 | STEL  | 6 ppm<br>15 mg/m3        | CA AB OEL |
|                 |          | TWA   | 3 ppm<br>7.5 mg/m3       | CA AB OEL |
|                 |          | TWA   | 3 ppm                    | CA BC OEL |
|                 |          | STEL  | 6 ppm                    | CA BC OEL |
|                 |          | TWAEV | 3 ppm<br>7.5 mg/m3       | CA QC OEL |
|                 |          | STEV  | 6 ppm<br>15 mg/m3        | CA QC OEL |
|                 |          | TWA   | 3 ppm                    | ACGIH     |
|                 |          | STEL  | 6 ppm                    | ACGIH     |
| 2-butoxyethanol | 111-76-2 | TWA   | 20 ppm<br>97 mg/m3       | CA AB OEL |
|                 |          | TWA   | 20 ppm                   | CA BC OEL |
|                 |          | TWAEV | 20 ppm<br>97 mg/m3       | CA QC OEL |
|                 |          | TWA   | 20 ppm                   | ACGIH     |
| ethanol         | 64-17-5  | TWA   | 1,000 ppm<br>1,880 mg/m3 | CA AB OEL |
|                 |          | STEL  | 1,000 ppm                | CA BC OEL |
|                 |          | TWAEV | 1,000 ppm<br>1,880 mg/m3 | CA QC OEL |
|                 |          | TWA   | 1,000 ppm                | ACGIH     |
|                 |          | STEL  | 1,000 ppm                | ACGIH     |
| propane         | 74-98-6  | TWA   | 1,000 ppm                | CA AB OEL |
|                 |          | TWA   | 1,000 ppm                | CA BC OEL |
|                 |          | TWAEV | 1,000 ppm<br>1,800 mg/m3 | CA QC OEL |
|                 |          | TWA   | 1,000 ppm                | CA ON OEL |

### Biological occupational exposure limits

| Components      | CAS-No.  | Control parameter s | Biological specimen | Sampling time                   | Permissible concentration | Basis     |
|-----------------|----------|---------------------|---------------------|---------------------------------|---------------------------|-----------|
| PROPAN-2-OL     | 67-63-0  | Acetone             | Urine               | End of shift at end of workweek | 40 mg/l                   | ACGIH BEI |
| 2-BUTOXYETHANOL | 111-76-2 | Butoxyacetic acid   | Urine               | End of shift (As)               | 200 mg/g Creatinine       | ACGIH BEI |

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

|  |  |       |  |                                         |  |  |
|--|--|-------|--|-----------------------------------------|--|--|
|  |  | (BAA) |  | soon as possible after exposure ceases) |  |  |
|--|--|-------|--|-----------------------------------------|--|--|

**Engineering measures** : effective ventilation in all processing areas

### Personal protective equipment

**Respiratory protection** : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

### Hand protection

**Material** : Protective gloves

**Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Safety glasses

Ensure that eyewash stations and safety showers are close to the workstation location.

**Skin and body protection** : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Hygiene measures** : When using do not eat or drink.  
When using do not smoke.

Wash hands before breaks and at the end of workday.

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                        |                                      |
|----------------------------------------|--------------------------------------|
| Physical state                         | : Aerosol containing a liquefied gas |
| Colour                                 | : white                              |
| Odour                                  | : alcohol-like, amine-like           |
| Odour Threshold                        | : No data available                  |
| pH                                     | : No data available                  |
| Melting point/freezing point           | : No data available                  |
| Boiling point                          | : No data available                  |
| Flash point                            | :<br>Not applicable                  |
| Evaporation rate                       | : < 1<br>n-Butyl Acetate = 1.0       |
| Flammability (solid, gas, liquid)      | : Flammable aerosol.                 |
| Upper explosion limit                  | : No data available                  |
| Lower explosion limit                  | : No data available                  |
| Vapour pressure                        | : No data available                  |
| Relative vapour density                | : No data available                  |
| Density                                | : No data available                  |
| Solubility(ies)                        |                                      |
| Water solubility                       | : soluble                            |
| Partition coefficient: n-octanol/water | : No data available                  |
| Auto-ignition temperature              | : not determined                     |
| Decomposition temperature              | : No data available                  |
| Viscosity                              |                                      |
| Viscosity, kinematic                   | : No data available                  |

---

### SECTION 10. STABILITY AND REACTIVITY

|                                    |                                                                                                       |
|------------------------------------|-------------------------------------------------------------------------------------------------------|
| Reactivity                         | : Stable                                                                                              |
| Chemical stability                 | : Stable under normal conditions.                                                                     |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air.<br>No decomposition if stored and applied as directed. |
| Conditions to avoid                | : Heat, flames and sparks.                                                                            |



# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Extremes of temperature and direct sunlight.

|                                  |                                           |
|----------------------------------|-------------------------------------------|
| Incompatible materials           | : Alkali metals<br>Copper<br>Strong acids |
| Hazardous decomposition products | : Carbon oxides<br>Nitrogen oxides (NOx)  |

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.  
Symptoms may include blistering, irritation, burns, and pain.  
Effects are dependent on exposure (dose, concentration, contact time).  
Causes skin irritation.  
Causes serious eye damage.  
Review section 2 of SDS to see all potential hazards.  
Treat symptomatically. Symptoms may be delayed.

#### Carcinogenicity:

##### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

##### ACGIH

Confirmed animal carcinogen with unknown relevance to humans

|                 |          |
|-----------------|----------|
| 2-butoxyethanol | 111-76-2 |
| ethanol         | 64-17-5  |

#### Acute toxicity

##### Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

Exposure time: 4 h

Test atmosphere: dust/mist

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

### **Components:**

#### **propan-2-ol:**

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg

Method: Calculation method

#### **2-aminoethanol:**

Acute oral toxicity : LD50 Oral Mouse: 700 mg/kg

LD50 Oral Rat: 1,515 mg/kg

Acute inhalation toxicity : LC50 Mouse: > 1.21 mg/l

#### **2-butoxyethanol:**

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

#### **ethanol:**

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l

Exposure time: 4 h

Test atmosphere: vapour

### **Skin corrosion/irritation**

#### **Product:**

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

---

Remarks: Irritating to skin.

### Serious eye damage/eye irritation

**Product:**

Remarks: May cause irreversible eye damage.

### Respiratory or skin sensitisation

No data available

### Germ cell mutagenicity

No data available

### Carcinogenicity

No data available

### Reproductive toxicity

No data available

### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

### Further information

**Product:**

Remarks: No data available

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

### Persistence and degradability

No data available

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

---

### Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : Remarks: No data available

#### Components:

##### **propan-2-ol :**

Partition coefficient: n-octanol/water : log Pow: 0.05

##### **butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

##### **2-aminoethanol :**

Partition coefficient: n-octanol/water : log Pow: -1.31

##### **ethanol :**

Partition coefficient: n-octanol/water : Remarks: No data available

### Mobility in soil

No data available

### Other adverse effects

No data available

#### Product:

Additional ecological information : No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

---

### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA):

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

---

### SECTION 15. REGULATORY INFORMATION

# SAFETY DATA SHEET

## ZEP PERIMETER 20N18 12CT

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

**The components of this product are reported in the following inventories:**

**DSL** All components of this product are on the Canadian DSL  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

### Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

---

## SECTION 16. OTHER INFORMATION

---

### WHMIS - GHS Label Information:

Hazard pictograms :



Flame

Gas cylinder

Corrosion

Signal word :

**Danger:**

Hazard statements :

Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye damage.

Precautionary statements :

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection.

**Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.

**Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

---

|                |            |
|----------------|------------|
| Version:       | 1.2        |
| Revision Date: | 12/21/2025 |
| Print Date:    | 12/21/2025 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it

# **SAFETY DATA SHEET**

## **ZEP PERIMETER 20N18 12CT**

Version 1.2

Revision Date 12/21/2025

Print Date 12/21/2025

---

is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.