

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP SELIG AIR AID 20N16 6CT

Material number : 000000000000940206

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street
Edmonton, Alberta T5S 1N6
Canada

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	red
Odour	solvent-like

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Eye irritation : Category 2A
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT


Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%] *
ethanol	64-17-5	>= 30 - < 60
Solvent naphtha (petroleum), light aliph.	64742-89-8	>= 30 - < 60
White mineral oil (petroleum)	8042-47-5	>= 10 - < 30
propane	74-98-6	>= 5 - < 10
butane	106-97-8	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5

* The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.
Get medical attention immediately.
- If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
Remove contaminated clothing and shoes.
Wash contaminated clothing before re-use.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
DO NOT induce vomiting unless directed to do so by a

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

physician or poison control center.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

- Most important symptoms and effects, both acute and delayed : Effects are dependent on exposure (dose, concentration, contact time).
Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.
Causes skin irritation.
Causes serious eye irritation.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Always replace cap after use.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis
------------	---------	----------------------------------	----------------------------------	-------

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

			concentration	
ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m3	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,880 mg/m3	CA QC OEL
		TWA	1,000 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m3	CA QC OEL
		TWA	1,000 ppm	CA ON OEL
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m3	CA QC OEL
		STEL	1,000 ppm	ACGIH
propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m3	CA QC OEL
		STEV	500 ppm 1,230 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses

Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Aerosol containing a liquefied gas

Colour : red

Odour : solvent-like

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: Not applicable
Boiling point	: > 37.7 °C
Flash point	: not determined
Evaporation rate	: > 1 n-Butyl Acetate = 1.0
Flammability (solid, gas, liquid)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 0.776 g/cm ³
Bulk density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

Hazardous decomposition products : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are dependent on exposure (dose, concentration, contact time).
Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.
Causes skin irritation.
Causes serious eye irritation.
Review section 2 of SDS to see all potential hazards.
Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

ethanol:

Acute oral toxicity : LD50 Oral Rat: 7,060 mg/kg

Acute inhalation toxicity : LC50 Rat: 124.7 mg/l

Exposure time: 4 h

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

Test atmosphere: vapour

propan-2-ol:

Acute oral toxicity

: LD50 Oral Rat: 4,396 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

ethanol :

Partition coefficient: n-octanol/water : Remarks: No data available

butane :

Partition coefficient: n-octanol/water : Pow: 2.89

propan-2-ol :

Partition coefficient: n-octanol/water : log Pow: 0.05

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory
DSL All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms

:



Flame



Gas cylinder



Exclamation mark

Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements

:

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection.

Response: IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Protect from

SAFETY DATA SHEET

ZEP SELIG AIR AID 20N16 6CT

Version 2.2

Revision Date 12/21/2025

Print Date 12/21/2025

sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/ container to an approved waste disposal plant.

Version:	2.2
Revision Date:	12/21/2025
Print Date:	12/21/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.