



Micro-Soak LNP (AFCO 4460)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 02/12/2025

Date of issue: 08/04/2014

Version: 1.1

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Micro-Soak LNP

Product Code: AFCO 4460

Intended Use of the Product

Non - metabisulfite membrane preservative. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

AFCO

550 Development Avenue

Chambersburg, PA 17201

T: 800-345-1329

www.afcocare.com

Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290

Skin Corr. 1C H314

Eye Dam. 1 H318

Aquatic Acute 3 H402

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

:



GHS05

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H290 - May be corrosive to metals
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H402 - Harmful to aquatic life

Precautionary Statements (GHS-US)

: P234 - Keep only in original container.
P260 - Do not breathe mist, spray, vapors.
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P321 - Specific treatment (see Section 4).
P363 - Wash contaminated clothing before reuse.
P390 - Absorb spillage to prevent material damage.

Micro-Soak LNP (AFCO 4460)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards: May be corrosive to the respiratory tract. When heated to decomposition, emits toxic fumes. Contact with some metals may evolve flammable hydrogen gas.

Unknown Acute Toxicity (GHS-US) Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Name	Product identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	70-90	Not classified
Citric acid	(CAS No) 77-92-9	10-20	Eye Irrit. 2A, H319
Lactic acid	(CAS No) 50-21-5	10-20	Skin Irrit. 2, H315 Eye Dam. 1, H318
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	(CAS No) 85536-14-7	1 - 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
Sodium xylene sulfonate	(CAS No) 1300-72-7	0.1-1.0	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of H-phrases: see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Remove contaminated clothing. Rinse cautiously with water for at least 30 minutes. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and serious eye damage. Corrosive to eyes and skin.

Inhalation: Not usually a source of exposure.

Skin Contact: Causes severe skin burns.

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects. Contact may cause immediate severe irritation progressing quickly to chemical burns.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Micro-Soak LNP (AFCO 4460)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Thermal decomposition generates: Carbon oxides (CO, CO₂). Sulfur oxides. Reacts violently with strong bases. May generate explosive hydrogen gas when in contact with soft metals.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not breathe fumes from fires or vapors from decomposition. Stop leak if safe to do so. Do not allow run-off from fire fighting to enter drains or water sources.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Sulfur oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not allow product to spread into the environment. Do NOT breathe (vapors, mist, spray). Do not get in eyes, on skin, or on clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to environment.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Cautiously neutralize spilled product with soda ash or lime. Absorb and/or contain spill with inert material, then place in suitable container. Ventilate area. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Contact with soft metals may evolve flammable hydrogen gas.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep away from incompatible materials.

Incompatible Materials: Strong bases. Strong oxidizers.

Specific End Use(s): Non-metabisulfite membrane preservative. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

None.

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. . Ensure all national/local regulations are observed.

Micro-Soak LNP (AFCO 4460)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal Protective Equipment: Safety glasses. Face shield. Corrosionproof clothing. Gloves. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses. Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: None usually needed.

Consumer Exposure Controls: Do not eat, drink, or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear pale yellow
Odor	: Moderate acidic
Odor Threshold	: Not available
pH	: <2
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 97.8°C (208.04°F)
Flash Point	: Not flammable
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not flammable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Specific Gravity	: 1.07
Solubility	: Complete in water
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates: Carbon oxides (CO, CO₂), sulfur oxides. Contact with soft metals may generate explosive hydrogen gas.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous reactions will not occur under normal conditions.

Conditions to Avoid: Incompatible materials.

Incompatible Materials: Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Thermal decomposition generates: Carbon oxides (CO, CO₂). Sulfur oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Micro-Soak LNP (AFCO 4460)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin Corrosion/Irritation: Causes severe skin burns. (pH: <2)
Serious Eye Damage/Irritation: Causes serious eye damage. (pH: <2)
Respiratory or Skin Sensitization: Not classified.
Germ Cell Mutagenicity: Not classified.
Teratogenicity: Not available.
Carcinogenicity: Not classified.
Specific Target Organ Toxicity (Repeated Exposure): Not classified.
Reproductive Toxicity: Not classified.
Specific Target Organ Toxicity (Single Exposure): Not classified.
Aspiration Hazard: Not classified.
Symptoms/Injuries After Inhalation: Not classified.
Symptoms/Injuries After Skin Contact: Causes severe skin burns.
Symptoms/Injuries After Eye Contact: Causes serious eye damage.
Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.
Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Water (7732-18-5)	
LD50 Oral Rat	>90000 mg/kg
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)	
LD50 Oral Rat	1219 mg/kg
Sodium xylene sulfonate (1300-72-7)	
LD50 Oral Rat	1000 mg/kg
LD50 Dermal Rabbit	>2000 mg/kg
Citric acid (77-92-9)	
LD50 Oral Rat	5400 mg/kg
LD50 Dermal Rat	>2000 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not classified.

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)	
LC50 Fish 1	>1-10 mg/l (Exposure time: 96 h)
EC50 Daphnia 1	>1-10 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Citric acid (77-92-9)	
LC50 Fish 1	440 mg/l (Exposure time: 48 h)
EC50 Daphnia 1	1535mg/l (Exposure time: 24 h - Species: Daphnia magna)

Persistence and Degradability

Micro-Soak LNP (AFCO 4460)	
Persistence and Degradability	Not established.

Bioaccumulative Potential

Micro-Soak LNP (AFCO 4460)	
Bioaccumulative Potential	Not established.

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)	
Log Pow	2 (at 23°C)

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way.

Micro-Soak LNP (AFCO 4460)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations. RCRA Waste Code: D002 (Corrosive Material).

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Citric Acid, Lactic Acid)
Hazard Class : 8
Identification Number : UN 3265
Label Codes : 8
Packing Group : III
ERG Number : 153



14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Citric Acid, Lactic Acid)
Hazard Class : 8
Identification Number : UN 3265
Packing Group : III
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
MFAG Number : 153



14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Citric Acid, Lactic Acid)
Packing Group : III
Identification Number : UN 3265
Hazard Class : 8
Label Codes : 8
ERG Code (IATA) : 8L



14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Citric Acid, Lactic Acid)
Packing Group : II
Hazard Class : 8
Identification Number : UN 3265
Label Codes : 8



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Micro-Soak LNP (AFCO 4460)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard.
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Sodium xylene sulfonate (1300-72-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Citric acid (77-92-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	
Lactic acid (50-21-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory.	

US State Regulations

Lactic acid (50-21-5)
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

Micro-Soak LNP (AFCO 4460)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

RTK - U.S. - Pennsylvania - RTK (Right to Know) List
Sodium xylene sulfonate (1300-72-7)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

Water (7732-18-5)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (85536-14-7)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Lactic acid (50-21-%)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Citric acid (77-92-9)
Listed on the Canadian DSL (Domestic Substances List) inventory.
Sodium xylene sulfonate (1300-72-7)
Listed on the Canadian DSL (Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.


SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date	: 02/12/2025
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H401	Toxic to aquatic life
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA Fire Hazard	: 0 - Materials that will not burn.
NFPA Reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur.
Flammability	: 0 - Minimal Hazard.
Physical	: 1 - Slight Hazard.

Micro-Soak LNP (AFCO 4460)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Party Responsible for the Preparation of This Document

AFCO
550 Development Avenue
Chambersburg, PA 17201
T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS SDS 2015 (U.S., Can., Mex.)