

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

- Trade name INTEROX® AG Spray 34-SR

1.2 Relevant identified uses of the substance or mixture and uses advised against**Uses of the Substance / Mixture**

- Disinfectants

1.3 Details of the supplier of the safety data sheet**Company**

SOLVAY CHEMICALS, INC.
1130 Independence Pkwy South,
La Porte, TX 77571
Tel: +1-800-443-2785

1.4 Emergency telephone

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CONTACT CHEMTREC (24-Hour Number): +1-800-424-9300 within the United States and Canada, or +1-703-527-3887 for international collect calls.

SECTION 2: Hazards identification

Although WHMIS has not adopted the environmental portion of the GHS regulations, this document may include information on environmental effects

2.1 Classification of the substance or mixture**Hazardous Products Regulations (WHMIS 2015)**

Acute toxicity, Category 4
Serious eye damage, Category 1

H302: Harmful if swallowed.
H318: Causes serious eye damage.

2.2 Label elements**Hazardous Products Regulations (WHMIS 2015)****Pictogram****Signal Word**

- Danger

Hazard Statements

- H302 Harmful if swallowed.
- H318 Causes serious eye damage.

Precautionary Statements

P00000228714

Version : 2.00 / CA (Z8)

www.solvay.com



INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

Prevention

- P264
- P270
- P280

Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear eye protection/ face protection.

Response

- P301 + P312 + P330
- P305 + P351 + P338 + P310

IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Disposal

- P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards which do not result in classification

- H401: Toxic to aquatic life.

SECTION 3: Composition/information on ingredients**3.1 Substance**

- Not applicable, this product is a mixture.

3.2 Mixture**WHMIS Hazardous Ingredients and Impurities**

Chemical name	Identification number CAS-No.	Concentration [% wt/wt or V/V]
Hydrogen peroxide (H ₂ O ₂)	7722-84-1	>= 33.5 - <= 34.5

SECTION 4: First aid measures**4.1 Description of first-aid measures****General advice**

- Show this material safety data sheet to the doctor in attendance.

In case of inhalation

- Move to fresh air.
- Oxygen or artificial respiration if needed.
- Victim to lie down in the recovery position, cover and keep him warm.
- Call a physician immediately.

In case of skin contact

- Remove and wash contaminated clothing before re-use.
- Wash off with soap and water.
- If symptoms persist, call a physician.

In case of eye contact

- Call a physician or poison control center immediately.
- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- In the case of difficulty of opening the lids, administer an analgesic eye wash (oxybuprocaine).
- Take victim immediately to hospital.

P00000228714

Version : 2.00 / CA (Z8)

www.solvay.com



INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

In case of ingestion

- Call a physician or poison control center immediately.
- Take victim immediately to hospital.
- If swallowed, rinse mouth with water (only if the person is conscious).
- Do NOT induce vomiting.
- Artificial respiration and/or oxygen may be necessary.
- If victim is conscious:
- If swallowed, rinse mouth with water (only if the person is conscious).
- Do NOT induce vomiting.
- If victim is unconscious:
- Artificial respiration and/or oxygen may be necessary.

4.2 Most important symptoms and effects, both acute and delayed**In case of inhalation****Symptoms**

- Breathing difficulties
- Cough
- pulmonary edema
- Nausea
- Vomiting

Effects

- Corrosive to respiratory system.

Repeated or prolonged exposure

- Nose bleeding
- Risk of chronic bronchitis

In case of skin contact**Symptoms**

- Redness
- Swelling of tissue

Effects

- Prolonged skin contact may cause skin irritation.

In case of eye contact**Symptoms**

- Redness
- Lachrymation
- Swelling of tissue

Effects

- Corrosive
- Causes severe burns.
- Small amounts splashed into eyes can cause irreversible tissue damage and blindness.

In case of ingestion**Symptoms**

- Nausea
- Abdominal pain
- Bloody vomiting
- Diarrhea
- Suffocation

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

- Cough
- Severe shortness of breath

Effects

- If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.
- Risk of respiratory disorder

4.3 Indication of any immediate medical attention and special treatment needed**Notes to physician**

- Take victim immediately to hospital.
- Immediate medical attention is required.
- Consult with an ophthalmologist immediately in all cases.
- If swallowed
- Avoid gastric lavage (risk of perforation).
- Keep under medical supervision for at least 48 hours.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

- Water
- Water spray

Unsuitable extinguishing media

- None.

5.2 Special hazards arising from the substance or mixture**Specific hazards during fire fighting**

- Oxidizing
- If subject to contamination or heating it will release oxygen which may intensify an existing fire.
- If heated under confinement there is a risk of pressure burst.
- Contact with flammable or combustible liquids could initiate a fire.
- Mixing with flammable or combustible liquids can create potentially explosive mixtures.

Hazardous combustion products:

- Oxygen

5.3 Advice for firefighters**Special protective equipment for fire-fighters**

- In the event of fire, wear self-contained breathing apparatus.
- Use personal protective equipment.
- Wear chemical resistant oversuit

Further information

- Keep product and empty container away from heat and sources of ignition.
- Keep containers and surroundings cool with water spray.
- Approach from upwind.
- Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****Advice for non-emergency personnel**

- Evacuate personnel to safe areas.
- Keep people away from and upwind of spill/leak.

Advice for emergency responders

- Use personal protective equipment.
- Drying of this product on clothing or combustible materials may cause fire.
- Keep wetted with water.
- Prevent further leakage or spillage.
- Keep away from incompatible products

6.2 Environmental precautions

- Should not be released into the environment.
- If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

- Dilute with plenty of water.
- Dam up.
- Do not mix waste streams during collection.
- Soak up with inert absorbent material.
- Keep in properly labeled containers.
- Keep in suitable, closed containers for disposal.
- Never return spills in original containers for re-use.
- Treat recovered material as described in the section "Disposal considerations".

6.4 Reference to other sections

- Refer to protective measures listed in sections 7 and 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Use only in well-ventilated areas.
- Before all operations, passivate the piping circuits and vessels according to the procedure recommended by the producer.
- Use only clean and dry utensils.
- Never return unused material to storage receptacle.
- Keep away from heat.
- Avoid inhalation, ingestion and contact with skin and eyes.
- Keep away from incompatible products

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

Hygiene measures

- Ensure that eyewash stations and safety showers are close to the workstation location.
- Take off contaminated clothing and shoes immediately.
- Wash contaminated clothing before re-use.
- When using do not eat, drink or smoke.
- Wash hands before breaks and at the end of workday.
- Handle in accordance with good industrial hygiene and safety practice.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures/Storage conditions**

- Keep only in the original container.
- Store in a receptacle equipped with a vent.
- Store in a well-ventilated place. Keep cool.
- Keep in properly labeled containers.
- Keep container closed.
- Keep in a contained area
- Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
- Regularly check the condition and temperature of the containers.
- Keep away from:
- Incompatible products

Packaging material**Suitable material**

- aluminum 99.5%
- stainless steel 304L / 316L
- Approved grades of HDPE.

7.3 Specific end use(s)

- Contact your supplier for additional information

SECTION 8: Exposure controls/personal protection

Introductory Remarks: These recommendations provide general guidance for handling this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Assistance with selection, use and maintenance of worker protection equipment is generally available from equipment manufacturers.

8.1 Control parameters**Components with workplace occupational exposure limits**

Consult local authorities for acceptable exposure limits.

Components	Value type	Value	Basis
Hydrogen peroxide (H2O2)	TWA	1 ppm	American Conference of Governmental Industrial Hygienists
		Confirmed animal carcinogen with unknown relevance to humans	

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

8.2 Exposure controls**Control measures****Engineering measures**

- Provide adequate ventilation.
- Apply technical measures to comply with the occupational exposure limits.

Individual protection measures**Respiratory protection**

- Self-contained breathing apparatus in confined spaces/insufficient oxygen/in case of large uncontrolled emissions/in all circumstances when the mask and cartridge do not give adequate protection.
- Use only respiratory protection that conforms to international/ national standards.
- Use NIOSH approved respiratory protection.
- Wear an approved full-face air supplied respirator for excessive or unknown concentrations. Selected chemical cartridges for respirators, i.e. OV, OV/AG, GME have been tested successfully under lab conditions to remove hydrogen peroxide and peracetic acid vapors in concentrations exceeding the applicable exposure limits. Further information is available in a Solvay Chemicals, Inc. Technical Communication, located at <http://www.solvaychemicals.us/resource.htm> in the Peracetic Acid section.
- In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection

- Impervious gloves
- Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Suitable material

- Nitrile rubber
- Break through time: > 480 min
- Glove thickness: 1.3 mm

- Nitrile/Neopren gloves
- Break through time: 190 min
- Glove thickness: 0.2 mm

Eye protection

- Chemical resistant goggles must be worn.
- If splashes are likely to occur, wear:
- Tightly fitting safety goggles
- Face-shield

Skin and body protection

- Impervious clothing
- If splashes are likely to occur, wear:
- Chemical resistant apron
- Boots
- Suitable material
- PVC
- Natural Rubber

Hygiene measures

- Ensure that eyewash stations and safety showers are close to the workstation location.
- Take off contaminated clothing and shoes immediately.
- Wash contaminated clothing before re-use.
- When using do not eat, drink or smoke.
- Wash hands before breaks and at the end of workday.
- Handle in accordance with good industrial hygiene and safety practice.

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

SECTION 9: Physical and chemical properties

Physical and Chemical properties here represent typical properties of this product. Contact the business area using the Product information phone number in Section 1 for its exact specifications.

9.1 Information on basic physical and chemical properties

<u>Physical state</u>	liquid
<u>Color</u>	colorless
<u>Odor</u>	pungent
<u>Odor Threshold</u>	No data available
<u>Melting point/freezing point</u>	<u>Freezing point</u> : -27 °F (-33 °C) H2O2 35 %
<u>Initial boiling point and boiling range</u>	<u>Boiling point/boiling range</u> : 226 °F (108 °C) H2O2 35 %
<u>Flammability (solid, gas)</u>	Not applicable
<u>Flammability (liquids)</u>	The product is not flammable.
<u>Flammability / Explosive limit</u>	No data available
<u>Flash point</u>	Not applicable
<u>Autoignition temperature</u>	No data available
<u>Decomposition temperature</u>	>= 140 °F (>= 60 °C) Self-Accelerating decomposition temperature (SADT) < 140 °F (< 60 °C) Slow decomposition
<u>pH</u>	2.0 (70 °F (21 °C)) H2O2 50 % <u>pKa</u> : 11.6 (77 °F (25 °C))
<u>Viscosity</u>	<u>Viscosity, dynamic</u> : 1.07 mPa.s
<u>Solubility</u>	<u>Water solubility</u> : completely miscible, in all proportions
<u>Partition coefficient: n-octanol/water</u>	log Pow: -1.57 Method: Calculation method
<u>Vapor pressure</u>	0.75 mmHg (1 hPa) (86 °F (30 °C)) H2O2 50 %
<u>Density</u>	<u>Bulk density</u> : Not applicable

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

<u>Relative density</u>	1.1
<u>Relative vapor density</u>	1 H2O2 50 %
<u>Particle characteristics</u>	No data available
<u>Evaporation rate (Butylacetate = 1)</u>	No data available

9.2 Other information

<u>Explosiveness</u>	Not explosive
<u>Explosiveness</u>	With certain materials (see section 10).
<u>Oxidizing properties</u>	Not considered as oxidizing.
<u>Self-ignition</u>	The product is not flammable.
<u>Surface tension</u>	74 mN/m (68 °F (20 °C))
<u>Molecular weight</u>	34 g/mol
<u>Henry's Constant</u>	0.00075 Pa.m ³ / mol (68 °F (20 °C)) not significant, Air, Volatility

SECTION 10: Stability and reactivity**10.1 Reactivity**

- Decomposes on heating.
- Potential for exothermic hazard

10.2 Chemical stability

- Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

- Fire or intense heat may cause violent rupture of packages.

10.4 Conditions to avoid

- Contamination
- To avoid thermal decomposition, do not overheat.

10.5 Incompatible materials

- Acids
- Bases
- Metals
- Heavy metal salts
- Powdered metal salts
- Reducing agents
- Organic materials
- Flammable materials

10.6 Hazardous decomposition products

P00000228714

Version : 2.00 / CA (Z8)

www.solvay.com



- Oxygen

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity

Hydrogen peroxide (H₂O₂)

Acute toxicity estimate : 431 mg/kg - Rat , male and female
Method: OECD Test Guideline 401
This product is classified as acute toxicity category 4
Unpublished reports

Acute inhalation toxicity

Hydrogen peroxide (H₂O₂)

LC50 - 4 h (vapor) : > 0.17 mg/l - Rat
Method: OECD Test Guideline 403
Not classified as hazardous for acute inhalation toxicity according to GHS.
Unpublished reports

Acute dermal toxicity

Hydrogen peroxide (H₂O₂)

Acute toxicity estimate : 6,440 mg/kg - Rabbit
Method: OECD Test Guideline 402
Not classified as hazardous for acute dermal toxicity according to GHS.
Unpublished reports

Acute toxicity (other routes of administration)

No data available

Skin corrosion/irritation

Not classified as irritating to skin

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Hydrogen peroxide (H₂O₂)

Does not cause skin sensitization.

Mutagenicity

Genotoxicity in vitro

Hydrogen peroxide (H₂O₂)

Ames test
with and without metabolic activation

positive
Published data

Chromosome aberration test in vitro
with and without metabolic activation

positive
Unpublished reports

Genotoxicity in vivo

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

Hydrogen peroxide (H₂O₂) In vivo micronucleus test - Mouse
Oral
Method: OECD Test Guideline 474

negative
Unpublished reports

Carcinogenicity

Hydrogen peroxide (H₂O₂) No data available

Toxicity for reproduction and development**Toxicity to reproduction / fertility**

Hydrogen peroxide (H₂O₂) No toxicity to reproduction

Developmental Toxicity/Teratogenicity

Hydrogen peroxide (H₂O₂) No toxicity to reproduction

STOT**STOT-single exposure**

Hydrogen peroxide (H₂O₂) Routes of exposure: Inhalation
Target Organs: Respiratory Tract
May cause respiratory irritation.

STOT-repeated exposure

Hydrogen peroxide (H₂O₂) The substance or mixture is not classified as specific target organ toxicant, repeated exposure according to GHS criteria.

Hydrogen peroxide (H₂O₂) Inhalation (vapor) 90-day - Rat
NOAEC: 7 ppm
Target Organs: Respiratory Tract
Method: OECD Test Guideline 413
Unpublished reports

90-day - Rat
NOAEL: 100 ppm
Target Organs: Gastrointestinal tract
Method: OECD Test Guideline 408
drinking water
Unpublished reports

Experience with human exposure

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information**12.1 Toxicity****Aquatic Compartment****Acute toxicity to fish**

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

Hydrogen peroxide (H₂O₂) LC50 - 96 h : 16.4 mg/l - Pimephales promelas (fathead minnow)
 semi-static test
 Analytical monitoring: yes
 Method: according to a standardized method
 Harmful to fish.
 Unpublished internal reports

Acute toxicity to daphnia and other aquatic invertebrates

Hydrogen peroxide (H₂O₂) EC50 - 48 h : 2.4 mg/l - Daphnia pulex (Water flea)
 semi-static test
 Analytical monitoring: yes
 Method: according to a standardized method
 Toxic to aquatic invertebrates.
 Unpublished internal reports

Toxicity to aquatic plants

Hydrogen peroxide (H₂O₂) ErC50 - 72 h : 2.62 mg/l - Skeletonema costatum (marine diatom)
 static test
 Analytical monitoring: yes
 Method: according to a standardized method
 Toxic to algae.
 Unpublished internal reports

Toxicity to microorganisms

Hydrogen peroxide (H₂O₂) EC50 - 0.5 h : 466 mg/l - activated sludge
 static test
 Analytical monitoring: yes
 Method: OECD Test Guideline 209
 Unpublished internal reports

Chronic toxicity to fish

No data available

Chronic toxicity to daphnia and other aquatic invertebrates

Hydrogen peroxide (H₂O₂) NOEC: 0.63 mg/l - 21 Days - Daphnia magna (Water flea)
 flow-through test
 Analytical monitoring: yes
 Method: according to a standardized method
 Harmful to aquatic invertebrates with long lasting effects.
 Published data

12.2 Persistence and degradability**Abiotic degradation**

No data available

Physical- and photo-chemical elimination

No data available

Biodegradation**Biodegradability**

Hydrogen peroxide (H₂O₂) Ready biodegradability study:
 Method: Degradation in sewage treatment plants
 The substance fulfills the criteria for ultimate aerobic biodegradability and ready biodegradability
 Inoculum: activated sludge
 Unpublished internal reports

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

Degradability assessmentHydrogen peroxide (H₂O₂)

The product is considered to be rapidly degradable in the environment

12.3 Bioaccumulative potential**Partition coefficient: n-octanol/water**Hydrogen peroxide (H₂O₂)

Not potentially bioaccumulable

Bioconcentration factor (BCF)Hydrogen peroxide (H₂O₂)

Not potentially bioaccumulable

12.4 Mobility in soil**Adsorption potential (K_{oc})**Hydrogen peroxide (H₂O₂)

Adsorption/Soil
K_{oc}: 1.58
Log K_{oc}: 0.2
Method: Structure-activity relationship (SAR)
Unpublished reports

Known distribution to environmental compartmentsHydrogen peroxide (H₂O₂)

Ultimate destination of the product: Water

12.5 Results of PBT and vPvB assessmentHydrogen peroxide (H₂O₂)

This substance is not considered to be persistent, bioaccumulating, and toxic (PBT).

This substance is not considered to be very persistent and very bioaccumulating (vPvB).

12.6 Other adverse effects**Ecotoxicity assessment****Short-term (acute) aquatic hazard**

Toxic to aquatic life.

Long-term (chronic) aquatic hazard

Not classified due to data which are conclusive although insufficient for classification.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product Disposal**

- Limited quantity
- Dilute with plenty of water.
- Flush into sewer with plenty of water.
- Maximum quantity
- Contact manufacturer.
- Contact waste disposal services.
- In accordance with local and national regulations.

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

Advice on cleaning and disposal of packaging

- Empty containers.
- Clean container with water.
- Dispose of rinse water in accordance with local and national regulations.
- Where possible recycling is preferred to disposal or incineration.
- In accordance with local and national regulations.

SECTION 14: Transport information

Transportation status: IMPORTANT! Statements below provide additional data on listed transport classification.

The listed Transportation Classification does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors.

TDG

14.1 UN number	UN 2014
14.2 Proper shipping name	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
14.3 Transport hazard class	5.1
Subsidiary hazard class	8
Label(s)	5.1 (8)
14.4 Packing group	
Packing group	II
ERG No	140
14.5 Environmental hazards	NO
Marine pollutant	

49 CFR

14.1 UN number	UN 2014
14.2 Proper shipping name	HYDROGEN PEROXIDE, AQUEOUS SOLUTIONS
14.3 Transport hazard class	5.1
Subsidiary hazard class	8
Label(s)	5.1 (8)
14.4 Packing group	
Packing group	II
ERG No	140
14.5 Environmental hazards	NO
Marine pollutant	

NOM

14.1 UN number	UN 2014
-----------------------	---------

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

14.2 Proper shipping name	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
14.3 Transport hazard class	5.1
Subsidiary hazard class	8
Label(s)	5.1 (8)
14.4 Packing group	
Packing group	II
ERG No	140
14.5 Environmental hazards	NO
Marine pollutant	

IMDG

14.1 UN number	UN 2014
14.2 Proper shipping name	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
IMDG Code segregation group	Peroxides (SGG16)
14.3 Transport hazard class	5.1
Subsidiary hazard class	8
Label(s)	5.1 (8)
14.4 Packing group	
Packing group	II
14.5 Environmental hazards	NO
Marine pollutant	
14.6 Special precautions for user	
EmS	F-H , S-Q

For personal protection see section 8.

14.7 Transport in bulk vessels according to IMO instruments
No data available

INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

IATA

14.1 UN number	UN 2014
14.2 Proper shipping name	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
14.3 Transport hazard class	5.1
Subsidiary hazard class:	8
Label(s):	5.1 (8)
14.4 Packing group	
Packing group	II
Packing instruction (cargo aircraft)	554
Max net qty / pkg	5.00 L
Packing instruction (passenger aircraft)	550
Max net qty / pkg	1.00 L
14.5 Environmental hazards	NO
14.6 Special precautions for user	
For personal protection see section 8.	
Remarks	: IATA: permitted under 40%

Note: The above regulatory prescriptions are those valid on the date of publication of this sheet. Given the possible evolution of transportation regulations for hazardous materials, it would be advisable to check their validity with your sales office.

SECTION 15: Regulatory information**15.1 Notification status**

Inventory Information	Status
United States TSCA Inventory	- All substances listed as active on the TSCA inventory
Canadian Domestic Substances List (DSL)	- Listed on Inventory
Australian Inventory of Industrial Chemicals (AIIC)	- Listed on Inventory
Japan. CSCL - Inventory of Existing and New Chemical Substances	- Listed on Inventory
Korea. Korean Existing Chemicals Inventory (KECI)	- Listed on Inventory
China. Inventory of Existing Chemical Substances in China (IECSC)	- Listed on Inventory
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	- Listed on Inventory
Taiwan Chemical Substance Inventory (TCSI)	- Listed on Inventory
New Zealand. Inventory of Chemical Substances	- All components are listed on the NZIoC inventory. Additional HSNO obligations may apply. Please refer to Section 15 of SDS for New Zealand.

P00000228714

Version : 2.00 / CA (Z8)

www.solvay.com



INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

EU. European Registration, Evaluation, Authorization and Restriction of Chemical (REACH)	- When purchased from a Solvay legal entity based in the EEA ("European Economic Area"), this product is compliant with the registration provisions of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt, and/or registered. When purchased from a legal entity outside of the EEA, please contact your local representative for additional information.
--	--

15.2 National Regulations**Canada. CEPA 1999 Significant New Activity (SNAc) List:**

- No substances are subject to a Significant New Activity Notification.

SECTION 16: Other information**Revision Date:**

07/10/2023

NFPA (National Fire Protection Association) - Classification

Health	3 serious
Flammability	1 slight
Instability or Reactivity	0 minimal

HMIS (Hazardous Materials Identification System (Paint & Coating)) - Classification

Health	3 serious
Flammability	1 slight
Reactivity	0 minimal
PPE	Determined by User; dependent on local conditions

Further information

- Distribute new edition to clients
- Update
- See section 1

Key or legend to abbreviations and acronyms used in the safety data sheet

- PEL: Permissible exposure limit
- TWA: 8-hour, time-weighted average
- ACGIH: American Conference of Governmental Industrial Hygienists
- OSHA: Occupational Safety and Health Administration
- NTP: National Toxicology Program
- IARC: International Agency for Research on Cancer
- NIOSH: National Institute for Occupational Safety and Health
- ADR: European Agreement on International Carriage of Dangerous Goods by Road.
- ADN: European Agreement on the International Carriage of Dangerous Goods by Inland Waterways.
- RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
- IATA: International Air Transport Association.
- ICAO-TI: Technical Specification for Safe Transport of Dangerous Goods by Air.
- IMDG: International Maritime Dangerous Goods.
- TWA: Time weighted average

P00000228714

Version : 2.00 / CA (Z8)

www.solvay.com



INTEROX® AG Spray 34-SR

Revision Date 07/10/2023

- ATE:	Estimated value of acute toxicity
- EC:	European Community number
- CAS:	Chemical Abstracts Service.
- LD50:	Substance that causes 50% (half) death in the test animals group (Median Fatal Dose).
- LC50:	Substance concentration causing 50% (half) death in the test animals group.
- EC50:	Effective Concentration of the substance causing the maximum of 50%.
- PBT:	Persistent, Bioaccumulative and Toxic substance.
- vPvB:	Very Persistent and Very Bioaccumulative.
- SEA:	Classification, labeling, packaging regulation
- DNEL:	Derived No Effect Level
- PNEC:	Predicted No Effect Concentration
- STOT:	Specific Target Organ Toxicity

Not all acronyms listed above are referenced in this SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. Such information is only given as a guidance to help the user handle, use, process, store, transport, dispose, and release the product in satisfactory safety conditions and is not to be considered as a warranty or quality specification. It should be used in conjunction with technical sheets but do not replace them. Thus, the information only relates to the designated specific product and may not be applicable if such product is used in combination with other materials or in any other manufacturing process, unless otherwise specifically indicated. It does not release the user from ensuring he is in conformity with all regulations linked to its activity.