



# CASSTEK PREMIUM 4T 20W-40 API SL/MA2

## PRODUCT DATA SHEET

The engine in your bike risks damage all the time, when starting up, when running and even when the engine is off.

CASSTEK PREMIUM 4T 20W-40 API SL/MA2 is a high performance 4 stroke Motorbike engine oil, which is engineered to protect your General Transportation and Power Bike engine and enhance its performance. By using world class additive molecule technology and high-quality base oil, CASSTEK oil clings to the engine and gearbox to provide excellent service in all operating conditions.

## PERFORMANCE

Meets the requirements of SAE 20W-40, API SL, JASO MA2

## APPLICATION

CASSTEK PREMIUM 4T 20W-40 API SL/MA2 can be used in all 4-stroke motorbike engines manufactured by leading global OEMs. OEM recommended drain interval is to be followed.

## PRODUCT BENEFITS

- Enhanced protection of engine parts at the point of engine start up.
- Reduced propensity of sludge deposits which ensures superior engine cleanliness during normal operation.
- Reduced propensity of oil thickening and oxidation thereby reducing oil consumption under normal operating conditions.
- Reduced Disc wear and Valve Train wear.
- Excellent corrosion protection, even when engine is off.

# CASSTEK PREMIUM 4T 20W-40 API SL/MA2

Test Parameters	Test Methods	Typical Values
Appearance	Visual	Clear
Colour	Visual	Brown
Density at 300C (g/ml)	ASTM D 1298	858
Kinematic Viscosity at 400C (cSt)	ASTM D445	130
Kinematic Viscosity at 1000C (cSt)	ASTM D445	14.8
Viscosity Index	ASTM D 2270	115
Pour Point (OC)	ASTM D 97	-21
Flash Point (COC) (OC)	ASTM D 93	240
TBN (mg KOH/g)	ASTM D 2896B	8

## STORAGE

All packages should be stored under cover and should not be stored where ambient temperature exceeds 60°C or freezing conditions. To avoid ingress of water and damage, drums should be stored horizontally if they are stored outside. Follow MSDS for further instructions on storage, safe handling, and disposal of the product.