



PPK2

D9710FAE5B42



DATA LOGGER

SCOPE

ABOUT

POWER SUPPLY MODE

Source meter


Ampere meter

Enable power output




SAMPLING PARAMETERS

100,000 samples per second



Sample for 20 minutes



Stop

Estimated disk space required 720.0 MB.
Current available space 548.9 GB

Save / Export

Screenshot

DISPLAY OPTIONS

Timestamps



Relative

Absolute

Digital channels



0 1 2 3 4 5 6 7

Show Minimap



TEMP DISK

Root directory

M:\PPK2

Change

Reset



Lock Y-axis



30 mA

25 mA

20 mA

15 mA

10 mA

5 mA

0 nA

00:00:07
731.62700:00:0
760.00

WINDOW

331.80 μ A
average14.75 mA
max

1

7

15:26:56.941 Getting serial port options from the persistent store for D
15:27:06.489 Selecting device with the serial number D9710FAE5B42
15:27:06.688 Selected device with the serial number D9710FAE5B42
15:27:06.689 Connected to the device with the serial number D9710FA
15:27:06.892 PPK started

“ESP32-S3 + SX1262 Deep-Sleep Baseline (14.59 μ A)”

SELECT DEVICE



Load

Save / Export

Screenshot

DISPLAY OPTIONS



Timestamps



Relative

Absolute

Digital channels



0 1 2 3 4 5 6 7

Show Minimap



TEMP DISK



Root directory

M:\PPK2

Change

Reset

Disk full trigger

10

MB



DATA LOGGER

SCOPE

ABOUT



Lock Y-axis



30 mA

25 mA

20 mA

15 mA

10 mA

5 mA

0 nA

00:00:07
195.37000:00:00
250.0

WINDOW

318.83 μ A
average14.09 mA
max

“SX1262 Auto Duty Cycle RX Window (~14 mA Peak)”

SELECT DEVICE



DATA LOGGER

SCOPE

ABOUT

Load

Save / Export

Screenshot

DISPLAY OPTIONS



Timestamps



Relative

Absolute

Digital channels



0

1

2

3

4

5

6

7

Show Minimap



TEMP DISK



Root directory

M:\PPK2

Change

Reset

Disk full trigger

10

MB



Lock Y-axis



30 mA

25 mA

20 mA

15 mA

10 mA

5 mA

0 nA

00:00:07
195.37000:00:07
250.000

WINDOW

318.83 μ A
average14.09 mA
max

2

7

15:26:56.941 Getting serial port options from the persistent store for D
15:27:06.489 Selecting device with the serial number D9710FAE5B42
15:27:06.688 Selected device with the serial number D9710FAE5B42
15:27:06.689 Connected to the device with the serial number D9710FAE5B42
15:27:06.892 PPK started

“Full Receive Duty Cycle Sequence: Sleep → Auto RX Window → Sleep”



PPK2

D9710FAE5B42



DATA LOGGER

SCOPE

ABOUT

POWER SUPPLY MODE

Source meter **Ampere meter**

Enable power output




SAMPLING PARAMETERS

100,000 samples per second



Sample for 20 minutes



Start

Estimated disk space required 720.0 MB.
Current available space 548.5 GB

Save / Export

Screenshot

DISPLAY OPTIONS

Timestamps



Relative

Absolute

Digital channels



0 1 2 3 4 5 6 7

Show Minimap



TEMP DISK

Root directory

M:\PPK2

Change

Reset



Lock Y-axis



100 mA

80 mA

60 mA

40 mA

20 mA

0 nA

00:04:27
115.11600:04:40
000.000

WINDOW

25.21mA
average98.63mA
max

7

15:26:56.941 Getting serial port options from the persistent store
15:27:06.489 Selecting device with the serial number D9710FAE5B42
15:27:06.688 Selected device with the serial number D9710FAE5B42
15:27:06.689 Connected to the device with the serial number D9710FAE5B42
15:27:06.892 PPK started

**“EoRa-S3-900TB Full Wake + Radio Activity Cycle
(ESP32-S3 + SX1262)”**

