



www.paypro.com.pk

API To Update Invoice Status as Paid On Client's System (CALLBACK API)

A Guide for Implementation and Development Teams

Contents

Disclaimer	2
Introduction.....	3
API Signature	3
HTTP Method.....	3
Input Parameters	3
Usage with Parameters	3
API Response with JSON format	3
Response codes with description.....	4
All Possible error description with their codes	4

Disclaimer

THIS DOCUMENT AND THE INFORMATION HEREIN ARE THE PROPERTY OF PAYPRO (PVT.) LTD. AND ALL UNAUTHORIZED USE AND REPRODUCTION IS STRICTLY PROHIBITED. COPYRIGHT 2020 BY PAYPRO (PVT.) LTD. ALL RIGHTS RESERVED.

CONFIDENTIAL, UNPUBLISHED PROPERTY OF PAYPRO (PVT.) LTD. FOR INTERNAL USE ONLY



Introduction

As PayPro allow merchants to create invoice in PayPro system through multiple channels (Portal/API), there is a need to update merchant's system in real time when an invoice gets paid in PayPro system through banking channels.

PayPro use these specifications to design a callback mechanism to invoke Merchant's API and update Merchant's system accordingly for payments received.

These specification will work as guideline for technical teams at merchant side to develop call back API. PayPro system will call this API with JSON Object sent in certain format with suitable parameters. The response codes are mentioned below which will be returned from merchant's system specifying the status of call.

API Signature : https://{ClientDomainName}/paypro/uis

HTTP Method : POST

Input Parameters

Given below are the mandatory parameters that will be used when calling above web API:

Parameter	Description	Data Type
username	Authentication ID for PayPro	String
password	Authentication Password for PayPro	String
csvinvoiceids	Comma separated invoices	String

Usage with Parameters

A post request will be sent to you with a json body

```
{
  "username": "xyz,
  "password": " xyz ",
  "csvinvoiceids": "WR-20231002-154811"
}
```

Note: "csvinvoiceids" will be your order ID.

API Response with JSON format

In case of success PayPro will get JSON result in following patterns:

In case of invalid username or password or username is empty or password is empty

```
{
  "StatusCode": "01",
  "InvoiceID": null,
  "Description": "Invalid Data. Username or password is invalid"
```

In case of single invoice sent and gets successful

Example invoiceid = INV0011

```
{
  "StatusCode": "00",
  "InvoiceID": "INV0011",
  "Description": "Invoice successfully marked as paid"
}
```

In case of failure in for above mentioned invoiceid

```
{
  "StatusCode": "03",
  "InvoiceID": "INV0011",
  "Description": "No records found."
}
```

OR It can also be 02 as well because maybe there was a service failure or internal error.**In case of multiple invoice ids of INV0031 and INV0041 was not successful.**

```
{
  "StatusCode": "00",
  "InvoiceID": "INV0011",
  "Description": "Invoice successfully marked as paid"
},{
  "StatusCode": "00",
  "InvoiceID": "INV0021",
  "Description": "Invoice successfully marked as paid"
},{
  "StatusCode": "03",
  "InvoiceID": "INV0031",
  "Description": "No records found."
},{
  "StatusCode": "02",
  "InvoiceID": "INV0041",
  "Description": "Service Failure"
},{
  "StatusCode": "00",
  "InvoiceID": "INV0051",
  "Description": "Invoice successfully marked as paid"
},{
  "StatusCode": "00",
  "InvoiceID": "INV0061",
  "Description": "Invoice successfully marked as paid"
}]
```

Response codes with description

Response Code	Description
00	Success
01	Invalid Data.
02	User not Authorized.
03	No Records Found

All Possible error description with their codes

Status	Description
01	Invalid Data. Username cannot be empty
01	Invalid Data. Username length is invalid
01	Invalid Data. Password cannot be empty
01	Invalid Data. Password length is invalid
01	Invalid Data. Username or password is invalid
01	Invalid Data. Username or password is invalid
02	Service Failed. User is not Authorized for this service
03	No data available