



7. Linux Networking Commands



TechData-Infinity-Devops with MultiCloud



Linux ifconfig –

The command ifconfig stands for interface configurator. This command enables us to initialize an interface, assign IP address, enable or disable an interface. It display route and network interface.

ifconfig

Hostname -i

```
root@ip-172-31-8-13:~# ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 9001
    inet 172.31.8.13 netmask 255.255.240.0 broadcast 172.31.15.255
    inet6 fe80::87b:4cff:feeb:da54 prefixlen 64 scopeid 0x20<link>
    ether 0a:7b:4c:cb:da:54 txqueuelen 1000 (Ethernet)
    RX packets 14055 bytes 2127912 (2.1 MB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 12256 bytes 1374101 (1.3 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 130 bytes 14273 (14.2 KB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 130 bytes 14273 (14.2 KB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

root@ip-172-31-8-13:~# hostname -i
172.31.8.13
root@ip-172-31-8-13:~#
```

Get details of specific interface-

ifconfig eth0

```
root@ip-172-31-8-13:~# ifconfig eth0
Command 'ifconfig' not found, did you mean:
  command 'ifconfig' from deb net-tools (1.60+git20181103.0eebece-1ubuntu5)
Try: apt install <deb name>
root@ip-172-31-8-13:~# ifconfig eth0
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 9001
    inet 172.31.8.13 netmask 255.255.240.0 broadcast 172.31.15.255
    inet6 fe80::87b:4cff:feeb:da54 prefixlen 64 scopeid 0x20<link>
    ether 0a:7b:4c:cb:da:54 txqueuelen 1000 (Ethernet)
    RX packets 14186 bytes 2136033 (2.1 MB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 12376 bytes 1386979 (1.3 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

root@ip-172-31-8-13:~#
```

TechData-Infinity-Devops with MultiCloud



Linux traceroute command-

Linux traceroute command is a network troubleshooting utility that helps us determine the number of hops and packets traveling path required to reach a destination. It is used to display how the data transmitted from a local machine to a remote machine. Loading a web page is one of the common examples of the traceroute. A web page loading transfers data through a network and routers. The traceroute can display the routes, IP addresses, and hostnames of routers over a network. It can be useful for diagnosing network issues.

apt install inetutils-traceroute

apt install traceroute

The above commands will install the traceroute utility on our system. After the successful installation, the output will look like as follows:

traceroute google.com

```
root@ip-172-31-0-59:~# traceroute google.com
traceroute to google.com (142.251.221.238), 30 hops max, 60 byte packets
 1  240.2.196.13 (240.2.196.13)  1.250 ms 240.2.196.14 (240.2.196.14)  1.217 ms 240.2.196.12 (240.2.196.12)  1.199 ms
 2  242.6.252.1 (242.6.252.1)  1.165 ms 242.6.252.135 (242.6.252.135)  1.572 ms 242.6.252.133 (242.6.252.133)  1.380 ms
 3  * * *
 4  * * 99.82.178.53 (99.82.178.53)  0.993 ms
 5  * * *
 6  192.178.86.238 (192.178.86.238)  1.743 ms 142.250.227.72 (142.250.227.72)  1.176 ms 142.250.228.48 (142.250.228.48)  1.078 ms
 7  192.178.110.104 (192.178.110.104)  2.172 ms 192.178.110.106 (192.178.110.106)  2.412 ms 108.170.234.157 (108.170.234.157)  0.770 ms
 8  142.250.209.71 (142.250.209.71)  2.823 ms pnbomb-bk-in-f14.1e100.net (142.251.221.238)  0.998 ms 142.250.209.71 (142.250.209.71)  2.761 ms
root@ip-172-31-0-59:~#
```

Linux tracepath –

It is similar to traceroute command, but it doesn't require root privileges. By default, it is installed in Ubuntu but you may have to download traceroute on Ubuntu. It traces the network path of the specified destination and reports each hop along the path. If you have a slow network then tracepath will show you where your network is weak.

tracepath <destination>

```
root@ip-172-31-0-59:~# tracepath google.com
1?: [LOCALHOST] pmtu 9001
 1:  ip-172-31-0-1.ap-south-1.compute.internal 0.106ms pmtu 1500
 1:  240.2.196.12 1.204ms asymm 5
 2:  242.6.252.129 1.361ms asymm 6
 3:  no reply
 4:  99.82.178.53 1.210ms asymm 10
 5:  no reply
 6:  no reply
 7:  no reply
 8:  no reply
 9:  no reply
10:  no reply
11:  no reply
12:  no reply
^C
root@ip-172-31-0-59:~#
```

Linux ping Command-

Linux ping command stands for (Packet Internet Groper). It checks connectivity between two nodes to see if a server is available. It sends ICMP ECHO_REQUEST packets to network hosts and displays the data on the remote server's response. It checks if a remote host is up, or that network interfaces can be reached. Further, it is used to check if a network connection is available between two devices. It is also handy tool for checking your network connection and verifying network issues.

TechData-Infinity-Devops with MultiCloud



Ping command keeps executing and sends the packet until you interrupt.

The ping command supports various command-line options. But, the basic syntax for the ping command is as follows:

ping <option> <destination>

```
root@ip-172-31-0-59:~# ping google.com
PING google.com (142.250.70.46) 56(84) bytes of data.
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=1 ttl=117 time=1.25 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=2 ttl=117 time=1.81 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=3 ttl=117 time=1.28 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=4 ttl=117 time=1.28 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=5 ttl=117 time=1.28 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=6 ttl=117 time=1.68 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=7 ttl=117 time=1.47 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=8 ttl=117 time=1.27 ms
^C
--- google.com ping statistics ---
8 packets transmitted, 8 received, 0% packet loss, time 7011ms
rtt min/avg/max/mdev = 1.249/1.414/1.812/0.203 ms
root@ip-172-31-0-59:~#
```

We can limit the number of sent packets by using the ping command. To limit the packet, specify the 'c' option followed by the number of packets to be sent. It will be executed as:

ping -c <number> <destination>

ping -c 5 google.com

```
root@ip-172-31-0-59:~# ping -c 5 google.com
PING google.com (142.250.70.46) 56(84) bytes of data.
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=1 ttl=117 time=1.68 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=2 ttl=117 time=1.33 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=3 ttl=117 time=1.29 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=4 ttl=117 time=1.50 ms
64 bytes from pnbomb-aa-in-f14.1e100.net (142.250.70.46): icmp_seq=5 ttl=117 time=1.27 ms
--- google.com ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4007ms
rtt min/avg/max/mdev = 1.272/1.414/1.678/0.155 ms
root@ip-172-31-0-59:~#
```

Linux netstat Command-

Linux netstat command stands for **Network statistics**. It displays information about different interface statistics, including open sockets, routing tables, and connection information. Further, it can be used to displays all the socket connections (including TCP, UDP). Apart from connected sockets, it also displays the sockets that are pending for connections. It is a handy tool for network and system administrators.

apt install net-tools

netstat- a

TechData-Infinity-Devops with MultiCloud



```
root@ip-172-31-8-13:~# netstat -a
Active Internet connections (servers and established)
Proto Recv-Q Send-Q Local Address           Foreign Address         State
tcp        0      0 0.0.0.0:ssh              0.0.0.0:*               LISTEN
tcp        0      0 0.0.0.0:http             0.0.0.0:*               LISTEN
tcp        0      0 localhost:domain        0.0.0.0:*               LISTEN
tcp        0    332 ip-172-31-8-13.ap-s:ssh 150.107.192.87:37514    ESTABLISHED
tcp6       0      0 [::]:ssh                [::]:*                  LISTEN
tcp6       0      0 [::]:http               [::]:*                  LISTEN
udp        0      0 localhost:domain        0.0.0.0:*               *
udp        0      0 ip-172-31-8-13.a:bootpc 0.0.0.0:*               *
udp        0      0 localhost:323           0.0.0.0:*               *
udp        0      0 ip-172-31-8-13.ap:55740 ip-172-31-0-2.ap:domain ESTABLISHED
udp6       0      0 ip6-localhost:323      [::]:*                  *
raw6       0      0 [::]:ipv6-icmp          [::]:*                  7
Active UNIX domain sockets (servers and established)
```

Linux dig Command (DNS Lookup)-

Linux dig command stands for **Domain Information Groper**. This command is used for tasks related to DNS lookup to query DNS name servers. It mainly deals with troubleshooting DNS related problems. It is a flexible utility for examining the DNS (Domain Name Servers). It is used to perform the DNS lookups and returns the queried answers from the name server. Usually, it is used by most DNS administrators to troubleshoot the DNS problems. It is a straightforward tool and provides a clear output. It is more functional than other lookups tools.

The dig command supports plenty of command-line options. Additionally, it facilitates batch mode, which is useful for accessing the lookup requests from a file. If it is not specified to the dig command to query a specific name server, it will access each of the servers from “/etc/resolv.conf.” The dig without any command-line options will perform an NS query for “.” (the root).

Query a Domain name

dig google.com

```
root@ip-172-31-0-59:~# dig google.com

; <<>> DiG 9.18.30-Ubuntu0.24.04.2-Ubuntu <<>> google.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 5946
;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
;; EDNS: version: 0, flags:; udp: 65494
;; QUESTION SECTION:
;google.com.                IN      A

;; ANSWER SECTION:
google.com.                 6       IN      A      142.250.70.46

;; Query time: 0 msec
;; SERVER: 127.0.0.53#53(127.0.0.53) (UDP)
;; WHEN: Fri Oct 03 17:51:32 UTC 2025
;; MSG SIZE rcvd: 55

root@ip-172-31-0-59:~#
```

TechData-Infinity-Devops with MultiCloud



Linux nslookup –

This command is also used to find DNS related query.

nslookup <domainName>

```
root@ip-172-31-0-59:~# nslookup google.com
Server:         127.0.0.53
Address:        127.0.0.53#53

Non-authoritative answer:
Name:   google.com
Address: 142.250.70.110
Name:   google.com
Address: 2404:6800:4009:81a::200e

root@ip-172-31-0-59:~#
```

```
root@ip-172-31-42-137:~# awk '/0$/' information.txt
Thomas      Shelby      30         Rio         400
Omega       Night      45         Ontario     600
Giorgos     Georgiou   35         London      300

root@ip-172-31-42-137:~#
```