

MOMOTOR MOWERS



MAIN FEATURES

STARTING: w. recoil starter

TRANSMISSION: belt & gears in oil bath

GEARBOX: 4 speed: 2 forward/2 reverse

WHEEL DISENGAGEMENT: controlled by lever

PTO: w. blocking/release lever
WHEELS: semi-differential hubs

FAST ATTACHMENT: for all tools

HANDLEBARS: cushioned and settable

WHEELS DIM.: 13.500-6"

ENGINE	TE I	<u> </u>	ENGINE	
	HORDA			HONDA GX 160







An helper for all the seasons!

With two forward and two reverse gears, belt transmission, gears in oil bath and a tough steel crankcase, this model is ideal for the hobbyist but also for the pro.

The possibility to use this machine with the mower bar and also with the sweeper makes it essential for those who want to have a garden that always seems perfect, in every season of the year.



MAIN FEATURES

STARTING: w/ recoil starter TRANSMISSION: gears in oil bath

GEARBOX: 2 speed, 1 forward / 1 reverse

CLUTCH: cone, oil immersed PTO: w/ control lever **FAST ATTACHMENT:** for all the tools

HANDLEBARS: cushioned and settable **SAFETY DEVICE:** combined on clutch



HONDA GX 160 Petrol 4,8 HP / 3,6 kW GB 210 V Petrol 5,4 HP / 4,0 kW











MAIN FEATURES

STARTING: w/ recoil starter TRANSMISSION: gears in oil bath

GEARBOX: 4 speed 2 forward/2 reverse

CLUTCH: multi-plate

PTO: independent, 1 speed

HANDLEBARS: cushioned and settable in height

SAFETY DEVICE: combined on clutch



MAIN FEATURES

STARTING: w/ recoil starter **TRANSMISSION:** gears in oil bath

GEARBOX: speed reverser 3 forward/3 reverse

CLUTCH: multi-plate

PTO: independent, 1 speed

WORKING SPEED (km/h): I° (1,8) - II° (2,8) - III° (3,9) - rm (1,4 ÷ 2,2 ÷ 3,0)

HANDLEBARS: cushioned and settable in height

SAFETY DEVICE: combined on clutch

FAST ATTACHMENT: serial WHEELS: 4.0-10



MFC 186 Alpina



MAIN FEATURES

STARTING: w/ recoil starter **TRANSMISSION:** gears in oil bath

GEARBOX: w/ reverser 6 speed (3fwd/3rvr)

CLUTCH: multi-plate

BLOCKING: independent on every wheel RELEASE: independent on every wheel

PTO: independent, 1 speed

WORKING SPEED (km/h): I° (1,8) - II° (2,8) - III° (3,9) - rm (1,4 ÷ 2,2 ÷ 3,0)

HANDLEBARS: cushioned and settable in height

SAFETY DEVICE: combined on clutch

FAST ATTACHMENT: serial WHEELS: 17.800x8

