




mongoDB®

MongoDB

Introduction



Introduction

- ❖ A database Management System provides the mechanism to store and retrieve the data.
- ❖ There are different kinds of database Management Systems:
 1. RDBMS (Relational Database Management Systems)
 2. OLAP (Online Analytical Processing)
 3. NoSQL (Not only SQL)

Limitations of RDBMS

- ❖ In relational database we need to define structure and schema of data first and then only we can process the data.
- ❖ Relational database systems provides consistency and integrity of data by enforcing ACID properties (Atomicity, Consistency, Isolation and Durability). However in most of the other cases these properties are significant performance overhead and can make your database response very slow.
- ❖ Most of the applications store their data in JSON format and RDBMS don't provide you a better way of performing operations such as create, insert, update, delete etc on this data.

Introduction to NoSQL

10gen | the
MongoDB
company

What is NoSQL Database?

- ❖ Not Only SQL (NoSQL) or non relational databases provides a mechanism for storage and retrieval of data other than tabular relations model used in relational databases.
- ❖ NoSQL database doesn't use tables for storing data.
- ❖ It is generally used to store big data and real-time web applications.

Why NoSQL Database?

- ❖ NoSQL databases were created in response to the limitations of traditional relational database technology.
- ❖ **Flexible Schema:** Allow for dynamic schemas, accommodating unstructured or semi-structured data without predefined structures.
- ❖ **Duplicacy over Relations:** Duplicates data across records (denormalization) to enhance performance and scalability, rather than relying on complex relationships and joins as in relational databases.
- ❖ **Horizontal Scalability:** Designed to scale out by adding more servers, handling large volumes of data efficiently.
- ❖ **Performance:** Optimized for high throughput and low latency, suitable for real-time applications.

When to use NoSQL Database?

- ❖ When you want to store and retrieve huge amount of data.
- ❖ The relationship between the data you store is not that important.
- ❖ The data is not structured and changing over time.
- ❖ Constraints and Joins support is not required at database level.
- ❖ The data is growing continuously and you need to scale the database regular to handle the data.

Where to use NoSQL Database?

- ❖ Data isn't relational (e.g. Documents)
- ❖ Too much data to fit in a relational database

SQL vs NoSQL

SQL Database	NoSQL Database
SQL databases are primarily called RDBMS or Relational Databases	NoSQL databases are primarily called as Non-relational or distributed database
SQL databases are table based databases	NoSQL databases can be document based, key-value pairs, graph databases
MySQL uses SQL to query database	MongoDB uses BSON to query database
Developed in the 1970s with a focus on reducing data duplication	Developed in the late 2000s with a focus on scaling and allowing for rapid application change driven by agile and DevOps practices.
Oracle, MySQL, Microsoft SQL Server, and PostgreSQL	Document: MongoDB and CouchDB, Key-value: Redis and DynamoDB, Wide-column: Cassandra and HBase, Graph: Neo4j and Amazon Neptune

NoSQL

FEATURE DESCRIPTION	COLUMN TITLE	COLUMN TITLE	COLUMN TITLE	COLUMN TITLE
First Row	●	●	●	●
Second Row	●	●	●	●
Third Row	●	●	●	●
Rowmanoe	●	●	●	●
Rowow	●	●	●	●
Rowanow	●	●	●	●

```
{
  "_id" : ObjectId("5d16f6a1e198c897a4105d0d"),
  "title" : "Networking",
  "description" : "Networking Essentials",
  "author" : "Gaurav Mandes"
}
{
  "_id" : ObjectId("5d16f6a1e198c897a4105d0e"),
  "title" : "Game Engineering",
  "description" : "Game Engineering and Development",
  "author" : "Gaurav Mandes"
}
{
  "_id" : ObjectId("5d16f6a1e198c897a4105d0f"),
  "title" : "PHP",
  "description" : "PHP as a General-Purpose",
  "author" : "Gautam"
}
>
```

Installation (Local)

❖ Official Website for **MongoDB** :

➤ MongoDB Community Server

<https://www.mongodb.com/try/download/community>

➤ MongoDB Compass

<https://www.mongodb.com/try/download/compass>

➤ MongoDB Shell

<https://www.mongodb.com/try/download/shell>

No-Installation (Online)

❖ Official Website for **MongoDB** :

➤ MongoDB Atlas

<https://www.mongodb.com/atlas>

MongoDB

- ❖ Source –available
- ❖ Cross-platform
- ❖ Document-oriented database
- ❖ Editions (Community, Enterprise, Atlas/Cloud)

Organizing Data

- Database

- Collections

- Records

Document store

RDBMS		MongoDB
Database	➡	Database
Table, View	➡	Collection
Row	➡	Document (JSON, BSON)
Column	➡	Field
Index	➡	Index
Join	➡	Embedded Document
Foreign Key	➡	Reference
Partition	➡	Shard

Document store

RDBMS		MongoDB
Database	➡	Database
Table, View	➡	Collection
Row	➡	Document (JSON, B
Column	➡	Field
Index	➡	Index
Join	➡	Embedded Document
Foreign Key	➡	Reference
Partition	➡	Shard

```
> db.user.findOne({age:39})
{
  "_id" : ObjectId("5114e0bd42..."),
  "first" : "Varun",
  "last" : "Dev",
  "age" : 39,
  "interests" : [
    "Reading",
    "Biking "
  ],
  "favorites": {
    "color": "Blue",
    "sport": "Cricket"
  }
}
```

Working with MongoDB

Create Database

- ❖ On MongoDB shell, command for create a database

use database_name;

- ❖ If the database doesn't exist, above command creates a new database otherwise opens the existing one.

Eg: use College;

```
test> use College
switched to db College
College>
```

Delete Database

- ❖ Use command to delete a database:

db.dropDatabase()

```
College> db.dropDatabase()  
{ ok: 1, dropped: 'College' }  
College>
```

List all Databases

- ❖ To list down all the databases, use the command below

`show dbs`

- ❖ This command lists down all the databases and their size on the disk.

```
test> show dbs
admin          40.00 KiB
car_dealership 72.00 KiB
config         84.00 KiB
local         192.00 KiB
```

- ❖ **Note:** *As you can see that the database “College” that we have created is not present in the list of all the databases. This is because a database is not created until you save a document in it*

Collection

- ❖ MongoDB stores documents in collections.
- ❖ Collections are analogous to tables in relational databases.
- ❖ A collection exists within a single database.
- ❖ Collections do not enforce a schema.
- ❖ A collection may store documents those which are not same in structure because its schema free database.

Create Collection –Method 1

- ❖ In MongoDB you need not to create collection before you insert document in it. With a single command you can insert a document in the collection and the MongoDB creates that collection on the fly.

Syntax: `db.collection_name.insert({key:value, key:value...})`

- ❖ Eg: To create a collection in the database College, we use the following command.

`db.student.insert({name:"Amit", age:23, marks:343});`

```
College> db.student.insert({name:'Amit', age:23, marks:343})
DeprecationWarning: Collection.insert() is deprecated. Use insertOne, insertMany, or bulkWrite.
{
  acknowledged: true,
  insertedIds: { '0': ObjectId('6989a48bea064713df63b112') }
}
```

Create Collection –Method 2

- ❖ We can also create collection before we actually insert data in it. This method provides you the options that you can set while creating a collection.

Syntax: `db.createCollection(name, options)`

- name is the collection name
- options is an optional field that we can use to specify certain parameters such as size, max number of documents etc. in the collection.

Eg: `db.createCollection("Course");`

```
College> db.createCollection('Course')
{ ok: 1 }
```

```
College> db
College
College> show collections
Course
student
College>
```

Create Collection –Method 2

- ❖ We can also create collection before we actually insert data in it. This method provides you the options that you can set while creating a collection.

Syntax: *db.createCollection(name, options)*

- name is the collection name
- options is an optional field that we can use to specify certain parameters such as size, max number of documents etc. in the collection.

Eg: *db.createCollection("Course", {capped: true,
autoIndexID: true, size: 6142800, max: 10000});*