

Python 3 for scientific computing

Lecture 1, 24.1.2018

Introduction and ~~30,000~~ ft overview
9,144 m

Juha Jeronen

juha.jeronen@tut.fi



Meta

- Seminar on Python 3 from the viewpoint of scientific computing
- Timeslot: Wednesday, 12–14, in RO105
- **5 credits**; O(10) meetings
- Formal requirements to pass the course:
 - Final assignment: write a small, possibly useful project in Python (details will be announced later)
 - No exam; exercises almost surely useful, but not compulsory
- Lecture material:
<https://github.com/Technologicat/python-3-scicomp-intro/>
- Also these slides will be available
- Don't worry, I will try to fix the course signup and any other practical issues.



Python?

Python natalensis, Sir Andrew Smith, 1840.

https://commons.wikimedia.org/wiki/File:Python_natalensis_Smith_1840.jpg

Python 3:

```


232 def remove_all(elt, lst): # remove all occurrences of elt from lst, return a copy
233     return [x for x in lst if x != elt]
234 def remove_all_in(elt, lists): # remove elt from all lists, return a copy
235     return [remove_all(elt, lst) for lst in lists]
236
237 def C3_merge(lists):
238     out = []
239     while True:
240         self.logger.debug("MRO: C3 merge: out: %s, lists: %s" % (out, lists))
241         heads = [head(lst) for lst in lists if head(lst) is not None]
242         if not len(heads):
243             break
244         tails = [tail(lst) for lst in lists]
245         self.logger.debug("MRO: C3 merge: heads: %s, tails: %s" % (heads, tails))
246         hd = C3.find_good_head(heads, tails)
247         self.logger.debug("MRO: C3 merge: chose head %s" % (hd))
248         out.append(hd)
249         lists = remove_all_in(hd, lists)
250     return out
251
252 mro = {} # result
253 try:
254     memo = {} # caching/memoization
255     def C3_linearize(node):
256         self.logger.debug("MRO: C3 linearizing %s" % (node))
257         seen.add(node)
258         if node not in memo:
259             # unknown class or no ancestors
260             if node not in self.class_base_nodes or not len(self.class_base_nodes[node]):
261                 memo[node] = [node]
262             else: # known and has ancestors
263                 lists = []
264                 # Linearization of parents...
265                 for baseclass_node in self.class_base_nodes[node]:
266                     if baseclass_node not in seen:
267                         lists.append(C3_linearize(baseclass_node))
268                 # ...and the parents themselves (in the order they appear in the ClassDef)
269                 self.logger.debug("MRO: parents of %s: %s" % (node, self.class_base_nodes[node]))
270                 lists.append(self.class_base_nodes[node])
271                 self.logger.debug("MRO: C3 merging %s" % (lists))
272                 memo[node] = (node) + C3.merge(lists)
273             self.logger.debug("MRO: C3 linearized %s, result %s" % (node, memo[node]))
274             return memo[node]
275         for node in self.class_base_nodes:
276             self.logger.debug("MRO: analyzing class %s" % (node))
277             seen = set() # break cycles (separately for each class we start from)
278             mro[node] = C3_linearize(node)
279 except LinearizationImpossible as e:
  
```

A fairly long history:

- Python 1.0: 1991
- Python 2.0: 2000
- Python 3.0: 2008

Family tree of languages:

<https://www.levenez.com/lang/>




<https://www.python.org/>

What & why for numerics

- Clear, general-purpose, high-level, well-designed complete programming solution
- Easy to learn
- Focus on clarity: often Python programs look clear, making it easier to return to old code later
- Open source; repeatability and transparency of science
- Free of cost; no need for licenses
- “Complete” includes numerics; a viable competitor for MATLAB

```
#!/usr/bin/env python3  
# -*- coding: utf-8 -*-
```

```
print("Hello, world!")
```




<https://www.python.org/>

Why now?

- Python 3 is a sufficiently stable platform to build science on
- Rise and popularization of Python during the last 15 years
- Python now part of the mainstream of programming: many libraries, extensive help available on the internet (especially StackOverflow)
- IEEE Spectrum 2017: Python the most popular language worldwide
<https://spectrum.ieee.org/computing/software/the-2017-top-programming-languages>

```
#!/usr/bin/env python3  
# -*- coding: utf-8 -*-
```


```
f = lambda x: x**2  
g = lambda x: x % 2 == 0  
A = range(10)  
B = [f(x) for x in A if not g(x)]  
print(B)
```




<https://www.python.org/>

Where MATLAB is good

- Quality-of-life features of a commercial product
 - All-in-one
 - Attempts to do some things automatically for the user, e.g. JIT:
<https://hips.seas.harvard.edu/blog/2013/05/13/jit-compilation-in-matlab/>
- Community focused solely on numerics
 - If an algorithm is not in MATLAB, it can likely be found in MATLAB File Exchange
- Polished integrated development environment (IDE) for scientists
- Interactive plot editor
- Some things easier to do than in Python (e.g. 3D plotting)
- SimuLink




VS.



Where Python is good

- Elegant language, in which it is easy to write clear code
- Control: does only what you explicitly tell it to
- Software ecosystem with dependency management (PyPI/pip)
 - A huge number of libraries for anything a computer can do
 - A sensibly sized numerics community, too
- Free of cost; no need for licenses
- Open; repeatability and transparency of science
 - In practice, also the libraries are open source. Sometimes a library already does 99% of what you need...



VS.




“Python”

- Technically speaking, “*Python*” is a specification, like “C” or “*Fortran*”
 - Several implementations: *CPython*, *Jython*, *IronPython*, *PyPy*
 - *CPython* however de facto standard; for most == Python
- Python 3 vs. Python 2
 - Python 3: current version (2017, v3.6.3)
 - Also unofficially known as *py3k*, *Python 3000*
 - Python 2: legacy (2010, v2.7, support ends by 2020)
 - Python 2.x ends at 2.7: *Python 2.8 Un-release Schedule*
<https://www.python.org/dev/peps/pep-0404/>
 - Practically all projects have already migrated to Python 3
 - This seminar: Python 3


```
#!/usr/bin/env python3  
# -*- coding: utf-8 -*-
```

```
import re  
print(re.sub(r'^monty\s*', r'', 'monty python') + " 3") https://www.python.org/
```



Python 2 vs. Python 3


- Almost the same language, but not quite
- Most significant change: Unicode support
 - Python was designed before Unicode, Unicode support was added on
 - Cleaned up in Python 3, but broke backward compatibility
- In some things Python 3 is a more elegant language, because it was cleaned up also in other respects in the major update
 - `print()` is a function; division `/` always outputs a float; integer division `//`; list comprehension has an internal scope
- Python core developer Nick Coghlan: we won't break backward compatibility again when the time for Python 4.0 comes
<http://www.curious efficiency.org/posts/2014/08/python-4000.html>
- Nick Coghlan: Python 3 Q&A:
http://python-notes.curious efficiency.org/en/latest/python3/questions_and_answers.html




Python 3.x and PEP

- PEP = **P**ython **E**nhancement **P**roposal
- The main mechanism for suggesting extensions to the language
- An evolving language; some picks from recent accepted PEPs:
 - Literal string interpolation (f-strings) (3.6+), a new clear syntax for formatting strings
<https://www.python.org/dev/peps/pep-0498/>
 - A dedicated infix operator for matrix multiplication (3.5+), A @ B
<https://www.python.org/dev/peps/pep-0465/>
 - Additional unpacking generalizations (3.5+), an extension for the *tuple unpacking* syntax
<https://www.python.org/dev/peps/pep-0448/>
 - Coroutines with async and await syntax (3.5+), decoupling of coroutines from generators (to avoid misleading programmer intuition)
<https://www.python.org/dev/peps/pep-0492/>

Tools




- **IPython:** advanced command line
- **Jupyter:** IPython's graphical cousin, based on a Mathematica-style *notebook* approach
- **Spyder:** integrated development environment (IDE)
- **Anaconda:** scientific Python distribution
 - Maybe the easiest way to install Python and its scientific libraries on a Windows computer.



Spyder IDE



- The **Scientific PYTHON** Development **EnviRonment**
- Designed for scientists
- MATLAB style IDE
- Matplotlib integration
- Debugger
- Profiler
- Static code analyzer
- REPL (IPython/Jupyter)
read-eval-print-loop




<https://github.com/spyder-ide>

- Mostly well balanced between scientific use oriented, interactive, and software development oriented features.
- Cons: no automatic refactoring or version control GUI. Tools exist; a matter of implementing a frontend.

Scientific Python

Welcome to the bazaar



NumPy

<http://www.numpy.org/>



SciPy

<https://scipy.org/>

SymPy

<http://www.sympy.org/>



Matplotlib

<http://matplotlib.org/>



Scientific Python

- Consists of separate libraries (as usual with general-purpose programming languages)
- **NumPy**, **SciPy**, **Matplotlib** the most important
 - These already do a lot
- **SymPy** for symbolic computing
 - We will look at this, too
- Some other, more specific libraries and their use cases are gathered in the lecture material (sec. 2)
 - We will also look at some of them later on the course




NumPy

<http://www.numpy.org/>

- n -dimensional arrays
- MATLAB style API, but instead of matrices, based on *cartesian tensors*:
 - A vector is a rank 1 tensor
 - A matrix is a rank 2 tensor

```
#!/usr/bin/env python3  
# -*- coding: utf-8 -*-
```

```
import numpy as np  
A = np.array( [[1, 2],  
               [4, 9]], dtype=np.float64 )  
b = np.array( [3, 7], dtype=np.float64 )  
x = np.linalg.solve(A, b)
```



SciPy

<https://scipy.org/>


- Advanced-user versions of linear algebra routines
- Sparse matrices
- I/O for MATLAB *.mat* files
- Numerical integration (quad), initial value problems (ODE), special functions
- Signal processing
- Some optimization routines
- Cython interface to LAPACK, for advanced users



Matplotlib

<http://matplotlib.org/>


- MATLAB-style plotting API
- Standard tool for publication-quality numerical graphics in Python



Also made with Matplotlib

```
#!/usr/bin/env python3  
# -*- coding: utf-8 -*-
```

```
import numpy as np  
import matplotlib.pyplot as plt  
xx = np.linspace(0, 1, 101)  
yy = np.sin(xx * np.pi)  
plt.plot(xx, yy)  
plt.savefig("sin_x.svg")
```



SymPy

<http://www.sympy.org/>


- Symbolic algebra, differentiation, integration

```
#!/usr/bin/env python3
# -*- coding: utf-8 -*-
```

```
import sympy as sy
x = sy.symbols('x')
λf, λg = sy.symbols('f,g', cls=sy.Function)
g = λg(x)
f = λf(g)
D = sy.diff(f, x).doit()
sy.pprint(D)
```



$$\frac{d}{dg(x)}(f(g(x))) \cdot \frac{d}{dx}(g(x))$$



- Python 3 allows Unicode variable names (with certain limitations).

Input e.g. using this:

<https://github.com/clarkgrubb/latex-input>

Zen of Python, The


<https://www.python.org/dev/peps/pep-0020/>

import this

A guiding philosophy for the design of the Python language, as well as many Python programs.
Consists of 20 aphorisms, 19 of which have been written down:

*Beautiful is better than ugly.
Explicit is better than implicit.
Simple is better than complex.
Complex is better than complicated.
Flat is better than nested.
Sparse is better than dense.
Readability counts.
Special cases aren't special enough to break the rules.
Although practicality beats purity.
Errors should never pass silently.
Unless explicitly silenced.
In the face of ambiguity, refuse the temptation to guess.
There should be one— and preferably only one —obvious way to do it.
Although that way may not be obvious at first unless you're Dutch.
Now is better than never.
Although never is often better than **right** now.
If the implementation is hard to explain, it's a bad idea.
If the implementation is easy to explain, it may be a good idea.
Namespaces are one honking great idea – let's do more of those!*

—Tim Peters




<https://www.python.org/>

Python as a programming language

- 1) Imperative (but also some FP features)
- 2) Interpreted
- 3) Object-oriented
- 4) Lexically scoped
- 5) Duck typed
- 6) Call-by-sharing (call-by-object)
- 7) Reflective

functional programming



```
#!/usr/bin/env python3  
# -*- coding: utf-8 -*-
```

```
class Duck:  
    def __init__(self):  
        pass  
    def quack(self):  
        print('quack quack')
```

```
d = Duck()  
d.quack()
```

Python as a programming language

1) Imperative, but also some FP features

- Imperative, like C, C++, *Fortran*, *Java*, *MATLAB*.
 - I.e. a program is a sequence of simple steps.
 - On the other hand, *imperative programming* has another connotation, especially in FP circles (e.g. *Haskell*, *Racket*):
 - Imperative programs contain *mutable state*, which is changed (*mutated*) as the computation proceeds; functional ones attempt to avoid this.
 - Cf. the thought of executable mathematics (L. Peter Deutsch)
<http://www.paulgraham.com/quotes.html>
- Python can also be used for functional programming (FP):
 - Functions are *first-class objects* (can be passed as arguments, returned from functions, saved in a variable, and so on)
 - Anonymous functions, **lambda** x: ..., like MATLAB's @(x) ...
 - Module *functools* in the standard library
 - High-level language; often, in the parts of the program that are not performance-critical, a functional approach is natural (no side effects ⇒ easier to test, fewer bugs).

Python as a programming language

2) Interpreted

- Typical modern interpreted language. Compiled to bytecode, like *Java* and *MATLAB*.
- Bytecode runs on the Python virtual machine, contained in the Python interpreter.
- Bytecode can be disassembled. Possibly useful, if curious about how Python works:

```
def f(x):  
    return x**2  
import dis  
print(dis.dis(f))
```

Python as a programming language

3) Object-oriented

- Everything is an object (also functions)
- Even the *types of objects* are objects
- At the top of the class hierarchy, everything inherits from *object*
- Multiple inheritance allowed
 - Method resolution order (MRO) determined by C3 linearization:
https://en.wikipedia.org/wiki/C3_linearization
- No separate *struct*; a data structure with named fields ⇒ **class**
- Classes can be defined anywhere, also inside a function.
- Python is not as strict about object-orientedness as e.g. Java, where even the `main()` function must be a static method of a class. Python allows also classical functions (not part of any class).
- Python is not as strict about the procedural model either (cf. C). Even **main()** does not need to be defined, unless one specifically wants to.
- Like in *MATLAB*, any sequence of statements (and/or expressions) is a valid Python program.

Python as a programming language


4) Lexically scoped

- Like in most modern languages.
- Lexical scope = a piece of the program's source code as text.
- A name declared in a certain lexical scope exists within the piece of text spanned by that scope, and nowhere else.
(Confused? We will have examples/exercises about this.)
- In Python, the smallest unit of scope is the function.
 - A **for** loop, or most other blocks for that matter (e.g. **while**, **try**, **with**), do **not** introduce a local scope (contrast C++, Java).
 - List comprehension however does; it is processed like a function.
 - This was one of the things that was changed in Python 3.0.
- Name lookup follows the **LEGB** rule: **L**ocal, **E**nclosing, **G**lobal, **B**uilt-in.

[https://en.wikipedia.org/wiki/Scope_\(computer_science\)#Lexical_scoping_vs._dynamic_scoping](https://en.wikipedia.org/wiki/Scope_(computer_science)#Lexical_scoping_vs._dynamic_scoping)

Python as a programming language

5) Duck typed



- “If it quacks...”
- *Any object may be used in any context, up until it is used in a way that it does not support.*
https://en.wikipedia.org/wiki/Duck_typing
- No (typed) variables!
 - In Python, types are attached to *values* (object instances), which are referred to using untyped *names*.
 - Assignment re-assigns the name to point to the new value; it does **not** modify the original value.
 - *Ned Batchelder: Facts and myths about Python names and values*
<https://nedbatchelder.com/text/names.html>
- Python is, however, both *dynamically typed* and *strongly typed*.
 - *Dynamically*: types are checked only at runtime (no compile-time checks).
 - *Strongly*: Types of values are never implicitly converted. Unlike in *Perl*, a string will not become a number even if it contains only digits.

Python as a programming language

6) Call-by-sharing (call-by-object)

- Cf. the traditional approaches of *call-by-value* and *call-by-reference*.
- *Call-by-sharing* is neither of these!
- In Python, the caller and callee *share the same object instance*.
- Combined with how assignment works, this implies that mutable instances and immutable instances behave differently as function arguments.
(We will have an exercise about this.)
- https://en.wikipedia.org/wiki/Evaluation_strategy#Call_by_sharing

Python as a programming language

7) Reflective

- A running program may modify almost anything (including its own code), at any time.
[https://en.wikipedia.org/wiki/Reflection_\(computer_programming\)](https://en.wikipedia.org/wiki/Reflection_(computer_programming))
- `compile()`, `eval()`, `exec()` – also possible to run code given or generated at run time.
 - **Note!** `eval()` for user-given input is a serious information security risk. Only use `eval()`, if it can be guaranteed that the input is harmless.
- Generally speaking, it is difficult or impossible to deduce anything about the behaviour of Python programs by static analysis approaches.
 - However, in practice, reflective features are used sparingly. Static code analyzers exist, and usually the results are good. (`pyan`, `pyflakes`, `pylint`)

Python as a programming language

+1) Other features

- 0-based indexing (contrast *MATLAB* and *Fortran*)
- Automatic memory management (garbage collection, GC)
- No need to declare names; assignment creates the name if nonexistent.
- *Expressions vs. statements*
 - Like in many imperative programming languages, starting with *Fortran 1* (1957).
 - An *expression* returns a value, a *statement* does not.
 - Explicit **return** statement required to return a value from a function.
The default return value (if no **return**) is always the special value `None`.
- Named arguments.
 - Function arguments can be passed also by name, not only by position in the argument list. (More on this in the exercises.)
- Aggressive use of namespaces.
 - Usually, a quick look at the source code of a Python program is sufficient to tell which library and module each function comes from.
- *Indentation is part of the language syntax.*
 - Improves readability, and no need to explicitly terminate blocks.

Meta: the next few weeks

- Weeks 2-3:
 - Putting the theory in practice: examples and exercises.
 - Exercises not compulsory, but almost surely useful.
- Week 4: Overview of the most important scientific libraries: NumPy, SciPy, Matplotlib, SymPy.
- Week 5: hands-on for NumPy, SciPy, Matplotlib, SymPy.

Literature

- Mark Lutz: *Learning Python*, 5th ed., O'Reilly, 2013.
 - Standard “bible” of the trade, very comprehensive.
 - A couple of minor versions behind the latest Python.
- Luciano Ramalho: *Fluent Python: Clear, Concise and Effective Programming*, O'Reilly, 2015.
 - Python 3 for programmers coming from other languages. Focuses on features that are easily missed, if the reader is used to thinking in another programming language.
- Zed A. Shaw: *Learn Python 3 the Hard Way*, Addison–Wesley, 2017.
 - For newcomers to programming.
- Internet!
 - The lecture material lists some web links with each topic.
- Questions? ▷ juha.jeronen@tut.fi