

Requirements Traceability and Acceptance Catalog

Media Reminder - Offline-First Adaptive Media Alarm

Prepared for Mohamed Aslam Abdul

2026-08-05

Contents

0.1 Document control

Field	Value
Document ID	MR-21
Version	1.0
Status	Approved baseline
Last updated	2026-08-05
Product owner	Mohamed Aslam Abdul
Package identifier	com.aslam.mediareminder
Purpose	Map normative requirements to priorities, verification evidence and critical release acceptance scenarios.

Reading rule: This pack specifies a production-oriented Android application, not a promise that third-party devices will behave identically. Where Android or an OEM controls presentation, timing, sound, or permissions, the app provides transparent status and the strongest compliant fallback.

0.2 Document conventions

The words **MUST**, **MUST NOT**, **SHOULD**, **SHOULD NOT**, and **MAY** are normative. A requirement ID is stable once published. Requirement IDs may be retired but **MUST NOT** be reassigned to a different meaning.

Term	Meaning
Reminder	A user-authored instruction that connects content, a schedule, and a presentation profile.
Occurrence	One calculated due instance of a reminder.
Alarm session	The bounded runtime state created

Term	Meaning
	when an occurrence is actively alerting.
Media asset	An app-owned local video, audio, image, or text item.
Profile	Reusable alert behavior such as Gentle, Standard, or Persistent.
Exact-alarm access	Android special app access that allows exact scheduling where the platform requires it.
Full-screen intent	Android notification mechanism for urgent, time-sensitive activity presentation. It is not a general overlay.
Heads-up notification	System-rendered high-priority notification shown temporarily over the current app when Android permits it.
Source of truth	The authoritative specification or local persisted record for a decision or state.

1 Purpose

This catalog is the release-facing index of normative requirements. It does not replace the detailed rationale and algorithms in MR-01 through MR-20. The verification ID points to a test, inspection or review artifact. P0 is required for public v1; P1 may be deferred only when the roadmap explicitly places it after v1.

2 Requirement summary

Domain	Total	P0	P1
Product and scope	39	39	0
Experience and design	14	12	2
Functional behavior	18	17	1
Android native and battery	18	18	0
Data and storage	12	12	0
Backup and migration	15	14	1
Security and privacy	12	11	1
Accessibility and localization	10	9	1
Non-functional budgets	12	12	0

Domain	Total	P0	P1
Release and maintenance	10	10	0

3 Requirement catalog

3.1 Product and scope

ID	Priority	Requirement	Verification
PRD-001	P0	Core import, scheduling, alert actions, playback and backup work in airplane mode.	E2E-OFFLINE-001; static manifest
PRD-002	P0	Production manifest contains no INTERNET permission.	SEC-MANIFEST-001
PRD-003	P0	No account, advertising, analytics or remote configuration is required.	SEC-STATIC-002; privacy review
PRD-004	P0	Onboarding explains that imported media is copied into app storage and removed on uninstall.	UX-ONBOARD-001
PRD-005	P0	User-facing copy never promises guaranteed delivery or exact heads-up size.	COPY-AUDIT-001
PRD-010	P0	Users can import supported video, audio and image through system pickers.	E2E-IMPORT-001..003
PRD-011	P0	Deleting the original gallery/provider file after import does not break app playback.	IT-FILE-004

ID	Priority	Requirement	Verification
PRD-012	P0	Users can rename, categorize, tag, preview and delete media.	E2E-LIB-001..005
PRD-013	P0	Deleting referenced media requires an explicit dependency policy.	E2E-LIB-DELETE-006
PRD-014	P0	Unsupported, corrupt, oversized and low-space imports leave no partial asset.	IT-FILE-010..014
PRD-020	P0	A reminder combines media, schedule, profile, snooze and label.	UT-DOMAIN-001; E2E-REM-001
PRD-021	P0	MVP supports once, daily and selected-weekday schedules.	UT-REC-001..040
PRD-022	P0	Users can create, edit, duplicate, enable, disable and delete reminders.	E2E-REM-002..008
PRD-023	P0	Editor displays the native-calculated next occurrence before final save result.	E2E-REM-009
PRD-024	P0	DST gaps and overlaps use documented deterministic policies with disclosure.	UT-REC-DST-001..020
PRD-025	P0	A reminder is not represented as reliably active when required capability is absent.	IT-CAP-001..008
PRD-030	P0	Locked or non-	IT-PRESENT-

ID	Priority	Requirement	Verification
		interactive devices may use eligible native full-screen alarm presentation.	LOCKED-001..006
PRD-031	P0	Unlocked interactive devices never receive a forced full-screen activity.	IT-PRESENT-UNLOCK-001..010
PRD-032	P0	The app does not request or use overlay permission.	SEC-MANIFEST-002; code search
PRD-033	P0	Play, Snooze and Dismiss work without React Native initialization.	IT-NATIVE-ACTION-001..009
PRD-034	P0	Attached media begins only after Play.	IT-PLAY-001
PRD-035	P0	Every ringing path has a visible stop action and finite timeout.	IT-RING-001..008
PRD-036	P0	Android/OEM ownership of heads-up presentation is explained.	COPY-AUDIT-002
PRD-040	P0	Idle operation has no resident service, wake lock, JS timer or periodic due worker.	PERF-IDLE-001..005
PRD-041	P0	Scheduler registers one ordinary globally earliest one-shot alarm.	IT-SCHED-001..012
PRD-042	P0	Boot, package update, timezone and clock changes reconcile	IT-RECON-001..012

ID	Priority	Requirement	Verification
		schedules.	
PRD-043	P0	Exact-alarm denial/revocation is visible and provides Limited or setup choices.	IT-CAP-EXACT-001..006
PRD-044	P0	Health accurately explains force-stop limitations after relaunch.	MAN-FORCESTOP-001
PRD-050	P0	Export creates a local versioned ZIP with logical JSON, media and checksums.	E2E-BKP-EXPORT-001
PRD-051	P0	Export excludes raw DB, cache, paths, permissions, channels and runtime sessions.	BKP-CONTENT-001
PRD-052	P0	Import validates path, limits, schema, references, checksums, media and space before mutation.	SEC-ZIP-001..030
PRD-053	P0	Import provides Inspect only, Merge and Replace.	E2E-BKP-MODE-001..003
PRD-054	P0	Replace has rollback-ready state and explicit destructive confirmation.	IT-BKP-ROLLBACK-001..010
PRD-055	P0	Restored reminders re-evaluate device permissions/capabilities before activation.	E2E-BKP-CAP-001
PRD-060	P0	Critical flows are operable with TalkBack and	A11Y-TASK-001..010

ID	Priority	Requirement	Verification
		switch/keyboard access.	
PRD-061	P0	Critical content/actions remain usable at 200% font scale.	A11Y-SCALE-001..008
PRD-062	P0	Color is not the sole state indicator.	A11Y-COLOR-001
PRD-063	P0	Reduced motion removes nonessential movement.	A11Y-MOTION-001
PRD-064	P0	Alarm actions use explicit verbs and large reachable targets.	A11Y-ALARM-001..004

3.2 Experience and design

ID	Priority	Requirement	Verification
UX-001	P0	Primary navigation is Today, Library, Reminders and Settings.	UI-NAV-001
UX-002	P0	Permission requests occur at the moment a selected feature needs them, not as a startup wall.	E2E-ONBOARD-002
UX-003	P0	Today shows next occurrence, today timeline and only capability warnings that affect active reminders.	UI-TODAY-001..004
UX-004	P0	Reminder editor preserves entered data when capability setup is incomplete.	E2E-REM-CAP-010
UX-005	P0	In-app due strip is nonmodal and at	UI-STRIP-001..004

ID	Priority	Requirement	Verification
		most min(144dp, 20% usable height).	
UX-006	P0	Unlocked due alert uses Play, Snooze and Dismiss actions in a system notification.	IT-NOTIF-001..006
UX-007	P0	Locked alarm displays static context and native Play, Snooze and Dismiss; no autoplay.	IT-ALARM-UI-001..006
UX-008	P0	Snooze confirmation states the absolute next time.	UI-SNOOZE-001
UX-009	P0	Multiple simultaneous due reminders are queued in one session, not stacked.	IT-COLLISION-001..005
UX-010	P0	Health distinguishes Ready, Limited and Action needed with consequence and action.	UI-HEALTH-001..006
UX-011	P0	Backup import shows inspection and conflict plan before commit.	E2E-BKP-PREVIEW-001
UX-012	P0	Copy is calm, factual and does not shame missed reminders.	COPY-AUDIT-003
UX-013	P1	Text cards may be added without changing the alarm core.	UT-TEXT-001
UX-014	P1	Local history uses factual outcomes	UI-HISTORY-001

ID	Priority	Requirement	Verification
		and no competitive streak pressure.	

3.3 Functional behavior

ID	Priority	Requirement	Verification
FUN-001	P0	Import streams to a pending file while calculating SHA-256.	IT-FILE-TXN-001
FUN-002	P0	Promote media atomically and journal every incomplete file operation.	IT-FILE-TXN-002..009
FUN-003	P0	Internal filenames use UUIDs and never user path segments.	SEC-PATH-001
FUN-004	P0	Search matches local title, notes, category and tags.	UT-SEARCH-001..006
FUN-005	P0	Missing media disables dependent reminders and offers repair choices.	E2E-REPAIR-001
FUN-006	P0	Next occurrence is strictly after cursor and occurrence key is unique.	PROP-REC-001..002
FUN-007	P0	Snooze creates a child occurrence and does not mutate base recurrence.	UT-SNOOZE-001..006
FUN-008	P0	Profiles hold bounded sound, vibration, timeout, retry and grace values.	UT-PROFILE-001..010
FUN-009	P0	Broken custom tone falls back to	IT-AUDIO-004

ID	Priority	Requirement	Verification
		packaged tone with safe diagnostic.	
FUN-010	P0	Only one active alarm session owns sound/vibration.	IT-COLLISION-006
FUN-011	P0	Alarm terminal actions are idempotent for duplicate intents.	IT-NATIVE-ACTION-010..020
FUN-012	P0	Play stops alarm before requesting media audio focus.	IT-AUDIO-PLAY-001
FUN-013	P0	History is optional, local and defaults to 90-day retention.	UT-RETENTION-001
FUN-014	P0	Diagnostics exclude content names, paths, notes and exact labels.	SEC-LOG-001..005
FUN-015	P0	Test reminders use synthetic content and do not write user history.	IT-TEST-REM-001..004
FUN-016	P0	Notification channels are versioned and never recreated to override user choices.	IT-CHANNEL-001..006
FUN-017	P0	Deleting/editing an active reminder resolves or snapshots current session safely.	IT-CONCURRENT-001..005
FUN-018	P1	Duplicate media hash flow can reuse existing bytes.	IT-DEDUP-001

3.4 Android native and battery

ID	Priority	Requirement	Verification
AND-001	P0	Use minSdk 26, compileSdk 37 and initial targetSdk 36, refreshed before release.	BUILD-SDK-001
AND-002	P0	Use SCHEDULE_EXACT_ALARM with contextual education and canScheduleExact Alarms checks.	IT-CAP-EXACT-007..012
AND-003	P0	Preferred exact scheduling uses setAlarmClock for user-visible due events.	IT-SCHED-API-001
AND-004	P0	Inexact Limited mode is explicitly selected and labeled as potentially delayed.	E2E-LIMITED-001
AND-005	P0	AlarmDispatchReceiver claims occurrence before presentation and rejects stale generation.	IT-DISPATCH-001..010
AND-006	P0	Unknown device state defaults to nonintrusive notification path.	UT-PRESENT-UNKNOWN-001
AND-007	P0	Full-screen intent is attached only for locked/non-interactive eligible path.	IT-FSI-001..010
AND-008	P0	Notification denial never starts invisible continuous ringing.	IT-NOTIF-DENIED-001
AND-009	P0	Native alarm	SEC-COMP-001; IT-

ID	Priority	Requirement	Verification
		activity is exported false and reconstructs from active session.	ACT-001
AND-010	P0	Ringing foreground service is session-bound, mediaPlayback typed and hard-capped.	IT-FGS-001..012
AND-011	P0	Wake locks have explicit timeouts and are released on every terminal/failure path.	IT-WAKE-001..015
AND-012	P0	Android 17 background audio rules are tested; alarm audio uses USAGE_ALARM/ex act exemption plus compliant FGS path.	IT-A17-AUDIO-001..006
AND-013	P0	Direct-boot envelope contains no labels/paths and supports generic pre-unlock alert.	IT-DIRECTBOOT-001..008
AND-014	P0	Wall-clock rules reconcile after TIME_SET/TIMEZONE_CHANGED without replay.	IT-TIME-001..010
AND-015	P0	Foreground app receives bridge event but notification remains sufficient fallback.	IT-FG-001..004
AND-016	P0	Notification visibility defaults private and supports generic	IT-LOCKPRIV-001..004

ID	Priority	Requirement	Verification
AND-017	P0	secret content. No DND-policy, phone-state or battery-exemption permission is requested.	SEC-MANIFEST-003
AND-018	P0	Stop service/audio within one second of terminal action.	PERF-ACTION-001

3.5 Data and storage

ID	Priority	Requirement	Verification
DAT-001	P0	Room is the sole durable logical source of truth.	ARCH-STATIC-001
DAT-002	P0	Foreign keys/check constraints and unique occurrence keys enforce invariants.	DB-CONSTRAINT-001..020
DAT-003	P0	Database stores no absolute filesystem paths.	DB-STATIC-001
DAT-004	P0	Scheduler desired/applied generations implement an outbox reconciliation pattern.	DB-SCHED-001..008
DAT-005	P0	At most one active_alarm_session exists.	DB-SESSION-001
DAT-006	P0	File/restore operations have durable phase journals and startup repair.	DB-OP-001..015
DAT-007	P0	Destructive Room migration is forbidden in release.	BUILD-DB-001
DAT-008	P0	Every public schema migration	DB-MIG-001..N

ID	Priority	Requirement	Verification
		has a fixture and invariant test.	
DAT-009	P0	Cache is regenerable and clearing it does not remove media/reminders.	IT-CACHE-001
DAT-010	P0	Storage reserve is checked before import/restore.	IT-SPACE-001..004
DAT-011	P0	History, diagnostics and idempotency have bounded retention.	UT-RETENTION-002..005
DAT-012	P0	Startup does not hash/enumerate the full library on the main path.	PERF-START-001

3.6 Backup and migration

ID	Priority	Requirement	Verification
BKP-001	P0	Archive root includes manifest, README, checksums, data JSON and media.	BKP-SCHEMA-001
BKP-002	P0	Archive identifiers and media UUIDs are stable across round trip.	E2E-BKP-ID-001
BKP-003	P0	SHA-256 covers every entry except the checksum file itself.	BKP-HASH-001
BKP-004	P0	Export uses streaming IO and bounded memory.	PERF-BKP-001..004
BKP-005	P0	Import rejects absolute, traversal, NUL, symlink, duplicate and case-collision entries.	SEC-ZIP-001..012
BKP-006	P0	Import enforces	SEC-ZIP-013..022

ID	Priority	Requirement	Verification
BKP-007	P0	entry count, per-entry, total-size, ratio, JSON-depth and string limits. Every reference, count, size, checksum and media header is validated before commit.	BKP-VALID-001..012
BKP-008	P0	Validated staging is represented by expiring digest-bound import token.	SEC-TOKEN-001..006
BKP-009	P0	Merge conflict choices are deterministic and serializable.	UT-CONFLICT-001..040
BKP-010	P0	Replace creates rollback-ready state before removing current data.	IT-BKP-ROLLBACK-011..020
BKP-011	P0	Crash at each restore phase repairs to old or fully committed state.	IT-BKP-CRASH-001..N
BKP-012	P0	Unsupported major archive version never modifies current data.	BKP-COMPAT-001
BKP-013	P0	Permissions, channels, ringtones and platform paths are not restored as app data.	BKP-EXCLUDE-001
BKP-014	P0	Plain ZIP privacy warning appears before export and import custody is clear.	UX-BKP-PRIV-001
BKP-015	P1	Encrypted archive	SEC-ENC-DESIGN-001

ID	Priority	Requirement	Verification
		uses reviewed authenticated format and new version, never custom crypto.	

3.7 Security and privacy

ID	Priority	Requirement	Verification
SEC-001	P0	Android automatic cloud backup and device transfer exclude all app data.	SEC-BACKUP-001..004
SEC-002	P0	Android components are exported false unless explicitly documented.	SEC-COMP-002
SEC-003	P0	PendingIntents are explicit and immutable; state/nonce is verified.	SEC-PI-001..008
SEC-004	P0	FileProvider exposes only completed export paths with read-only grants.	SEC-FP-001..006
SEC-005	P0	Selected URIs are treated as untrusted streams with bounded validation.	SEC-URI-001..006
SEC-006	P0	No archive field becomes SQL or a path without typed validation.	SEC-INJECT-001..006
SEC-007	P0	Release logs/diagnostics contain no private media metadata.	SEC-LOG-006..012
SEC-008	P0	Signing key and credentials never enter repository, logs or AI	REL-KEY-AUDIT-001

ID	Priority	Requirement	Verification
SEC-009	P0	prompts. Dependency changes are pinned, licensed, scanned and permission-reviewed.	SEC-SUPPLY-001..006
SEC-010	P0	Release includes SBOM and third-party notices.	REL-SBOM-001
SEC-011	P0	Security reporting route does not require users to upload private media/backups.	DOC-SECURITY-001
SEC-012	P1	Optional screen protection is user-controlled and does not block normal ownership use.	UI-PRIVACY-001

3.8 Accessibility and localization

ID	Priority	Requirement	Verification
ACC-001	P0	Interactive elements expose meaningful name, role, state and enabled status.	A11Y-SEM-001..010
ACC-002	P0	Touch targets are at least 48dp; alarm actions at least 56dp.	A11Y-TARGET-001
ACC-003	P0	Initial alarm focus and order are summary, Play, Snooze, Dismiss, more.	A11Y-FOCUS-001
ACC-004	P0	Alarm title/time is announced once without repeated focus stealing.	A11Y-ANNOUNCE-001
ACC-005	P0	Swipe-only or long-press-only critical actions	A11Y-MOTOR-001

ID	Priority	Requirement	Verification
ACC-006	P0	have direct alternatives. Progress announces phase/meaningful thresholds, not every byte.	A11Y-PROGRESS-001
ACC-007	P0	Strings are externalized, plural-aware and not concatenated.	L10N-STATIC-001
ACC-008	P0	Layouts use start/end and pass RTL pseudo-locale.	L10N-RTL-001..006
ACC-009	P0	Date/time follows locale and 12/24-hour system preference.	L10N-TIME-001
ACC-010	P1	Tamil/Arabic release requires native-speaker review of critical copy.	L10N-REVIEW-001

3.9 Non-functional budgets

ID	Priority	Requirement	Verification
NFR-001	P0	Receiver entry to notification is <=500ms p95 and <=2s hard on reference devices.	PERF-ALERT-001
NFR-002	P0	Action tap to sound stop is <=150ms p95 and <=1s hard.	PERF-ACTION-001
NFR-003	P0	Cold usable shell is <=2s p95 reference and <=3.5s low class.	PERF-START-002
NFR-004	P0	Earliest occurrence query at 10k reminders is <=100ms p95 and <=250ms hard.	PERF-DB-001

ID	Priority	Requirement	Verification
NFR-005	P0	Import/export heap growth is bounded and independent of file size.	PERF-IO-001..004
NFR-006	P0	No-due 24h test has no structural idle violation and <=0.5 percentage-point attributed drain target.	PERF-IDLE-006
NFR-007	P0	No wake/service leak remains after 100-cycle alarm soak.	SOAK-ALARM-001
NFR-008	P0	Scheduler supports 10k reminders and 50k retained occurrences.	PERF-SCALE-001
NFR-009	P0	Diagnostics <=5MB and thumbnail cache <=250MB with eviction.	PERF-STORAGE-001
NFR-010	P0	Universal APK target <=60MB and arm64 target <=35MB, reviewed exceptions allowed for security.	PERF-APK-001
NFR-011	P0	Critical/High data, security, alarm-action and accessibility defects are zero at release.	QA-GATE-001
NFR-012	P0	All operations preserve old or complete state under injected crash.	QA-ATOMIC-001

3.10 Release and maintenance

ID	Priority	Requirement	Verification
REL-001	P0	Public APK is signed and tied to an immutable source tag.	REL-SIGN-001
REL-002	P0	Release publishes artifact SHA-256 and signing certificate fingerprint.	REL-HASH-001
REL-003	P0	Release includes privacy, known limitations, changelog, licenses and documentation.	REL-ASSET-001
REL-004	P0	Published artifact is independently downloaded, verified and installed.	REL-PUBLISH-001
REL-005	P0	Upgrade tests cover every supported public database and archive version.	REL-UPGRADE-001
REL-006	P0	Manifest and current Android/RN/Play policy baseline are refreshed before release.	REL-RESEARCH-001
REL-007	P0	Portfolio claims use measured achieved evidence, not planned budgets.	PORT-AUDIT-001
REL-008	P0	Public screenshots/demo use owned, licensed, public-domain or synthetic media.	PORT-LICENSE-001
REL-009	P0	No debug APK, signing key or private fixture is	REL-SECRET-001

ID	Priority	Requirement	Verification
REL-010	P0	published. End-of-life or withdrawn release is clearly labeled with export/recovery guidance.	REL-EOL-001

4 Verification suite dictionary

Prefix	Evidence type
UT / PROP	Pure unit or property test
DB	Room constraint, DAO, migration or query test
IT	Android instrumented integration test
E2E	User-flow end-to-end test
SEC	Security/static/fuzz/manifest test
A11Y / L10N	Manual and automated accessibility/localization test
PERF / SOAK	Measured performance, battery or long-run reliability evidence
UI / COPY	Component, screenshot, interaction or content review
BUILD / ARCH	Build-time or dependency-boundary inspection
REL / PORT / DOC	Release, portfolio or documentation evidence
MAN	Controlled manual platform scenario

A range such as IT-NATIVE-ACTION-001..009 is a defined group in the test repository/report, not permission to claim unimplemented placeholders. Before release, the generated QA report expands every range into concrete passing cases.

5 Critical acceptance scenarios

5.1 AC-01 - First reminder offline

Given a clean install in airplane mode, the user imports a supported local video, creates a daily Standard reminder and sees a correct next occurrence. No network permission or request exists.

5.2 AC-02 - Locked presentation

Given notifications/exact/full-screen eligibility and a locked non-interactive phone, when the reminder is due, a native alarm surface appears, sound/vibration follows profile, and Play/Snooze/Dismiss work with RN disabled.

5.3 AC-03 - Unlocked noninterruption

Given the user is actively using another app, when a reminder is due, no full-screen activity launches. Android receives a high-importance notification without FSI and actions are available. Absence of a heads-up due to system settings is reported as platform behavior, not overridden with overlay.

5.4 AC-04 - Play transition

Given an active alert, when Play is selected, sound/vibration stops within the action budget, the occurrence resolves once, and attached media begins only after the player becomes visible. Missing media fails safe without continued ringing.

5.5 AC-05 - Snooze idempotency

Given duplicate Snooze PendingIntents for one nonce, exactly one child occurrence is created, one next alarm is registered, and every duplicate response returns the same absolute snooze time.

5.6 AC-06 - Process death and reboot

Normal process death does not prevent the due native alert. Reboot restores a generic pre-unlock envelope and full detail after unlock. No labels or paths exist in device-protected storage.

5.7 AC-07 - Exact access revoked

Future exact alarms are canceled/reconciled, active intent is retained, Health shows Limited/Action needed, and no silent inexact downgrade occurs unless preauthorized.

5.8 AC-08 - Notification blocked

No invisible continuous sound service starts. The occurrence is recorded blocked/needs setup and the next app launch explains recovery.

5.9 AC-09 - Import interruption

Crash/cancel/storage loss at each copy phase leaves no partial normal asset and startup repair reaches a documented state.

5.10 AC-10 - Export/import round trip

All supported logical records are canonically equal after clean-device Replace restore and every media hash matches.

5.11 AC-11 - Malicious archive

Traversal, absolute, duplicate, symlink, bomb, invalid checksum and higher-major fixtures are rejected before current data or scheduler changes.

5.12 AC-12 - Replace crash recovery

Termination at every restore phase recovers to the old state or complete new state, never mixed references or missing current data without rollback path.

5.13 AC-13 - Accessibility

A TalkBack user at 200% font completes import, reminder creation, locked alert action, Health recovery and backup inspection without focus trap, clipped action or color-only information.

5.14 AC-14 - Idle battery

With reminders configured and none due, no process/service/wake lock/timer is resident for time monitoring and one ordinary alarm registration exists.

5.15 AC-15 - Public release integrity

The downloaded APK matches published SHA-256, verifies under the published certificate fingerprint, upgrades from prior public version, and contains no prohibited permission/exported component.

6 Release acceptance decision

A release is **Accepted** only when every P0 row has passing evidence, all critical scenarios pass, and no Critical/High blocker remains in the domains defined by MR-14. `Not applicable` requires a written reason tied to product scope and reviewer approval; it cannot be used to hide an unimplemented P0 feature. Any platform limitation is accepted only when the specified fallback and user disclosure both pass.

6.1 Governance

This document is part of the **Media Reminder Source-of-Truth Pack v1.0**. In case of conflict, apply this precedence order: (1) explicit platform safety and permission rules, (2) Architecture Decision Records, (3) Android specification, (4) data and backup specifications, (5) PRD and feature specification, (6) UX and visual guidance, (7) implementation notes. Record any intentional deviation in the decision log before release.