

API Documentation

API Documentation

June 28, 2013

Contents

Contents	1
1 Package voix	2
1.1 Modules	2
1.2 Variables	2
2 Module voix.client	3
2.1 Variables	3
2.2 Class Client	3
2.2.1 Methods	3
2.2.2 Properties	5
3 Module voix.connection	6
3.1 Variables	6
3.2 Class Connection	6
3.2.1 Methods	6
3.2.2 Properties	7
3.2.3 Class Variables	7
4 Package voix.interface	8
4.1 Modules	8
4.2 Variables	8
5 Module voix.interface.cli	9
5.1 Variables	9
5.2 Class CLI	9
5.2.1 Methods	9
5.2.2 Properties	10
6 Module voix.interface.gui	11
6.1 Variables	11
6.2 Class GUI	11
6.2.1 Methods	11
6.2.2 Properties	13
7 Module voix.message_handler	15
7.1 Variables	15
7.2 Class MessageHandler	15

7.2.1	Methods	15
7.2.2	Properties	15
8	Module voix.parser	16
8.1	Variables	16
8.2	Class Parser	16
8.2.1	Methods	16
8.2.2	Properties	16

1 Package voix

1.1 Modules

- **client**: The main client.
(Section 2, p. 3)
- **connection** (Section 3, p. 6)
- **interface** (Section 4, p. 8)
 - **cli** (Section 5, p. 9)
 - **gui** (Section 6, p. 11)
- **message_handler** (Section 7, p. 15)
- **parser** (Section 8, p. 16)

1.2 Variables

Name	Description
<code>--package--</code>	Value: None

2 Module `voix.client`

The main client.

2.1 Variables

Name	Description
<code>--package--</code>	Value: <code>'voix'</code>

2.2 Class `Client`



Client object.

2.2.1 Methods

`--init--(self)`

Initializes the client object

Overrides: `object.__init__`

`register_update_callback(self, func)`

`set_host(self, data)`

Sets the value of a given field.

Arguments:

- `'field'`:

The field to set the given `'value'`.

- `'value'`:

The value to set.

set_port(*self*, *data*)

Sets the value of a given field.

Arguments:

- 'field':

The field to set the given 'value'.

- 'value':

The value to set.

connect(*self*, *data*)

Connects to the server if both hostname and username is set.

pong(*self*, *data*)**join_channel**(*self*, *data*)**message**(*self*, *data*)

Client > Server:

'MSG #Lobby: Hello there!' (Public message in #Lobby. Sender is assigned on server side)

'MSG John: Hi John!' (Private message. Sender is assigned on server side)

Server > Client:

'MSG Mike #Lobby: Hello there!' (Public message in #Lobby. Sent to all clients in the room.)

'MSG Mike John: Hi John' (Private message)

Arguments:

- 'data':

Given the scenarios above, data is a list where 'data[0]' may be a nickname or a channel if 'data[1]' is None.

If 'data[1]' is not None, it can either be a channel or a nickname. In that case 'data[0]' will always be a nickname.

'data[2]' is always the message.

talk(*self*, *data*)

Client > Server:
 'TALK John: Request'

Server > Client:
 'TALK Mike John: Request' (Private message)

Arguments:
 - 'data':
 Given the scenarios above, data is a list where 'data[0]' is
 always a nickname.
 If 'data[1]' is not None, this will be the receiver of the
 code message.
 'data[2]' is always the code i.e. Request, Accept, Deny, End.

accepted(*self*, *data*)

denied(*self*, *data*)

joined_channel(*self*, *data*)

userlist(*self*, *data*)

close(*self*)

Wrapper for the sockets close function.

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,
`__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

2.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

3 Module voix.connection

3.1 Variables

Name	Description
<code>__package__</code>	Value: 'voix'

3.2 Class Connection



3.2.1 Methods

`__init__(self, client, type)`

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature

Overrides: `object.__init__` extit(inherited documentation)

`connect(self, address)`

`send(self, data)`

`tcp_handler(self)`

`udp_in_handler(self)`

`udp_out_handler(self)`

`is_connected(self)`

`open_stream(self)`

Opens a UDP stream to the server, which redirects the traffic to the connected clients.

close_stream (<i>self</i>)

Opens a UDP stream to the server, which redirects the traffic to the connected clients.

close (<i>self</i>)

Wrapper for the sockets close function.

Inherited from object

`--delattr--()`, `--format--()`, `--getattr--()`, `--hash--()`, `--new--()`, `--reduce--()`, `--reduce_ex--()`,
`--repr--()`, `--setattr--()`, `--sizeof--()`, `--str--()`, `--subclasshook--()`

3.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>--class--</code>	

3.2.3 Class Variables

Name	Description
<code>types</code>	Value: <code>{ 'TCP': 1, 'UDP': 2 }</code>

4 Package voix.interface

4.1 Modules

- **cli** (*Section 5, p. 9*)
- **gui** (*Section 6, p. 11*)

4.2 Variables

Name	Description
--package--	Value: None

5 Module voix.interface.cli

5.1 Variables

Name	Description
<code>__package__</code>	Value: <code>'voix.interface'</code>

5.2 Class CLI



5.2.1 Methods

`__init__`(*self*, *client*)

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature

Overrides: `object.__init__`

`update`(*self*, *channel*=None, *userlist*=None)

`write_message`(*self*, *author*=None, *recipient*=None, *channel*=None, *message*=None)

Arguments:

- `'message'`:

```
talk_prompt(self, requester=None, responder=None, code=None)
```

Handles all ‘TALK’ related requests and responses.

Arguments:

– ‘message’:

[VoIP] ‘requester’ wish to have a conversation with you. Accept? (y/n)

[VoIP] Awaiting response from ‘responder’...

[VoIP] ‘responder’ has rejected your conversation request.

[VoIP] Your conversation with ‘responder’ has been terminated.

```
talk_timeout_timer(self)
```

```
main_loop(self)
```

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,
`__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

5.2.2 Properties


Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

6 Module voix.interface.gui

6.1 Variables

Name	Description
<code>--package--</code>	Value: <code>'voix.interface'</code>

6.2 Class GUI



6.2.1 Methods

<code>--init--</code> <i>(self, parent, id, title)</i>
Initializes the GUI
Arguments:
- 'self':
- 'parent':
- 'id':
- 'title':
Return Value
EvtHandler
Overrides: <code>object.__init__</code>

Inherited from wx._windows.Frame

`Command()`, `Create()`, `CreateStatusBar()`, `CreateToolBar()`, `DoGiveHelp()`, `DoMenu-`

Updates(), GetClassDefaultAttributes(), GetMenuBar(), GetStatusBar(), GetStatusBarPane(), GetToolBar(), PopStatusText(), ProcessCommand(), PushStatusText(), SendSizeEvent(), SetMenuBar(), SetStatusBar(), SetStatusBarPane(), SetStatusText(), SetStatusWidths(), SetToolBar()

Inherited from wx._windows.TopLevelWindow

CenterOnScreen(), CentreOnScreen(), EnableCloseButton(), GetDefaultItem(), GetIcon(), GetTitle(), GetTmpDefaultItem(), Iconize(), IsActive(), IsAlwaysMaximized(), IsFullScreen(), IsIconized(), IsMaximized(), MacGetMetalAppearance(), MacGetTopLevelWindowRef(), MacGetUnifiedAppearance(), MacSetMetalAppearance(), Maximize(), RequestUserAttention(), Restore(), SetDefaultItem(), SetIcon(), SetIcons(), SetShape(), SetTitle(), SetTmpDefaultItem(), ShowFullScreen(), __repr__()

Inherited from wx._core.Window

AcceptsFocus(), AcceptsFocusFromKeyboard(), AddChild(), AdjustForLayoutDirection(), AssociateHandle(), CacheBestSize(), CanSetTransparent(), CaptureMouse(), Center(), CenterOnParent(), Centre(), CentreOnParent(), ClearBackground(), ClientToScreen(), ClientToScreenXY(), ClientToWindowSize(), Close(), ConvertDialogPointToPixels(), ConvertDialogSizeToPixels(), ConvertPixelPointToDialog(), ConvertPixelSizeToDialog(), DLG_PNT(), DLG_SZE(), Destroy(), DestroyChildren(), Disable(), DissociateHandle(), DragAcceptFiles(), Enable(), FindFocus(), FindWindowById(), FindWindowByLabel(), FindWindowByName(), Fit(), FitInside(), Freeze(), GetAcceleratorTable(), GetAdjustedBestSize(), GetAutoLayout(), GetBackgroundColour(), GetBackgroundStyle(), GetBestFittingSize(), GetBestSize(), GetBestSizeTuple(), GetBestVirtualSize(), GetBorder(), GetCapture(), GetCaret(), GetCharHeight(), GetCharWidth(), GetChildren(), GetClientAreaOrigin(), GetClientRect(), GetClientSize(), GetClientSizeTuple(), GetConstraints(), GetContainingSizer(), GetCursor(), GetDefaultAttributes(), GetDropTarget(), GetEffectiveMinSize(), GetEventHandler(), GetExtraStyle(), GetFont(), GetForegroundColour(), GetFullTextExtent(), GetGrandParent(), GetGtkWidget(), GetHandle(), GetHelpText(), GetHelpTextAtPoint(), GetId(), GetLabel(), GetLayoutDirection(), GetMaxHeight(), GetMaxSize(), GetMaxWidth(), GetMinHeight(), GetMinSize(), GetMinWidth(), GetName(), GetParent(), GetPosition(), GetPositionTuple(), GetRect(), GetScreenPosition(), GetScreenPositionTuple(), GetScreenRect(), GetScrollPos(), GetScrollRange(), GetScrollThumb(), GetSize(), GetSizeTuple(), GetSizer(), GetTextExtent(), GetThemeEnabled(), GetToolTip(), GetToolTipString(), GetTopLevelParent(), GetUpdateClientRect(), GetUpdateRegion(), GetValidator(), GetVirtualSize(), GetVirtualSizeTuple(), GetWindowBorderSize(), GetWindowStyle(), GetWindowStyleFlag(), GetWindowVariant(), HasCapture(), HasFlag(), HasMultiplePages(), HasScrollbar(), HasTransparentBackground(), Hide(), HitTest(), HitTestXY(), InheritAttributes(), InheritsBackgroundColour(), InitDialog(), InvalidateBestSize(), IsBeingDeleted(), IsDoubleBuffered(), IsEnabled(), IsExposed(), IsExposedPoint(), IsExposedRect(), IsFrozen(), IsRetained(), IsShown(), IsShownOnScreen(), IsTopLevel(), Layout(), LineDown(), LineUp(), Lower(), MakeModal(),

Move(), MoveAfterInTabOrder(), MoveBeforeInTabOrder(), MoveXY(), Navigate(), NewControlId(), NextControlId(), PageDown(), PageUp(), PopEventHandler(), PopupMenu(), PopupMenuXY(), PostCreate(), PrepareDC(), PrevControlId(), PushEventHandler(), Raise(), Refresh(), RefreshRect(), RegisterHotKey(), ReleaseMouse(), RemoveChild(), RemoveEventHandler(), Reparent(), ScreenToClient(), ScreenToClientXY(), ScrollLines(), ScrollPages(), ScrollWindow(), SetAcceleratorTable(), SetAutoLayout(), SetBackgroundColour(), SetBackgroundStyle(), SetBestFittingSize(), SetCaret(), SetClientRect(), SetClientSize(), SetClientSizeWH(), SetConstraints(), SetContainingSizer(), SetCursor(), SetDimensions(), SetDoubleBuffered(), SetDropTarget(), SetEventHandler(), SetExtraStyle(), SetFocus(), SetFocusFromKbd(), SetFont(), SetForegroundColour(), SetHelpText(), SetHelpTextForId(), SetId(), SetInitialSize(), SetLabel(), SetLayoutDirection(), SetMaxSize(), SetMinSize(), SetName(), SetOwnBackgroundColour(), SetOwnFont(), SetOwnForegroundColour(), SetPosition(), SetRect(), SetScrollPos(), SetScrollbar(), SetSize(), SetSizeHints(), SetSizeHintsSz(), SetSizeWH(), SetSizer(), SetSizerAndFit(), SetThemeEnabled(), SetToolTip(), SetToolTipString(), SetTransparent(), SetValidator(), SetVirtualSize(), SetVirtualSizeHints(), SetVirtualSizeHintsSz(), SetVirtualSizeWH(), SetWindowStyle(), SetWindowStyleFlag(), SetWindowVariant(), ShouldInheritColours(), Show(), Thaw(), ToggleWindowStyle(), TransferDataFromWindow(), TransferDataToWindow(), UnregisterHotKey(), Update(), UpdateWindowUI(), UseBgCol(), Validate(), WarpPointer(), WindowToClientSize()

Inherited from wx._core.EvtHandler

AddPendingEvent(), Bind(), Connect(), Disconnect(), GetEvtHandlerEnabled(), GetNextHandler(), GetPreviousHandler(), ProcessEvent(), ProcessPendingEvents(), SetEvtHandlerEnabled(), SetNextHandler(), SetPreviousHandler(), Unbind()

Inherited from wx._core.Object

GetClassName(), IsSameAs()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

6.2.2 Properties

Name	Description
<i>Inherited from wx._windows.Frame</i>	
MenuBar, StatusBar, StatusBarPane, ToolBar, thisown	
<i>Inherited from wx._windows.TopLevelWindow</i>	
DefaultItem, Icon, Title, TmpDefaultItem	
<i>Inherited from wx._core.Window</i>	

continued on next page

Name	Description
	AcceleratorTable, AutoLayout, BackgroundColour, BackgroundStyle, BestSize, BestVirtualSize, Border, Caret, CharHeight, CharWidth, Children, ClientAreaOrigin, ClientRect, ClientSize, Constraints, ContainingSizer, Cursor, DefaultAttributes, DropTarget, EffectiveMinSize, Enabled, EventHandler, ExtraStyle, Font, ForegroundColour, GrandParent, GtkWidget, Handle, HelpText, Id, Label, LayoutDirection, MaxHeight, MaxSize, MaxWidth, MinHeight, MinSize, MinWidth, Name, Parent, Position, Rect, ScreenPosition, ScreenRect, Shown, Size, Sizer, ThemeEnabled, ToolTip, ToolTipString, TopLevel, TopLevelParent, UpdateClientRect, UpdateRegion, Validator, VirtualSize, WindowStyle, WindowStyleFlag, WindowVariant
	<i>Inherited from wx._core.EvtHandler</i> EvtHandlerEnabled, NextHandler, PreviousHandler
	<i>Inherited from wx._core.Object</i> ClassName
	<i>Inherited from object</i> __class__

7 Module `voix.message_handler`

7.1 Variables

Name	Description
<code>__package__</code>	Value: None

7.2 Class `MessageHandler`



7.2.1 Methods

<code>__init__(self)</code>
SAP!
Overrides: <code>object.__init__</code>

<code>register_message_callback(self, func)</code>
author, recipient, channel, message

<code>register_talk_callback(self, func)</code>
requester, responder

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

7.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

8 Module voix.parser

8.1 Variables

Name	Description
<code>--package--</code>	Value: 'voix'

8.2 Class Parser

object └─
 voix.parser.Parser

8.2.1 Methods

`--init--`(*self*, *client*)

x.`--init--`(...) initializes *x*; see `help(type(x))` for signature

Overrides: `object.--init--` extit(inherited documentation)

`parse`(*self*, *data*)

Arguments:

- 'self':
- 'data':

Inherited from object

`--delattr--`(), `--format--`(), `--getattribute--`(), `--hash--`(), `--new--`(), `--reduce--`(), `--reduce_ex--`(),
`--repr--`(), `--setattr--`(), `--sizeof--`(), `--str--`(), `--subclasshook--`()

8.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>--class--</code>	

Index

- voix (*package*), 2
 - voix.client (*module*), 3–5
 - voix.client.Client (*class*), 3–5
 - voix.connection (*module*), 6–7
 - voix.connection.Connection (*class*), 6–7
 - voix.interface (*package*), 8
 - voix.interface.cli (*module*), 9–10
 - voix.interface.gui (*module*), 11–14
 - voix.message_handler (*module*), 15
 - voix.message_handler.MessageHandler (*class*), 15
 - voix.parser (*module*), 16
 - voix.parser.Parser (*class*), 16