Assignment No 5 :- Design n-Queens matrix having first Queen placed. Use backtracking to place remaining Queens to generate the final n-queen‘s matrix.

Code:-

```
#include
<iostream> #include
<vector> using namespace
std;

class NQueens
{ private: int N;

    // Function to print the chessboard void
    printBoard(const vector<vector<int> > &board) {
        for (int i = 0; i < N; i++) {
            for (int j = 0; j < N; j++) {
                cout << (board[i][j] ? " Q " : " - ");
            }
            cout << endl;
        }
    }

    // Function to check if a queen can be placed at board[row][col]
    bool isSafe(const vector<vector<int> > &board, int row, int col) {
        for (int i = 0; i < col; i++) { if (board[row][i])
            return false; // Check row
        }
        for (int i = row, j = col; i >= 0 && j >= 0; i--, j--) { if
            (board[i][j]) return false; // Check upper diagonal
        }
        for (int i = row, j = col; j >= 0 && i < N; i++, j--) { if
            (board[i][j]) return false; // Check lower diagonal
        }
        return true;
    }

    // Recursive function to solve the N-Queens problem bool
    solveNQueensUtil(vector<vector<int> > &board, int col) {
        if (col >= N) return true; // All queens are placed
        for (int i = 0; i < N; i++) { if (isSafe(board, i, col))
        {
```

```
            board[i][col] = 1; // Place queen if
            (solveNQueensUtil(board, col + 1)) return true; // Recur
            board[i][col] = 0; // Backtrack
        }
    }
    return false; // No valid position found
  }

public:
  // Function to initiate solving the N-Queens
  problem void solveNQueens(int n) { N = n;
    vector<vector<int> > board(N, vector<int>(N, 0));
    if (!solveNQueensUtil(board, 0)) {
      cout << "No solution exists." << endl;
      return;
    }
    printBoard(board);
  }
};

int main() {
  NQueens nq;
  int n; cout << "Enter the size of the chessboard
  (N): "; cin >> n; nq.solveNQueens(n); return 0;
}
```

Output :-