

Hands-On: Passing Arguments and Preventing Default Behavior in React

In this lab, you will create a simple React component that uses event handling to display a message when a button is clicked. You will also learn how to pass arguments to event handlers and prevent the default behavior of an event.

Step 1: Create a new React component

Create a new file called `Button.js` and add the following code:

```
import React from 'react';

function Button(props) {
  const handleClick = (event) => {
    event.preventDefault();
    alert(`Hello, ${props.name}!`);
  };

  return (
    <button onClick={handleClick}>Click me</button>
  );
}

export default Button;
```

This component takes a `name` prop and displays a button that triggers an event when clicked. The `handleClick` function prevents the default behavior of the event and displays an alert message with the name passed in as a prop.

Step 2: Render the component

Create a new file called `App.js` and add the following code:

```
import React from 'react';
import Button from './Button';

function App() {
  return (
    <div className="App">
      <h1>Passing Arguments and Preventing Default Behavior in React</h1>
      <Button name="John" />
      <Button name="Jane" />
    </div>
  );
}

export default App;
```

This component simply renders two `Button` components with different names passed in as props.

Step 3: Run the app

Run the app using `npm start` and test the `Button` component by clicking the "Click me" button to display the alert message with the name passed in as a prop.

Congratulations! You have successfully implemented passing arguments to event handlers and preventing default behavior in a React component.