

Hands-On: Using Lists and Keys in React

In this lab, you will create a simple React component that uses an array of data to render a list of items with unique keys.

Step 1: Create a new React component

Create a new file called `TodoList.js` and add the following code:

```
import React, { Component } from 'react';

class TodoList extends Component {
  state = {
    todos: [
      { id: 1, title: 'Learn React' },
      { id: 2, title: 'Build a project' },
      { id: 3, title: 'Deploy to production' },
    ],
  };

  render() {
    const { todos } = this.state;

    return (
      <div>
        <h1>Todo List</h1>
        <ul>
          {todos.map(todo => (
            <li key={todo.id}>{todo.title}</li>
          ))}
        </ul>
      </div>
    );
  }
}
```

`export default TodoList;`

This component has an initial state with an array of todo items. The `render` method maps over the array and renders a list item for each todo item with a unique key based on the `id` property.

Step 2: Render the component

Create a new file called `App.js` and add the following code:

```
import React from 'react';
import TodoList from './TodoList';

function App() {
  return (
    <div className="App">
      <h1>Using Lists and Keys in React</h1>
      <TodoList />
    </div>
  );
}
```

```
    </div>  
  );  
}
```

```
export default App;
```

This component simply renders the `TodoList` component.

Step 3: Run the app

Run the app using `npm start` and test the `TodoList` component by verifying that each todo item has a unique key.

Congratulations! You have successfully used lists and keys in a React component.