

1. What is CSS? Explain the full form of CSS.
CSS stands for Cascading style sheets. It is used to style and design web pages. CSS Controls colors, fonts, spacing, layout, and other visual effects.

2. What is Cascading in CSS? give a ^{real-time} example?
Cascading means when multiple CSS rules are applied to the same element, the browser chooses the rule with higher priority.

Expk:-

```
p {  
    color: blue;  
}  
p {  
    color: red;  
}
```

3. What is the difference between Cascading and Specificity?

Cascading: Decides which CSS rule is applied based on priority and order.

Specificity: Decides which selector has higher priority (ID > class > Element).

4. What are the three types of CSS? which one is recommended in real-time project and why?

Inline CSS, Internal CSS, External CSS, External CSS is recommended one, because it is reusable, easy to maintain, and keeps HTML and CSS separate.

5. Explain the following selectors with examples.

Universal selector

selects all elements.

```
*{  
  margin: 0;  
}
```

Element Selector

Selects all elements of a specific tag.

```
p{  
  color: blue;  
}
```

Class selector

selects element with the same class.

```
.card{  
  background: lightgray;  
}
```

ID selector

selects one unique element.

```
#header{  
  color: red;  
}
```

Group selector

Applies the same style to multiple elements.

```
h1, p{  
  color: green;  
}
```

Descendant Selector

Selects all child elements inside a parent.

```
div p{  
  color: blue;  
}
```

child Selector

Selects only the direct child.

`div > p {`

`color: red; }`

6. What is the difference between class selector and ID selector?

Class Selector (.): Can be used for multiple elements.

ID Selector (#): Used for one unique element only.

7. What is the difference between Descendant selector and child selector?

Descendant selector (space): selects all matching elements inside the parent.

child selector (>): selects only the direct child elements.

8. Explain the CSS box model.

Name its four parts.

The CSS box model describes how the size of an element is calculated.

Four parts:

Content

Padding

Border

Margin

- Ans: 9. **Padding** - Space inside the border, part of the element box, Background color applies.

Margin - Space outside the border, outside the element.

box, Background color does not apply.

10. box-sizing: border-box makes sure that padding and border are included in the element's total width and height. it makes layout calculate easier and prevent overflow.
11. display: Block - Takes full width, start new line, set width/height.
- ii) display: inline - only needed width, stay line, cannot set W/h.
- iii) display: inline-block - only needed width, stay in line, can set W/h.

Element	Can apply w/h	why
div	Yes	It is a block-level element
span	No (by default)	It is an inline element
button	Yes	It is an inline-block element

13. display: none
- i) Element is removed from layout
- ii) Does not affect other element
- Visibility: hidden
- i) Element is hidden but still place or space taken but we can see the content
- ii) Affects layout

14) Flex is a layout model that arranges items in flexible container. Type of Components: - 1) Flex Container, 2) Flex item. 3) Main Axis. 4) Cross Axis.

15). Container {

display: flex;
justify-content: center; /* Center horizontally */
align-items: center; /* Centers Vertically */
height: 100vh; /* Full Viewport height */