

Assignment – 12  
Using the operators IN, ANY, and ALL.

- 1) Write a query that selects all customers whose ratings are equal to or greater than ANY of Serres'.

```
W2_93085_Tejal select *from customers
-> where rating >= any
-> (select rating from customers
-> where snum=1002);
```

Cnum	Cname	City	Rating	Snum
2002	Giovanni	Rome	200	1003
2003	Liu	San_Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San_Jose	300	1007

4 rows in set (0.00 sec)

- 2) Write a query using ANY or ALL that will find all salespeople who have no customers located in their city.

```
W2_93085_Tejas select *from salespeople
-> where city != all
-> (select city from customers);
```

Snum	Sname	City	Comm
1007	Rifkin	Barcelona	0.15
1003	Axelrod	New_York	0.10

2 rows in set (0.00 sec)

- 3) Write a query that selects all orders for amounts greater than any for the customers in London.

```
W2_93085_Teja1 SELECT *  
-> FROM ORDERS  
-> WHERE AMT > ANY (  
->     SELECT AMT  
->     FROM ORDERS  
->     WHERE CNUM IN (  
->         SELECT CNUM  
->         FROM CUSTOMERS  
->         WHERE CITY = 'London'  
->     )  
-> );
```

Onum	Amt	Odate	Cnum	Snum
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001

7 rows in set (0.00 sec)

4) Write the above query using MIN or MAX.

```
W2_93085_Teja1 SELECT *
-> FROM ORDERS
-> WHERE AMT > (
->     SELECT MIN(AMT)
->     FROM ORDERS
->     WHERE CNUM IN (
->         SELECT CNUM
->         FROM CUSTOMERS
->         WHERE CITY = 'London'
->     )
-> );
```

Onum	Amt	Odate	Cnum	Snum
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001

7 rows in set (0.00 sec)

```
W2_93085_Teja1 SELECT *
-> FROM ORDERS
-> WHERE AMT > (
->     SELECT MAX(AMT)
->     FROM ORDERS
->     WHERE CNUM IN (
->         SELECT CNUM
->         FROM CUSTOMERS
->         WHERE CITY = 'London'
->     )
-> );
Empty set (0.00 sec)
```

