

BABA LAGIN

Database Structure

Schema reference for the registrations, payments and users tables

Version	1.0
Date	June 27, 2026
Application	loginapp (Spring Boot 2.7.18, JPA / Hibernate)
Schema name	matrimonial
Engine	MySQL 8 (InnoDB) - default profile
Dev option	H2 in-memory (dev profile)

1. Overview

The application stores its data in three tables. The schema is generated automatically by Hibernate (spring.jpa.hibernate.ddl-auto=update) on startup, so these tables are created/updated without manual DDL. This document describes the structure for reference and manual setup.

Database: matrimonial (auto-created via createDatabaseIfNotExist on MySQL).

Tables: registrations, payments, users.

Tables at a glance

Table	Purpose	Source entity
registrations	One row per submitted enroll form (6 sections embedded).	Registration
payments	Payment verification submissions + screenshot metadata.	Payment
users	Login accounts for authentication (admin seeded).	AppUser
documents	User-uploaded files/images stored as base64 (e.g. profile photo).	Document
contact_messages	Contact Us form submissions.	ContactMessage
notifications	User notifications (interest & payment events).	Notification
messages	In-app chat between accepted connections.	Message
registrations_temp	Personal-details drafts saved on enroll step 1.	RegistrationTemp

Relationships

payments.registration_id refers to registrations.id, but is stored as a string and is NOT enforced as a foreign key. This is deliberate: the frontend may send a placeholder ("temp-id") when the generated registration id has not been threaded through, so a hard FK would reject valid submissions. The users table is independent.

```
registrations (id) 1 ---- * payments (registration_id)    [logical, not enforced]
users : standalone
```

Type mapping (JPA - MySQL)

Java type	MySQL type	Notes
Long (id)	BIGINT AUTO_INCREMENT	Primary key, IDENTITY strategy
String	VARCHAR(255)	Default length
String @Column(length=1000)	VARCHAR(1000)	Long text fields
boolean / Boolean	BIT(1)	true / false
LocalDateTime	DATETIME(6)	Timestamp

2. Table: registrations

One row per enroll-form submission. The six form steps are embedded as column groups, prefixed by section (p_ personal, h_ horoscope, edu_ education, addr_ address, fam_ family, exp_ expectation).

Keys & metadata

Column	Type	Null	Key	Notes
id	BIGINT	No	PK	Auto-increment
registration_code	VARCHAR(255)	Yes	UQ	Login code, e.g. REG00001

created_at	DATETIME(6)	Yes		Set on insert
created_date	DATETIME(6)	Yes		Date row inserted
updated_date	DATETIME(6)	Yes		Date row last changed
is_active	VARCHAR(1)	Yes		Y (default) / N
success_story	VARCHAR(1)	Yes		Y / N (default N)
partner_id	VARCHAR(20)	Yes		Linked partner's code/id
renewed_until	DATETIME(6)	Yes		Membership validity; set when a payment is verified (NEW=+6mo, RENEWAL=+period)

personal (p_)

Column	Type	Null	Key	Notes
p_first_name	VARCHAR(255)	No*		Required at API level
p_middle_name	VARCHAR(255)	Yes		
p_last_name	VARCHAR(255)	No*		Required at API level
p_email	VARCHAR(255)	No*		Required; used for profile login
p_mobile	VARCHAR(255)	No*		Required; 10-digit mobile
p_gender	VARCHAR(255)	Yes		Groom / Bride (search)
p_community	VARCHAR(255)	Yes		e.g. Marathi (search)
p_height_total_inches	INT	Yes		feet*12+inch (height range search)
p_dob_day	VARCHAR(255)	Yes		Day of birth
p_dob_month	VARCHAR(255)	Yes		Month of birth
p_dob_year	VARCHAR(255)	Yes		Year of birth
p_sub_caste	VARCHAR(255)	Yes		
p_marital_status	VARCHAR(255)	Yes		Unmarried/Divorced
p_height_feet	VARCHAR(255)	Yes		
p_height_inches	VARCHAR(255)	Yes		
p_weight	VARCHAR(255)	Yes		
p_blood_group	VARCHAR(255)	Yes		
p_complexion	VARCHAR(255)	Yes		
p_physical_disability	VARCHAR(255)	Yes		Yes/No
p_disability_details	VARCHAR(255)	Yes		
p_diet	VARCHAR(255)	Yes		Veg/Non-Veg
p_spectacles	VARCHAR(255)	Yes		Yes/No

horoscope (h_)

Column	Type	Null	Key	Notes
h_rashi	VARCHAR(255)	Yes		

h_nakshatra	VARCHAR(255)	Yes		
h_charan	VARCHAR(255)	Yes		
h_gan	VARCHAR(255)	Yes		
h_gotra	VARCHAR(255)	Yes		
h_manglik	VARCHAR(255)	Yes		Yes/No
h_birth_time	VARCHAR(255)	Yes		
h_birth_place	VARCHAR(255)	Yes		

education (edu_)

Column	Type	Null	Key	Notes
edu_highest_education	VARCHAR(255)	Yes		
edu_field_of_study	VARCHAR(255)	Yes		
edu_institution	VARCHAR(255)	Yes		
edu_occupation	VARCHAR(255)	Yes		
edu_occupation_type	VARCHAR(255)	Yes		e.g. Private Service (search)
edu_employer	VARCHAR(255)	Yes		
edu_annual_income	VARCHAR(255)	Yes		

address (addr_)

Column	Type	Null	Key	Notes
addr_country	VARCHAR(255)	Yes		Defaults to India
addr_state	VARCHAR(255)	Yes		
addr_city	VARCHAR(255)	Yes		
addr_native_place	VARCHAR(255)	Yes		Native place (search)
addr_pincode	VARCHAR(255)	Yes		
addr_permanent	VARCHAR(1000)	Yes		Permanent address
addr_current	VARCHAR(1000)	Yes		Current address
addr_same_as_permanent	BIT(1)	Yes		true/false

family (fam_)

Column	Type	Null	Key	Notes
fam_father_name	VARCHAR(255)	Yes		
fam_father_occupation	VARCHAR(255)	Yes		
fam_mother_name	VARCHAR(255)	Yes		
fam_mother_occupation	VARCHAR(255)	Yes		
fam_siblings	VARCHAR(255)	Yes		
fam_family_type	VARCHAR(255)	Yes		Nuclear/Joint

fam_family_status	VARCHAR(255)	Yes		
-------------------	--------------	-----	--	--

expectation (exp_)

Column	Type	Null	Key	Notes
exp_age_from	VARCHAR(255)	Yes		
exp_age_to	VARCHAR(255)	Yes		
exp_height_from	VARCHAR(255)	Yes		
exp_height_to	VARCHAR(255)	Yes		
exp_education	VARCHAR(255)	Yes		
exp_occupation	VARCHAR(255)	Yes		
exp_location	VARCHAR(255)	Yes		
exp_other_preferences	VARCHAR(1000)	Yes		Free text

3. Table: payments

Stores each payment-verification submission and the metadata of the uploaded screenshot (the image file itself is stored on disk under uploads/payments).

Column	Type	Null	Key	Notes
id	BIGINT	No	PK	Auto-increment
registration_id	VARCHAR(255)	Yes		Logical ref to registrations.id (or "temp-id")
transaction_id	VARCHAR(255)	Yes		UPI transaction id
upi_id	VARCHAR(255)	Yes		Payee UPI id
amount	VARCHAR(255)	Yes		Amount paid
payment_type	VARCHAR(255)	Yes		NEW (default) or RENEWAL
renewal_months	INT	Yes		Renewal period in months (RENEWAL only)
screenshot_path	VARCHAR(1000)	Yes		Server file path
screenshot_filename	VARCHAR(255)	Yes		Original filename
screenshot_content_type	VARCHAR(255)	Yes		e.g. image/png
status	VARCHAR(255)	Yes		PENDING_VERIFICATION/VERIFIED/REJECTED
status_note	VARCHAR(1000)	Yes		Admin note
created_at	DATETIME(6)	Yes		Set on insert
updated_at	DATETIME(6)	Yes		Set on status change

4. Table: users

Login accounts used for authentication. There is no self-service signup; an admin account is seeded on first startup (default admin / admin123, BCrypt-hashed).

Column	Type	Null	Key	Notes
id	BIGINT	No	PK	Auto-increment
username	VARCHAR(255)	No	UQ	Unique login name
password	VARCHAR(255)	No		BCrypt hash
role	VARCHAR(255)	No		e.g. ADMIN (mapped to ROLE_ADMIN)
enabled	BIT(1)	No		Account active flag

5. Table: documents

Files/images uploaded by users, stored base64-encoded. The most recent row of a given doc_type for a registration is the active one (older uploads are retained).

Column	Type	Null	Key	Notes
id	BIGINT	No	PK	Auto-increment
registration_code	VARCHAR(255)	Yes		Owner, e.g. REG00001
doc_type	VARCHAR(255)	Yes		e.g. profileImage
file_name	VARCHAR(255)	Yes		Original filename
content_type	VARCHAR(255)	Yes		e.g. image/png
data_base64	LONGTEXT (CLOB)	Yes		Base64 file contents (@Lob)
created_at	DATETIME(6)	Yes		Upload time

6. Table: contact_messages

Submissions from the public Contact Us form.

Column	Type	Null	Key	Notes
id	BIGINT	No	PK	Auto-increment
full_name	VARCHAR(255)	Yes		Sender name
phone	VARCHAR(255)	Yes		
email	VARCHAR(255)	Yes		
subject	VARCHAR(255)	Yes		
message	VARCHAR(2000)	Yes		Message body
created_date	DATETIME(6)	Yes		Submitted at

7. Table: notifications

Notifications for logged-in profile users (interest received/accepted/rejected, payment updates).

Column	Type	Null	Key	Notes
id	BIGINT	No	PK	Auto-increment
registration_code	VARCHAR(255)	Yes		Recipient
type	VARCHAR(255)	Yes		INTEREST_* / PAYMENT

message	VARCHAR(500)	Yes		
from_code	VARCHAR(255)	Yes		Sender (interest)
from_name	VARCHAR(255)	Yes		Sender name
status	VARCHAR(255)	Yes		PENDING/ACCEPTED/REJECTED
is_read	BIT(1)	Yes		Read flag
created_date	DATETIME(6)	Yes		

8. Table: messages

In-app messages exchanged between two profiles that have an accepted-interest connection. Email and mobile are never exposed, so connected users communicate here instead.

Column	Type	Null	Key	Notes
id	BIGINT	No	PK	Auto-increment
from_code	VARCHAR(20)	No		Sender registration code
to_code	VARCHAR(20)	No		Recipient registration code
content	VARCHAR(2000)	No		Message text
created_date	DATETIME(6)	Yes		Set on insert
is_read	BIT(1)	Yes		Read flag (reserved)

9. Table: registrations_temp

Draft of the personal section, saved when the user clicks Next on enroll step 1 (upsert by p_email). Deleted automatically when the full profile is created. Holds the same p_* personal columns as registrations, plus audit dates.

Column	Type	Null	Key	Notes
id	BIGINT	No	PK	Auto-increment
p_first_name ... p_*	VARCHAR/INT	Yes		Embedded Personal columns (same as registrations)
created_date	DATETIME(6)	Yes		Set on insert
updated_date	DATETIME(6)	Yes		Set on each save

10. Reference DDL (MySQL)

Equivalent CREATE TABLE statements (Hibernate generates these automatically; shown for manual setup or review).

registrations

```

CREATE TABLE registrations (
  id BIGINT NOT NULL AUTO_INCREMENT,
  registration_code VARCHAR(255),
  created_at DATETIME(6),
  created_date DATETIME(6),
  updated_date DATETIME(6),
  is_active VARCHAR(1) DEFAULT 'Y',
  success_story VARCHAR(1) DEFAULT 'N',
  partner_id VARCHAR(20),
  renewed_until DATETIME(6),
  p_first_name VARCHAR(255), p_middle_name VARCHAR(255), p_last_name VARCHAR(255),
  p_email VARCHAR(255), p_mobile VARCHAR(255),
  p_gender VARCHAR(255), p_community VARCHAR(255), p_height_total_inches INT,
  p_dob_day VARCHAR(255), p_dob_month VARCHAR(255), p_dob_year VARCHAR(255),
  p_sub_caste VARCHAR(255), p_marital_status VARCHAR(255),
  p_height_feet VARCHAR(255), p_height_inches VARCHAR(255), p_weight VARCHAR(255),
  p_blood_group VARCHAR(255), p_complexion VARCHAR(255),
  p_physical_disability VARCHAR(255), p_disability_details VARCHAR(255),
  p_diet VARCHAR(255), p_spectacles VARCHAR(255),
  h_rashi VARCHAR(255), h_nakshatra VARCHAR(255), h_charan VARCHAR(255),
  h_gan VARCHAR(255), h_gotra VARCHAR(255), h_manglik VARCHAR(255),
  h_birth_time VARCHAR(255), h_birth_place VARCHAR(255),
  edu_highest_education VARCHAR(255), edu_field_of_study VARCHAR(255),
  edu_institution VARCHAR(255), edu_occupation VARCHAR(255),
  edu_occupation_type VARCHAR(255),
  edu_employer VARCHAR(255), edu_annual_income VARCHAR(255),
  addr_country VARCHAR(255), addr_state VARCHAR(255), addr_city VARCHAR(255),
  addr_native_place VARCHAR(255),
  addr_pincode VARCHAR(255), addr_permanent VARCHAR(1000),
  addr_current VARCHAR(1000), addr_same_as_permanent BIT,
  fam_father_name VARCHAR(255), fam_father_occupation VARCHAR(255),
  fam_mother_name VARCHAR(255), fam_mother_occupation VARCHAR(255),
  fam_siblings VARCHAR(255), fam_family_type VARCHAR(255),
  fam_family_status VARCHAR(255),
  exp_age_from VARCHAR(255), exp_age_to VARCHAR(255),
  exp_height_from VARCHAR(255), exp_height_to VARCHAR(255),
  exp_education VARCHAR(255), exp_occupation VARCHAR(255),
  exp_location VARCHAR(255), exp_other_preferences VARCHAR(1000),
  PRIMARY KEY (id),
  UNIQUE KEY uk_registration_code (registration_code)
) ENGINE=InnoDB;

```

payments

```

CREATE TABLE payments (
  id BIGINT NOT NULL AUTO_INCREMENT,
  registration_id VARCHAR(255),
  transaction_id VARCHAR(255),
  upi_id VARCHAR(255),
  amount VARCHAR(255),
  screenshot_path VARCHAR(1000),
  screenshot_filename VARCHAR(255),
  screenshot_content_type VARCHAR(255),
  payment_type VARCHAR(255),
  renewal_months INT,
  status VARCHAR(255),
  status_note VARCHAR(1000),
  created_at DATETIME(6),
  updated_at DATETIME(6),
  PRIMARY KEY (id)
) ENGINE=InnoDB;

```

users


```
CREATE TABLE users (
  id BIGINT NOT NULL AUTO_INCREMENT,
  username VARCHAR(255) NOT NULL,
  password VARCHAR(255) NOT NULL,
  role VARCHAR(255) NOT NULL,
  enabled BIT NOT NULL,
  PRIMARY KEY (id),
  UNIQUE KEY uk_users_username (username)
) ENGINE=InnoDB;
```

notifications

```
CREATE TABLE notifications (
  id BIGINT NOT NULL AUTO_INCREMENT,
  registration_code VARCHAR(255),
  type VARCHAR(255),
  message VARCHAR(500),
  from_code VARCHAR(255),
  from_name VARCHAR(255),
  status VARCHAR(255),
  is_read BIT,
  created_date DATETIME(6),
  PRIMARY KEY (id)
) ENGINE=InnoDB;
```

messages

```
CREATE TABLE messages (
  id BIGINT NOT NULL AUTO_INCREMENT,
  from_code VARCHAR(20) NOT NULL,
  to_code VARCHAR(20) NOT NULL,
  content VARCHAR(2000) NOT NULL,
  created_date DATETIME(6),
  is_read BIT,
  PRIMARY KEY (id)
) ENGINE=InnoDB;
```

registrations_temp

```
CREATE TABLE registrations_temp (
  id BIGINT NOT NULL AUTO_INCREMENT,
  created_date DATETIME(6),
  updated_date DATETIME(6),
  p_first_name VARCHAR(255), p_last_name VARCHAR(255),
  p_email VARCHAR(255), p_mobile VARCHAR(255),
  p_gender VARCHAR(255), p_marital_status VARCHAR(255),
  p_dob_day VARCHAR(255), p_dob_month VARCHAR(255), p_dob_year VARCHAR(255),
  p_height_feet VARCHAR(255), p_height_inches VARCHAR(255), p_height_total_inches INT,
  -- ...remaining embedded Personal (p_*) columns, same as registrations
  PRIMARY KEY (id)
) ENGINE=InnoDB;
```

contact_messages

```
CREATE TABLE contact_messages (
  id BIGINT NOT NULL AUTO_INCREMENT,
  full_name VARCHAR(255),
  phone VARCHAR(255),
  email VARCHAR(255),
  subject VARCHAR(255),
  message VARCHAR(2000),
  created_date DATETIME(6),
  PRIMARY KEY (id)
) ENGINE=InnoDB;
```

documents

```
CREATE TABLE documents (  
  id BIGINT NOT NULL AUTO_INCREMENT,  
  registration_code VARCHAR(255),  
  doc_type VARCHAR(255),  
  file_name VARCHAR(255),  
  content_type VARCHAR(255),  
  data_base64 LONGTEXT,  
  created_at DATETIME(6),  
  PRIMARY KEY (id)  
) ENGINE=InnoDB;
```