

A hand-drawn diagram on blue grid paper illustrating the relationship between different programming languages. It consists of three concentric circles. The outermost circle is labeled "python" in red, with a blue oval around the word and a blue arrow pointing to it. The middle circle is labeled "C++, java" in red, with blue checkmarks under each language. The innermost circle is labeled "Assembly language" in red. At the center of the innermost circle is a blue circle containing a red "C".

Example 1 : basic CGPA

23 May 2026 11:58

Example 2: Score check

23 May 2026 12:24

**Int,
Float,
String,
Char,
Byte,
Unsigned int,
Long int,**

Conditional Statements if, else

23 May 2026

12:25

**If,
If/else,
Else if,
Switch,
Ternary operator**

Questions

23 May 2026

12:06

Q.1

main.cpp



Share

```
1 // Online C++ compiler to run C++ program online
2 #include <iostream>
3 using namespace std;
4 int main() {
5     int x = 5;
6     if(x == 5)
7         cout<<"X is equal to 5"<<endl;
8
9     return 0;
10 }
```

Q.2

main.cpp



Share

Run

```
1 // Online C++ compiler to run C++ program online
2 #include <iostream>
3 using namespace std;
4 int main() {
5     int x = 5;
6     if(x == 4);
7         cout<<"X is equal to 5"<<endl;
8
9     return 0;
10 }
```

Q.3.

main.cpp



Share

Run

```
1 // Online C++ compiler to run C++ program online
2 #include <iostream>
3 using namespace std;
4 int main() {
5     int x = 3;
6     if(x == 5)
7         cout<<"X is equal to 5"<<endl;
8     else
9         cout<<"X is not equal to 5"<<endl;
10    return 0;
11 }
```

0.4.

main.cpp



Share

Run

```
1 // Online C++ compiler to run C++ program online
2 #include <iostream>
3 using namespace std;
4 int main() {
5     float x = 0.5;
6     if(x == 0.5)
7         cout<<"abc"<<endl;
8     else
9         cout<<"def"<<endl;
10    return 0;
11 }
```

**What is array,
initialization, printing
array and so on.,**

For loops,
While loops,
Do-while loops.

Questions 2

23 May 2026 12:19

Q.1

```
1 // Online C++ compiler to run C++ program online
2 #include <iostream>
3 using namespace std;
4 int main() {
5     int arr[5] = {1,2,3,4,5};
6     cout<<arr[0];
7
8     return 0;
9 }
```

Q.2

```
cpp
#include <iostream>
using namespace std;
int main() {
    int arr[5] = {1, 2, 3, 4, 5};
    for (int i = 0; i < 5; i++) {
        cout << arr[i] << " ";
    }
    return 0;
}
```

Q.3

```
cpp
#include <iostream>
using namespace std;
int main() {
    int arr[5] = {1, 2, 3, 4, 5};
    for (int i = 4; i >= 0; i--) {
        cout << arr[i] << " ";
    }
    return 0;
}
```

Q.5

```
cpp
#include <iostream>
using namespace std;
int main() {
    int arr[5] = {10, 20};
    for (int i = 0; i < 5; i++) {
        cout << arr[i] << " ";
    }
    return 0;
}
```

Q.6.

```
cpp
#include <iostream>
using namespace std;
int main() {
    int arr[5] = {1, 2, 3, 4, 5};
    int sum = 0;
    for (int i = 0; i < 5; i++) {
        sum += arr[i];
    }
    cout << sum;
    return 0;
}
```

Q.7.

```
cpp
#include <iostream>
using namespace std;
int main() {
    int arr[5] = {1, 2, 3, 4, 5};
    for (int i = 0; i < 5; i++) {
        arr[i] = arr[i] * 2;
    }
    for (int i = 0; i < 5; i++) {
        cout << arr[i] << " ";
    }
    return 0;
}
```