

REVIO Project Setup Guide

1. Clone Repository

Clone the REVIO repository:

```
git clone https://github.com/Tejashree2004/Review.git
```

Move into the project:

```
cd Review
```

2. Database Setup

- Install PostgreSQL.

- Create database:

```
CREATE DATABASE ReviewDB;
```

- Configure the database connection in:

```
backend/Review.API/appsettings.json
```

Set your PostgreSQL username and password:

```
"ConnectionStrings": {  
  "DefaultConnection":  
    "Host=localhost;Port=5432;Database=ReviewDB;Username=postgres;Password=YOUR_PASSWORD"  
}
```

- Install Entity Framework Core CLI:

```
dotnet tool install --global dotnet-ef
```

- Run migrations:

```
cd backend/Review.API
```

```
dotnet ef database update
```

3. Backend Setup

Go to the backend folder:

```
cd backend/Review.API
```

Restore dependencies:

```
dotnet restore
```

Build the project:

```
dotnet build
```

Run the project:

dotnet run

Backend:

<http://localhost:5213>

Swagger:

<http://localhost:5213/swagger>

4. Frontend Setup

Open a new terminal.

Go to the frontend folder:

cd frontend

Install dependencies:

npm install

Run the project:

npm run dev

Frontend:

<http://localhost:5173>

5. Environment Variables

REVIO uses SMTP credentials for email/OTP functionality.

Configure:

SMTP_EMAIL=your-email@gmail.com

SMTP_PASSWORD=your-app-password

For Gmail, use a Gmail App Password.

Do not commit passwords or other secrets to GitHub.

6. Done

Project will run on:

- Backend: <http://localhost:5213>
- Swagger: <http://localhost:5213/swagger>
- Frontend: <http://localhost:5173>

MailKit SMTP Configuration – .NET 10

1. Package Installation

REVIO uses MailKit for sending emails.

Install-Package MailKit

2. Namespace Changes

using MailKit.Net.Smtp;

using MailKit.Security;

using MimeKit;

3. Email Service Implementation

- MimeMessage is used to create email messages.
- SmtplibClient is used to connect to the SMTP server.
- SendAsync() is used to send emails asynchronously.

4. SMTP Configuration

Gmail SMTP:

Host: smtp.gmail.com

Port: 587

Security: StartTls

Example:

```
await client.ConnectAsync(  
    "smtp.gmail.com",  
    587,  
    SecureSocketOptions.StartTls  
);
```

5. Environment Variables

SMTP_EMAIL=your-email@gmail.com

SMTP_PASSWORD=your-app-password

6. Secure Connection Setup

```
await client.ConnectAsync(  
    host,  
    port,
```

```
SecureSocketOptions.StartTls  
);
```

7. Authentication

```
await client.AuthenticateAsync(  
    email,  
    password  
);
```

8. Sending Email

```
await client.SendAsync(message);  
await client.DisconnectAsync(true);
```

9. HTML Email Support

```
new TextPart("html")
```

This can be used for formatted OTP and email messages.

10. Dependency Injection

In Program.cs:

```
builder.Services.AddScoped<EmailService>();
```

11. Error Handling

```
try  
{  
    // Send email  
}  
catch (Exception ex)  
{  
    // Handle email error  
}
```